EDN

Digital synthesizer eases testing of complex circuits

SCSI host adapters

Instrumentation amplifiers

Technology Feature: Parallel processing

ELECTRONIC TECHNOLOGY FOR ENGINEERS AND ENGINEERING MANAGERS










When it comes to competition in the compatibles marketplace, are you going to grab the bull by the tail?



Writing a GPIB program shouldn't take an eternity.

You shouldn't have to hammer out hundreds of lines of BASIC, or look up all those instrument commands. All you should have to do is tell the computer what kind of test you want to run, what

instruments to use, and what to do with the data.

Then it should do the rest.

After all, it is a computer.

Starting now, that's how it'll

be, if you have our new WaveTest® software.

Just point to the program elements you need, assemble them either as a flowchart or a string of icons. WaveTest writes all the program code, including the GPIB commands for more than fifty different makes and models of instruments.

You'll be able to take months off of test development. Best of all, you'll be putting your time into the design of the program—and

not into tedious code writing. WaveTest runs on your PCcompatible computer and it uses Microsoft® Windows and a mouse, making it very user-friendly.


To write another program without WaveTest would be a basic error. For immediate information, call our Applications Department at (619) 279-2200.

Wavetek San Diego, Inc., P.O. Box 85265, San Diego, CA 92138. TWX 910-335-2007.


CIRCLE NO 110



Until we acquired Sealectro, this was the strongest group of companies in the electronics industry.




Cannon Connectors




Schadow Switches



Jeanrenaud Switches



Pomona Electronics Test Accessories



MTI Relays

With the recent acquisition of one of the world's leading manufacturers of coaxial RF connectors, we've become stronger than ever.

Add to that an equally strong commercial line of Vero low-frequency connectors and cable assemblies, and you've got an expanded group of companies offering you even more worldwide resources. As well as a significantly broadened product line to help you narrow your supplier base.

ITT Cannon, Schadow, Jeanrenaud, Pomona Electronics, MTI. And now Sealectro. All part of the ITT group of companies known as **ITT ElectroMechanical Components** Worldwide.

From connectors and switches to test accessories and relays, ITT can now service your systems needs more thoroughly than ever before.

To learn more about our capabilities, contact us today. You'll see how we made the world's strongest group of electronics companies even stronger.

> Worldwide Headquarters 10550 Talbert Avenue Fountain Valley, CA 92708 Or call (714) 964-7400

7 ElectroMechanical Components Worldwide

Discover our strengths.



ELECTRONIC TECHNOLOGY FOR ENGINEERS AND ENGINEERING MANAGERS



On the cover: It's not a mirage—computer-controlled instruments on a card that connect to industry-standard backplanes are finally materializing. By combining these cards with personal computers or single-board computers, you can create virtual instrumentation. See pg 120. (Photo courtesy National Instruments)

SPECIAL REPORT

Virtual instruments

120

Not only can virtual instruments simulate many conventional instruments, they can function as unique, specialized instruments as well. Once uniform, easy-to-use software interfaces are introduced, virtual instruments will allow design engineers to export their instrumentation expertise to others.—Charles H Small, Associate Editor

DESIGN FEATURES

Video op amps find use in RF and active filters

137

Video op amps designed for radio frequencies offer relatively high output current and low power consumption in comparison with conventional ap amps. They can work well in various high-frequency analog-signal-processing applications, including driving flash converters and active antialiasing filters.—Ken Schaefer and John Shier, VTC Inc

Use a single-chip μ C as the heart of your position controller

161

A single chip can be the basis of a computer-based position controller. This article provides enough detail about hardware and microcode to allow you to design your own position controller—even if you have little experience with motion control.—William C Warner, Consultant

Digital synthesizer aids testing of complex analog, digital circuits

185

A digitally based signal synthesizer (DSS) provides the test engineer with a high degree of flexibility in the generation of test signals. When used with a digitizing scope, the DSS greatly simplifies the testing of complex analog and digital circuits found on pc boards for hard-disk-drive applications.—Al Kovalick, Hewlett-Packard Co

Continued on page 7

EDN®(ISSN 0012-7515) is published 40 times a year (biweekly with 1 additional issue a month, except for July which has 3 additional issues) by Cahners Publishing Company, A Division of Reed Publishing USA, 275 Washington Street, Newton, MA 02158-1630. Terrence M McDermott, President; Frank Sibley, Electronics/Computer Group Vice President, Jerry D Neth, Vice President/Publishing Operations; J J Walsh, Financial Vice President/Magazine Division; Thomas J Dellamaria, Vice President/Production and Manufacturing, Circulation records are maintained at Cahners Publishing Company, 44 Cook Street, Denver, CO 80206-5800. Telephone: (303) 388-4511. Second-class postage paid at Denver, CO 80206-5800 and additional mailing offices. POSTMASTER: Send address corrections to EDN® at the Denver address. EDN® copyright 1988 by Reed Publishing USA; Saul Goldweitz, Chairman; Ronald G Segel, President and Chief Executive Officer; Robert L Krakoff, Executive Vice President; William M Platt, Senior Vice President Annual subscription rates for nonqualified people: USA, \$100/year; Canada/Mexico, 115/year; Europe air mail, \$135/year; all other nations, \$135/year for surface mail and \$210/year for air mail. Except for stpecial issues where price changes are indicated, single copies of regular issues are available for \$6, \$8, and \$10 (USA, Canada/Mexico, and foreign). Please address all subscription mail to Eric Schmierer, 44 Cook Street, Denver, CO 80206-5800.





PHILIPS



This meter has what you need most— Superb accuracy and proven reliability

The Fluke 8840A is your best choice for accuracy, readability and overall performance in a 51/2 digit multimeter.

The Fluke 8840A is the world's best selling 51/2 digit DMM. For good reason. Basic dc accuracy is 0.005% at one year. Basic ac accuracy at one year is 0.16%, and one year basic resistance accuracy is 0.013%. With users discovering their 8840A's typically exceeding these specs at each oneyear calibration cycle.



The specs are even better for the 8842A. It offers 0.003% basic dc accuracy and

0.08% basic ac accuracy at one year. Resolution is 100 nV on dc readings, and 100 $\mu\Omega$ resolution on resistance readings. Plus a two year calibration cycle and

Nothing in its class can match the 8840 Series for field-proven reliability: 60,000 hours MTBF for the 8842A, and nearly 70,000 hours for the 8840A.

And nothing can match the 8840 Series for ease of operation. The vacuum fluorescent display is the most readable you've ever seen. True-RMS ac and IEEE-488 interface options let you configure the unit the way you need, so you aren't stuck with features you don't want.

An adjustable tilt-stand for bench use is standard. But rack mounting is quick and trouble free. Closed-case calibration reduces maintenance time. And throughput can be set for 2.5, 20, or 100 readings per second, making the 8840A the fastest in its class.

Put the world's most popular 51/2 digit multimeters to work for you today. For your nearest distributor call 1-800-44-FLUKE, ext. 33.

John Fluke Mfg. Co. Inc., P.O. Box C9090, M/S 250C, Everett, WA 98206. U.S.: 206-356-5400 CANADA: 416-890-7600 OTHER COUNTRIES: 206-356-5500

C Copyright 1988 John Fluke Mfg. Co., Inc. All rights reserved.

FROM THE WORLD LEADER IN DIGITAL MULTIMETERS

FLUKE	8840A

0.005% basic dc accuracy (1 Yr.) 0.16% basic ac accuracy (1 Yr.) 0.013% basic ohms accuracy (1 Yr.) Resolution to 1 μ V, 10 μ A, 1 m Ω One year warranty


8840A-09K AC True-RMS option\$205

FLUKE 8842A

0.003% basic dc accuracy (1 Yr.) 0.08% basic ac accuracy (1 Yr.) 0.008% basic ohms accuracy (1 Yr.) Resolution to 100 nV, 1 μ A, 100 μ Ω Two year warranty 8842A 8840A-05K IEEE-488 option \$170 8842A-05K IEEE-488 option \$170 8842A-09K AC True-RMS option\$270







SCSI host adapters open the door to disk-transfer rates of 1M byte/sec and faster (pg 59).

EDN magazine
now offers
Express Request,
a convenient way
to retrieve product
information by
phone. See the
Reader Service
Card in the front
for details on how
to use this free
service.

TECHNOLOGY UPDATE

SCSI host adapters offer superspeed to personal-computer I/O systems

59

Personal-computer I/O performance has not kept pace with the processing power offered by 80286- and 80386-based systems. But IBM PC/AT- and Micro Channel-compatible SCSI host adapters can provide interfaces to the highest performance 5¼-in. disk drives available.

—Maury Wright, Regional Editor

IAs pull low-level signals out of noisy environments

77

Unwanted noise can contaminate electronic signals and complicate their acquisition in various ways. If you need to acquire a differential signal that is mixed with unwanted common-mode noise and voltage, consider using instrumentation amplifiers.—David Shear, Regional Editor

Technology Feature: Parallel processing

86

Today's parallel processors, techniques, and languages can help you create powerful minicomputers whose processing capabilities equal or exceed those of supercomputers.—John Gallant, Associate Editor

PRODUCT UPDATE

Interactive test-generation software	105
Graphics processor	108
Multibus I 32-bit CPU card	113
Modem processor	114

DESIGN IDEAS

Dual potentiometer controls up/down counter	201
Circuit lowers photodiode-amplifier noise	203
XOR gates add up/down function	204
Watchdog timer catches I/O-chip crashes	204
Spare flip-flop forms inverter	208

Continued on page 9

Cahners Publishing Company, A Division of Reed Publishing USA ☐ Specialized Business Magazines for Building & Construction ☐ Manufacturing ☐ Foodservice & Lodging ☐ Electronics & Computers ☐ Interior Design ☐ Printing ☐ Publishing ☐ Industrial Research & Technology ☐ Health Care ☐ and Entertainment. Specialized Consumer Magazines: ☐ American Baby ☐ and Modern Bride.

TEK'S NEW \$2795 16-64 CHANNEL LOGIC ANALYZER. EASY TO START WITH. TOUGH TO OUTGROW.

For \$2795, you can have a logic analyzer that makes things simple when you're just starting out. That may never make you rummage through the manual. But that recognizes you won't be a rookie forever.

Starting with 16 channels, Tek's new 1230 guides the new user through timing and state analysis with on-screen prompts. We kept keystrokes to a minimum, common sense to a maximum.

As you grow more experienced, and your applications grow more ambitious, the 1230 gives you room to grow—to 32, 48 or 64 channels with 8 and 16-bit microprocessor debug capability—via

expansion cards and probes you can easily add yourself.

You can do hardware analysis and microprocessor systems integration, using up to four 2K deep memories for reference and comparison. You can do sophisticated triggering. Acquire and compare signals automatically via built-in babysitting mode. Or, take the 1230 into the field: its rugged package takes rough handling in stride.

No other logic analyzer is so affordable,

and hasslefree. For further proof of why the Tek 1230 boasts the shortest learning curve and the longest life expec-

expandable

tancy, talk to your Tek representative soon. Or call (800) 245-2036. In Oregon, 231-1220.



Circle No. 127 for sales contact

Circle No. 126 for literature





VP/Publisher Peter D Coley
VP/Associate Publisher/Editorial Director Roy Forsberg
Editor Jonathan Titus
Managing Editor
John S Haystead Assistant Managing Editor
Joan Morrow Special Projects
Gary Legg
Home Office Editorial Staff 275 Washington St, Newton, MA 02158 (617) 964-3030
Tom Ormond, Senior Editor Joanne Clay, Associate Editor
John A Gallant, Associate Editor
Clare Mansfield, Associate Editor Michael C Markowitz, Associate Editor Dave Pryce, Associate Editor
Dave Pryce, Associate Editor
Cynthia B Rettig, Associate Editor Charles Small, Associate Editor
Dan Strassberg, Associate Editor Chris Terry, Associate Editor
Valerie Lauzon, Staff Editor Helen McElwee, Staff Editor Julie Anne Schofield, Staff Editor
Julie Anne Schofield, Staff Editor
Steven Paul, Senior Production Editor
Editorial Field Offices Margery S Conner, Regional Editor Los Osos, CA: (805) 528-0833
Doug Conner, Regional Editor Los Osos, CA: (805) 528-0865
Steven H Leibson, Regional Editor Boulder, CO: (303) 494-2233
J D Mosley, Regional Editor Arlington, TX: (817) 465-4961
Richard A Quinnell, Regional Editor San Jose, CA: (408) 296-0868
David Shear, Regional Editor San Jose, CA: (408) 997-5452
Maury Wright, Regional Editor San Diego, CA: (619) 748-6785
Peter Harold, European Editor 0603-630782
(St Francis House, Queens Rd, Norwich, Norfolk NR1 3PN, UK)
Contributing Editors Robert Pease, Bob Peterson, Don Powers, Bill Travis
Editorial Services
Kathy Leonard, Office Manager Loretta Curcio, Nancy Weiland
Art Staff Kathleen Ruhl, Senior Art Director
Ken Racicot, Associate Art Director Chinsoo Chung, Staff Artist Cathy Filipski, Staff Artist
Production/Manufacturing Staff
William Tomaselli, Production Supervisor Donna Pono, Production Manager
Danielle M Biviano, Production Assistant Linda Lepordo, Production Assistant
Linda Lepordo, Production Assistant Diane Malone, Composition
Graphics Director Norman Graf
VP/Production/Manufacturing Wayne Hulitzky
Director of Production/Manufacturing John R Sanders


EDITORIAL	51
Before committing money to the Superconducting Super project, engineers and scientists should debate its merits.	Collider
NEW PRODUCTS	
Computers & Peripherals	213
Integrated Circuits	218
Components & Power Supplies	
CAE & Software Development Tools	
Test & Measurement Instruments	
LOOKING AHEAD	253
Hardware outpaces software in information technology	Growth in
UPS market spawns new strategies.	

DEPARTMENTS News Breaks 21 News Breaks International 24 Signals & Noise 32 Calendar 44 Literature 242 Career Opportunities 243 Business/Corporate Staff 249 Advertisers Index 250

EDN September 1, 1988

Business Director Deborah Virtue Marketing Communications Janice Molinari, Director Anne Foley, Promotion Manager Sara Morris, Promotion Assistant

0



Mentor Graphics lets you simulate an 80386-based motherboard in only 4.3 minutes.

You're designing a complete 32-bit PC motherboard. And you're running out of time.

Your only hope is to bypass the time-consuming breadboard phase and debug directly through simulation. Which means simulating 32 I/O write cycles that program the board's peripheral chips for normal operation — 27,942ns of execution time, including a memory refresh.

So you turn to Mentor Graphics' QuickSim[™] logic simulator and run the design file—21 sheets in all, including an Intel 80386 microprocessor and 155 other IC packages, each represented by a SmartModel[™] from Logic Automation, Inc.

The result? Simulation completed in just 4.3 minutes.

Introducing the soft breadboard.

With Mentor Graphics, you have a production-proven way to create and debug systems designs—in software. During simulation, design schematics can be displayed, probed, modified, and resimulated. And to complement your simulation, QuickPath™ rapidly checks your design for critical path timing problems. All in a single, interactive work environment.

Your debug operations stay right on your Mentor Graphics workstation, where engineering changes are fast, simple and inexpensive.

Modeling is the key.

Systems simulation requires a wide range of

SmartModel is a trademark of Logic Automation, Inc.

modeling technologies. And that's precisely what we deliver. Like Behavioral Language Models (BLMs), which transcend basic functionality and deliver features such as automatic error detection and reporting. And QuickParts, which combine maximum speed with minimum memory requirements—and produce timing behavior identical to the data book.

There's also our Hardware Modeling Library,™ which provides modeling for VLSI parts, including the latest microprocessors. Plus unparalleled support for ASIC libraries, so you can include your ASIC directly in your board simulation.

Once design and analysis is complete, other Mentor Graphics tools follow your design through PCB layout, mechanical packaging, thermal analysis and documentation.

To be continued.

So much for the present. We're already developing new EDA tools for systems design that will extend to every dimension of electronic product development. From high-level systems descriptions to CASE.

It's all part of a vision unique to Mentor Graphics, the leader in electronic design automation. Let us show you where this vision can take you.

Call us toll-free for an overview brochure and the number of your nearest sales office.

Phone 1-800-547-7390 (in Oregon call 284-7357).



Yourideas. Our experience.

No one can sol but we solve

Everyone thought gate arrays would be a great solution to their semi-custom design needs. Then they designed one and discovered that "semi-custom" translated into "expensive," "time consuming" and "risky."

PGAs let you spot system problems before they become a real headache. No more risking large sums of money and time

PROGRAMMABI GATE VARRAYS

The solution to the solution.


Meet the Logic Cell Array the first Programmable Gate Array. It's a high density CMOS chip of unmatched technology that's user programmable where it's easiest for you to program—in software.

Your development cycle is cut to a week or two instead of six months. So you can get your product to market that much sooner. design in hardware. And if you need to change your design you can do it in a matter of minutes. Not months. And you won't have to spend any more money.

9000 ways to get ahead of schedule.

The Am2000 series has densities from 1000 to 2000 usable gates and the Am3000 series has densities from 2000 to 9000 usable gates. With those densities (we'll have even higher densities later), you need fewer parts to get the same functions as

ve the problem, d the solution.



EPLDs or discrete logic.

There is no other PGA technology available today. And over 5000 designers are already using it. **Even getting started is easy.**

Your investment is minimal You don't have to finance months of NRE. You can get started for the price of a PC (which you probably already have) and some software.

PGAs are the epitome of the just-in-time product. They are the only gate arrays stocked in production quantities at your distributor. And they're programmable instantly. Which means you can go from design to production as fast as you need to.

Even overnight.

See for yourself.

Contact us for a free diskette that gives you a detailed product overview, an interactive session where you can plug in your own design criteria and find out how PGAs can help your design. Part of the PGA development software is included so you can get started saving time and money right away.


Just call (800) 222-9323. Or drop us a line.

Advanced Micro Devices 2

901 Thompson Place, P.O. Box 3453, Sunnyvale, CA 94088. © 1988 Advanced Micro Devices, Inc. Logic Cell is a trademark of Xilinx, Inc.

13


CIRCLE NO 131 EDN September 1, 1988



The highest performance development tools.

Now you can build a high performance development environment around the engineering workstation you already own. And get your embedded microprocessor designs completed more quickly and with less effort than ever before.

Your Sun, Apollo or DEC workstation has the processing power and high resolution graphics. Applied Microsystems adds the debuggers, utility software and excellent emulation you need to complete your system. Only Applied Microsystems can make all of these pieces work together seamlessly.



Our ES 1800 Series of emulators provide the most powerful transparent emulation system available anywhere.

in a closely coupled development environment. What's more, VALI-DATE is supported by a rich library of linkers, loaders, compilers and assemblers.

Add the real-time, transparent emulation capabilities of our ES

you the largest overlay memory capability in the industry.

Make your workstation work even harder.

Get full value from your investment in engineering workstations.

Applied Microsystems can turn your workstation into the heart of a high performance microprocessor development environment.

To find out more, write Applied Microsystems Corporation, P.O. Box 97002, Redmond, Washington, USA 98073-9702. Or call

(800) 426-3925, in Washington call (206) 882-2000.

In Europe contact Applied Microsystems Corporation Ltd., Chiltern Court, High Street, Wendover, Aylesbury, Bucks, HP22 6EP, United Kingdom. Call 44-(0)-296-625462.

UNIX is a registered trademark of AT&T. AMC-228



Applied Microsystems Corporation

Operating Environment Host Operating		Software Utilities Languages Tools	Emulation Link	Debuggers
VAX VMS MicroVAX ULTRIX Apollo UNIX* Sun MS-DOS PC PC XT PC AT PC Compatibles	Intel: 8048 family, 8051 family 8080, 8085, 8086/8, 80186/188 and 80286 Motorola: 68HC11, 6800/2/8, 6809/9E, 68000/08/10 and 68020 Zilog: Z80, Z80H, MK 3880/4 and Z8001/2 NSC: NSC 800 Hitachi: 64180	C Compilers Pascal Assemblers FORTRAN Linkers PL/M Locators Assembler Jovial ADA (VERDIX)	ES 1800 (16 & 32-bit) EC 7000 (8-bit microcontrollers) EM Series and EL 800 (8-bit microprocessors)	validate and other soft- ware products for source and symbolic debugging

We offer debug and development tools with a difference: they are integrated solutions for virtually any development environment.

Source or symbolic debugging for Intel, Motorola, and Zilog. Plus the best emulation.

The VALIDATE family of source and symbolic debuggers and host control software has been specifically tailored by Applied Microsystems to work with our emulators 1800 Series of 16-bit and 32-bit emulators, and you have the most powerful emulation system anywhere. The high speed SCSI interface option lets you upload and download files more than twenty times faster than with RS 232. Our Advanced Event Monitor System lets you precisely control emulation with logical statements of system conditions. The ES 1800 also gives

CIRCLE NO 124



"Well, first, we're feeling enormous pressure to get products out faster. The key is designs that'll go through manufacturing the first time. If we're going to stay competitive, we've got to tackle the overall product development process—and it starts right here in design."

Look, HP's gone through the same thing. Our own divisions deal with the same problem daily. We came up with a solution called DesignCenter. It combines our electronic design automation tools with the rest of the process to produce a high degree of manufacturability right from the start—in design."

"That's exactly what we need. A single data path from design right on through production and out the door. If we could somehow combine electronic design with microprocessor development and mechanical engineering and tie it into manufacturing and test, we'd be a lot happier. Are you saying HP can do that for us now?"

"We're not there 100% yet. Nobody is. But that's the whole idea behind our DesignCenter. Right now, we've got the broadest set of EDA tools there is. Match them up with the HP test and measurement tools you've used for years, and you'll be way ahead of the game."

"We've always counted on HP test equipment. But how does that relate to your EDA tools?"

> "We were able to bridge the gap between design and prototype test. Now you can create higher quality tests—faster, too—by transferring data directly between our logic analyzers and simulation. And the design and layout tie directly into HP board test systems."

"That's terrific. But testing is only one part of the process. We're making decisions on everything from ASICs and PLDs to microwave hybrids to multi-layer PCBs. And they all have different parts and technologies. I'll tell you, it's impossible to keep up."

"We agree, it's a big problem. But that's the reason we have digital, analog, and microwave CAE tools for design, simulation, and layout. We even support it all with information management to handle the tough tradeoffs your team has to make in choosing between all the technologies and complex interactions."

"There's one thing that's always a concern. We've got systems in here from some of your competitors. If we go with HP, can you fit into our existing environment?"

"Absolutely. Using either off-the-shelf or customized interfaces, we'll help you integrate HP tools into your existing systems. And, since HP supports EDIF and IGES standards, you'll have the flexibility you need down the road."

"Speaking of standards, tell me about your platforms."

"Well, HP is among the industry leaders in standardization because the marketplace is demanding it. Our family of workstations and servers supports UNIX and networking standards. They thrive in a multi-vendor environment, making it easier to get your job done right the first time. That's the bottom line these days."

"I get the feeling you understand that we're interested in a lot more than just tools. I mean, you seem to be talking about more than hardware and software."

"I am. HP is totally committed to this idea of getting more correct-by-design products through your plant. We are talking about a lot more than the tools. We'll sit down with you and help create a system that meets your needs...not ours or somebody else's. And I mean we'll get right down to solving problems and training your people. That's what we do better than anyone else."

"I want to keep talking about this whole thing. And I want to include some other engineers, too. What are you doing next Wednesday?"

"I've got a feeling I'll be back here."
"Right."

"Name a time"

The dialogue continues ...

More and more project managers are talking to HP about EDA tools and DesignCenter. Start a dialogue today. Call toll free. Ask for information on HP Electronic Design Automation and bridging the gap from design to prototype test: 1-800-752-0900, Ext. C215.



This chip enabled us to process signals of the past.



Signal processing, when you come right down to it, is multiplication, addition, subtraction and storage. Doesn't sound very exciting.

But put together a set of building blocks that do those simple operations with almost unimaginable digital speed and precision. Then add A/D converters that bring in information from the world around you. Plus D/A converters that restore the digitally processed signals to a form your senses can understand.

And you've built a signal processing system that will enable you to do things that couldn't be done before, see things that couldn't be seen before and understand things that could never be understood before.

That's exciting. And we can help make it happen.

Complete systems solutions.

Our approach to signal processing is simple.

We've taken our unparalleled experience in data conversion and added to it a set of signal processing chips that perform operations that used to require entire circuit boards.

Here's a sample of what they can do for you: *ISP 9110 12-Bit Microprogram Sequencer*: expanded 33 word stack, 50 ns minimum cycle time.

ISP 9119 FIFO RAM Controller: uses standard RAMs to build FIFOs up to 64K deep, 15 MHz operation.

ISP 9128 FIR Filter Controller: implements 16-bit filters to 128 Taps, 128 Tap sampling rate of 100kHz.

ISP 9210 16x16 Multiplier Accumulator: innovative high-speed architecture (65 ns commercial, 75 ns military), low-power operation.

ISP 9216 16x16 Multiplier: low-power, industry-standard compatible to AM29516 and MPY016.

ISP 9520/21 Pipeline Register: high-speed access,

These are the chips you need to process signals of the future.

Our DSP building blocks, combined with our data conversion know-how, will help you design systems that depict reality more clearly than ever before possible.



output selectable from any resistor.

With devices like these, we can give you a total integrated signal processing solution. Plus the added benefits of single-vendor support and package pricing.

Position yourself for the future.

Signal processing is changing every day. That's why you need more than a signal processing supplier who has a few good parts.

You need a long-term partner who has a commitment to signal processing, and the resources in every area that signal processing calls upon.

For example, the chips of tomorrow will very likely combine signal processing, data conversion and high-speed logic. When you work with us, you'll get our Intersil expertise in processing and conversion. Plus our RCA Advanced CMOS Logic capabilities. Plus the more than 20 years of GE

experience in radar, sonar, medical imaging and other demanding DSP applications.

If worries about complexity and cost have deterred you from taking the exciting step into digital signal processing, call us. Together, we'll step into the future.

For more information, contact your local GE Solid State sales office or distributor. Or call toll-free, 800-443-7364, extension 30.


In Europe, call: Brussels, (02)246-21-11; Paris, (1) 39-46-57-99; London, (276) 68-59-11; Milano, (2) 82-291; Munich, (089) 63813-0; Stockholm (08) 793-9500.

General Electric Company, U.S.A.



GE Solid State

How to crack 86 protected mode.



Unlock selectors and descriptor tables. Break open task state segments (TSS) and call gates. Microtek's In-Circuit-Emulator (MICE) cracks 80386 protected mode with real-time, non-intrusive emulation to 20 MHz.

MICE unravels all the intricacies of the 80386, so you harness its full potential. Internal registers. including GDT and IDT base values are all directly accessible. And MICE also provides decoded access to all selector and descriptor bits, like privilege level, segment type and page accessed bits.

Use MICE as a stand-alone device, or integrate it into your development environment. MICE easily interfaces with the IBM® PC/XT/AT, VAX® Apollo® and Sun® computers.

And the 80386 emulation system is just one of our many embedded software development tools.

Our Software Analysis Workstation (SAW) delivers hardware-based, real-time software analysis in a source code environment. For source code development, our Microtec® Research products provide you

with C and Pascal cross-compilers, crossassemblers and debuggers for many popular microprocessors.

And MicroCASE™ backs all of its products with solid applications support, both at the local and factory level.

Microtek enjoys a long track record of being first to market with quality support for many major microprocessors. We were the first alternative for 80386 emulation. We're first to provide non-proprietary support for 80386 protected mode.* And you can count on the same support in the future.

For more information and product literature on our full line of MICE, call us at (408) 253-5933.

Crack 80386 protected mode, and open the door to exciting design possibilities—with the best 80386 emulation system now available. From MicroCASE.



P.O. Box 1309 • Beaverton, OR 97075

*Without the use of a proprietary "bond-out" chip. IBM is a registered trademark of International Business Machines. VAX is a trademark of Digital Equipment Corporation. Apollo is a trademark of Apollo Computer. Inc. Sun is a trademark of Sun Micro Systems

NEWS BREAKS

EDITED BY JOANNE CLAY

WORM DRIVE DELIVERS WINCHESTER-LIKE PERFORMANCE

The APX-4000 Series 51/4-in. WORM (write-once, read-mostly) optical disk drives from Maximum Storage Inc (Colorado Springs, CO, (719) 531-6888) store 488M bytes of data on double-sided media and achieve an effective access time of 28 msec. The manufacturer arrived at this access-time spec by pitting its WORM-drive subsystem against Winchester hard-disk subsystems in speed tests that transferred large files. In these tests, the APX-4000 achieved overall transfer rates similar to those of hard disks that had an average access-time rating of 28 msec.

The company is initially offering APX-4000-based WORM-disk subsystems for the IBM PC. The APX-4100, an internally mounted subsystem, costs \$4250; the APX-4200, a version for external use that adds a power supply and cabinet, costs \$4450. Each subsystem includes a controller card that adapts the PC's bus to the WORM drive's modified ESDI interface, cables, and software. Instead of merely providing hardware-driver software, the company's Maxsys software package implements a complete hierarchical file manager. The company plans to port this same file manager to other operating systems, starting with Unix. This approach allows any operating system to read files written by other operating systems.—Steven H Leibson

SOFTWARE ALLOWS PROCESS-INDEPENDENT ASIC DESIGN

The Avid (ASIC vendor-independent designer) software package from Mentor Graphics (Beaverton, OR, (503) 626-7000) allows you to proceed through the early stages of an ASIC design before selecting your ASIC vendor. You can develop a schematic and functionally simulate the design before selecting the process. After functional simulation, you'll need to choose the ASIC process to perform an accurate timing simulation. Using Avid also means you won't have to spend time learning the process-dependent constraints of each ASIC process. Avid translates your design into a format compatible with the ASIC processes you select. Companies that have formally committed to supporting Avid include Fujitsu, GE Solid State, Gould, Intel, and Toshiba. Avid is available this month; a site license costs \$27,500.—Doug Conner

C-LANGUAGE LIBRARY AVAILABLE FOR NEURAL NETWORKS

A C-language library of neural-network software from Olmsted & Watkins (Escondido, CA, (619) 746-2765) lets you develop your own neural-network application programs. The software runs on an IBM PC, PC/XT, PC/AT or compatible computer with Microsoft C 5.0 or higher. Priced at \$349, the application package supports the following network topologies: back propagation (with any number of layers), adaptive resonance, brain-state-in-a-box, Hopfield, adaptive BAM (bidirectional associative memory), and the Boltzmann machine. A networks package priced at \$849 provides the source code for all networks in the applications package, allowing you to modify or create custom networks.—Doug Conner

ELECTROMECHANICAL RELAYS SWITCH HIGH VOLTAGE AND CURRENT

You can switch at least 270V dc at 10A with the KP2A series of electromechanical vacuum relays from Kilovac (Santa Barbara, CA, (805) 684-4560). Because the contact elements are enlosed in a vacuum, there's no air in the gap to ionize and allow arcing. (This lack of arcing is important in military applications that require no EMI radiation.) The gap between the contacts is smaller than in a relay that's open to the air, so it results in a smaller actuating coil and overall package outline: The KP2A

EDN September 1, 1988

NEWS BREAKS

measures $2.63 \times 1.74 \times 1.81$ in. Note that a semiconductor switch may have a smaller package outline, but the heat sink it requires gives the semiconductor relay a considerably larger overall size. The KP2A costs \$125 (OEM qty).—Margery S Conner

NEURAL-NETWORK SIMULATOR SOFTWARE TEACHES CONCEPTS

For those who've always wanted to investigate the AI concepts of neural networks, but didn't know where to start, NeuralWare Inc (Sewickley, PA, (412) 741-5959) offers the NeuralWorks Explorer. This \$199 program runs on IBM PC-compatible computers equipped with a hard-disk drive and at least 512k bytes of RAM. Developed with the novice user in mind, this neural-network simulation program provides 13 network paradigms and comes with more than 580 pages of indexed documentation.—J D Mosley

C COMPILER GENERATES PROGRAMS FOR CONCURRENT DOS

Containing functions that take advantage of Concurrent DOS's multitasking capability, the Lattice C Compiler (Lombard, IL, (312) 916-1600) generates native-mode programs so that your applications won't require PC-mode emulation when running under the Concurrent DOS operating system. Although this compiler contains all the functionality of the manufacturer's previous version, its new features include library functions for file passwords and file sharing, alternate end-of-file treatment, multisector I/O, and shared peripherals. The compiler also offers you the option of generating code that multiple copies of a program can share when running simultaneously; this method reduces memory requirements. The compiler lists for \$500 and comes with a disassembler, sample programs, and documentation.

—J D Mosley

ASIC TESTER USES SCAN-PATH TECHNIQUES


The DV-6005 design verifier from Gillytron (San Jose, CA, (408) 435-3043) allows designers to test products that were designed for scan-based testing. The basic unit offers logic testing, dc parametric testing, and an ac ring frequency test for measuring propagation delays. The unit has a modular design that's expandable to allow for the testing of pc boards and entire systems with scan-based techniques. The unit operates under menu-driven software. It lets you use a proprietary language based on C to generate test programs. The basic unit costs \$125,000 and is available within 60 days ARO.—Richard A Quinnell

FIFO DEVICES OFFER PARALLEL/SERIAL CONVERSION

Four FIFO devices from Integrated Device Technology (Santa Clara, CA, (408) 727-6116) are simplifying data buffering for high-speed serial applications. The IDT72131/72141 devices have 2048×9/4096×9-bit organization with parallel input and serial output. The IDT72132/72142 devices offer serial input and parallel output. You can connect the devices to handle serial word lengths of 7, 8, 9, 16, 17, 18, and 32 bits, and you can expand their depth without using external components.

All four devices feature a 35-nsec parallel-access time and a 50-MHz serial shift rate. They feature zero fall-through time and provide five status flags: full, almostfull (7 /8), half-full, almost-empty (1 /8), and empty. The devices are available in 28-pin ceramic or plastic DIPs, 32-pin LCCs, and 32-lead PLCCs. Prices start at \$65 for the 72131/72132 and \$95 (100) for the 72141/72142.—Richard A Quinnell

NOW IT ONLY TAKES TWO TO TRANSFORM YOUR IMAGE



Sound fishy?
Believe it.
Video image
manipulation is now
possible with just two
chips. TRW LSI

Products introduces the TMC2301 Image Resampling Sequencer — the industry's first low-cost solution to real-time graphics manipulation. One pair eliminates literally hundreds of components and costly board space previously required to perform the same graphic functions.

A TMC2301-based board system can offer performance equal to many video-effect systems currently available. This powerful two-chip set, along with three multiplier-accumulators, can expand, rotate, zoom, pan, compress, warp and/or filter a two-dimensional bit-mapped color image. Even complex transformations such as polar-to-rectangular coordinates and video standards conversion can be achieved easily and economically.

the TMC2301 reduces the cost of video manipulation by hundreds of dollars.

In fact, with

a price tag of

just \$53 each*,

The TMC2301 utilizes power-conserving CMOS technology and operates at up to 18MHz from a single 5V supply. It's ideal for video broadcast equipment, personal computer graphics, medical imaging, satellite image processing and defense electronic systems. And, it's available now from your nearby Hall-Mark or Hamilton/Avnet distributor.

TRW LSI Products — bringing the worlds of Data Acquisition and DSP together.

TRW has made video image manipulation easy and inexpensive.

And we're working to simplify many other image processing tasks for you. For details contact TRW LSI Products. Our applications engineers are always available to help answer your questions. For full data sheet and application notes, contact:

TRW LSI Products Inc. P.O. Box 2472 La Jolla, CA 92038 619.457.1000

In Europe, phone: TRW LSI Products Inc. Munich, 089.7103.124; Paris, 1.69.82.92.41; Guildford (U.K.), 0483.302364

In the Orient, phone: Hong Kong, 3.880629; Tokyo, 3.487.0386, 3.461.5311; Taipei, 751.2062; Seoul, 2.553.0901



NEWS BREAKS: INTERNATIONAL

WINDOWS LET YOU TRACE PROGRAMS AT ALL SOFTWARE LEVELS

In conjunction with the company's PC-based in-circuit emulators, the ViewFinder and PathFinder software packages from Ashling Microsystems Ltd (Limerick, Ireland, TLX 70357) provide a windows environment in which you can simultaneously trace programs at both the assembler and the source-code level. ViewFinder is supplied free of charge when you purchase one of the company's development systems. Owners of existing systems can obtain the package as a \$275 upgrade. ViewFinder allows you to display standard or user-defined screen windows containing trace information. You can also establish virtual windows; although they're not displayed, the virtual windows are continuously updated as you trace through a program, and they can be brought onto the screen as required. In addition, you can control the emulator's operation from the windows environment. By adding the PathFinder software package (which sells for between \$1250 and \$1500) and a suitable compiler, you can trace program activity at all software levels. For example, you can display the high-level-language source code that relates to a real-time program trace, so you can compare intended and actual program flow. To capture elusive program bugs, PathFinder allows you to perform continuous trace-and-compare operations, automatically storing any errors for later examination. PathFinder is currently available for use with a PL/M-51 compiler, but versions that run with C compilers for 8051, 68HC11, Z80, and 64180 µPs are scheduled for release between now and the first quarter of 1989. As part of a joint marketing agreement, ViewFinder and PathFinder will be available in the US from Microcosm Inc (Beaverton, OR, (503) 626-6100). -Peter Harold

PERSONAL VOICE-INPUT WORD PROCESSOR IS JAPAN'S FIRST

The first Japanese personal word processor with voice-input capability hails from Sharp Corp, which plans to sell the system for ¥400,000 to ¥500,000 (around \$3000 to \$3900)—far less than the \$18,500 to \$23,000 that users shell out for Sharp's and NEC's current business voice-input systems. The company plans to release the personal voice-input system in early 1989. The system is speaker-dependent, but takes only about 10 minutes to register the user's voice. It accepts complete sentences as well as individual words, and it generates mixed kanji and kana text. Users can make corrections on a keyboard. Including the time needed for manual corrections, the system can produce 40 wpm.—Joanne Clay

SOLID-STATE LASER USES LASER DIODE AS EXCITATION SOURCE

A solid-state laser device from Asahi Glass Co uses a laser diode instead of the conventional electrical-discharge lamp as the excitation light source, according to reports in the Japanese press. Using a laser diode as the excitation light source makes the laser system much smaller than its predecessor, which used the electrical-discharge lamp. The new system is 1/20 of its former length and 1/1600 of its former volume. The yttrium aluminum garnet laser absorbs almost 100% of the excited light. The company increased the laser's conversion efficiency to light from 1% to 15.5%, which greatly reduced the heat produced by the system. When they're used as excitation light sources, semiconductor lasers often exhibit poor spectral purity and the inability to achieve high peaks in Q-switch operation. Asahi employed a proprietary optical monocrystalline technology to solve these problems in the solid-state laser system. Applications for the solid-state laser include optical measuring systems and optical communication systems. Including the power source, the laser system costs ¥1,000,000 (about \$7700).—Joanne Clay

Flexible Triggering An Issue?









Get the Ultimate in Flexibility and Speed!

Preview Of Trigger Settings

-995.000nS

- Operate With Independent Trigger and Timebase Settings for Each Plug-in.
- 200 MegaSamples per second
- Real Time Functions
- Zoom to x256
- Floppy Disk Storage
- PC Software
- · Downloadable Software Programs

Flexibility — With Nicolet's 4180 plug-in and 4094C Digital Storage Oscilloscope, you can take the guesswork out of triggering. The Trigger View feature gives you a graphic representation of trigger slope, level and sensitivity superimposed on the actual trigger input signal. What this means for you is easy and accurate trigger setting. Using the 4094C with two 4180's allows four input channels with each two-channel plug-in having its own independent time base and trigger settings. That's flexibility!

Speed — Wideband input amplifiers allow you to capture signals up to a 100MHz bandwidth at digitizing speeds up to 200 MegaSamples per second.

Support — All this with unequalled factory support. As a user, your questions are answered quickly without the need for customer account numbers or other qualification.

Write or give us a call!

Nicolet

INSTRUMENTS OF DISCOVERY

Nicolet Test Instruments Division

-130.0000mV



value-packed

dc to 3GHz

- less than 1dB insertion loss over entire passband
- greater than 40dB stopband rejection
 5 section, 30dB per octave roll-off
 VSWR less than 1.7 (typ)
- over 100 models, immediate delivery
- meets MIL-STD-202
- rugged hermetically sealed package (0.4 x 0.8 x 0.4 in.)
- BNC, Type N, SMA available

setting higher standards

finding new ways.

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500
Fax (718) 332-4661 Domestic and International Telexes: 6852844 or 620156


LOW PASS	Model	*LP-	10.7	21.4	30	50	70	100	150	200	300	450	550	600	750	850	1000
Min. Pass Ban			10.7	22	32	48	60	98	140	190	270	400	520	580	700		900
Max, 20dB Stop Frequency (MHz)				32		70				290	410	580	750	840	1000	1100	1340
Prices (ea.): P	Prices (ea.): P \$9.95 (6-49), B \$24.95 (1-49), N \$27.95 (1-49), S \$26.95 (1-49)																

HIGH PASS	Model	*HP-	50	100	150	200	250	300	400	500	600	700	800	900	1000
Pass Band (MHz	.\	start, max.	41	90	133	185	225	290	395	500	600	700	780	910	1000
Pass Band (IVITIZ	-)	end, min.	200	400	600	800	1200	1200	1600	1600	1600	1800	2000	2100	2200
Min. 20dB Stop I	Frequenc	y (MHz)	26	55	95	116	150	190	290	365	460	520	570	660	720

Prices (ea.): P \$12.95 (6-49), B \$27.95 (1-49), N \$30.95 (1-49), S \$29.95 (1-49)

*Prefix P for pins, B for BNC, N for Type N, S for SMA example: PLP-10.7

C105 REV D



tough attenuators

one-piece design defies rough handling from (1-49)

- Each unit undergoes high-impact shock test
- Unexcelled temperature stability, .002 dB/°C
- 2W max. input power (SMA is 0.5W)
- BNC, SMA and N models (TNC, consult factory)
- Immediate delivery, one-year guarantee
- 50 ohms, dB values,

1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 12, 15, 20, 30, and 40

- 75 ohms dB values, 3, 6, 10, 15, 20 BNC only
- Price (1-49 qty.)
 CAT (BNC) \$14.95
 NAT (N) \$19.95

finding new ways ... setting higher standards

Mini-Circuits

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 Domestic and International Telexes: 6852844 or 620156

*Freq. (MHz)	Atten. Tol. (Typ.)		nange, (Typ.) req. Range	VSWR (Max.)				
		DC-1000	1000-1500	DC-1000 MHz	1000-1500 MHz			
DC-1500 MHz	±0.3	0.6	0.8	1.3	1.5			
*DC-1000 MHz	(all 75 ohm o	or 30 dB mo	odels) DC-5	00 MHz (all 40 d	B models)			

Model Availability


SAT (SMA) CAT (BNC) NAT (N)
Model no. = a series suffix and dash number of attenuation.
Example: CAT-3 is CAT series, 3 dB attenuation.

Precision 50 ohm terminations only \$7.95 (1-24) DC to 2 GHz, 0.25W power rating, VSWR less than 1.1 BNC (model BTRM-50), TNC (consult factory) SMA (model STRM-50), N (model NTRM-50)

C 92 REV. D

27

When You Need Toshiba Is



A Single Source, The One.

FLOPPY DISK DRIVES.

With our Universal Installation Kit you can easily fit our 3.5", 1 or 2 megabyte floppy in the slot

where a 5.25" drive used to go. But if a 5.25" is what you really want,

then you've got plenty of options there too.







We shipped the world's first optical drive back in 1981. And with our choice of 5.25" or 12" WORM drives and our half-high CD-ROM, we're still light years ahead.

QUALITY PRODUCTS WITH QUALITY SUPPORT.

Floppy, optical or Winchester, you'll find the quality drives you need at Toshiba. Along with J.I.T. delivery, complete technical support and full service. Because, it's doing it all that's made

TOSHIBA

doing it all that's made us the best single source drive supplier around.

To find out how good a source we can be for you, call us at 1-800-456-DISK.



WINCHESTER DISK DRIVES.

Toshiba Winchester drives are available in 3.5", 5.25" and 8" diameters. With the speeds, capacities and interfaces for almost any application.


In Touch with Tomorrow

TOSHIBA

TOSHIBA AMERICA, INC.

Disk Products Division, 9740 Irvine Blvd., Irvine, CA 92718

CIRCLE NO 111



Anything this system can think of,

Now there's a family of test systems that will change the way you think about Analog VLSI testing.

Torrely me's revolutionary A 500. The only


The system on the left thinks up new device designs so fast that most test systems can't keep up with it. Except the one on the right.



Teradyne's revolutionary A500. The only system that's ready to test the most complex "system silicon" devices as fast as you can dream them up. In fact, the A500 is already helping many leading companies cut critical product development time and bring their advanced products to market faster, and with a lower overall cost to test.

Now, you can test anything from standard linear to mixed-signal AVLSI.

Teradyne has taken its revolutionary A500 architecture and created two new, compatible systems. The A510, a workstation-based standard linear tester, with the lowest cost



this system can test.

to test per test head, and the A520, which packs all the performance of an A500 into a smaller footprint at a lower capital cost. Teradyne's new A500 family not only gives you the capability to test the range of today's devices, it's ready to help you test tomorrow's devices, as well.

The A500 family shares an architecture based on today's "open systems" standards—dual Sun computers, a UNIX operating system, powerful C-based IMAGE™ software and Ethernet TCP/IP networking. In addition, each system provides full tester simulation on stand-alone workstations, with graphic debug and analyzer tools as powerful as any CAD/CAE tools.

Spend your time testing designs instead of designing tests.


If you want to help your company bring nextgeneration products to market faster, prevent premature product rollouts and cut test engineering costs drastically, use the system on the left. Which can only lead you to the system on the right.

For more thoughtful details, call Beth Sulak at (617) 482-2700, ext. 2746. Or call your nearest Teradyne sales office or write: Teradyne, Inc., 321 Harrison

Avenue, Boston, Massachusetts 02118.



International Series Approved! Linear Power Supplies Supplies



UL File No. E104173 CSA Certification No. LR81336 TUV License No. R88104-6

- World-wide AC input capability 100/120/220/230/240 VAC, 47-63 Hz.
- · World-wide safety standards.
- Single, dual, and triple outputs.
- Tight regulation: 0.05% line & load.
- Built-in OVP on 5V output: Optional OVP for 12V, 15V, 24V outputs.
- Overload protection with automatic recovery.
- Remote sense on main outputs.
- 100% burn-in.
- · Two year warranty.

If you have a custom design, call us. Also ask us about our DC-DC and switcher lines.

For further information, contact:



ELECTRONICS CORP.

2380 Qume Drive, Suite A San Jose, CA 95131 (408) 434-0877 Fax # (408) 434-0539 Telex 279366

SIGNALS & NOISE

Thermocouple misconceptions are common

Jim Williams's fine article "Clever techniques improve thermocouple measurements" (EDN, May 26, 1988, pg 145) is sadly flawed by a basic misunderstanding of the physics of thermocouples. It is a common misconception that the voltage of a thermocouple is generated across the junction. This is simply not true. The voltage is generated along the wires and is driven by the temperature difference between the sensing junction and the reference ("cold") junction. For a given temperature difference, the two dissimilar wires generate unequal voltages. The voltage appearing across the thermocouple circuit at the reference junction is the difference between these unequal voltages.

The more technical explanation is that for a given temperature gradient dT/dx, an electric field dV/dx is generated. This electric field is a function of both dT/dx and absolute temperature. The local value of the difference dV/dT for a given alloy pair at a particular temperature is called the Seebeck coefficient. If the integral of the Seebeck coefficient is evaluated between the sensing junction and the reference junction, the thermoelectric voltage results.

Thermal voltages in thermocouple circuits are always the result of thermal gradients. If a section of a thermocouple circuit has an unknown or undesirable Seebeck coefficient, then its influence can be diminished by suppressing thermal gradients in that section. For example, when you make a connection in a thermocouple circuit, it's best to thermally anchor each of the wires to a common temperature before they reach the electrical connection point. The connection point should also be thermally anchored to this temperature. This procedure tends to suppress thermal gradients across the oxides, unknown alloys, etc, that make up the connection. If the thermal gradients are suppressed, spurious thermal voltages will be reduced.

I hope this explanation will help clear up some of the misconceptions about the physics of thermocouples. Jim Williams is not alone in his misunderstanding—I have seen a remarkably similar treatment of thermocouples in a high-school physics text that is currently being used by the Denver School Dept. Bill Dubé

Mechanical Engineer Denver, CO

Jim Williams responds:

Some friends and I have reviewed Bill Dubé's comments and found them to be quite correct. As such, I find myself corrected, educated, and apologizing for any confusion I may have caused EDN's readers. Although Bill's distinctions are subtle, they are still the more correct interpretation, and I appreciate his remarks.

Circuits cannot live by breadboarding alone

I must take issue with the impression created by both Jim Williams's guest editorial "Should Ohm's law be repealed?" (EDN, March 3, 1988, pg 47) and Forrest M Mims III's supporting letter "CAD systems can't replace breadboards" (EDN, May 12, 1988, pg 32). Both Williams and Mims seem to long for a return to pre-CAE days.

Analog-circuit simulation must be used in conjunction with bread-boarding. Neither is sufficient on its own. How many times has an engineering breadboard functioned correctly, meeting all performance specifications (even over temperature), and then a team of engineers has had to "live" in the assembly line because the first production boards couldn't be built? CAE is simply the only viable method we have of performing worst-case, tolerance, and stability analysis in an economic and timely fashion. Sometimes the



PROOF THAT THE TOP NAME IN POWER SUPPLIES PUTS THE BIGGEST IDEAS INTO THE SMALLEST PACKAGES.

Just look at our powerful DC-DC converters, packaged in one of the market's smallest footprint.

Thanks to some big ideas, bright minds, and an advanced production technique or two, the Astec line of DC-DC converters gives you the high-performance you'll need to power your best ideas.

Plus You Can Keep A Low Profile.

With a total height of only 0.4 inches, Astec's DC-DC converters deliver an impressive 5 watts per cubic inch. All with a 400 KHz switching frequency. Not to mention our rugged ceramic hybrid, 100% surface mount construction, high efficiency (typically 80%), and a MTBF of over 684,000 hours. And, they're easy to mount and fit perfectly in rack systems.

Best of all, there's almost certain to be an Astec DC-DC converter to fit your exact needs. We make versions in single, dual, and triple output combinations, which makes them ideal for a wide range of uses—especially telecommunications, industrial, and distributed power applications.

Sometimes, Bigger Is Better.

At Astec, our manufacturing capability can exceed 4 million power supplies per year. That's one reason why we've sold more power supplies than any company anywhere (15 million at last count). Another reason is our efficient production that keeps costs down and quality up.

Then there's our U.S. headquarters in the heart of the Silicon Valley, where we provide sales, engineer-

ing, and service around the nation. So all you supply is the need. And we'll supply the power—exactly what you want.


To find out more about The Real Power, or to locate the distributor nearest you, call Astec now: 800-7AS-TEC7, ext. 11. Or write: Astec USA, 2880 San Tomas Expressway, Santa Clara, CA 95051; (408) 748-1200.

Because when it comes to DC-DC converters, the biggest ideas are now available in the smallest packages.



33

DATA ACQUISITION: 20 MHz for < \$1500!



GOLEM's Plug-In Board and Software Provides Your IBM Compatible PC with these Capabilities:

Digital Storage Oscilloscope Spectrum Analyzer Front End to 1-2-3 and Other Packages

Features:

- Two Channels on Monitor (Hercules, CGA, EGA, VGA) 20 MHz (40 MS/sec)—Single Channel 10 MHz (20 MS/Sec)—Two Channel
- Two Independent Cursors
- All Setups from Keyboard or File
- Programmable Retrievable Test Routines
- Trigger Modes: Auto, Ch 1/Ch 2, Ext. TTL
- · Arithmetic, Integration, Differentiation, Mean + RMS, FFT—Selectable Windows
- Output to Standard Printers and as ASCII Files
- Available with 4K, 16K, 128K Buffers
- Hot-Line Tech Support

(800) 942-1441 Call for orders or more information Master Card and VISA honored

GOLEM Golem Systems
1526 Holly Ct., Thousand Oaks, CA 91360

SIGNALS & NOISE

worst possible scenario is the one in which the breadboard works!

An analog engineer must be capable of using all the tools available in a balanced and thoughtful way. Only the judicious use of CAE together with physical breadboarding will result in robust, produceable circuits.

Philip E Teicher Vice President of Engineering MICRA Corp Hauppauge, NY

(Ed Note: Jim Williams's editorial clearly stresses the use of breadboards and CAE tools instead of blind reliance on CAE tools alone.)

Sorry, this one's taken

I'd like to inform you of the inadvertent use of our registered trademark within a listing for another company's product in EDN's New Products section (May 26, 1988, pg 257). The paragraph used the phrase "C Executive" to describe a part of Microware Systems Corp's C compiler control program that calls each successive phase of the compiler. In fact, "C EXECUTIVE" is a registered trademark for our realtime, multitasking operatingsystem kernel, which currently runs on 15 architectures, including everything from the 8080 to the Clipper. It has frequently been mentioned in the New Products section of EDN and in other trade magazines.

Edward J Rathje Vice President JMI Software Consultants Inc Spring House, PA


WRITE IN

Send your letters to the Signals and Noise Editor, 275 Washington St. Newton, MA 02158. We welcome all comments, pro or con. All letters must be signed, but we will withhold your name upon request. We reserve the right to edit letters for space and clarity.



NEW! KEPCO/TDK LOW-COST, MINIATURE, LOW-PROFILE a-c TO d-c SWITCHING MODULES.


SERIES FMP, FCP, ECM POWER SUPPLIES




Specification	Condition	FMP, FCP	ECM		
Voltage		85-132V a-c,	110-170V d-c		
Current (rms typ)	At 120V a-c	3W: 0.08A 10W: 0.25A	0.5A		
	At 85V a-c	3W: 0.1A 10W: 0.35A	0.6A		
Fuse value		External 125V Internal fuse recom. Wire le 3W: 125V, 20.16A ~ 1.6A 10W: 1A~8A			
Frequency		47-440Hz			
Switching frequency		80~300KHz (depending on load)	35 ~ 185KHz (depending on load)		
Brownout voltage	Low operating limit	80V a-c/	105V d-c		
Initial turn-on surge, first ½-cycle	120V a-c, rated load 25°C cold start	16A max	20A max		
EMI	Conducted	FCC Class B			
Leakage current	At 25°C, (UL method)	0.5mA r	ms max		
Startup time	25 °C, nom input, max load	100msec 50msec to reach 90% nom.			
Holdup time	25 °C, nom. input, max load	20mse	ec min		
Circuit type		FMP: flyback FCP: Output #1 flyback Output #2: flyback plus linear post	Output #1: flyback Outputs #2 & #3: flyback plus linear post		

GENERA	A SEASON .					
Specification	Condition	FMP, FCP	ECM			
Temperature	Operating	0-50°C;	0-40°C			
		See Fig. 1	See Fig. 2			
	Storage	- 40 °C to 85 °C				
Humidity	Operating & storage	95% RH non-c				
Shock	non- operating	20 g per ½ sine pulse, 3 sho ±5 msec do	ak, ocks each axis uration			
Vibration	non- operating		10mm amplitude cceleration each axis			
Isolation	Output to ground	500V d-c, 100N	IΩ, 1 min			
Dielectric strength	Input/ output to gnd	2KV a-c, 1	min			
Dimensions	inch:	3W: 2.17 x 1.97 x 0.75 10W: 2.17 x 3.15 x 0.75	3.6 x 4.72 x 1.2			
mm:		3W: 55 x 50 x 19 10W: 55 x 80 x 19	91.5 x 120 x 32.			
Weight	ounces/ grams	3W: 2.82/80 10W: 3.53/100	13/370			
Mounting (see dwg)		2 blind-threaded brass inserts 4-40	2 surfaces; 4-40 thread			
Max screw penetration	inches/mm	0.24/6				
Connectors		AMP Faston series 187 or equivalent	Barrier strip (M3; gnd M4			
Safety		UL 478 recognized CSA 1402 certified				
Package material		Plastic Chassis UL 94V-1 or Cover: (94V-0 steel, plated, chromate				
Type of construction		Unencapsulated, repairable	Printed circuicards, enclose			

Specification	Source	effect	Load 6	effect	Tempe		Combine	ed effect	Time effect	Recovery chi (50 to 100%		Overvoltage protection
Condition	min-in	max put	10-10 loa	0.00	0-5	0°C	Source & te	A CONTRACT OF THE PARTY OF THE	½ hr-8hr max	Excursion	Recovery to within	
	typ	max	typ	max	typ	max	typ	max			±1%	
FMP, FCP	0.1%	0.5%	0.8%	2.0%	1.0%	3.0%	± 1.0%	± 3.0%	0.5%	< ± 4%	<1msec	zener diod
ECM Output #1	0.5%	1.5%	1.0%	3.0%	1.5%	3.5%	± 2.0%	± 4.0%				
Outputs #2 & #3	0.5%	1.5%	0.5%	1.5%	1.0%	3.0%	± 1.5%	± 4.0%	0.5%	< ± 4%	<2msec	NA







SERIES FMP

These are plastic encased (not encapsulated) 3- and 10-Watt, single output a-c to d-c flyback voltage stabilizers, producing 5V, 12V, 15V or 24V.

Output is adjustable $\pm\,10\%$. Voltage is limited by a zener diode across the output. Current is limited with a rectangular OC characteristic so that units may be connected in series and in parallel, and can drive both capacitive and nonlinear loads.

SERIES FCP

These are plastic encased (not encapsulated) 3- and 10-Watt, flyback a-c to d-c switchers producing a dual output (\pm 12V or \pm 15V).

The principal (plus) output is adjustable \pm 10% of nominal, and the auxiliary (minus) output tracks it with an accuracy of \pm 2% using a 3-terminal (linear) regulator. Both outputs have a rectangular current limiter to protect against overloads.

SERIES ECM

These are triple output, 16 Watt, metal enclosed power supplies featuring simplicity and high reliability. Their principal output is stabilized by a flyback switching circuit, while their auxiliary outputs employ linear post regulators for stabilization.

85-132V (brownout operation down to 80V a-c); input d-c range is 110-170 (nominal 145). Because of an input bridge rectifier, the d-c may be applied to the inputs with either polarity. Input EMI filters attenuate conducted noise to below limits of the FCC Class B (0.45-30MHz.,

In all models, input a-c range is



48dB max.)


SINGLE C	OUTPUT PL	ASTIC EI	NCASE	D SERIE	ES FMP		
Specification	Output	Voltage	Output current	Current	Ripple (source & switching)	Noise (spike)	Efficience
Units	Vo	Its	Amps	Amps	mV	mV	percen
Condition	Factory set, nom input, max load 25°C	Adjustment range	0-50°C	Setting at 25 °C nom input	Nom input max load p-p max	d-c to 50MHz nom input, max load p-p max	Nom inp max loa typ
3 WATT MO	DDELS						
FMP 5-0.6K	5.1	4.5- 5.5	0-0.6	0.7 ~ 1.2	50	100	68
FMP 12-0.25K	12.1	10.8-13.2	0-0.25	0.3 ~ 0.5	80	150	70
FMP 15-0.2K	15.1	13.5-16.5	0-0.2	0.25~0.4	80	150	70
FMP 24-0.13K		21.6-26.4	0-0.13	0.15~0.3	100	150	74
10 WATT N			0 0110				
FMP 5-2K	5.1	4.5- 5.5	0-2.0	2.2 ~ 3.3	50	100	75
FMP 12-0.85K	12.1	10.8-13.2	0-2.0	0.9 ~ 1.4	80	150	78
FMP 15-0.7K	15.1	13.5-16.5	0-0.83	0.75 ~ 1.2	80	150	78
FMP 24-0.45K	24.1	21.6-26.4	0-0.7	0.75 ~ 0.8	100	150	81
						100	01
DUAL OU	TPUT PLA	STIC ENC	ASED	SĘRIES	FCP		
Specification	Output V	oltage	Output	Current limit	Ripple (source & switching)	Noise (spike)	Efficien
Units	Volt	s	Amps	Amps	mV	mV	percer
Condition	Factory set, nom input, max load 25°C	Adjustment range	0-50°C	Setting at 25°C nom input	Nom input max load p-p max	d-c to 50MHz nom input, max load p-p max	Nom inp max loa typ
3 WATT MO	ODELS						
FCP 031K							
Output #1	+ 12.1	10.8-13.2	0-0.12	0.14~0.25	80	150	64
Output #2	- 12.1 ⁽¹⁾	(2)	0-0.12	0.14~0.25	00	150	04
FCP 032K							
Output #1	+ 15.1	13.5-16.5	0-0.1	0.12~0.2	80	150	64
Output #2	- 15.1 ⁽¹⁾	(2)	0-0.1	0.12~0.2	00	150	04
10 WATT N							
	IODELO						
FCP 101K	. 10.1	10 9 12 2					
Output #1	+ 12.1	10.8-13.2	0-0.4	0.45 ~ 1.0	80	150	77
Output #2	- 12.1 ⁽¹⁾	12)					
FCP 102K		105 105					
Output #1	+ 15.1	13.5-16.5	0-0.32	0.35~0.9	80	150	77
Output #2	- 15.1 ⁽¹⁾						
(1) Output #2 is ±2	2% of the Output #1	setting. (2) O	utput #2 traci	ks ±2%.	Alexander and	ALL THE	
TRIPLE C	OUTPUT ME	TAL ENC	LOSE	SERIE	SECM		
Specification	Output		Output current	Current	Ripple (source & switching)	Noise (spike)	Efficiend
Units	Vo	Its	Amps	Amps	mV	mV	percen
Condition	Factor nom i	ry set, nput,	0-50°C min max	Setting	Nom input max load p-p max	d-c to 20MHz nom input, max load p-p max	Nom inp max loa typ

Specification	Output Voltage	Output	Current limit	Ripple (source & switching)	Noise (spike)	Efficiency
Units	Volts	Amps	Amps	mV	mV	percent
Condition	Factory set, nom input, max load 25°C	0-50°C min max	Setting at 25°C nom input	Nom input max load p-p max	d-c to 20MHz nom input, max load p-p max	Nom inpu max load typ
16 WATT MOI	DELS					
ECM 021K-CB						
Output #1	+ 5	0.5 2.0	2.2	120	2% of	
Output #2	+ 12	0.0 0.3	0.4	60	output	67
Output #3	- 12	0.0 0.2	0.3	60	+ 50mV	
ECM 022K-CB			March 1			
Output #1	+ 5	0.5 2.0	2.2	120	2% of	A. S. T
Output #2	+ 15	0.0 0.3	0.4	60	output	67
Output #3	- 15	0.0 0.2	0.3	60	+ 50mV	


Contact factory for OEM discounts

OUTLINE DIMENSIONAL DRAWINGS

3 WATT MODELS FMP/FCP




10 WATT MODELS FMP/FCP



NOTES:

- 1. Material: phenylene oxide.
- 2. Dimensions in parentheses are in millimeters, others in inches.
- 3. Tolerance: ± 0.03 (± 0.7) unless noted otherwise.
- 4. AC & DC terminals: 0.187 inch series tabs.
 5. AC & DC mating receptacles: AMP, Inc., Faston 187 series or equivalent.
 6. Maximum mounting screw penetration: 0.24 (6).

16 WATT MODELS ECM



Weight: 13 oz. (370 grams) Max.

NOTES:

- 1) Dimension in parentheses are in millimeters, others are in inches.
- 2) Tolerances: ±0.015 (0.4mm) between mounting holes; ±0.03 (\pm 0.7 mm) all other dimensions.
- 3) Mounting screw penetration: 0.24 (6mm) maximum.
- 4) Material and finish: A) Chassis: 1mm steel,
 - cadmium plated, yellow chromate wash
 - B) Cover 0.5 mm steel, cadmium plated, yellow chromate wash.



Data subject to change without notice. c 1988 KEPCO, INC. Litho in U.S.A.



FINALLY, A SYSTEM THAT MEASURES UP. THE XD/P HIGH DENSITY CONNECTOR SYSTEM.

Now you can get higher density and higher performance in all of vour board-to-board interconnections. Our XD/P™Extended Density/Performance two-piece PCB connector system offers you benefits that you just can't get with other connectors.

For example, our Flex-Fit™ double compliant pin contact provides a solderless, gas-tight pressure termination between pin, multilayer hole plating and internal circuits. This means faster installation, reduced assembly costs and front and rear repairability.

In addition, our unique dualopposing beam female receptacle contact provides superior contact wipe and depth engagement.

New, state-of-the-art materials coupled with superior molding

capability help produce the tightest end-to-end tolerance in the business. All this while maintaining full signal integrity of fast

switching logic systems and low insertion/ extraction force (typically 1.5 oz./0.5 oz.). You can control impedance by selecting the length, type and placement of the contacts.

HIGH DENSITY PLUS HIGH **PERFORMANCE**

The XD/P[™] two-piece high density connector system also provides for all types of packaging/ system designs.

Standard designs include three and four rows of contacts on

a .100" grid, in one-, two- or three-cell configurations with as many as 684 positions. Also offered are eight contact styles and 16 plating options.

In addition to pin and receptacle connector assemblies, we offer backplane shrouds, hardware, accessories, and a complete application tooling package, from simple hand tools to fully automated presses.

The XD/P™ high density connector system lets you expand your imagination. See how it measures up. To get our new XD/P^{-1} system catalog, simply write or call: Thomas & Betts Corporation, Electronics Division, 1001 Frontier Road, Bridgewater, NJ 08807; (201) 685-1600.



Flex-Fit™ double compliant contact



Save nanoseconds on logic.



And months on design.

Logic Automation's model cell library now contains all RCA Advanced CMOS Logic circuits. Any other approach to logic design is a waste of time.

You know the advantages of CMOS, such as low power dissipation, high noise immunity and wide operating temperature range.

And you probably know that AC/ACT logic adds a new dimension to CMOS: advanced speed.

But you may not know that this faster logic can now be designed-in much faster.

System-level AC/ACT simulations.

RCA AC/ACT is the first advanced-speed CMOS logic to have all its circuits (more than 100 and growing rapidly) available as SmartModels[†] in Logic Automation's library.

These sophisticated behavioral-level models don't need the computing power of a mainframe. So you can use them on just about any popular engineering workstation.

But what really sets SmartModels apart is their technique of Knowledge-Based Design Verification. Each model has been worked on by engineers and systems designers who know the design problems you're most likely to encounter when using parts from the AC/ACT library.

If any of these errors does occur, it is immediately pinpointed. You get the exact time, location and nature of the problem.

All circuits are checked for timing (including setup, hold, frequency and pulse width), and usage (specific checks for each device).


The result is far less prototyping. Which means savings of months. And thousands of dollars.

A new world of design possibilities.

RCA AC/ACT gives you the speed of FAST.*

But power dissipation and idling power are small fractions of FAST ICs.

So, for example, you can design a computer that doesn't have a cooling system. Or a sealed system to prevent dust problems. Or dramatically reduce your system's size.



System-level simulations eliminate the need for prototypes, saving time and money.

In addition, AC/ACT gives you latch-up and ESD protection. All this at FAST prices.

And these circuits are available in Military/Aerospace versions for the most demanding applications.

Start saving time on both logic and design right now, by calling toll-free 800-443-7364, ext. 29.

Or contact your local GE Solid State sales office or distributor.

In Europe, call: Brussels, (02)246-21-11; Paris, (1) 39-46-57-99; London, (276) 68-59-11; Milano, (2) 82-291; Munich, (089) 63813-0; Stockholm (08) 793-9500. †SmartModel is a registered trademark of Logic Automation, Incorporated.

*FAST is a trademark of National Semiconductor Corporation.

General Electric Company, U.S.A.





The Great 16-bit Solution! Car CDs Disk Drives Auto ECU 277 Automotive OKI 1-800-223-8266 Network ISDN OKI 1-800-223-8266 OKI Telecomm Bar Code Reader 1-800-223-8266 OKI 1-800-223-8266



From OKI system technologies, the solution for high-end multitasking applications.

Call on OKI **NXC**, and you move that tough multitasking application into the next generation of microcomputing. It's the performance of tomorrow — available today, with OKI's new 66301 MCU. The industry's first core-based 16-bit CMOS controller. Our first **NXC** solution.

OKI system technologies have implemented a true macro-cell approach with the 66301. Essentially a static part, this MCU presents a whole new level of integration. On board, in addition to the 16-bit CPU: 16K bytes of ROM (48K bytes external). 512 bytes of built-in RAM (512K bytes external).

You also get four 16-bit timers, 2 PWMs, plus a watchdog timer. And a rich range of instructions, including special instruc-

tions for word-length multiplication and division.

Now add in an 8-channel, 10-bit A-D converter and a baud rate generator, with variable bit length operations and context switching. On a single chip, our revolutionary macro-cell design packs far more options, capabilities and sophisticated functions than any 16-bit industry standard can now offer.

With the 66301 on line (and an E² version available soon), OKI's exclusive **NXC** introduces a new generation of high-level integration — for your most demanding automotive, telecomm and instrumentation system requirements.

16-bit development solutions

OKI's total commitment to development ease and support gives you a headstart in **NKC** microcomputing.

We can provide a special development version of the 66301 chip — built to accept an EPROM piggyback. To check out your design in realtime, snap on your coded



memory. This allows you to keep burning code variations into inexpensive EPROMs, until you get a working prototype ...at a very minimal cost.

Of course, OKI's 66301 MCU is solidly backed with a full-scale development system. For realtime in-circuit emulation (ICE), use the **NXC** EASE system. The portable EASE package includes your ICE hardware,

user's manual, plus complete assembler and debugger software for both MSDOS and VMS. With a compatible high-effi-

ciency C-Compiler option as well. All available from OKI. All part of the NXC solution to highend multitasking applications, produced by the most system-oriented technologies in the field today.



16-bit Solutions - on call.

- Please send complete technical data on the NXC 16-bit CMOS MCU solution produced by OKI system technologies.
- () Call me, I have immediate requirements.
 Tel:(____)

Name

11110____

Company

Please clip coupon to business card or letterhead and return to: *NXC Customer Service*, OKI Semiconductor, 650 N. Mary Ave., Sunnyvale, CA 94086. (408) 720-1900.

EDN090188



CIRCLE NO 48

Tight Schedule? Complex Project? Tough Problems?

Add MicroDimensions to Your Team

Let MicroDimensions assist you — with complete hardware and software development services.

- We can help you with part of a project you prefer not to handle or all of the job from start to finish
- Hardware design facilities include a complete electronic design lab including CAD design tools & PC layout
- Software development capability in a wide range of languages, environments, including VAX/VMS, and the 68xxx family
- System integration services include system design, prototyping, assembly and testing
- Our specialties include VME, MAP, communications, and process control. We have extensive servo experience
- We are proud of our proven record of performance on schedule, within budget
- A prestigious client list including many Fortune 100 companies


For a corporate brochure contact Bruce R. Knox, President



MicroDimensions, Inc.

7345 Production Drive Mentor (Cleveland), Ohio 44060 Phone: (216) 974-8070 • FAX: (216) 974-1648

CIRCLE NO 18



Dry Desert to Wet World

Survival! That's what you can expect from OTTO precision snap-action pushbutton switches. Sealed to survive the rigors of industrial, commercial and military applications, these switches are available in momentary and alternate (push-on, push-off)

action, miniature and subminiature sizes, choice of front panel appearance and button colors.

Sealed against dirt and water. Electrical ratings from computer level to 10 Amperes. Contact resistance < .025 ohms.

OTTO.

CONTROLS Division, OTTO ENGINEERING, INC.

2 East Main Street • Carpentersville, Illinois 60110 • Phone: 312/428-7171 • FAX 312/428-1956 • TELEX: 72-2426

CALENDAR

Modern Electronic Packaging (seminar), Santa Clara, CA. Technology Seminars, Box 487, Lutherville, MD 21093. (301) 269-4102. September 7 to 9.

International Test Conference, Washington, DC. Doris Thomas, ITC, Box 264, Mount Freedom, NJ 07970. (201) 267-7120. September 12 to 14.

Worst-Case Circuit Analysis (seminar), Boston, MA. Design and Evaluation, 1000 White Horse Rd, Suite 304, Voorhees, NJ 08043. (609) 770-0800. September 12 to 14.

C Programming Workshop (short course), Seattle, WA. SSC, Box 55549, Seattle, WA 98155. (206) 527-3385. September 12 to 15.

12th International Fiber Optic Communications and Local Area Networks Exposition, Atlanta, GA. Information Gatekeepers, 214 Harvard Ave, Boston, MA 02134. (800) 323-1088; in MA, (617) 232-3111. September 13 to 16.

Unix Hands-on Workshop (short course), Montreal, Canada. Integrated Computer Systems, Box 3614, Culver City, CA 90231. (800) 421-8166; in CA, (213) 417-8888. September 13 to 16.

Troubleshooting Microprocessor-Based Equipment and Digital Devices, Atlanta, GA. Micro Systems Institute, 73 Institute Rd, Garnett, KS 66032. (800) 247-5239; in KS, (913) 898-4695. September 19 to 22.

Unix Hands-on Workshop (short course), Washington, DC. Integrated Computer Systems, Box 3614, Culver City, CA 90231. (800) 421-8166; in CA, (213) 417-8888. September 20 to 23.

34th IEEE Holm Conference on Electrical Contacts, San Francisco, CA. IEEE Holm Conference Registrar, 345 E 47th St, New

BREAKTHROUGHS IN POWER,

SPEED AND **VOLTAGE ...**



HIGH VOLTAGE

PA85/PA88

- MOSFET Technology
- 450 Volts
- 1000V/µsec Slew or 2mA IQ



HIGH SPEED

PA19

- 900V/µsec
- 4A/±40V
- Thermal Shutoff



- 5000V/µs
- 100MHz
- 400mA



SUPER POWER

PA03

- 1KW
- ±75V
- 30A



For more information, call our Application Hotline... (800) 421-1865

or ask for our NEW AMPLIFIER HANDBOOK!

...176 pages of data and applications information on 23 models.

Describes 65 choices including military versions and high-performance gradeouts.





DEDICATED TO EXCELLENCE

APEX MICROTECHNOLOGY CORP. ● 5980 N. Shannon Rd. ● Tucson, AZ 85741 USA ● (602) 742-8600 BELGIQUE (02) 219.58.62 - CANADA (416) 821-7800 - DEUTSCHLAND (BRD) (06152) 61081 - FRANCE (1) 69.07.08.24 ISRAEL (03) 9233257 - ITALIA (02) 6131341 - NEDERLANDEN 010-451-9533 - NIPPON (03) 244-3511 - NORGE (2)500650 ÖSTERREICH (1) 505-15-22-0 - SCHWEIZ (042) 41 24 41 - SVERIGE (08) 795 9650 - TAIWAN (02) 506-0757 - UK 08446 8781 **CIRCLE NO 46**

Get your hands on the standard: POMONA.

Since 1951 POMONA has grown to become the standard of the industry. And for good reason. Our test products assure honest test results because they are the best you can buy. Specify POMONA and get unsurpassed quality, the broadest product line, the greatest selection, the industry standard.



CIRCLE NO 20

DID YOU KNOW?

Half of all EDN's articles are staff-written.

EDN

CALENDAR

York, NY 10017. (212) 705-7405. September 26 to 29.

Troubleshooting Microprocessor-Based Equipment and Digital Devices, Chicago, IL. Micro Systems Institute, 73 Institute Rd, Garnett, KS 66032. (800) 247-5239; in KS, (913) 898-4695. September 27 to 30.

Unix Hands-on Workshop (short course), San Diego, CA. Integrated Computer Systems, Box 3614, Culver City, CA 90231. (800) 421-8166; in CA, (213) 417-8888. September 27 to 30.

Connector and Interconnection Technology Symposium, Dallas, TX. Electronic Connector Study Group, 104 Wilmot Rd, Suite 201, Deerfield, IL 60015. (312) 940-8800. October 3 to 5.

IEEE International Conference on Computer Design: VLSI in Computers and Processors, Port Chester, NY. Gail Clanton, IEEE, 1730 Massachusetts Ave NW, Washington, DC 20036. (202) 371-1013. October 3 to 5.

Autotestcon, Minneapolis, MN. Steve Palmer, Unisys, 3333 Pilot Knob Rd, Eagan, MN 55121. (612) 456-2349. October 4 to 6.

Buscon/88 East, New York, NY. Conference Management Corp, 200 Connecticut Ave, Norwalk, CT 06856. (203) 852-0500. October 4 to 6.

Electronic Imaging Conference East, Boston, MA. MG Expositions Group, 1050 Commonwealth Ave, Boston, MA 02215. (800) 223-7126; in MA, (617) 232-3976. October 4 to 6.

Power Electronics East, New York, NY. Conference Management Corp, 200 Connecticut Ave, Norwalk, CT 06856. (203) 852-0500. October 4 to 6.

SIEMENS

Announcing a 27 Billion Dollar backer for your Siemens ASIC team.

Siemens, a proven winner in electronics with \$27 billion in sales, just entered the U.S. ASIC market. And our team is geared for the ASIC circuit.

With our first effort, we've combined ECL and CML technology in one gate array family. This means you can now design-in the ideal combination of super ECL speed with economical, high-density CML performance on one chip...everytime. You no longer must compromise the speed you need for the power you don't. In addition, speed/power programming, as well as I/Os designed for both ECL 10K/100K and TTL interfaces give you

And that's just the start. Coming down the home stretch are more Siemens entries...1.5/1.2 micron CMOS standard cells and 1.2/1.0 micron CMOS sea of gates arrays. Use our sea of gates CMOS family for quick turn logic and memory on one chip or design your high-performance, cell-based ASICs utilizing the common

ADVANCELL™ ASIC library and guarantee yourself compatible second sources.

The Siemens ASIC team's responsive service and technical innovation provides you with the winning edge.

For more information on how to put your design into high gear write to Siemens Components, Inc., ASIC Marketing, 2191 Laurelwood Road, Santa Clara, California 95054. Or call ASIC Marketing at 408/980-4568, and see for yourself how Siemens is making the difference on the ASIC circuit.

Siemens... your partner for the future.

© 1988 Siemens Components, Inc. ADVANCELL is a trademark of Siemens AG, or licensed from Toshiba or General Electric Co., USA in certain countries.

CIRCLE NO 47

Siemens



At about strange things happen to

As rise times approach 3ns, all cable/ connector assemblies become transmission line assemblies.

But not necessarily good ones.


Newer, faster logic families require controlled impedance cable assemblies. Designed for high-speed performance. Engineered for controlled impedance and propagation rate. And manufactured for absolute conformity to specifications.

Creating controlled impedance assemblies to these standards demands extensive CAD/CAE use. Plus a wide range of specialized connector choices. Plus the capability to custom design quickly. Plus intimate knowledge of the various termination techniques, including advanced wire attachment techniques.

Our people are equipped to work







t_r=3ns, ordinary cable assemblies.

with you early in the design stage to provide an optimum solution to your requirements. We help you determine the characteristics for impedance and propagation velocity that you need to match timing requirements, and the crosstalk figures you have to meet.

We engineer and manufacture controlled impedance assemblies in a way you'll especially appreciate.

Our manufacturing facilities are unmatched in the industry. Every assembly is individually inspected and 100% electrically tested. All work is part of the overall statistical process control system at AMP, and comes under our corporate-wide quality program.

For technical literature and more information on high-speed controlled impedance assemblies—for logic rise times from 3ns down to the sub-nanosecond range—call 1-800-522-6752. AMP Incorporated, Harrisburg, PA 17105-3608.

AMP Interconnecting ideas





LabVIEW Instrumentation Software. Our Users Tell the Story.

EDUCATION

University of Southwestern Louisiana

"LabVIEW is the best single software entity that has been written to date for any computer for any purpose." Dr. John O'Dell, professor of Mechanical Engineering, uses LabVIEW in his course on computer-controlled systems.





AUTOMATED TESTING

Sundstrand-Sauer

With LabVIEW, I have reduced testing time for our control panels from 15 minutes to less than 1 minute." Jay Herman is in charge of testing Sundstrand control panels used on concrete paving machines. A GPIBcontrolled power supply tests the power requirements for these machines. Analog and digital lines on the control panel are tested with the NB MIO-16 board.

PHYSICS

The University of Texas at Austin

"We initially set up our system on a MicroVAX. It took 6 months. With LabVIEW and a Macintosh II, we got it working in a couple of weeks." Azucena Overman, graduate student in the Physics Department, researches the chemical properties of surfaces. In her research LabVIFW controls GPIB instruments and graphs the data collected.

CIVIL ENGINEERING

Stanford University

"LabVIEW is the most flexible data acquisition software I've ever seen-it's also a bit of fun." Dr. Steven Monismith of the Civil Engineering Department uses an experimental pond to research double diffusive systems. LabVIEW and an NB-MIO-16 board measure signals from temperature and conductivity probes in the pond, and control a motor that varies the depth of the probes.

MEDICINE

Sahlgren University Hospital-Sweden

"Without any earlier experience with programming, we were writing our own applications after the LabVIEW 3-day training course." Dr. Anders Ullman uses LabVIEW in clinical pharmacology. Muscle contractions evoked by nerve stimulation or by different drugs are measured via iso metric force transducers with a plug-in analog input board. Each channel is monitored on a LabVIEW strip chart.

OPTICS

Newport Corporation

"LabVIEW is the software system we needed to complement our instruments." Scott Jordan includes LabVIEW with a Newport Optical Power Meter and a Newport Programmable Controller in a laser control system marketed by Newport Corporation.

Raytheon Company

"LabVIEW is the system of choice

for data acquisition." John Day


ments to measure physical proper

capacitance versus frequency and

uses LabVIEW and GPIB instru-

ties of GaAs semiconductors LabVIEW generates graphs of

capacitance versus voltage.



Now...LabVIEW®2.0

Faster, more versatile, and even easier to use.

Graphical Instrumentation Software for Data Acquisition, Analysis, and Presentation.



12109 Technology Blvd. Austin, Texas 78727-6204 512/250-9119 800/531-4742 800/IEEE-488 in Texas

SIMULATION

Engineering Measurements Company

"LabVIEW saved me several months of development." John Waers simulates digital signal processing algorithms with LabVIEW. The algorithms are burned into EPROMs on intelligent flow meters manufactured by Engineering Measurements Company.

National Instruments of Ianan 81 (03) 788-1922 • National Instruments of France (1) 48 65 33 70 • National Instruments United Kingdom 44-01-549-3444 • ARGENTINA 541/46-5776/0628 • AUSTRALIA 61 (3) 879-2322 * BELGIUM 02/735.21.35 * CANADA 416/890-2010 - 613/596-9300 - (514) 747-7878 - 403/295-0822 - (604) 988-2195 * CHILE 56 2253689 * DENMARK 45 02-251122 * FINIAND 358 90-372 144 * FRANCE 33 (1) 69077802 * HONG KONG 852 0-262707 - 852 0-262945 * IRELAND 353 042 72282 * ISRAEL 972 324298 * ITALY 39-2-98491071-2-3 * KOREA (02) 776-3 THE NETHERIANDS 31 070-996360 • NEW ZEALAND 64 09 444-2645 • NORWAY 02-531250 • PORTUGAL 19545313 • SINGAPORE 65 29 11336 • SOUTH AFRICA 27 (011) 787-0473 • SPAIN 34 (1) 455 81 12 • SWEDEN 46 08-792 11 00 • SWITZERLAND 41 65 52 8949 • TAIWAN/THE REPUBLIC OF CHINA 886 (02) 7036280 • THAILAND 66 2349330 • UNITED KINGDOM

EDITORIAL

Spend a lot, get a little



It looks as though preliminary work on the Superconducting Super Collider project will get underway next year. Because scientists describe the project as a 20-trillion electron-volt proton synchrotron, most people just call it the SSC or Super Collider. The project will require a particle-accelerator ring that is about 13 miles in diameter, so the SSC will be large, both in size and cost. Early next year, the Super Collider project will receive \$100 million in seed money; \$16 million is budgeted for equipment, and the remainder is targeted for site selection and day-to-day operations. The seed money may seem like a small amount, but the Department of Energy—the project's sponsor—puts the SSC's final price at over \$5 billion. That figure doesn't include the \$500 million per year necessary to run the project.

For such a big project, however, there has been little public debate within the engineering and science communities about whether we should build this massive device. That's unfortunate, because building the SSC will affect government-funded science and engineering for many years.

On one hand, the SSC's supporters provide promotional literature that describes the Super Collider's construction and operation. The basic premise is that much interesting research will be done at the SSC, and that many practical benefits will "spin off." There is a subtle message here: Our national pride and scientific stature—future Nobel prizes—are tied to this project, so let's do it. Also, backers hope that such a large project will rekindle the public's fascination with science, and that it will draw bright students to scientific careers.

On the other hand, some critics wonder if the project isn't a massive physics and construction relief project. The project would fund research for a small number of particle physicists and would create about 5000 temporary construction jobs. Certainly, equipment and service suppliers would benefit, but spending over \$5 billion on a project that meets the research needs of only a few scientists seems wasteful. Even without the SCC, science will continue to fascinate the public, who has little understanding of subatomic particles. Also, few among us can name even three or four recent winners of Nobel prizes that were awarded for scientific research.

It's safe to assume that the billions of dollars of tax money needed for the SSC must come from other programs' budgets rather than from new tax revenues. So, it's time to decide whether the Super Collider is worth the price. If we must take money from existing and planned projects, let's consider refurbishing and rejuvenating college and university laboratories with it. The payoff would be quick. We'd still be buying equipment, supporting research, and doing some construction. And, we would fortify a broad range of engineering and scientific fields instead of waiting for potential spinoffs from particle physics.



Jesse H Neal Editorial Achievement Awards 1987, 1981 (2), 1978 (2), 1977, 1976, 1975

American Society of Business Press Editors Award 1988, 1983, 1981 Jon Titus Editor

How the fa

7.5 ns PAL Device vs. FAST & AS

tPD

tPD

tLEO

tCO

tS

FAST

8.0

11.0

10.0

8.0

13.0

5.5

11.0

25

10.0

AS .

100

15.0

9.0

60

8.0

5.0

13.5

11.0

SSI/MSI

Combinatorial

Decoder

Register/Latch

Octal Register

Four bit Ctr

Eight bit Ctr

74269/869

74138

74151

Mux

74374

74373 Octal Latch

Counters 74161

Our new 7.5ns PAL® device is fast enough to prove that standard logic shouldn't set the standard anymore.

It's also fast enough to finally let today's new microprocessors run at the speeds for which they were designed—breathtaking.

Raising your standard.

How fast would you like your standard logic?

How about faster than any TTL logic around? Even FAST™ or AS? You've got it with the 7.5 ns PAL device.

And the fact that you can config-

ure it yourself means you can get exactly what you want.

If you want to redesign some-

7.5ns PAL

Device

75

6.5

7.5

7.0

6.5

7.0

thing, you change the PAL device. Not the board.

Not only is this the fastest way to get high speed logic, it's also the most practical. One 75ns PAL device replaces two to six standard TTL devices.

Which cuts down on board size.

And cuts down chances for a device failure.



What to give the microprocessor that has everything.

We suggest the first PAL device that can keep up with it.

The 7.5 ns PAL device runs at 74 Mhz. It can deliver the speed the new high performance microprocessors need.

Processors like the 29K, the 386 and the 68030.

This PAL device delivers 25% more speed than any other PAL device.

We even have the fastest 22V10.

Our 15ns 22V10 runs at 50Mhz. That's 10ns faster than anyone else on the market. And it lets you run at twice the rate of the new 25Mhz microprocessors.

We've been shipping 20 pin 10ns

PAL devices for eighteen months. And now you can get the new 24 pin 10ns PAL device as well.

There's plenty of service and support to get and keep your project moving. And all our fast PAL devices are available in volume when you need them. Now, for example.

For all the facts about our fast PAL devices, drop us a line. Or call us at (800) 222-9323.


Because you can never be too fast.

Advanced Micro Devices A Monolithic Memories

901 Thompson Place, P.O. Box 3453, Sunnyvale, CA 94088.


PAL is a registered trademark of Advanced Micro Devices, Inc. FAST is a trademark of National Semiconductor Corporation. ©1988 Advanced Micro Devices, Inc.

Do you have to design in



HOST

what it takes real-time?



TARGET

Successful real-time design for embedded systems takes more than extraordinary helpings of craft and creativity. It also takes the right tools. Which may explain why our CARD (Computer-aided Real-time Design) technology is behind the development of well over fifty million lines of real-time code.

We're not talking about ordinary tools spruced up with a few real-time extensions. CARD technology was created exclusively for the real-time world specifically for integrating run-time and software development environments.

We are talking about tools such as reusable software components like VRTX,® the real-time operating systems standard. Real-time implementations of C and Ada. Automated analysis tools for verifying system performance. Our CARDtools™ product gives you everything you need including specifically tailored design aids to manage software organization and data flow.


And automated documentation so complete, so accurate, it satisfies even the DoD's rigid 2167A specs. Not to mention the demands of our hundreds of exacting commercial customers.

So if you'd like to have what it takes to make your next real-time project run more efficiently call us, toll free, at (800) 228-1249. Or (214) 661-9526 in Texas.

Because you can only be a success in real-time design if you've got the right stuff.

⋄READY SYSTEMS

Microprocessor Support Made Simple



ow, ZAX simplifies microprocessor design, integration and testing with their advanced line of ERX- and ICD-series emulators. You simply tell us the processor that drives your design and we tailor a development system especially for your environment, including full software support.

Our ERX-series emulators provide over 80 debugging commands, with 256,000 hardware breakpoints, real-time performance analysis, high-level language debug and trace analysis of program execution while you emulate in real-time. And they interface directly to your personal computer (AT-class) to provide you with a complete host development station and emulation manager. This consolidated approach utilizes industry-standard equipment and eliminates the use of a proprietary dedicated chassis.

ZAX established the benchmark for standalone emulation tools when they introduced their versatile line of ICD-series emulators. Completely flexible, ICD-series emulators can be interfaced to either a simple terminal or host computer (from pc to mainframe) depending on your requirements. This makes them ideal for both in-house development and on-site testing.

Simplify support for your microprocessor development projects with the help of ZAX! Call today to arrange a product demonstration or write for complete details about our product line. Call us TOLL FREE at 800-421-0982 (in California phone 800-233-9817) or write to ZAX CORPORATION, 2572 White Road, Irvine, CA 92714.

In Europe, call United Kingdom: 0628 476 741, West Germany: 02162-3798-0, France: (03) 956-8142, Italy: (02) 688-2141.







TECHNOLOGY UPDATE


SCSI host adapters offer superspeed to personal-computer I/O subsystems

Maury Wright, Regional Editor

Personal-computer I/O performance -particularly the disk throughput -has not kept pace with the processing power offered by 80286-, and 80386-based systems. But IBM PC/AT- and Micro Channel-compatible SCSI (Small Computer Systems Interface) host adapters can provide interfaces to the highest performance 54-in. disk drives available. These adapters thus open the door to disk data-transfer rates of 1M byte/sec and faster. Furthermore, a single host adapter can give you a great deal of flexibility by connecting a variety of other peripherals, such as tape and optical-disk drives, printers, scanners, and communication controllers, with your personalcomputer system.

As it evolved out of SASI (Shugart Associates Standard Interface), which was a simple intelligent disk interface, SCSI developed into a truly intelligent universal systems interface. Theoretically, its 8-bit parallel bus can connect with any peripheral. The SCSI specification committee, which is a standing ANSI group, is in the process of defining device command sets for software interfaces to various peripheral types, each of which requires a completely different command set. The committee defined a command set for disk and tape drives several years ago.

Manufacturers of ¼-in.-cartridgetape drives have adopted SCSI as the interface of choice. According to Emulex's product manager Kevin Drum, at least half of the sales of the company's IB02 host adapter for the PC/AT bus have been to customers that use the product strictly as a tape-drive interface. The adapter is



The Micro Channel SCSI host adapter from Future Domain, Model MCS-350, supports both bus POS and arbitration schemes, and is compatible with optical and tape drives as well as disk drives.

currently compatible with the company's dedicated tape and disk controllers. And the company has recently been working to ensure the compatibility of the adapter with tape and disk drives that have the SCSI and its controller embedded. The IB02 costs \$325.

SCSI proliferates

The committee working on SCSI didn't stop with tape and disk command sets. It has also written command sets for optical disks and printers, and for communications between multiple SCSI hosts. In fact, many optical-disk products now use SCSI exclusively. Moreover, the committee plans to eventually write command sets for image scanners, communication controllers, and other devices. A number of companies have already introduced

such products with proprietary command sets that work with the SCSI bus, even though no standard set yet exists.

Integrators and system designers can use a SCSI host adapter as a cost-effective interface to connect as many as seven different peripherals to a personal computer. NCL America, for example, sells its 5109 host adapter for \$95 (100). The product only performs 8-bit host-bus transfers, but it can still outperform typical personal-computer disk controllers.

Data rate is key

While SCSI can give you versatility in the number and types of peripherals your system can use, it can go even further when it comes to disk drives—it can increase disk throughput somewhat dramatically.



Spend ten minutes at the Advantest booth and go beyond VLSI testing.

Enter the world of Advantest Test Systems. A world combining the best of VLSI, memory, burnin and E-beam test systems. A world of absolute system timing accuracy. High quality and reliability. And the most efficient system architecture available today.

Advantest's mature software and system integration, along with complete training and support, puts you in the most sophisticated, trouble-free testing environment in the world. And here's your chance to see it all!

Also see these Advantest test systems!

- T5381 Memory Test System—with our newest handler, the M3811A for ZIPs, SOPs, SOJs and other large device packages. Rest easy with its 200MHz test speed and timing accuracy of ±600ps.
- E1330 E-Beam Test System—integrated capability with a wide range of our VLSI test systems (like the T3313) allows you to probe VLSI weak points quickly and efficiently. Accurate waveform

readings on sub-µm lines make it perfect for your current and future IC testing needs.

- E1231 E-Beam Stand Alone System everything you need in a stand-alone E-beam test system, including advanced DUT chamber for opening up unlimited possibilities of handling devices under test. Perfect for integrating with existing CADs.
- B2150 Burn-in Test System—test during burn-in with this state-of-the-art screening device that simplifies detection of intermittent failures. Ideal for VLSIs, ASICs and large capacity RAMs.

Stop by the Advantest booth at 1988 International Test Conference in Washington, DC on September 12–15.

ITC'88 Booths 1511-1521 and 1610-1620.

ADVANTEST

Advantest America, Inc.

300 Knightsbridge Parkway • Lincolnshire, IL 60069 312-634-2552

TECHNOLOGY UPDATE

Increasing throughput means reducing the time required to transfer data from system memory onto the disk drive, or the time required to transfer data from the disk into system memory. The SCSI specification sets the maximum rate for asynchronous data transfers at 1.5M bytes/sec, and the maximum rate for synchronous data transfers at 4M bytes/sec.

In most MS-DOS-based systems, a combination of a disk's seek time and its data-transfer rate directly determine a disk's throughput (other factors such as multithreading affect disk throughput in multitasking environments like Unix systems and networks). Today most personal computers, even 80386-based systems, come equipped with an ST-506 controller and disk drive.

Average seek times on high-end ST-506 drives have dropped to less than 30 msec. Most ST-506 controllers, however, use MFM encoding that results in a 5M-bit/sec disk data rate. RLL encoded drives are becoming increasingly popular; they can produce 7.5M and sometimes 10M bits/sec (albeit not always reliably).

New drives seek in 20 msec

State-of-the-art drives with embedded SCSI controllers, by comparison, have average seek times of less than 20 msec, and transfer rates ranging from 1M to 1.5M bytes/sec. Granted, the intelligence inherent in a SCSI subsystem does result in a small amount of command overhead not found in ST-506 subsystems. The embedded controller must de-

code SCSI commands, and the consequent overhead can be as much as 5 msec on older drives, but is typically less than 1 msec on newer products. The **box**, "The SCSI advantage," provides an example of how a SCSI system can improve a computer's performance.

Adapter for Micro Channel

IBM recognized the problem of poor disk throughput, and on its high-end Micro Channel personal computers offers an ESDI (Enhanced Small Device Interface) controller and drive. ESDI drives include a data separator and typically generate a 10M-bit/sec serial data stream from the disk drive to the controller. Some new ESDI drives even operate at 15M bits/sec. Other companies, such as Compaq, ship

The SCSI advantage

A number of disk-drive and controller manufacturers and technical publications have run a variety of benchmarks on personal-computer I/O implementations. Unfortunately, different benchmarks yield dramatically different results. To evaluate the SCSI-based disk I/O in a personal computer completely, you should test an I/O subsystem in your intended application. But some simple tests do provide an example of the potential performance of SCSI-based systems compared with ST-506-based systems.

Measuring the time it takes to load a standard set of office-automation programs into memory, for example, is one simple test of disk I/O. I tried loading the Wordperfect Library Shell, Wordperfect 4.2, and the Library companion programs. For a second test, I loaded Windows/286 and the Calendar, Cardfile, Clock, and Control Windows' application programs.

I ran the tests on a 10-MHz IBM PC/AT compatible with an EGA monitor and MS-DOS, version 3.2. I tested two SCSI host adapters, the Adaptec AHA-1540 and the Future Domain TMC-830, and two disk drives, a Maxtor (San Jose, CA) 280M-byte XT3280 drive and a Priam (San Jose, CA) 280M-byte Model 728 drive. For comparison, I tested a Western Digital ST-506 controller with a 40M-byte Micropolis ST-506 drive.

The Maxtor and Micropolis drives specify an av-

erage seek time of 28 msec; the Priam drive specs 20 msec. I conducted all of the tests after a fresh disk format, so the disks held only the test programs. I measured the load times with a manual stopwatch.

Predictably, all combinations of a SCSI host adapter and SCSI disk produced virtually identical results. Using the SCSI components, the computer loaded the Wordperfect programs in times ranging from 2.5 to 2.75 secs (my manual measuring probably accounts for the variation). The SCSI subsystems loaded the Windows/286 program and applications in times ranging from 8 to 9 secs. The system, when accessing the ST-506 controller and drive, required 4 to 4.25 secs to load the Wordperfect test, and 11 to 12 secs to load the Windows test.

Don't just take these figures at face value. The addition of the SCSI components may actually enhance performance more than those figures strictly say. For example, the system spends a some portion of the time required to load Windows/286 and its applications setting up the EGA graphics. So in the Windows test, the 3-sec improvement represents exclusively the advantage gained in the time it takes to read data off the disk into memory because the time it takes to set up the EGA graphics remains constant.

TECHNOLOGY UPDATE


ESDI controllers with IBM PC/ATbus systems. In fact, Western Digital, Adaptec, NCL America, and Scientific Micro Systems all offer such controller products.

SCSI and ESDI disk drives feature equivalent mechanical seek times—average seek times can be as fast as 16 msec. The magnetic-recording technology limits the read-channel data rate on either type of drive to 15M bits/sec at the present

tomatic configuration. Adaptec and Western Digital have also introduced Micro Channel SCSI host adapters and will start shipping them in volume later this fall. SCSI supports faster data rates than ESDI does. And although the SCSI maximum transfer rates exceed disk read-channel data rates, the intelligent interface provides ways to take advantage of the higher rate.

Quantum (Milpitas, CA), for ex-

you must first buy a SCSI adapter. Surprisingly, price isn't a critical issue because you can buy even the highest performance host adapters for prices competitive with the prices of the other types of controllers. Within a year or two, drives with embedded intelligent controllers will be the lowest-cost drives available—the intelligent interface lets drive manufacturers mask defects and so increase yields.



Capable of a maximum 10M-byte/sec data rate across the IBM PC/AT bus, the Adaptec AHA-1540 includes a local μP and supports synchronous and asynchronous SCSI transfers.

time. And neither a SCSI host adapter or ESDI controller has an inherent advantage in data-transfer rate across the system bus. Using SCSI does impose the minimal command overhead time of the embedded controller. But SCSI host adapters provide a potentially higher performance alternative.

Future Domain offers one of these potentially higher-performance alternatives to an ESDI controller for Micro Channel. The \$390 MCS-350 Micro Channel SCSI host adapter supports the maximum 1.5M-byte/sec SCSI transfer rate. The host adapter supports Micro Channel arbitration, DMA, and the POS (Program Option Select) scheme for au-

ample, includes a read-ahead cache on embedded controllers for its disk drives. On cache hits, the SCSI interface can operate at maximum speed, reading out of the cache semiconductor memory rather than from the disk. And the cache hit eliminates mechanical seek time. Most manufacturers of high-end drives will have introduced a similar feature by the end of this year. SCSI also allows schemes such as simulating a single drive with an array of drives operating in parallel. Micropolis (Chatsworth, CA) offers a 5-drive array that can effectively quadruple data-transfer rates.

To take advantage of the higher performance rates that SCSI offers,

Consider compatibility first

Instead of price, performance and compatibility, including software support, should guide your choice of a SCSI adapter for personal computers. In terms of compatibility, you should keep in mind that no standard for SCSI host-adapter register sets or software interfaces exists, primarily because IBM has never offered a SCSI host adapter for its personal computer. For several years, rumors have hinted that IBM would offer a SCSI board for its personal computers, but no product has appeared.

BIOS handles MS-DOS disks

Achieving compatibility between MS-DOS and hard disks is relatively easy for host-adapter manufacturers. They either include BIOS software that emulates the standard interrupt-13 interface used by MS-DOS with the ST-506 controllers, or they include an installable device driver. Some do both. The problem is that MS-DOS presently includes no facilities to control tape drives, optical disks, or other peripherals such as scanners.


The picture becomes cloudier when you consider other operating systems and network environments. If you're an OEM, you can write driver and application software for any type of SCSI device, and for any operating system, but this option requires extra time and money for software development. Generally then you should want to select an adapter that has sufficient software support as well as compatibility.

The low-pass filter for real signals



The SR640 dual channel, programmable, low-pass filter.

115 dB/octave rolloff. \$2990.



The SR640 offers a unique combination of filter specifications, preamplifier performance, and programmability at a price far less than other instruments. Featuring two fully independent 8-pole, 6-zero elliptic filters with less than 0.1 dB p-p passband ripple and 115 dB/octave rolloff, the SR640 is the ideal filter for general purpose signal processing as well as anti-aliasing for digital signal processing systems.

The GPIB and RS232 interfaces allow complete control of all instrument settings via computer control. The microprocessor components are optically isolated from the filter sections to provide optimum noise performance.

Whether your needs are for laboratory benchtop filters or signal conditioning filters in data acquisition systems, the SR640 is the natural choice.

SR640

\$2990

1 Hz to 100 kHz cutoff frequency 3 digit frequency resolution 0.1 dB passband ripple 115 dB/octave rolloff 80 dB stopband attenuation 10 nV/√Hz input noise 60 dB prefilter gain 20 dB postfilter gain GPIB, RS232 interfaces standard

Stanford Research Systems

CIRCLE NO 55

1290 D Reamwood Avenue Sunnyvale, CA 94089 TEL (408) 744-9040 FAX 4087449049 TLX 706891 SRS UD


TECHNOLOGY UPDATE



A 16k-byte read-ahead cache created in system memory by the driver software supplied with Western Digital's 7000-FASST2 board eliminates disk-access and data-transfer delays on consecutive disk reads of contiguous data.

Of all the packages available, Future Domain currently offers the most comprehensive hardware-software combination by far for its host adapters. The TMC-800 family of host adapters for the IBM PC and PC/AT buses and for the MCS-350 Micro Channel bus feature a common SCSI architecture and system software interface. The TMC-800 boards range in price from \$198 to \$220; some include standard floppy-disk-drive controllers.

A kit including a cable and a menu-driven installation software for MS-DOS, Xenix, and Netware, adds \$90 to the basic board price.



An MS-DOS software driver for WORM drives available with the Rancho Technology RT10-AT host adapter installs the optical drive for use as a standard disk.

The kit contains partitioning software that breaks the 32M-byte disk volume limit of MS-DOS. The boards are compatible with virtually all MS-DOS software, including third-party disk-partitioning packages and several optical-disk and tape-drive control packages. The company also has established an OEM interface module that allows you to easily integrate new peripherals with its adapters.

Adaptec introduced its AHA-1540 host-adapter board about a year ago. It's compatible with MS-DOS, Xenix, Unix, and Netware, and sells for \$349. In addition, Sytron's (Londonderry, NH) tape-backup package supports the board. For normal MS-DOS use, you can install the board by simply accessing onboard firmware with the operating system's Debug utility.

The RT10-AT from Rancho Technology is MS-DOS compatible and includes a proprietary tape-backup package (\$299). A Unix or Xenix driver costs \$35 for 80286-based machines and \$65 for 80386-based machines (both in 100-unit quantities). A Netware driver costs \$45 (single-

unit price). An optical-disk package is also available for an extra \$450.

Western Digital includes MS-DOS, Xenix, Unix, and Netware drivers with its 7000-FASST2 host adapter for \$495. It's also compatible with the Sytron tape-backup system. The boards should be available in quantity this month.

OS/2 causes logistic problems

Every manufacturer of PC add-in boards plans to offer OS/2 compatibility, although none has finalized its plans. The operating system is only available to OEMs, however, and it will not accept installable device drivers as boot devices. The host-adapter manufacturers therefore can't offer a generic OS/2 driver.


For typical MS-DOS applications, any of the products discussed in this article will perform equally well. Keep in mind that MS-DOS is a single-tasking operating system—the CPU performs no other task while disk I/O takes place.

All of the host adapters discussed here offer transfer rates faster than a typical disk can accomplish. And all of them can transfer data across the system bus faster than the SCSI bus operates. Therefore, the physics of the disk drive actually define the performance limits of the I/O system.

There are some exceptions to this general rule. A cache-based controller, for example, can exceed the standard asynchronous SCSI data rate. If you plan to use a drive with a cache, you should consider the Adaptec and Western Digital boards. Both boards can operate in the faster synchronous SCSI mode. Western Digital also offers a cache feature with its host-adapter board. The MS-DOS driver supplied with the board establishes a 16k-byte read-ahead cache in system memory. On cache hits, the driver never even accesses the SCSI bus.

For applications in multitasking or networked systems, you should compare performance specifications

LOW ESR & MORE.



4SW-4129R2

Sprague Type 550D Solid-Electrolyte Tantalex® Capacitors, designed for use in power supply filters at frequencies to 100 kHz, feature extremely low ESR and high ripple current capability. Maximum ESR for a 300 μ F, 6 VDC unit is only 0.045 Ω at 100 kHz. Additional advantages include small size, long

If the composition of the compo

environments. Capacitance values: 5.6 to 330 μ F. Voltage ratings: 50 to 6 WVDC. Write for Engineering Bulletin 3548 to Technical Literature Service, Sprague Electric Co., P.O. Box 9102, Mansfield, MA 02048-9102.

SPRAGUE THE MARK OF RELIABILITY

TECHNOLOGY UPDATE



Menu-driven MS-DOS, Netware, and Xenix installation software, and compatibility with other third party application programs, I/O managers, and operating systems are key features of Future Domain's IBM PC/AT-compatible host adapters for turnkey applications.

much more carefully than you do with MS-DOS systems. Because multitasking can occur both at the SCSI-bus and host-bus levels, the transfer rates of both buses become more critical in these environments. For instance, while a SCSI host adapter transfers a block of data into memory, a network controller has to wait to use the system bus. Therefore, a fast host-bus transfer rate frees the bus sooner.

The IBM PC/AT bus lacks sophisticated features such as multimaster arbitration; the bus also has to be

cleared regularly for a refresh cycle. The host-adapter manufacturers have made every attempt to speed this bus up, but they all have different ideas about which host-adapter architecture is the best.

Future Domain, for example, does not use DMA to move data. The company's host adapters depend on the CPU to perform memory-mapped I/O. Company president Jack Allweiss believes you obtain better performance if you let the 80286 or 80386 handle the I/O rather than giving it to a less powerful

processor. Allweiss points out that it takes 2 $\mu secs$ of overhead to start a DMA operation. And in 80386 and protected-mode 80286 environments, the data is typically fragmented in physical memory, which adds additional overhead to some DMA operations.

Mailboxes provide interface

Bruce Bonner, marketing manager at Western Digital, and Ed Turner, marketing manager at Adaptec, both claim that the CPU is best utilized performing other tasks during I/O operations. Both Western Digital and Adaptec include a μP on its host adapters, and both use mailboxes for passing messages between the CPU and the host adapter.

Adaptec, Western Digital, and Rancho Technology host adapters all use first-party DMA to move data. In a first-party DMA operation, the host adapter takes control of the bus and performs the DMA operation independently of the mother-board DMA controller. The Rancho Technology R10-AT, however, does not include a local μP . According to company vice president John Fobel, a local μP and firmware restricts the flexibility you have in writing drivers for a host adapter.

Rates exceed 5M bytes/sec

All four of the architectures discussed result in impressive performances. All of the boards transfer data across the host bus at speeds in

For more information . . .


For more information on the SCSI host adapters discussed in this article, contact the following manufacturers directly or circle the appropriate numbers on the information Retrieval Service card.


Adaptec Inc 691 S Milpitas Blvd Milpitas, CA 95035 (408) 945-8600 TLX 910-338-0060 Circle No 700

Emulex Corp Box 6725 Costa Mesa, CA 92626 (714) 662-5600 TLX 183627 Circle No 701 Future Domain Corp 1582 Parkway Loop, Suite A Tustin, CA 92680 (714) 259-0400 Circle No 702

NCL America Corp 1221 Innsbruck Dr Sunnyvale, CA 94089 (408) 734-1006 Circle No 703 Rancho Technology Inc 8632 Archibald Ave, Suite 109 Rancho Cucamonga, CA 91730 (714) 987-3966 TLX 362087 Circle No 704

Scientific Micro Systems Inc Box 7777 Mountain View, CA 94039 (415) 964-5700 TLX 172555 Circle No 705 Western Digital Corp 2445 McCabe Way Irvine, CA 92714 (714) 863-0102 TWX 910-595-1139 Circle No 706





company in the world can offer. We call it the Harris/3M promise. And it guarantees, in writing, that your copier will be up and running when you need it. But that's only part of what we offer you



Give us a call or send in this coupon and we'll tell you how. until October 31, 1988, you can save up to \$1000 on a new Harris/3M copier. We'll also send you two free booklets to help you evaluate

> vour copier needs. Get all the facts on the Harris/3M promise and our valuable trade-in offer soon. You'll be convinced

that your next copier should be a Harris/3M. We guarantee it.

Call 1-800-TLC-COPY

Or send in this coupon to receive information on our trade-in offer plus two FREE booklets to help you evaluate your copier needs.

☐ I'd also like information on your full line of fax machines.

Company Name

Telephone_


Mail to Harris/3M Document Products, Inc., P.O. Box 785, Dayton, OH 45401.

CN988FPR

ARRIS/3

Get more than a copier. Get a commitment.

Offer is valid at participating U.S. dealers for a limited time and other restrictions and limitations apply; see your Harris/3M sales representative for details. Free loaner offer is valid if copier is installed within 50 miles of an authorized Harris/3M service facility. © 1988 Harris/3M Document Products, Inc. Harris is a trademark of the Harris Corporation. 3M is a trademark of the 3M Company.



CIRCLE NO 21

DID YOU KNOW?

EDN serves electronic engineers and engineering managers in more than 100 countries worldwide.



UPDATE

excess of 5M bytes/sec. The Future Domain host adapters achieve the data rate using only 8-bit transfers. The Adaptec board specifies the highest transfer rate at 10M bytes/sec, but all host-bus data-rate specifications are subject to the speed of the host IBM-PC/AT compatible.

Manufacturers of host adapters will continue to improve their products in the areas of both compatibility and performance, since each manufacturer would like to establish a defacto standard for SCSI in IBM-compatible personal computers. And other vendors will soon join the fray. Scientific Micro Systems, for example, plans to ship a host adapter that matches the performance of the boards discussed here. The board should be available this fall, and the company plans to offer it at a price lower than the competition.

Don't rule out IBM. It can establish a standard flavor for SCSI on personal computers with a single product introduction. Although IBM is not very likely to introduce an IBM PC/AT bus product now, a Micro Channel host adapter could still establish a register set and software interface.

Reference

Wright, Maury, "SCSI ICs simplify I/O-bus configurations, but options entail extra design effort," *EDN*, Sept 18, 1986, pg 97.

Article Interest Quotient (Circle One) High 518 Medium 519 Low 520

XICOR RAISES MILITARY DESIGNS TO A HIGHER LEVEL.





Our full military E²PROM line-up gives you one-stop shopping convenience.

Now you can promote your memory-intensive military designs to a higher level of functionality. With Xicor's complete line of military E^2PROMs , NOVRAMs and E^2 potentiometers.

They raise system performance and power economies to a new level. And unlike most memories, Xicor E² devices can be remotely reprogrammed in the field, via telephone link. In the case of our E² potentiometers, they can automatically tune themselves while in service—kind of like an "electronic screwdriver." Plus our high density E²PROM memories are loaded with features like Page Mode, DATA Polling, Toggle Bit and Software Data Protection.

Volume-manufactured in JEDEC-approved pin-outs, Xicor E² devices come in all the popular packaging configurations, including surface mount. And they're backed by Xicor's on-site technical design support. For more details on JAN, DESC Drawing and 883C products, call (408) 432-8888 today, or write: Xicor,

Inc., 851 Buckeye Court, Milpitas, CA 95035.

E ² PROM Part No.	Organ.	Page Size (# Bytes)	
X2804AM	512 x 8	N/A	300, 350, 450
X2816AM	2048 x 8	N/A	300, 350, 450
X2816BM	2048 x 8	16	250, 300
X2864AM	8192 x 8	16	250, 300, 350, 450
X2864BM	8192 x 8	32	120, 150, 180
X2864HM	8192 x 8	32	90
X28256M	32768 x 8	64	250, 300, 350
X28C256M	32768 x 8	64	250, 300, 350
XM28C010M	131072 x 8	64	250, 300
min.			
A WILL			

NOVRAM Part No.	Organ.		
X2210M	64 x 4		
X2212M	256 x 4		
X2004M	512 x 8		
Serial I/O Part No.	Organ.		
NOVRAM X2444M	16 x 16		
E ² PROM X2404M	512 x 8		
E ² PROM X24C16M	2048 x 8		
E ² POT™ Part No.	Max. Resis.		
X9103M	10K Ω		
X9503M	50K Ω		
X9104M	100K Ω		

E²POT™ digitally controlled potentiometer is a trademark of Xicor, Inc.



CIRCLE NO 57



MAKES IT MEMORABLE



Only HP can put real teeth into faster

Test development and execution speed. We know they're your top priorities. HP BASIC,*combined with our range of controllers and instrumentation, is the answer. Even if you're running on MS™DOS or the UNIX™ operating system. And of course, it's all backed by HP's measurement expertise, and the product reliability you've come to count on from an industry leader.

HP BASIC: Optimized for instrument control.

It's no secret that a critical element of automated instrument control is fast development time. That's where HP BASIC really shines. With power, versatility and ease of use. We invite you to find a better instrument control language.

A few examples:

■ Fast program development with interactive editing, syntax checking and the ability to search and replace

strings, or move blocks of code easily.

■ Optimized for I/O with advanced constructs to simplify otherwise complex tasks. Interrupts, high speed data transfers, automatic data formatting and branching on events can all be handled easily. Since HP BASIC was designed for instrument control, these capabilities are integral, not tacked on as an afterthought.

■ Structured programming lets you make your program modular with independent subprograms which can be re-used in other applications. Constructs like CASE statements, IF-THEN-ELSE, WHILE, REPEAT-UNTIL and LOOP are useful for rapid program development and invaluable for program maintenance.

■ Powerful computation lets you take advantage of a full range of matrix manipulations such as multiplication, inversion and scalar operations. HP's complex number implementation allows for powerful arithmetic operations.

■ Graphic capabilities are simple to program, yet powerful. One program statement can draw axes or grids, a second will plot your data, a third will label your plot and a fourth will provide a permanent copy.


HP Controllers: The right horsepower for the job.

Hewlett-Packard provides a wide range of instrument controllers and operating systems to meet your performance needs, allowing you to choose the most cost effective controller for your job.

Just look:

■ Personal computers; the HP BASIC Language Processor allows you to use HP BASIC on the world's most prevalent operating system, MS DOS. It's available for the HP VECTRA or the IBM PC-AT.

*Sometimes called Rocky Mountain BASIC or BASIC 5.0.



test development.

■ Dedicated controllers up to 4 MIPS, HP's Series 300 controllers provide a dedicated, high performance system for maximum I/O throughput.

■ HP-UX workstations. HP BASIC will also be available for use in the Series

Trim more time: Deal with the pros.

Our sales, service and support team can get your test up and running when time is of the essence. With over



Call HP for a free video. 1-800-752-0900, Dept 215R




300 HP-UX environment. Our implementation combines the ease-of-use and performance of HP BASIC with the full networking, multitasking and windowing capabilities of the UNIX operating system.

No matter the controller demand, HP makes it in the optimum package. Ask for our free videotape on HP BASIC or a brochure on HP instrument controllers. Learn how Hewlett-Packard can help you cut test development time significantly.

© 1988 Hewlett-Packard Co. EI 15814/EDN



"I shop the specs



because it's my job. But I buy the product because it's my career."

WHAT YOU SHOULD KNOW ABOUT THE NEW PRODRIVE SERIES™OF 3½-INCH HARD DISK DRIVES FROM QUANTUM.

The numbers are the easy part. Either a product has them or it doesn't.

But you can't build a system out of specs.

You also need dedicated product-support people who will sit down and help you solve some tough engineering problems and put those specs to work.

Quantum is ready to deliver both.

Our new ProDrive Series of 3½-inch hard disk drives offers you the broadest range of capacities in the broadest range of interfaces in the industry. 42 and 84 megabytes formatted with embedded SCSI and AT-Bus interface, right now. And later this year, up to 168 megabytes, in SCSI, ESDI and AT-Bus. Ten new drives in all.

With access times of 19 ms or less.

With synchronous data transfers to the SCSI bus of 4 megabytes per second, and asynchronous data transfers of 2 megabytes per second.

With an MTBF of 50,000 hours.

And with DisCache, Quantum's unique 64 kilobyte data-buffering scheme that can make our 19-ms intelligent drive perform like a 12-ms drive—or even faster, depending on your application.

But Quantum also offers you the people who can help you put those numbers to work in your own system. A dedicated team of engineering professionals who understand the particular needs of the systems designer—and can help meet those needs quickly, efficiently, cost-effectively.

The new ProDrive Series. The specs you want. The support you need. That's what Quantum delivers.



INTRODUCING THE PRODRIVE SERIES

- · 31/2-inch form factor
- 42,84,103,120,145,
 168 MB formatted
- · SCSI, ESDI, AT-Bus
- 19 ms or faster average access time
- 64 KB buffer with exclusive DisCache
- · 50,000-hour MTBF
- 42,84 MB SCSI and AT-Bus units now in mass production.

ProDrive. Now available with AT-Bus and SCSI interfaces. Call today for a brochure or to find out how you can get an evaluation unit.



Quantum Corporation 1804 McCarthy Blvd. Milpitas, CA 95035 Western Region (408) 980-8555 Eastern Region (603) 893-2672

When World Class Precision and Performance Are Required



Highest precision available with 10 μ V input offset voltage from Raytheon.

Raytheon's RC4077 Series high-precision op amp family offers the highest performance in the industry. Looking for the lowest input offset voltage—Raytheon has it. The lowest power dissipation—Raytheon has it. The 4077 Series can upgrade your system to new heights of precision and performance. You can depend on Raytheon's reliability and advanced design techniques to enhance your system.

 \Box Ultimate precision: \pm 10 μV maximum guaranteed input offset voltage, delivered in a variety of package types including low-cost commercial plastic DIPs, sets the RC4077 series apart from other precision op amps. No monolithic op amp—except noisy chopperstabilized types—has better V_{OS} perfor-

mance. Additionally Raytheon offers an 8-lead SOIC specified at $\pm 25 \mu V$.

☐ Well balanced specs:

I_B: 2 nA maximum Gain: 5 million minimum Power dissipation: 50 mW maximum CMRR: 120 dB minimum

PSRR: 110 dB minimum

 \square Companion product: Raytheon's LT1001 high-precision, high-performance op amp follows RC4077's lead with a very low 15 μ V offset voltage. The LT1001 offers 2 nA offset current and gain of .45 million minimum.

□ **No wait:** The RC4077, LT1001 and other members of Raytheon's broad line of op amps are available now from your

local distributor. The RC4077 with 10 μ V offset is priced at \$3.00 each in 100-piece quantities.

Call Raytheon for access to the right operational amplifier technology at the right price. We offer the precision and performance your system needs to compete.

Raytheon Company Semiconductor Division 350 Ellis Street Mountain View, CA 94039-7016 415/966-7716

Access to the right technology

Raytheon


IAs pull low-level signals out of noisy environments

David Shear, Regional Editor

Unwanted noise can contaminate electronic signals and complicate their acquisition in various ways, so if you need to acquire a differential signal that is mixed with unwanted common-mode noise and voltage, consider using instrumentation amplifiers (IAs). They are high-gain dc-coupled differential amplifiers characterized by three traits: a single-ended output, high input impedance, and high common-mode rejection (CMR). Generally designers use these devices to amplify small differential signals coming from transducers that may generate large common-mode signals (Ref 1).

Fig 1 shows the noise sources that can affect a system. The es voltage is the desired signal from a transducer. The ec voltage is any commonmode voltage or signal; it could be a 60-Hz signal from a bad ground or ground loop; ec could also be a dc bias voltage that the transducer requires. The en voltage is any radiated noise such as the ubiquitous 60 Hz or any signal picked up by nearby digital circuitry. If you assume that the physical properties of the cable connecting the transducer to the IA are identical for both inputs, then you can also assume that any radiated noise (en) is equal in magnitude and phase at the inverting and noninverting inputs of the IA. Therefore, the infinite commonmode rejection of an ideal IA would eliminate the effects of e_n. Similarly, the signal from e, would be equal on both of the inputs to the IA and would also be eliminated.

But in reality, an IA's commonmode rejection is finite. CMR defines how well an amplifier rejects common-mode signals. The ratio of



Low noise, fast settling time, and high CMR highlight the instrumentation amplifiers that are available today. The AD624 from Analog Devices also offers 0.001% nonlinearity for precision transducer applications.

the change in output voltage to a change in common-mode input voltage represents the common-mode gain. The ratio of the differential gain to the common-mode gain is the common-mode rejection ratio (CMRR). The general equation for this relationship is logarithmic: CMR=20log₁₀CMRR. When the CMR is high enough, you can reduce the unwanted signals to the point where they no longer affect your measurements.

Three kinds of IAs

IAs come in three flavors: the differential amplifier, the classic 3-op-amp voltage-feedback IA, and the current-feedback IA (also called the differential transconductance amplifier). The differential amplifier is a single op amp with a feedback network that accepts a differential signal (Fig 2). You can make a differential amplifier yourself very easily with an op amp and four resis-

tors. Getting resistors that are matched and that track each other over the temperature range, however, is not so easy.

To solve the problem, Burr-Brown offers a series of differential amplifiers that have the resistors on board. The INA105 is a precision unity-gain differential amplifier that combines a precision op amp and a laser-trimmed low-drift resistor network on a single chip. The device has a maximum gain error of 0.01% and a maximum nonlinearity of 0.001%. Prices start at \$3.50 (100). For those applications that require higher gain, consider the INA106, which has a gain of 10 (from \$5.15, 100). The INA117 is a unity-gain differential amplifier that can accept as much as ±200V of common-mode voltage. It costs \$4.20 and up (100).

Differential amplifiers have some drawbacks: The feedback network is connected directly to the source. As a result, the input impedance of the

SECOND SOURCE SHOULD BE YOUR FIRST CHOICE.


First of all, better performance. In high speed op-amp applications you need high slew rate, but not without good phase margin, low overshoot, and fast settling time. Sipex cov-

100mc 100ms Time

OUR 2510

ers you on all counts. Look at our SP2510 op-amp. It achieves its 65 V/µsec slew rate with better phase margin,less than 5% overshoot, and a settling time of under 250 nSec. Our other high speed op-amps, such as the SP2500/02/05, SP2520/22/25, SP2600/02/05, and the SP2620/22/25, offer you an equivalent edge.

And there's more. We'll deliver these high performance products *without* the usual hassles.



THEIR 2510

Our op-amps come in the package you need, when you need them, and are specified to your commercial or military requirements, including MIL-STD-883 screening. That's

second sourcing that puts you first every time.

For a free copy of our 382-page 1988 catalog, call our Sipex literature hot line: 1-800-272-1772. In Massachusetts call (508) 663-7811. For product samples, write on letterhead to Sipex, DataLinear Division, 491 Fairview Way, Milpitas, CA 95035




SIGNAL PROCESSING EXCELLENCE

TECHNOLOGY UPDATE

differential amplifier depends on the value of the input resistor, which usually isn't very high. With a rather low input impedance, the two source resistances of the transducer being measured must be very low and extremely well matched, or both the gain accuracy and the CMR suffer. Also, for many measurements, you need a 100- to 120-dB CMR, and the differential amp's CMR of about 80 dB just isn't quite high enough. Thus for many applications, the differential amplifier will not meet your needs.

Beyond the differential

For those applications where the differential amplifier can't quite cut the mustard, consider a classic 3-opamp voltage-feedback IA (Fig 3). This IA has two op amps (IC1 and IC₂) that buffer the input and present a very high impedance to the source. Further, IC1 and IC2 provide high differential gain for the desired signal but only unity gain for the common-mode signal. This combination improves the amplitude of the differential signal relative to the common-mode signal and thus results in a higher CMR than is possible when using a differential amplifier. The output of the first stage (IC₁ and IC₂) goes to the differentialamplifier stage (IC₃); the result is a single-ended signal with very high CMR.



Software-selectable gains are useful for software-controlled data acquisition. The AD625 from Analog Devices allows you to add external gain switches and a resistor network without the added errors caused by the on-resistance of the switches.

Many of the voltage-feedback IAs have extra terminals to improve the precision of the IA even further. A sensing terminal can compensate for any drop between the output and the load, and the reference can compensate for any differences in ground potential between the IA and the load. The guard terminal allows the use of a shielded cable on the input without increasing the parasitic capacitance from the shield.

The AD524 (from \$9.90, 100) and the AD624 (from \$11.90, 100) from Analog Devices are two 3-op-amp voltage-feedback IAs that are pinprogrammable for gains of 10, 100, or 1000, and of 1, 100, 200, or 500, respectively. Or you can use a single external resistor to select the gain for these devices within a range from 1 to 1000. At a gain of 1000, the CMR is 130 dB for the AD624 and 120 dB for the AD524.

For gains from 1 to 10,000, consider the AD625 (from \$6.95, 100). Three external resistors set the gain of this IA. Using the AD625, you can program the gain via external switches. Generally, employing those switches for gain control can




Fig 1—A sufficiently large CMRR can virtually eliminate the noise sources that can affect your desired signal.




Fig 2—The differential amplifier includes an op amp and feedback resistors. The INA105 (Burr-Brown) has matched and stable resistors built on the device so you don't have to worry about them.

TECHNOLOGY UPDATE




Fig 3—The classic 3 op-amp voltage-feedback IA has excellent CMR along with very high input impedance. You can use the fourth op amp (IC_4) to drive the guard.

cause inaccuracies because of the on-resistance of the switch. The AD625 is designed to eliminate this error source.

Burr-Brown's INA101 is a 3-opamp IA that costs \$5.35 (100). It's also available in a military version the INA101/883B—for prices starting at \$40.50 (100). The INA104 (from \$15.55, 100) has a fourth op amp on board to allow gains as high as 10,000; or you can use the extra op amp for filtering, shifting the output level, or driving the guard. Prices start at \$15.55 (100). For low-power applications, you can use the INA102 (from \$5.65, 100). Its quiescent current is 1 mA; it has pin-programmable gains of 1, 10, 100, or 1000.

Another option for IAs

Current-feedback IAs (Fig 4), such as the AMP-01 from Precision Monolithics, differ from the classic IAs, which use voltage feedback. Two resistors set the gain over a range of 0.1 to 10,000. The ratio of a scale resistor (R_{SCALE}) and a gain-set resistor (R_{GAIN}) determines the gain. Current sources control the flow of internal currents, developing

the input voltage across R_{GAIN} . This current flows through R_{SCALE} and produces an output voltage that is proportional to the input voltage. Prices start at \$9.90 (100).

Precision Monolithics' AMP-05 is similar to the AMP-01 except it also has JFET inputs, dual guard-drive circuitry, and a 100-μA current source for transducer excitation. In comparison with the AMP-01, the AMP-05 doesn't have as high an output-drive capability or as low an input offset and drift.

The current-feedback IA is also known as a differential transcon-




Fig 4—The current-feedback instrumentation amplifier uses a different circuit topology to achieve the same goal as the classic 3-op-amp voltage-feedback IA. This current-feedback IA has the advantage of nearly constant bandwidth with changing gain.



One of the precise hand-held instruments that didn't need one of our cable assemblies.

Annie never missed. Well, almost never. As long as she was ahead of second best, the room for error was there.

Not so in the critical engineering of micro-miniature cable and connector solutions at Precision Interconnect. Tolerances are getting tighter, desired sizes smaller, and development time shorter.

Working with exact electrical requirements, plus challenging mechanical parameters,

we design and produce extremely reliable, long flex-life cable, with conductors terminated to standard connectors or active devices, and with protective flex-strain reliefs. These complete interconnect systems, usually using 30 AWG and smaller conductors, provide the critical link in hand-held applications on test and measurement equipment and medical diagnostic devices.

Our expertise, increasing with each unique problem we solve, ensures that reliability is designed in, built in, and tested. So we're right on target. Every time.



16640 S.W. 72nd Avenue, Portland, OR 97224 (503) 620-9400

Offices in San Francisco, Boston, Wilmington and Düsseldorf

High frequency probe provides matched impedance and matched time delay for a Tektronix logic analyzer.

CIRCLE NO 102

TECHNOLOGY UPDATE

ductance amplifier. A popular term at present, current-feedback has become synonymous with the capability of varying the gain without changing the bandwidth of the IA. The INA110 from Burr-Brown is an FET input IA with pin-programmable gains of 1, 10, 100, 200, or 500. Prices start at \$6.20 (100).

IA in an 8-pin DIP

The Precision Monolithics AMP-02 current-feedback IA is available in an 8-pin DIP for even more space savings than you normally have with IAs (from \$5, 100). One resistor sets the gain of this IA from 1 to 10,000. For a gain of 1, no resistor is needed.

The PGA200/201 from Burr-Brown is a programmable-gain IA that is controlled by a 2-bit TTL input. The PGA200 provides gains of 1, 10, 100, and 1000; the PGA201 offers gains of 1, 8, 16, 64, and 512. For gain selection, these 3-op-amp IAs feature an onboard latch along with a multiplexer and a resistor network. Prices start at \$39.40 (100).

National Semiconductor's LH0084 (from \$33.50, 100) allows a gain of from 1 to 100. The first stage is software controllable for a gain of

1, 2, 5, or 10; you jumper-select the second stage for a gain of 1, 4, or 10.

If you want to have an on-chip T/H amplifier for use with A/D converters, you might consider the Analog Devices AD365 programmable-gain IA. Two unlatched digital inputs set the gain of this IA to 1, 10, 100, or 500. Pricing begins at \$61.95 (100). Another combination device is the XTR101 from Burr-Brown. This device combines an IA front end with a 4- to 20-mA 2-wire transmitter. Prices start at \$6.35 (100).

Even if you decide you must build your own IA, you don't have to start from scratch. You can use a differential amplifier as the difference amplifier in a 3-op-amp design. The LTC1043 from Linear Technology, which starts at \$2.95 (100), is a dual, precision-instrumentation switched-capacitor building block. With this device and one op amp, you can make an IA that has CMR of 120 dB to well beyond 10 kHz and that runs off a single 5V supply.

Some typical problems

IAs create some common problems. One is the potential for saturating the input without knowing it. To avoid saturating the input, make sure that the input voltage doesn't exceed the common-mode voltage range (CMVR). You can calculate the CMVR for linear operation from:

 $CMVR = \pm (IVR - (V_{OUT}/(2G)),$

where IVR is the data-sheet specification for input-voltage range, $V_{\rm OUT}$ is the maximum output signal, and G is the chosen voltage gain.

You must also always make sure you refer the input to common ground—otherwise you end up with a floating output. If the source resistance is more than 1 k Ω , you must use two 1-M Ω resistors to ground at the input. To avert another potential problem, you should add the settling time of the IA to the acquisition time when you use an IA with a multiplexer.

Lately, the op-amp industry has been bustling as long-awaited processes and designs are finally entering the market. These same advances will soon begin to show up in the IAs, too. You can expect to see single 5V and low-power devices and more combination devices with adjustable frequency response. And you can also expect to encounter some IAs that begin to approach the ideal in CMR, bandwidth, and input-bias currents.

For more information . . .

For more information on the instrumentation amplifiers described in this article, contact the following manufacturers directly, circle the appropriate numbers on the Information Retrieval Service card, or use EDN's Express Request service.

Analog Devices Inc 2 Technology Way Norwood, MA 02062 (617) 329-4700 TLX 174059 Circle No 720

Burr-Brown Corp Box 11400 Tucson, AZ 85734 (602) 746-1111 TLX 666491 Circle No 721

Linear Technology Corp 1630 McCarthy Blvd Mipitas, CA 95014 (408) 432-1900 TLX 499-3977 Circle No 722 National Semiconductor Corp 2900 Semiconductor Dr Santa Clara, CA 95051 (408) 721-5756 Circle No 723

Precision Monolithics Inc 1500 Space Park Dr Santa Clara, CA 95052 (408) 727-9222 TLX 172070 Circle No 724

References

1. Horowitz, Paul, and Winfield Hill, The Art of Electronics, Cambridge Univ Press, 1980, pg 279.

2. Fleming, Tarlton, "Monolithic instrumentation amplifiers save space without sacrificing performance," *EDN*, March 20, 1986, pg 57.

3. Graeme, Jerald, "Instrumentation amps begin to challenge op amps," *Electronics*, April 28, 1988, pg 125.


Article Interest Quotient (Circle One) High 515 Medium 516 Low 517

OP-07 PERFORMANCE AT 1/6TH THE POWER

3.6mA



4.0mA





... No speed sacrifice.

And at 1/20th the input bias current, too! PMI's new OP-97 beats even JFET op amps at +125°C! OP-97 drops directly into existing OP-07 sockets immediately saving power and delivering greater accuracy.

Check the specs for yourself:

		OP-97	OP-07	
7.	Vos	25	25	μV Max
	TCVOS	0.6	0.6	μV/°C Max
	A_{VO}	300	300	V/mV Min
	I _B @ 25°C	±100	$\pm 2,000$	pA Max
2 2	I _B @ 125°C	± 250	$\pm 4,000$	pA Max
	I _{SY} @ ±15V	600	4,000	μA Max

If it's precision you need, PMI wrote the book. Circle the reader service number or call 1-800-843-1515.

Precision Monolithics Inc. A Bourns Company Santa Clara, California, USA 408-727-9222

ATLANTA: (404) 263-7995, ALTAMONTE SPRINGS: (407) 260-9780, BLOOMFIELD: (203) 242-1014, BOSTON: (617) 764-9026, CHICAGO: (312) 250-0808, DALLAS: (214) 341-1742, DENVER: (303) 792-9595, DETROIT: (313) 227-2190, HOUSTON: (713) 481-6460, LOS ANGELES: (818) 886-6881, MILPITAS: (408) 942-8060, ORANGE COUNTY: (714) 637-9602, PHILADELPHIA: (215) 953-1070, SCOTTSDALE: (602) 941-1946



The precision solution.
CIRCLE NO 116





Now you can mold the silicon to fit the logic. Not the other way around.

PROGRAM OUR GENERIC ARRAY LOGIC ANYWAY YOU WANT. REPROGRAM ANYTIME YOU WANT

These new GAL* devices emulate the full range of PAL* architectures with 100 percent socket compatibility. They can even be configured to all the in-between architectures — like a 16R1 or 20R7.

You can also change architectures during the design process. And when your design is complete, you can move functions from pin to pin to simplify your board layout. You can even make changes during manufacturing — without huge penalties.

The one-device-does-all approach not only gives you unlimited design freedom, it also reduces parts counts and inventories and decreases your system costs.

REAL TESTABILITY

The first PLDs to use electrically erasable CMOS technology, GAL devices are instantly erasable and reprogrammable. (No time-consuming trips to the UV lamp.) And we guarantee 100 erase/write cycles.

This makes them ideal for prototyping and for pattern changes or

Device Type	ECL PAL	TTL PAL	EECMOS GAL
Speed	fastest	fast	fast
Power	highest	high	low
Density	low	medium	high
Programmability	OTP	OTP	100%
100% Testability	no	no	yes

error recovery on the manufacturing floor—with no waiting or waste.

More important, it allows us to program and erase each device many times during manufacturing to directly test all characteristics, including AC, DC and functionality. As a result, we can assure you 100 percent programming and functional yields without any board rework.

REAL REDUCTIONS IN POWER

Another advantage of CMOS technology is that these new devices are just as fast as bipolar but consume less than half the power—as little as 45 mA active and 25 mA standby.

And because they consume less power, you'll have fewer cooling problems and a much more reliable system.

REAL SOFTWARE SUPPORT

GAL devices are fully supported by industry-standard development

tools, including ABEL*, CUPL™, and PLAN.™ You don't need any sophisticated or expensive upgrades.

And you don't need any special programming hardware either. Almost all hardware manufacturers support GAL parts on existing models.

So get real design freedom. These new devices are like putty in your hands.

Call National — for information on GALs or any other type of PLD. We're the only manufacturer that offers three different technologies — ECL,TTL, and EECMOS.

For a free copy of our new programmable logic brochure, call your local National sales engineer, authorized distributor, or National Semiconductor, MS23/200, P.O. Box 58090, Santa Clara, CA 95052-8090, 1-800-252-4488, ext. 733.



85

©1988 National Semiconductor Corporation

PLAN is a trademark of National Semiconductor Corp. GAL is a registered trademark of Lattice Semiconductor Corporation. PAL is a registered trademark of Advanced Micro Devices (Monolithic Memories Inc.) ABEL is a registered trademark of Data I/O Corp. And CUPL is a registered trademark of Assisted Technologies Inc.

Parallel processing ushers in a revolution in computing

John Gallant, Associate Editor

arallel processing is not a new idea—it's been around at least since the 1960s. Back then, however, it couldn't be implemented practically. For one thing, there were no compilers that could use parallelism efficiently. Neither was there any way to transport large programs running on giant von Neumann computers to parallel machines. Now, both these problems have been solved: The programs are transportable, and parallel compilers are commercially available. You can now design powerful, efficient parallel-processing computers by using a variety of parallel-computing techniques.

Parallel processing can take many forms, but in essence, it spreads computing tasks over more than one processor. The goal is either to speed up a given application by running different tasks in parallel or to solve more-complex problems. Several recently developed computer architectures increase computational power over that of earlier architectures by replicating the elements that process the data. The elements are connected to some type of network, so that the multiple tasks can communicate with each other.


The parallel architectures attempt to break through the speed limitations imposed by the traditional von Neumann architecture. The von Neumann machine, which was conceived more than 30 years ago and is the basis for most single-processor machines, consists of one processing element (PE), a number of storage registers, a program-sequence control unit, and a global memory. The machine executes programs by fetching instructions from memory, reading an operand, executing the instruction, and storing the result.

The various parallel architectures are designed to break through the von Neumann bottleneck. This bottleneck occurs because the single processor must access the global memory sequentially, so the memory-access time limits the speed at which a program can execute. The early parallel machines used a combination of multiple processors and vector-processing units to solve specialized matrix problems. The supercomputers, such as the Cray II and the Cray X-MP/48, are outgrowths of this activity. These supercomputers use expensive hardware technologies, such as ECL (and, in some cases, GaAs) to deliver hundreds of millions of floating-point operations per second (M flops), and their prices start at \$2 million.

Computer systems whose performance is in the VAX to Cray range take advantage of less-expensive technologies and innovative system architectures to achieve performance figures approaching those of the supercomputers while maintaining prices in the \$100,000 to \$2 million range. These computers owe their increase in performance to a variety of parallel-processing architectures. It is this class of computers that affords the most representative view of the various parallel-processing techniques.

Because a von Neumann machine operates on each piece of data in a sequential manner, it's considered to

For years, parallel-computing architectures existed merely as university research projects. Now these architectures are commercial realities. Today's parallel processors, techniques, and languages can help you create powerful minicomputers whose processing capabilities equal or exceed those of supercomputers.



Ray-tracing techniques produced this 1024×1024-pixel image in approximately five seconds on the DAP 510 computer from Active Memory Technology.

The parallel architectures attempt to break through the speed limitations imposed by the traditional von Neumann architecture.



Iterated function codes reproduced this representation of a fern on Active Memory Technology's DAP 510 computer.

be a single-instruction single-data (SISD) architecture. Parallel machines are classified as either single-instruction multiple-data (SIMD) or multiple-instruction multiple-data (MIMD). In an SIMD machine, a single instruction operates on many data elements. Examples include vector and array processors that perform the same mathematical operation on each element of a vector or an array. Most of the parallel-processing machines, however, are MIMD structures, so they can perform multiple tasks or processes in parallel.

Three interconnected factors characterize the various parallel-processing architectures (Ref 1). The first factor is the topology of the interconnections between the parallel-processing elements (PEs) and the system memory. Parallel-computing architectures range from tightly to loosely coupled networks. A tightly coupled network results when each PE and the global memory share an address space. The elements communicate with each other via addressing on a word-by-word basis. A loosely coupled network dosen't share any address space; therefore, the elements must communicate by message passing.

The second factor is granularity. Granularity is a qualitative measure of the computational power of the PEs. PEs with lots of computational power have coarse granularity; PEs with limited computational ability have fine granularity. Commercially available systems range from many single-bit PEs to a few powerful general-purpose PEs.

The third factor is the control and synchronization of the various processes that each of the elements performs. The balanced distribution of tasks is essential for



The Symmetry Series computers have a shared-memory architecture, which can have as many as thirty 32-bit processing elements. These systems, from Sequent, can deliver from 6 to 81 MIPS.

efficient parallel processing. The time required for communication among processes also affects the system's efficiency: The overall program control must synchronize all the tasks. To design a parallel-processing computer, therefore, you must take into account the relationship among the system architecture, software parallel-control features, and the specific application.

Shared-memory architectures are tightly coupled

Taking a look at the architectures for some parallel machines will help to explain these three factors. The most tightly coupled topology for a parallel machine is one in which multiple PEs are connected to a shared memory via a single high-speed bus. Examples of machines with this topology include the Encore Multimax family, the Sequent Balance and Symmetry series, and the Alliant FX Series of computers. These MIMD machines can dynamically distribute tasks to any of the PEs by using a Unix-based operating system that's symmetrically distributed over all processors. The operating system's kernel queues the processes on a priority basis and maximizes the load balancing between PEs.

The PEs in both the Encore and the Symmetry

machines are coarsely granular; the PEs in the Alliant machine are moderately and coarsely granular. The Multimax 320 can interconnect as much as 128M bytes of shared memory with as many as 20 CPUs (the NS32332 $\mu P)$ operating on a 100M byte/sec bus (the Nanobus). The system can deliver from 4 to 40 MIPS performance. Similarly, Sequent's Balance and Symmetry series of computers use a system bus capable of an 80M byte/sec transfer rate. The Symmetry Series can connect as much as 240M bytes of shared memory to as many as 30 CPUs (the 80386 $\mu P)$ operating on the bus. The system can deliver 6 to 81 MIPS performance.


The FX/80 has as many as eight 64-bit vector processors that are capable of providing a peak perfomance rating of 188.8M flops. In addition, the computer has 12 scalar PEs that handle the data transfer to 12 independent I/O channels. The system has as much as 256M bytes of memory and a 188M-byte/sec bus.

How many PEs a single high-speed bus architecture can accommodate is determined by the bus bandwidth. Although the shared-memory systems use high-speed coherent cache memories to reduce the bus traffic, the high-speed bus architecture probably can't support more than 50 processors. To scale a program over a much larger array of processors, the interconnection topology must be looser.

The scale for shared resources is limited

Shared memory systems that connect the PEs and global memory through switches stand at the cross-roads of tightly coupled and loosely coupled architectures. Even though these systems transfer data through an address mechanism, additional information is required to route the data through the switch network. In addition, the cost of the switching elements places a practical limit on how many nodes you can have.

Systems are available that connect the elements through crossbar switches. The C240 computer from Convex, for example, connects four tightly coupled processors to a global memory through a crossbar switch constructed on an 800M-byte/sec bus. Although there's no physical limitation on how many processors you can connect in this manner, the cost for a large number of switches can become prohibitive. System configurations that have a PE and a portion of the global memory at each of the N nodes require a crossbar switch that has N² switch points. To date, commercially available systems that use crossbar switches have been limited to less than 20 nodes.



The Multimax 310 is a shared-memory system with two to 10 processing elements. The system supplied by Encore computer delivers from 4 to 20 MIPs.

A butterfly switch is a practical alternative to the crossbar switch for increasing the nodes in the system. The number of switch points required for a butterfly switch is Nlog₄N. Because this function increases more slowly as you increase N than does the square function, it's a more economical switching method for connecting a large number of nodes. BBN's Butterfly GP1000 computer is an example of a shared-memory system connected by a butterfly switch.

The butterfly switch resembles the butterfly operation found in FFT calculations. The GP1000 computer can have one to 256 nodes connected through a butterfly-switch network. Each of the coarse-grained nodes contains 4M bytes of memory. Each node has a Motorola 68020 μP for a PE, a bit-slice μP that acts as a memory controller, and a memory-management unit (MMU) that translates a virtual address into a physical address.

Parallel-processing architectures can be characterized by three interconnected factors: topology, granularity, and synchronization.




Fig 1—This block diagram shows a 16-node butterfly switch (organized as eight 4×4 switches) that decodes addresses for routing data. The diagram shows a collision occurring between two packets at node P_{10} . (Courtesy Intertext Publications)

When one of the PEs in the GP1000 computer references a virtual address, the memory controller interprets it to see if the memory location is local or remote. If it's local, the MMU translates it to the local physical memory location. If it's remote, the memory controller packages a remote node address and a remote physical address location into the address word being sent to the butterfly switch. The butterfly-switch elements are custom ICs that can interpret the remote-node address bits.

The butterfly switch decodes the address bits by using packet-switching techniques to create a path through the switch to the remote node (Fig 1). If multiple messages collide, the system creates redundant paths to transmit the messages. The extra switching overhead makes the system less tightly coupled than the high-speed bus architecture. The bandwidth of the switch interface is 4M bytes/sec for each node; a 256-element system can deliver 250-MIPS performance.

Distributed-memory systems use message passing

Loosely coupled architectures have the greatest range of granularity. You can scale coarse-grained distributed-memory systems to a large number of nodes containing lots of computational power and dedicated memory. Array processors and pipeline processors have specialized processors at each node with




Fig 2—Loosely coupled architectures can have a variety of topologies, such as a tree network (often used in sorting algorithms) (a), a 2-dimensional mesh (b), a torus (c), a ring connection (d), a 4-dimensional hypercube (e), and a star connection (f).

very little or no memory. These fine-grained parallel machines must be attached to a central processor. They all have one thing in common, however: Communications take place via message passing.

The loosely coupled architectures can be connected in a variety of ways to fit particular applications that are implicitly parallel (**Fig 2**). Messages passing among processors that aren't directly connected to each other must pass through intermediate processors. Because a processor can pass messages more quickly to its neighbors than to a processor that's not connected to it, you'll want to implement an interconnection scheme that minimizes the number of intermediate processors. The n-dimensional hypercube is such a scheme.

An n-dimensional hypercube computer has N processors interconnected as an n-dimensional binary cube, where $N=2^n$. You can map the nodes for all




Fig 3—The flexibility of a hypercube computer lets the programmer choose different topologies for different applications. For example, by using number coding, you can treat a 16-node hypercube as a 3-dimensional mesh, a 2-dimensional mesh, a ring, or a tree.

dimensional meshes and trees to the nodes of the hypercube, so that communications occur only between neighboring nodes. By number-coding each node, you can map the implicit parallelism of an application to the hypercube with minimum communication overhead (Fig 3). It is this feature that makes the hypercube a good candidate for large-scale general-purpose parallel processing.

The Transputer is an example of a PE that can be readily connected as a 4-dimensional hypercube. Inmos developed the Transputer as a processor for loosely coupled parallel processing. The T800 has a 32-bit CPU, a 64-bit floating-point unit, 4k bytes of on-chip RAM, a 32-bit external memory interface, and four bidirectional serial communication links. The four links allow you to construct a 16-node, 4-dimensional hypercube.

Meiko's Computing Surface computer uses the T800 as a PE at each node. The mainframe has a high-speed backplane that houses a number of computing boards with different degrees of granularity. A board with four PEs can have from 256k to 8M bytes of memory per PE; one with two PEs can have 16M bytes of memory per PE; and one with one PE can have 48M bytes. The four data links, which can transmit data at 5M, 10M, or

20M bps, are sent to an electronic telephone exchange network. The user can arrange the topology of the network to suit the explicit parallelism of a particular application.

A local host, such as a VAX or Sun computer or one of the PEs, builds a physical map of the entire Computing Surface computer for the particular problem. The host supervises the network topology under software control, manages the I/O interfaces and coordinates the program by sending different tasks to each node. A task scheduler at each node monitors all incoming messages to determine whether the task is to be performed at this node. If so, the task is buffered and queued for work; otherwise, the scheduler forwards the task to the next node. When a task is complete, the scheduler forwards the task to the host as a result.

Intel's iPSC/2 family and the NCube/10 hypercube are examples of loosely coupled MIMD computers capable of hypercubes with dimensions greater than 4. The iPSC/2 family has a maximum of 128 coarse-grain nodes with an 80386 CPU, an 80387 coprocessor, and as much as 16M bytes of memory at each node. A direct-connect routing network permits messages to be passed at 2.8M bytes/sec over eight bidirectional links. This combina-

The most tightly coupled topology for a parallel machine is to connect multiple PEs to a shared memory via a single high-speed bus.

tion lets the programmer configure the computer as a hypercube with as many as seven dimensions and 512-MIPS performance.

The NCube/10 from the NCube Corp has a maximum of 1024 coarse-grained nodes with a VAX-like, 32-bit custom VLSI chip and six dynamic-RAM chips with as much as 512k bytes of memory at each node. The 160,000-transistor VLSI chip has a 32-bit CPU, a 64-bit floating-point unit, a memory-interface unit, and 11 bidirectional serial I/O channels for communication between nodes at 1M byte/sec. This combination lets you configure the computer as a hypercube with 10 dimensions and 2000-MIPS performance.

So many problems in science and other disciplines involve the manipulation of arrays that it seems natural to arrange the PEs in a computer as an array. Problems that naturally map into arrays include: problems including a large number of equations, image processing on the row×column matrix of pixels on a graphics terminal, and molecular modeling. The DAP 510 (Distributed Array of Processors) from Active Memory Technology Inc and the Connection Machine from Thinking Machines Corp have a large number of fine-grained single-bit processors arranged as arrays. Each of the PEs in these SIMD machines has its own local memory.

The DAP 510 has 1024 single-bit PEs arranged as a 32×32-PE, 2-dimensional mesh implemented with 16 VLSI chips, each containing 64 PEs. Each PE has a communication connection to its neighbors. In addition, each PE has a direct connection to its local memory that can range from 32k to 1M byte per PE. The Connection Machine has 16,384; 32,768; or 65,536 single-bit pro-

New thinking revises limits of parallelism

The highly scalable distributedmemory architectures offer the greatest promise of approaching the ideal parallel-processing machine. In the ideal parallel-processing machine, each process runs in parallel, and the processes don't communicate with one another. Also, the ideal par-

TIME = 1

S

RUN ON
SERIAL
PROCESSOR

1

N

SPEED-UP = 1 ÷ (s + p/N)

RUN ON PARALLEL
PROCESSOR

TIME = s + p/N

Fig A—According to Amdahl's law, the speed-up factor of a fixed-size problem running on a parallel-processing machine is eventually limited by the communication time between processors. (Courtesy Sandia National Laboratories)

allel-processing machine can have an infinite number of processes running in parallel, and for each added PE there should be a linear increase in processing speed. In practice, however, each process must be capable of some interprocess communication so that the tasks can be synchronized to the overall program. Eugene Amdahl proposed

his now-famous law back in 1967 to show that the serial communication between tasks places an upper limit on how many processors can be used efficiently in a system (**Ref 1**).

Amdahl's argument runs like this: Certain portions of a fixedsized problem running on a uniprocessor can be run in parallel on a parallel machine, and some




Fig B—For a problem with a fixed run time running on a parallel-processing computer, the speed-up continues to increase as you add processing elements. (Courtesy Sandia National Laboratories)

cessing elements arranged as 14-, 15-, or 16-dimensional hypercubes. A router allows data to be sent among any PEs in the system. Each PE has 4k bytes of local memory that is upgradable to 64k bytes. These SIMD machines connect to a host computer that sends a single instruction to be performed on the data at each PE.

A pipeline runs parallel problems in series

Some classes of problems exhibit a sequence of steps whose execution can be overlapped in the fashion of a pipeline. In a pipeline processor, the execution unit consists of a number of stages that perform a function within a specified time period. Each stage routes its data to the succeeding stage in a serial fashion. The pipeline decreases the overall execution time by overlapping the execution time for each stage. Because data

from each stage can only be transferred after the slowest task is complete, efficient pipelining requires that the execution time be evenly balanced between stages. The granularity at each stage can be moderate to fine.

The Pipe System from Aspex Inc is a pipeline processor that has as many as eight stages for low-level image processing. Low-level processing consists of finding the features in raw images—such as edges, texture, and the direction and velocity of motion. The tasks consist of performing repetitive processes on a regular data structure, so they lend themselves to a pipeline. The stages in the pipeline have a feedforward pathway, a pathway for each stage back to its input, a pathway from each stage back to the previous stage, and six video buses that can transfer data to any combination of

portions must run serially to coordinate the overall activity. Let s represent the portion of the time spent in serial communication and let p represent the time for parallel operation. For algebraic simplicity, set the total program run time to unity so that s+p=1 (Fig A). If the parallel portion of the program is divided over N number of PEs, the run time on a parallel machine is s+p/N. Therefore, the speed-up factor (the ratio of the time taken on a uniprocessor machine to that of a parallel machine) for running a fixed-sized problem on a parallel machine is:

speed-up=1/(s+p/N)

As the program is scaled over more PEs, the speed-up is asymptotically limited to 1/s and, therefore, the serial component places a limit on the efficiency of a parallel machine.

Sandia National Laboratories has recently published a differ-

ent view of the scaleability issues (Ref 2). Working on an NCube/10 hypercube machine with 1024 PEs, the laboratory observed that problems running on a more powerful machine generally expanded to make use of the increased facilities. Users could adjust such parameters as the number of time steps, the grid resolution, and the complexity of difference operators to allow the program to run in a desired amount of time.

The speed-up factor, the lab concluded, should be calculated on the basis of constant run time, not constant problem size. It could well be that the newly scaled problem can't run on a serial processor, because of insufficient memory. Instead of asking how long it would take to run a fixed-sized serial problem on a parallel machine, you should ask how long the newly-scaled parallel problem will take on a serial machine.

Fig B shows the speed-up of a

problem that's scaled for a constant run time on a parallel machine. The run time on the parallel machine is set to unity (s+p=1). The time to run the same scaled problem on a serial machine is s+Np. The speed-up factor, therefore, is s+Np, which increases continually as more PEs are added to the system.

References

1. Amdahl, G M, "Validity of the single processor approach to achieving large scale computing capabilities," *Proceedings of the AFIPS Computing Conference*, Volume 30, 1967

2. Gustafson, John L, Garsy R Montry, and Robert E Benner, "Development of parallel methods for a 1024-processor hypercube," SIAM Journal on Scientific and Statistical Computing, Volume 9, No 4, July 1988.

EDN September 1, 1988

Loosely coupled architectures can be connected in a variety of topologies to fit the implicit parallelism of a particular application.




Fig 4—This block diagram shows the eight pipeline stages found in the Pipe/800 from Aspex Inc. The pipeline can transmit data through three data pathways and six video buses.

other stages. Fig 4 shows a block diagram of the Pipe 1/800. Each stage is controlled by a 256-bit word which can be downloaded from an IBM PC/AT computer or a more-powerful host.

Data-flow architectures are unique MIMD parallel machines in that a sequence of data—not instructions—controls the execution of the machine. The Cydra 5 from Cydrome computers is a commercial example of a data-flow computer; for the most part, however, these machines are still in the research stage at various universities. The underlying principle behind these machines is that they operate on data when it becomes available. Data flows from one instruction to another, and the order of execution does not depend on the location of the instruction in memory.

The basic data-flow computer architecture consists of a circular pipeline (Fig 5). Program graphs define the data-flow operations. The graphs consist of links and actors that perform an operation when the operands (called tokens) are present on the links (Fig 6). When an actor completes its operation, it produces a new token. Each newly generated token is assigned an

operation, some control information, and destination information. The newly created tokens are sent to a matching network, which gathers the tokens for a particular operation. When all the tokens for a particular operation are present, they go to the next available PE for processing. You can design the data-flow machine to be tightly or loosely coupled and to have fine-to coarse-grained PEs.

Take a systematic approach to parallel design

Although the hardware architecture for a parallel machine is largely an issue of topology and granularity, program synchronization and control is primarily a software issue. The software must contain primitives that coordinate the tasks and must provide locks to ensure that a resource is used only for one process at a time.

Locks are necessary in a parallel machine. When more than one PE operates on a data structure, the possibility that two processes can simultaneously access the same data can cause erroneous results. Consider two processes, running in parallel, that must update a

Glossary of parallel-processing terms

As with most new disciplines, parallel computing introduces a number of new terms to the computing lexicon. The following is a list of some specialized terminology used in parallel processing.

Array processor—a parallel-processor architecture characterized by a 2-dimensional rectangular grid of processing elements (PEs). Each PE is connected to its neighbors to the north, south, east, and west. Butterfly Switch—a communication switch whose configuration is based on the butterfly operation of an FFT.

Concurrent execution—pertains to the simultaneous processing of two or more instructions, as opposed to the sequential execution of the same instructions.

Crossbar switch—is a rectangular grid that contains a switch at each of the grid intersections and connections to communicating components along the grid edges.

Data flow—is a mode of operation where the availability of data and operands—rather than a series of instructions—controls the execution.

Distributed memory—refers to memory that is allocated for use by one of the nodes in a multinode parallel system.

Efficiency (of a computer)—
the ratio of the output computational power to its theoretical
computational power. In the
ideal parallel computer, all computations take place in parallel
without communication between
processes. Any communication

between processes would reduce the overall computational efficiency of the machine.

Explicit parallelism—occurs when sections of a program are run in parallel even though the sections aren't naturally parallel. Granularity—the qualitative measure of the computational power of a processing element. A coarse-grained processor has a large amount of computational power while a fine-grained processor has a small amount of computational power.

Hypercube—an architecture that results when a cube architecture is extended to more than three dimensions. Each node in an n-dimensional hypercube has n connections to its neighbors. Implicit parallelism—occurs when certain sections of a program run in parallel because of the parallel nature of the sec-

Lock—a mechanism that grants exclusive access of a resource to one of the processing elements. Loose coupling—an interconnection topology characterized by message-passing communication. The processing elements do not share the same address space.

tions in the problem.

Multiple Instruction Multiple Data (MIMD)—a class of computer organization in which several different instructions operate simultaneously on several different data structures within a single computer.

Pipeline parallelism—a class of parallelism that operates on the elements in a data structure in stages. In a pipeline, several elements are at various degrees of completion at the same time. **Processing element** (**PE**)—is one of a set of processors in a parallel-processing computer. **Scalability**—refers to how many processing elements a particular architecure can have. Sharedmemory schemes are generally restricted to fewer than 50 PEs; a massively parallel machine has over 1000.

Shared memory—a global memory scheme for a parallel machine in which each processing element has direct access to all of the memory.

Single Instruction Multiple Data (SIMD)—a class of computer organization in which a single instruction operates on several different data elements simultaneously.

Single Instruction Single Data (SISD)—is a class of computer organization in which a single instruction operates on one data element during an instruction cycle time.

Tightly coupled—an interconnection topology characterized by a shared address space for all the processing elements. Communication takes place on a word-by-word basis.

Token (in a data-flow machine)
—an operand or data that is
waiting to be executed or
matched.

Transportability—the ability to transport an application from one machine to another. Because of the wide variations in architectures, most applications require some reprogramming when they are transported from one architecture to another.

EDN September 1, 1988 95

So many problems in science and other disciplines involve the manipulation of arrays that it seems natural to arrange the PEs in a computer as an array.




Fig 5—A data-flow machine consists of a circular pipeline in which the results of an operation are sent to a matching unit. The matching unit collects the results assigned to the next instruction. When the data is available, it's sent through a transmission network to the next available PE.

universal counter after the completion of a task. Each process must execute the following pseudo-machine instructions at the end of each task:

LOAD	COUNTER
ADD	1
STORE	COUNTER

The following interleave of instructions for two simultaneous processes places the wrong value in the counter:

LOAD	COUNTER	(PROCESS 1)
LOAD	COUNTER	(PROCESS 2)
ADD	1	(PROCESS 2)
STORE	COUNTER	(PROCESS 2)
ADD	1	(PROCESS 1)
STORE	COUNTER	(PROCESS 2)

Parallel machines, therefore, require some method of mutual exclusion to avoid these critical sections in a program. One method is the use of semaphores. A simple Boolean semaphore is an integer variable that can only take the value 0 or 1. A P operation causes the semaphore to decrease by 1, providing it's not already 0. A V operation causes the semaphore to increase by 1, providing it's not already 1.

The programmer ensures the mutual exclusion of a critical section in the program by bracketing it with P




Fig 6—A data-flow graph consists of a number of nodes called "actors," which fire whenever an operand is present. The data-flow diagram shown in **b** executes the code shown in **a**. (Courtesy Intertext Publications)

and V primitives. When a process enters a critical section, it monitors whether the semaphore is a 1 or a 0. If it's a 1, the process sets the semaphore to 0 to lock out the other processes. When the critical section is completed, it sets the semaphore to 1. If the semaphore is initially 0, the process must continually sample the semaphore until another process resets it to a 1. A process must spin on a small section of code while it's locked out; this operation is called spin locking.

Go till you get to the end and then stop

Synchronization of processes in a parallel machine takes place primarily through message-passing primitives in high-level languages. Although you can obtain compilers that can detect some implicit parallelism in a serial program, these compilers usually don't provide maximum efficiency for every application. Generally, a programmer must recognize portions of a program to run in parallel and insert message-passing primitives so that the machine can reach maximum efficiency. Essentially, processes pass messages to each other when they wish to communicate.

In 1978, C A R Hoare proposed an experimental parallel language called Communicating Sequential Processes (CSP), which is the basis of many of today's high-level parallel languages. For example, a process called SENDER might send information to the process

PADS SUPERSTATION Completely Integrated CAE/CAD



he Integrated PADS-Superstation is a new and powerful PC-Based Design Station that allows the Engineer or Circuit Designer to perform the entire design sequence from cradle-to-grave. Every decision required in the design effort, from Logic Capture to Printed Circuit Design, to 100% Connection Routing, to Checking, to generating Manufacturing Aids is made by the responsible engineer and implemented on a single, fully integrated CAE/CAD SUPERSTATION!

LOGIC CAPTURE

The PADS-CAE system maximizes Logic Capture automation, while allowing the engineer to concentrate on the design task. This high degree of automation results from the use of a new type of database. A Design-Oriented-Database. All drawing sheets of the design are simultaneously available - not merely a single sheet, as with most other Logic Capture systems.

Among the many advantages of this new database are Automatic (hands-off) entry of Reference Designation, gate and pin data, on-line real time data checking across all drawing sheets, rapid paging from sheet-to-sheet, and instantly available (no batching) Annotation Lists to both PADS-PCB and other board CAD systems using FUTURE NET**

The most tedious and error-prone phase of Engineering Documentation, i.e., Engineering Change Order (ECO), is easy with PADS. ECOs generated in either the Schematic, or the Board database are used to automatically (hands-off) update the corresponding database.

BOARD DESIGN

PADS-PCB is today's most popular board CAD System and is the heart of the Superstation. PADS-PCB has revolutionized Printed Circuit Board CAD expectations by demonstrating an alternative to today's \$100,000 Work Stations. Thousands of designers, engineers, and Board Design Centers use PADS-PCB - and for good reasons: 1 mil resolution, 30 layers, large board (over 400 14 pin ICs per board), complete SMD support, fine line (1, 2 & 3 tracks between IC pins), both Analog & Digital capability, fast Air Gap & Data checking, Gate & Pin swapping, dynamic rubber banding, rats' nest display, interactive and auto placement, interactive & auto routing, and all required Manufacturing Aids (CAM).

PADS-PCB is tightly coupled, both to and from PADS-CAE, and from other Logic Capture systems using FutureNet™.

100% COMPLETION AUTOROUTING

The most demanding phase of board design is routing the connections; approximately 70% of the board design effort is spent in this time consuming, labor-intensive task. Every Designer and Engineer's dream is to have a 100% completion autorouter, and PADS-Superrouter™ brings this capability to the Superstation™.

Here's how it works: the Designer places the components on the board, selects the "Route"

on the board, selects

command, and the SUPERROUTER takes over, routing around the clock, hour after hour, performing this tedious task to completion, or near completion, while the Designer is involved in other tasks. It's that easy! PADS-Superrouter allows the designer to set up a routing strategy based upon the requirements of each board. A costed Maze Search algorithm, using obstacle hugging on a 10, 20, 25 or 50 mil grid, and up to 12 simultaneous layers attempts to achieve 100% completion. A Rip-up-and-Retry Algorithm is used to obtain this objective.

Following routing, an Ease-of-Manufacturing Optimizer prepares the board for maximizing the manufacturing yield. Bends and curves put in by obstacle hugging are removed, closely spaced tracks are unpacked, corners are made at 45°, and all possible Vias are removed. The results equal or exceed that of the most experienced board designer.

LOW PRICE

While the performance and functionality of the PADS-SUPERROUTER is equal to any Workstation at any price, its price is competitive with the very low cost PC-based CAD systems. The price has been structured to allow every engineer in the organization to have his/her own personal SUPERSTATION.

EVALUATION PACKAGE

So that you can appreciate the impact the PADS-Superstation™ will have in your organization, we have created a Superstation Evaluation Package. It is available at no cost to qualified engineers and designers. Please call our Sales Department at (800) 255-7814; Inside Mass. (508) 486-9521.



CAD Software, Inc. Suite #6 119 Russell Street Littleton, MA 01460

Manufacturers of parallel-processing computers

For more information on parallel-processing computers, contact the following manufacturers directly, circle the appropriate numbers on the Information Retrieval Service card, or use EDN's Express Request service.

Active Memory Technology Inc 16802 Aston St Suite 103 Irvine, CA 92714 Phone (714) 261-8901 FAX 714-261-8802 Circle No 675

Alliant Computer Systems Corp 1 Monarch Dr Littleton, MA 01460 Phone (508) 486-4950 Circle No 676

Amdahl Corp 1250 E Arques Ave Box 3470 Sunnyvale, CA 94088 Phone (408) 746-6000 Circle No 677

Ametek Computer Research Div 606 E Huntington Dr Monrovia, CA 91016 Phone (818) 359-2835 FAX 818-303-0748 Circle No 678

Aptec Systems Inc Box 6750 Portland, OR 97228 Phone (503) 626-9000 TLX 467167 Circle No 679

Aspex Inc 530 Broadway New York, NY 10012 Phone (212) 966-0410 Circle No 680 BBN Advanced Computers Inc 10 Fawcett St Cambridge, MA 02238 Phone (617) 873-6000 Circle No 681

Cogent Research Inc 1100 NW Compton Dr Beaverton, OR 97006 Phone (503) 690-1450 Circle No 682

Convex Computer Corp 701 N Plano Rd Box 833851 Richardson, TX 75083 Phone (214) 952-0200 Circle No 683

Cray Research Inc 608 Second Ave S Minneapolis, MN 55402 Phone (612) 333-5889 Circle No 684

Cydrome Inc 1589 Centre Pointe Dr Milpitas, CA 95035 Phone (408) 945-6300 FAX 408-262-8938 Circle No 685

Encore Computer Corp 257 Cedar Hill St Marlboro, MA 01752 Phone (508) 460-0500 Circle No 686 Floating Point Systems Inc Box 23489 Portland, OR 97223 Phone (503) 641-3151 Circle No 687

Intel Scientific Computers 15201 NW Greenbrier Parkway Beaverton, OR 97006 Phone (503) 629-7629 Circle No 688

International Parallel Machines Inc 700 Pleasant St New Bedford, MA 02740 Phone (508) 990-2977 Circle No 689

Meiko Lim Whitefriars Lewins Mead Bristol BS1 2NT, UK (0272) 277409 TLX 449731 FAX 0272-277082 Circle No 690

Multiflow Computer Inc 175 N Main St Branford, CT 06405 Phone (800) 777-1428 Circle No 691 Myrias Research Corp Suite 900, Park Plaza 10611 98th Ave Edmonton, Alberta, CA T5K 2P7 Phone (403) 428-1616 FAX 403-421-8979 Circle No 692

NCube Corp 1825 NW 167th Place Beaverton, OR 97006 Phone (503) 629-5088 Circle No 693

Prime Computer Inc Prime Park Natick, MA 01760 Phone (800) 343-2540 Circle No 694

Sequent Computer Systems Inc 15450 SW Koll Parkway Beaverton, OR 97006 Phone (503) 626-5700 Circle No 695

Stellar Computer Inc 85 Wells Ave Newton, MA 02159 Phone (617) 964-1000 Circle No 696

RECEIVER by executing an output command in the form

RECEIVER! LINK (expression),

where "!" indicates output and LINK identifies the type of message being sent. The process RECEIVER enters information from the process SENDER in the program by executing an input command in the form

SENDER? LINK (variables),

where "?" indicates input and the variables receive the data being sent.

Occam, a parallel-programming language developed by Inmos for the Transputer, is based on CSP. Occam contains primitives such as "par," which indicates that the following statements should be performed on parallel PEs, and "alt," which can send a message to several alternative processes. Ada, Modula-2, Pascal Plus, and various versions of Fortran for parallel processors have similar constructs for synchronizing processes.

The stumbling block that has prevented the widespread use of parallel processing has been transportability. Moving existing code from a conventional singleprocessor machine to a parallel machine or moving code among parallel machines usually requires some reprogramming. A parallel language called Linda, which is currently under investigation at Yale University, may help resolve some of the differences among the many parallel languages.

Linda consists of a few simple primitives that can be added to a standard language such as C or Fortran. To overcome the synchronization constraints of the send and receive operations, the Linda model creates an n-tuple space in memory. Instead of exchanging messages with other processes, a process that wishes to communicate data adds it to the n-tuple space, and a process that needs to receive data searches the space and reads it. For example, the statement

out("P",5,false)

adds the data "5" and "false" to the tuple with the logical name P. The subsequent execution of the statement

in("P",int i, bool b)

withdraws the tuple from the space and assigns "i" to




POWER SUPPLIES AT YOUR COMMAND.

Introducing a complete system of modular hybrid components for military SMPS designs.

What do you do when all the primary electronics are in place, but there's precious little time, budget or real estate left for the power supply?

Call Teledyne Philbrick. We offer a unique, new series of complete modular hybrid power components that are designed to be customized to your exact specifications.

Just choose the configuration you need. The 2491 Regulating Pulse Width Modulator provides all the control functions for the PSU. The 2473 is a dual MOFSET switch with high speed drivers and current sensing circuitry. And the 2478 Dual Schottky Bridge Rectifier provides up to three output voltages from a single power package.



supply—in a fraction of the time, and at a fraction of the cost, it would take to start from scratch.

Qualified to MIL-STD-1772, Teledyne Philbrick is a leading manufacturer of high performance, high reliability standard and custom microcircuits for industrial, medical, military and space applications worldwide. Send for complete specifications. Or call us toll-free at 1-800-325-1330 (outside MA).

MIL-STD-1772 Qualified

TELEDYNE PHILBRICK

40 Allied Drive, Dedham, MA 02026-9103, Tel: 617-329-1600 Fax: 617-326-6313

WEST: 30423 Canwood St., Suite 212 Agoura Hills CA 91301 Tel: 818-889-3827

Fax: 818-889-8215

U.K.: The Harlequin Centre Southall Lane Southhall Middlesex UB2, 5NH, U.K. Tel: 571-9596 Telex: 935008 Fax: 571-9439 JAPAN: 4th Floor Taiko No. 3 Bldg. 2-10-7 Shibuya-Ku Tokyo 542, Japan Tel: 797-5251 Telex: 781-24335 Fax: 797-5255



EIA - 530 TO RS - 232 CONVERTER

- Supports 10 Category 1 & 3 Category II circuits
- Full EIA 530 compliance
- DTE & DCE models

1-800-835-3298

Meets Mil-Std-188-114 Type 2

(516) 423-3232

• Up to 1 MBS data rate

• Doubles as RS-422 converter

TWX 510-226-0449

TELEBYTE TECHNOLOGY, INC.

270 E. Pulaski Road Greenlawn, NY 11740 A Public Company

CIRCLE NO 23

Be An Author!

When you write for EDN, you earn professional recognition. And you earn \$75 per published magazine page.

EDN publishes how-to design application information that is read by more than 137,300 electronics engineers and engineering managers worldwide. That's an audience that could belong to you.

If you have an appropriate article idea, send your proposal and outline to: John Haystead, 275 Washington Street, Newton, MA 02158-1630.

For a FREE EDN Writer's Guide—which includes tips on how to write for EDN and other technical publications—please circle number 800 on the Information Retrieval Service Card.



First in Readership among Design Engineers and Engineering Managers in Electronics.

"5" and "b" to "false." The statement

read("P", inti, bool b)

is the same as the "in" statement, except that the tuple remains in the space. Because these primitives are machine independent, you can add them to languages operating on different classes of machines. Linda has been implemented in shared-memory parallel computers such as the Multimax, the Balance Series, and the FX/8, and on distributed-memory computers such as the iPSC hypercube.

A revolutionary age is dawning

Although the largest variety of parallel-processing structures currently under investigation is for minisupercomputers, board-level parallel-processing products are available for many popular host computers, such as the IBM PC, the Macintosh, and the Sun family of workstations (Ref 2). Most of the boards contain Inmos Transputers. In addition NCube offers an IBM PC/AT board containing as many as four of the VLSI CPU chips that are found in the NCube/10. Many computing professionals believe that parallel processing is the programming wave of the future. These board-level products offer an economical way of trying your hand at parallel-processing computer design.

References

- 1. Desrochers, George R, Principles of Parallel and Multiprocessing, McGraw-Hill, 1987.
- Gallant, John, "Add-in μP boards break various hosts' speed limits," EDN, July 21, 1988, pg 240.
 Ahuja, Sudhir, Nicholas Carriero, and David
- 3. Ahuja, Sudhir, Nicholas Carriero, and David Gelernter, *Linda and Friends*, IEEE Computer Society, August 1986.
- 4. Carriero, Nicholas, and David Gelernter, *How to write parallel programs: A guide to the perplexed*, Yale University, May 1988.
- 5. Karashev, Lana, and Stevan Karashev, *Proceedings of the third international conference on supercomputing*, International Supercomputing Institute Inc, Vols 1, 2, and 3, 1988.
- Lipovski, G Jack, and Miroslaw Malek, Parallel Computing, Theory and Comparisons, John Wiley & Sons, 1987.
- 7. Perrott, R H, Parallel Programming, Addison Wesley, 1987.

Article Interest Quotient (Circle One) High 485 Medium 486 Low 487



SPECTACULAR DISPLAYS OF SPEED.

Introducing video driver hybrids from Teledyne Philbrick.

High-resolution graphic displays require quick response. That's why Teledyne Philbrick has combined all the driver ICs and transistors you need in one powerful space-saving package.

Where discrete components fall short, new 1900 Series Video Display hybrids come on strong as high speed trans-conductance amplifiers with high voltage, open collector outputs. They accommodate standard RS-170 or RS-343 interfaces. And accept differential or single-ended inputs with a commonmode input voltage range of +3V.

The 1901 is capable of driving up to 50V pp swings into 6pF loads with bandwidths of over 146MHz. Combining an output buffer stage with the 1901, the 1902 provides up to 100V pp swings in 20pF loads. These specifications provide flexibility in CRT selection and ease of mechanical mounting in projection and high brightness displays. Both the 1901 and the 1902 eliminate the need for pre-amps, ensure rise times of 2-4ns and provide easy thermal management.

Altogether, the 1900 Series gives you a powerful, new edge in designing sophisticated, compact imaging systems for CAD, avionics and large screen applications.

Qualified to MILSTD-1772, Teledyne Philbrick is a leading manufacturer of high performance, high reliability standard and custom microcircuits for industrial, medical, military and space applications worldwide. Send for complete specifications. Or call us toll-free at 1-800-325-1330 (outside MA).

101

MIL-STD-1772 Qualified

TELEDYNE PHILBRICK

40 Allied Drive, Dedham, MA 02026-9103, Tel: 617-329-1600 Fax: 617-326-6313

WEST: 30423 Canwood St., Suite 212 Agoura Hills CA 91301 Tel: 818-889-3827 Fax: 818-889-8215 U.K.: The Harlequin Centre Southall Lane Southhall Middlesex UB2, 5NH, U.K. Tel: 571-9596 Telex: 935008 Fax: 571-9439 JAPAN: 4th Floor Taiko No. 3 Bldg. 2-10-7 Shibuya-Ku Tokyo 542, Japan Tel: 797-5251 Telex: 781-24335 Fax: 797-5255

ems Design Handbook

SECOND EDITION

Programmable Logic Data Manus

HIGH PERFORMANCE CMOS DATA

.....





Packaging Makes the Difference

If you want your system to look its very best, look to Electronic Solutions.

The first thing you'll find is that the beauty we add to your board level system is a lot more than skin deep. It will look better, sell better, and work better in an Electronic Solutions enclosure, for a lot of

Engineered Cooling for maximum performance from the new, highdensity cards.

Built from Experience: We've been the enclosure experts since board-level systems began.

Safety and EMI/RFI Approvals by UL, CSA, TUV(IEC380) and the FCC.









Off the Shelf or Built to Order:

From simple needs like paint and labeling to complete reshaping for the most unusual requirements—we do it all. Most of the time we have a big head start.

See how packaging can make the big difference to your system. Give us a call today on our toll-free numbers

Huge Selection of Complete Enclosures



Tabletop 4,7,10,12,15 slots 31/2" Rack 4 slots 7" Rack 7,10 slots 101/2" Rack 12.15 slots DeskMate 7,10,12,15 slots



Tabletop 3,5,6,7,12, 20 32 40 slots 31/2" Rack 3 slots 7" Rack 5,7 slots 101/9" Back 12 slots 14" Rack 12,20,32,40 slots DeskMate 5,7,12 slots



Tabletop 6,7,12,20 slots 7" Rack 7 slots 14" Rack 12,20 slots



We'll FAX you the facts.

Want the latest data in a hurry? Nothing is faster than Electronic Solutions' new "FAX the FACTS" program. Call our "800" number and give us the information you need from us. We'll FAX it to you immediately.



6790 Flanders Drive, San Diego, CA 92121 (619) 452-9333 Telex II(TWX): 910-335-1169

Call Toll Free: (800)854-7086 In Calif: (800)772-7086 **CIRCLE NO 120**

Interactive test-generation software eases complex instrument programming

As computer-controlled test instruments proliferate, so do their various command sets. This ever-increasing conglomeration of differing command mnemonics creates big headaches for test engineers. The E2000A Interactive Test Generator (ITG), a mouse-driven software package that runs on specially equipped IBM PC/ATs and compatible computers as well as on the company's HP 9000 workstations, helps you manage this problem by creating Basic test programs that are independent of the measurement instruments. ITG software drivers, which are tailored to specific instruments, then link the device-independent test program to a particular test system.

At its most basic level, the ITG gives you interactive control over the state of an instrument. The instrument-specific software driver produces a window that appears on your computer's screen (Fig 1). When you move a mouse-controlled pointer onto a function box within the instrument window and click the mouse's button, the ITG pops up another window, providing you with all of the possible selections relating to that function. The software sends the appropriate command string to properly configure the instrument when you click the mouse on the desired setting.

The ITG software maintains a copy of the instrument's current state in a state vector. When you are satisfied that the instrument is correctly set up for a particular measurement, you can save the instrument's state in a file on your computer's disk. A test program can then use this file to set the instrument to the proper configura-




Fig 1—An on-screen window allows you to control the state of a computer-controlled test instrument through the Interactive Test Generator's mouse-driven user interface.

tion during a test. Though the initial release of the ITG generates Basic programs, the state-vector files contain ASCII descriptions and can be read by any programming language.

If you must change an instrument's state during a test sequence, the ITG's automatic incremental state-programming feature can reduce program execution time compared with more conventional programming methods. Because the software maintains a copy of the instrument's current state, it can calculate the minimum number of commands necessary to bring the instrument to a new state and send only those commands. This feature shrinks test times because test instruments receive fewer commands to interpret and act upon, and bus traffic between the computer and

the instruments is reduced.

The ITG writes test programs in Basic. Usually, it does not use instrument-specific commands to control the devices in a test system. Instead, the ITG employs a unified set of measurement commands that call instrument-specific software drivers. Thus, you can convert a test program written by the ITG from one multimeter to another, for example, simply by changing the program's instrument-driver specification to the software driver for the new instrument.

In the same manner, you can change a program so that it takes voltage readings with a digital sampling oscilloscope instead of a digital voltmeter. The software drivers mask the differing instrument command sets. If you prefer to use explicit instrument command strings

HIGH PROGRAMMING YIELDS



LOW PROGRAMMING COSTS



PC-Remote Programmers

- · All EPROM's up to 40 pin!
- P275127 seconds per device!
- No limit on RAM size!

Our Programmer range includes:

3000 PC based to megabit EPROMs 4000 Gang EPROM/EEPROM Copiers

5000 Editing/Remote Set EPROM

1011 Bipolar PLD (logic)

1012 Bipolar PROM/EPROM

1013 Set/Gang EPROM (up to 8 x 32 pin)

1014 EPLD & CMOS PLD

1015 Set/Gang EPROM (up to 8 x 40 pin) & Elan's Universe 1000 (full universal) (World's 1st Intel flash EPROM approval)

Options cover single chip micros, PLCC, IBM/VAX remote and Elan Logic compilers.

Ask for our Demo disks.

Elan Digital Systems 2162 North Main Street, Walnut Creek, CA. 94596

Tel: (415) 932-0882 Tel: (800) 541-ELAN



UPDATE

in your program, you can instruct the ITG to use those strings in conjunction with Basic's "Output" and "Enter" statements.

The ITG runs on IBM PC/AT and compatible machines that are equipped with the company's Basic Language Processor card. In addition, the product works on the company's Model 9000 workstations. running the company's Basic Rev 5.11. For either configuration, the Interactive Test Generator costs \$995. The E2001A, a bundle of all available ITG software drivers. costs \$495. The initial release of the driver package contains approximately 20 drivers for IEEE-488based instruments. The company plans to add more drivers for additional IEEE-488 devices and for modules based on the VXI instrumentation bus. Through February 28, 1989, you can order both the ITG and the software drivers for \$995.—Steven H Leibson

Hewlett-Packard Co, 1820 Embarcadero Rd, Palo Alto, CA 94303. Phone local office. TWX 910-373-1267.

Circle No 711



Big 8-bit performance. Tiny 18-pin package. Miniscule price.

Introducing the smallest Z8 microcontroller yet, the high-performance Micro8 (Z86C08). Just imagine what you'll be able to do with all this capability, packed into a DRAM-sized chip. For what amounts to pocket change.

The Z8 Family: Still setting the standards.

From the first, the Z8 microcomputer has been one of the industry's finest examples of simplicity and elegance. The most sophisticated microcontroller family continues to grow

Today, there is 28 support for every phase of your system development, from prototying to full production. Along with devices you know and trust, there are new parts with an increasing number of options and features for your design. Recently, the Z8 is found in such diverse uses as fans, puppy door controllers, induction bot plates, and high-performance bard disk controllers, printers, and local area networks (LAN)

Since demand for Z8 products, and their importance to the industry continues to increase, we are developing new members of the Family. The Super8" is now clearly established as the high-end Z8, and the Micro8 can be expected to have as much an impact on low-end Z8 applications. Among the other new Z8 Family members you should be keeping an eye on are:

- ➤ Z86C91 High-performance CMOS ROMless microcontroller
- ► Z86C10 Low cost 28-pin CMOS, bas 22 I/O lines and 4K bytes of on-board ROM
- ► Z86C21 8K ROM Z8, bas 32 1/0 lines, 2 levels of security

Mighty strong performance

First of all, the Micro8 features the high-end Z8 architecture. Then there's 128 bytes of RAM, two counter/timers, two single-supply analog comparators, and low power consumption. Not to mention all the advantages of Superintegration™ and CMOS technology.

Mighty powerful protection

The Micro8 may be tiny, but it's as bullet-proof as they come. You get brown-out protect and a watchdog timer, for instance. You get an operating range of 3-5.5V. And you get CMOS I/O levels and hysteresis for noise protection.

Mighty impressive bit bang for your buck

The Micro8 gives everything you want in an 8-bit microcontroller. In the smallest package you've ever seen. For about a buck and a half. Plus you're working with the familiar software and proven performance of the Z8 Family. And it's all backed by Zilog's solid reputation for quality and reliability.

You really ought to see for yourself just what the mighty Micro8 can mean to your design application. Why wait? Contact your local Zilog sales office or your authorized distributor today. Zilog, Inc., 210 Hacienda Avenue, Campbell, CA 95008, (408) 370-8000.

Right product. Right price. Right away. **Zilog**

ZILOG SALES OFFICES: CA (408) 370-8120, (714) 838-7800, (818) 707-2160, CO (303) 494-2905, FL (813) 585-2533, GA (404) 923-8500, IL (312) 885-8080, MA (617) 273-4222, MN (612) 831-7611, NJ (201) 288-3737, OH (216) 447-1480, PA (215) 653-0230, TX (214) 231-9090, CANADA Toronto (416) 673-0634, ENGLAND Maidenhead (44) (628) 39200, WEST GERMANY Munich (49) (89) 612-6046, JAPAN Tokyo (81) (3) 587-0528, HONG KONG KOWloon (852) (3) 723-8979. Taiwan (886) (2) 731-2420, U.S. AND CANADA DISTRIBUTORS: Anthem Electric, Bell Indus., Hall-Mark Elec., JAN Devices, Inc., Lionex Corp., Schweber Elec., Western Microtech. CANADA Future Elec., SEMAD

Graphics processor upgrades TMS34010, maintains software compatibility


The TMS34020 graphics processor performs floating-point calculations, software graphics primitives, and software windowing three to 20 times faster than its predecessor, the first-generation TMS34010 chip. The 34020 has a 32-bit data bus and a 512-byte instruction cache. (The 34010 had a 16-bit external data bus and a 256-byte instruction cache.) Object code developed for the 34010 is upwardly compatible with the 34020.

Although it still lacks on-chip floating-point hardware, the 34020 can make use of the manufacturer's TMS34082 floating-point math coprocessor to accelerate graphics functions such as coordinate transformations. Such hardware floating-point capability will become in-

creasingly important in graphics applications because of the trend toward using world coordinates (coordinates that are not specific to any particular graphics adapter) in graphics-application software. Integer arithmetic alone is usually sufficient for programming with screen coordinates (coordinates that are specific to a particular display resolution), but graphics-application software developers are increasingly using world coordinates to create general-purpose software interfaces. When you program with world coordinates, you'll require many transformations, so you'll need a chip, such as the 34082, that has fast floating-point capability. The 34082 operates at 40M flops and interfaces directly to the 34020's

data and address buses. You can connect as many as eight 34082 chips to each 34020.

The 34020 has 25% more microcode than the 34010, reflecting the greater number of graphics primitives the 34020 implements in hardware. For example, the chip now performs trapezoidal and seed fills in hardware. In addition, the microcode now supports 3-operand and 2-operand pixel block transfers (PixBlts), which are arithmetic BitBlts, or bit-block transfers. In a 2-operand PixBlt, for example, the first operand is ANDed with the second, and the result is stored in place of the second. In a 3-operand PixBlt, the first operand is ANDed with the second and is stored in a third place. Keep in mind that if



You can use the TMS34020 graphics processor to perform all the graphics processing for this 1024×1024×8-pixel display controller; for applications that require intensive numerical processing, you can gain speed by adding a TMS34082 floating-point unit.



HP humbly introduces the highest performance multimeter in the world.



100,000 readings per second and Cal Lab accuracy.

Lots of people claim they have the best multimeter, but we're just going to let the specs do the talking. You'll see we've created a multimeter that doesn't present you with a bunch of trade-offs—you can have speed and accuracy.

- 100,000 readings per second at 4½ digit resolution. If you need 5½ digit resolution, you'll get it at 50,000 readings per second.
- Remarkable throughput rate change a function and change a range, take

- a measurement and output to the bus 200 to 300 times per second.
- Calibration standard accuracy and 8½ digits.
- Modest price: \$5,900.00*

To get complete technical specifications before you order an HP 3458A DMM for your system, call 1-800-752-0900, Dept. A215.

*U.S. List Price ©1988 Hewlett-Packard Co. 0901802/EDN



EDN INFO CARDS

The Fastest, Most Cost-Effective Way to Generate Sales Leads!



With EDN Info Cards, you can turn a small investment into high-quality sales leads.

Issued six times per year in loose-deck packs, EDN Info Cards are delivered to EDN magazine's U.S. circulation of 121,500 specifiers and buyers. Which means they deliver results! In fact, the average card in a deck pulls literally hundreds of prospects.

You'll enjoy this steady, dependable source of qualified leads for less than 1½¢ per name. And because all inquiries come directly back to you, the faster you respond, the faster you get results.

Used as an adjunct to an advertising/promotion campaign or all by themselves, EDN Info Cards will generate the qualified leads you need to sell your products.

For further information, contact Lauren Fox, EDN Info Cards Manager, at (203) 328-2580.

* Numbers represent actual responses.

UPDATE

you need to customize any hardware primitives, you still have the option of writing your own graphics functions.

The 34020 supports window clipping/picking, which is the removal of line segments or display elements that lie outside a window's boundaries. The 34010 was slower at windowing than graphics coprocessors, such as Intel's 82786, that are optimized for hardware windowing. The 34020's window-clipping/picking capability gives the chip windowing speeds that are competitive with coprocessors that have hardware windowing capabilities.

The 34020 can take advantage of the manufacturer's 1M-bit video RAM, the TMS44C251. The manufacturer claims the 34020 is the only processor that can use the video RAM's block-write, write-per-bit, enhanced-page-mode, and split-register-reload functions. (For definitions of these terms, see "1M-bit video RAMs offer speed for high-resolution graphics displays," EDN, March 31, 1988, page 79.)

The 34020 comes in a 144-pin pingrid array (PGA). Samples will be available in the fourth quarter of 1988 for \$500; you can expect the price to drop by an order of magnitude within 18 months. Samples of the 34082 will also cost \$500, but that price will probably not drop as far or as fast.—*Margery S Conner*

Texas Instruments Inc, Box 809066, Dallas, TX 75380. Phone (800) 232-3200 ext 700.

Circle No 712

Think SAE Stanford Applied Engineering





or 25 years OEMs have selected SAE to manufacture their backplanes, PCBs, connectors, and card cages. Now they are using us as their manufacturing partner. We take total responsibility to design, fabricate, test and deliver a complete "engineered assembly." This allows the OEM to concentrate all their time and monies on marketing and developing new products — not on new and expanded manufacturing facilities and personnel.

Here's why our customers think of us for all phases of their OEM products:

- Engineered Assemblies backplane, wire wrap, card cage, connectors, PCBs, wiring, filters, power supplies, fans, mounting hardware, peripherals, and accessories; complete design, fab and test — ready for your functional test.
- Military MIL-28859/28754 backplanes, NAFI headers; PCBs to MIL-P-55110D.
- Commercial VMEbus, VERSAbus, S-100, DEC, STD, Multibus backplanes; PCBs, QPL to 16 layers, UL to 4 mils.
- Assembly and Test components, wiring and system.
- Connectors commercial and military.
- Filters EMI/RFI, emission test lab.
- Magnetic Components transformers, modules and filters.
- Card Cages custom, kits, and accessories.
- Wire Wrap semi and automatic, numerous formats and test.

Call, write or FAX for our "engineered assembly" brochure and your local representative/distributor . . . Think SAE!



Stanford Applied Engineering

3520 De La Cruz Blvd., Santa Clara, California 95054 • Ph: (408) 988-0700 • Fax: (408) 727-6438

CADDOCK's Precision and Ultra-Precision Resistor Networks provide a designer's choice of performance that will optimize solutions in precision analog circuit designs.





Type T912

o: 1:1, 9:1, 10:1

.095-

.500

Type T914

-900

.095-


Precision and Ultra-Precision Resistor 'Pairs' and 'Quads' deliver a selection of Ratio Tolerance to as tight as $\pm 0.01\%$ and Ratio Temperature Coefficient to 2 PPM/°C combined with exceptional long-term stability.

Standard Type T912 and T914 Precision and Ultra-Precision Resistor Networks.

Standard models of the Type T912/T914 Precision and Ultra-Precision Resistor Networks combine all of these performance characteristics:

- Absolute Tolerance: 0.1% for all resistors
- Ratio Tolerances: 0.1%, 0.05%, 0.02% and 0.01%
- Ratio Temperature Coefficients: from 10 PPM/°C to 2 PPM/°C.
- Absolute Temperature Coefficient: 25 PPM/°C from 0°C to +70°C.
- Ratio Stability of Resistance at Full Load for 2000 Hours: within 0.01%.
- Shelf Life Stability of Ratio for Six Months: within 0.005%.

The standard part number below provides a selection of over 500 in-production models of Type T912/T914 precision and ultra-precision 'pairs' and 'quads':



Custom Type T912 and T914 Precision and Ultra-Precision Resistor Networks.

Custom models of these precision 'pairs' and 'quads can include these special performance features:

- Resistance Values: from 1K to 2 Megohms with maximum ratios of 250-to-1.
- . Absolute TC: as low as 15 PPM/°C.
- Ratio TC: as low as 2 PPM/° C.
- For Type T912/T914 data, circle Number 201.






Precision Decade Resistor Voltage Dividers and Current Shunt Resistor Networks deliver many optimum combinations of precision and temperature coefficient performance for high accuracy range-switching circuitry.

Standard Type 1776 Precision Decade Resistor Voltage Divider Networks.

The Type 1776 Precision Decade Resistor Voltage Dividers provide a family of networks that includes 3, 4 and 5-decade voltage dividers with ratios from 10:1 to 10,000:1. Standard performance includes a wide range of specifications in particular combinations that meet the most often requested requirements.

- Absolute Tolerances: from 0.25% to 0.1%.
- Ratio Tolerances: 0.25%, 0.1% or 0.05%.
- Absolute TC: from 50 PPM/°C to 25 PPM/°C.
- Ratio TC: from 50 PPM/°C to 5 PPM/°C.
- Voltage Coefficient: As low as 0.02 PPM/Volt.



1776-C621

With 36 standard models to choose from, each circuit designer can specify the exact levels of performance required by each application.

• For Type 1776 data, circle Number 202.


Standard Type 1787 Precision Current Shunt Resistor Networks.

The Type 1787 Current Shunt Resistor Networks achieve the combination of performance requirements necessary to meet the demands of precision current measurement circuits, including laboratory and bench-type instrumentation:



- Resistance Values: 1 ohm, 10 ohms, 100 ohms and 1000 ohms.
- Absolute Tolerances: 0.25%, 0.1% or 0.05%.
- Absolute TCs: 100 PPM/°C, 80 PPM/°C or 50 PPM/°C.

There are now 12 standard models of the Type 1787 Current Shunt Resistor Networks available for 3 and 4-decade applications, and prototype quantities of many models are normally available from factory stock.



• For Type 1787 data, circle Number 203.

Caddock's new 28-page General Catalog describes over 200 models of both standard and custom precision and ultra-precision resistors and resistor networks. For your personal copy, call or write our main offices at –

Caddock Electronics, Inc., 1717 Chicago Avenue, Riverside, California 92507 ● Phone (714) 788-1700 ● TWX: 910-332-6108



PRODUCT UPDATE

Multibus I 32-bit CPU card hosts a 33-MHz 68030 µP

With the introduction of the SM31 board, users of Multibus I systems can upgrade their systems to use the 68030 μP . The card includes either a 20- or 33-MHz CPU and a 68882 math coprocessor. And, it features a 32-bit extension to the Multibus I standard, called Multiplus, which it implements on unassigned P2 connector contacts.

Another feature of the single-board computer is a SCSI port that is capable of synchronous operation at 4M bytes/sec. The card hosts a minimum of 4M bytes of dynamic RAM, but you can expand the memory bank to 40M bytes via a local bus. It also includes 2M bytes of EPROM and five 16-bit timers.

Although the 68030 has an onchip MMU based on a descriptor cache, the SM31 board includes a custom MMU compatible with the SUN (Stanford University Network) MMU. The SUN MMU features a 256M-byte address range and 64,000 descriptors, and it is suitable for applications that require frequent switching between a large number of tasks.


You can add extra functions to the single-board computer using daughter cards. Available add-on modules, for example, include a 20M-flops math processor, a 1660×1280-pixel video controller, an Ethernet interface, and a keyboard and mouse interface.

Multiplus offers full compatibility with the original Multibus I specification. The extension provides dynamic bus sizing, burst-data transfers, and a maximum data-transfer rate of 40M bytes/sec.

For software development, you can choose from the Unix, OS-9, and PDOS operating systems. In addition, the board includes a Forth interpreter and a monitor program in firmware. Configured with a 20-MHz processor and 4M bytes of RAM, the board costs \$4575 (100).—Maury Wright

Synergy Microsystems, 179 Calle-Magdalena, Encinitas, CA 92024. Phone (619) 753-2191.

Circle No 713



A custom Stanford University Network MMU and a 68882 math coprocessor provide the 68030-based SM31 Multibus I board with the power to execute workstation-class software.

Your Custom Precision and Ultra-Precision Resistor Networks from Caddock:

- Can be delivered in only 6 weeks ARO
- With total NRE charges typically under \$950°°
- Includes 10 prototype networks for your in-circuit

evaluation.



Thin-Profile, Single-In-Line package design.

Type T1794 Custom Low TC Precision and Ultra-Precision SIP Resistor Networks.

Caddock's **Tetrinox**® resistance films provide a wide choice of **Absolute TCs**, **Ratio TCs** and



precision tolerance specifications. Select the performance of your custom network from the following:

- · Resistance Values: from 500 ohms to 50 Megs.
- Absolute Tolerances: 1.0%, 0.50%, 0.25%, 0.20%, 0.10%, 0.05% and 0.025%.
- Ratio Tolerances: 1.0%, 0.50%, 0.25%, 0.20%, 0.10%, 0.05% and 0.025%.
- Absolute Temperature Coefficients: 50 PPM/° C, 25 PPM/° C and 15 PPM/° C from 0° C to +70° C.
- Ratio Temperature Coefficients: 50 PPM/° C, 25 PPM/° C, 10 PPM/° C and 5 PPM/° C from 0° C to +70° C.
- For Type T1794 information, circle Number 204.

Type 1789 Custom Low Resistance Value Precision SIP Resistor Networks.

1789-21 8512 Current-Sensing

Using Caddock's **Micronox**® resistance films, your **low resistance** custom networks can now include:

- Resistance Values: from 0.5 ohms to 10,000 ohms
- Absolute Tolerances: 1.0%, 0.50%, 0.25%, 0.20%, 0.10% and 0.05%.
- Ratio Tolerances: 1.0%, 0.50%, 0.25%, 0.20% 0.10% and 0.05%.
- Absolute Temperature Coefficients: 100 PPM/°C, 80 PPM/°C and 50 PPM/°C from 0°C to +70°C
- Ratio Temperature Coefficients: 80 PPM/°C, 50 PPM/°C, 25 PPM/°C and 15 PPM/°C from 0°C to +70°C.
- For Type 1789 information, circle Number 205.

Caddock's high thru-put manufacturing capabilities provide cost-effective, on-time delivery of your custom resistor network requirements. Custom network designs are now in-production in quantities from 500 networks per year to as high as 500,000 networks per year.

For fast solutions to your custom resistor network needs, call our Applications Engineers at Telephone No. (714) 788-1700.




Modem processor implements networking protocol for error-free communication

If you're including a 2400-bps modem in a design, consider implementing the Microcom Networking Protocol (MNP) along with the modem. The MNP provides full-duplex, error-free communication over phone lines. The SC11013/SC11006 chip set implements the MNP for you. By using the chip set, in effect, you'll be able to build a modem that implements the MNP for less than \$11 over the cost of producing a standard 2400-bps modem.

When sending instrument data or new software versions that update equipment in the field, you need error-free data. Slipped digits in data or in programs can cause expensive problems. As a result, you'll need a protocol that checks data at the receiving end. Often, block-transmission protocols similar to Xmodem or Kermit can provide the solution. With this method, the modem sends data in blocks with headers that describe the blocks and contain error-checking information. The error-ridden block gets retransmitted until no errors surface. Unfortunately, both receiving and transmitting systems have to run the same program.

With the MNP, the entire transmission service is performed by the modem at each system. This approach removes the need for each system to run the same protocol program. You can then connect any system to a modem and automatically send error-free data. In addition, the protocol compresses data, offering rates to 2900 bps with a 2400-bps modem. Other software-driven protocols transmit at less than 2400 bps because of blockheader overhead.



By adding some additional components (shaded) to those required for a standard 2400-bps modem, you can implement the Microcom Networking Protocol (MNP) to obtain error-free modem communication.

A modem based on the chip set will provide two modes of operation. The direct mode allows the modem to function as a standard 2400-bps, Hayes-compatible modem. And, in the autoreliable mode, the modem can communicate with modems that don't have the MNP implemented. After the modemhandshake sequence is completed, an answering modem looks for the protocol's characters from the originating modem. If the modem detects the error-correction characters within 8 sec, the MNP begins to control data transmission. If the characters are not detected, the modem makes a normal connection.


To implement the MNP in a standard modem, you'll need an 8k-word×8-bit static RAM; an 8530-type USART; and 4053, 74HC08, 74LS74, and 74HC27 logic circuits. All the chips required to build a standard 2400-bps modem cost \$36 (25,000); with the MNP implemented, they cost \$46.85 (25,000). The SC11013/SC11006 chip set alone costs \$33.50.—David Shear

Sierra Semiconductor, 20 N Capitol Ave, San Jose, CA. Phone (408) 263-9300. TLX 384467.

Circle No 710



We're eliminating the competition with something everyone else seems to have forgotten you need...



Plessey - Unsurpassed Process Technology

As system design becomes more and more challenging, and product life cycles become increasingly shorter, design flexibility and getting it right the first time have become critical factors in gaining and maintaining that maximum performance edge you've been looking for.

Plessey's investment in advanced process technology is unequaled in the industry. Successive reductions in feature size and continued improvement in process techniques are at the heart of leading-edge Plessey products.

Plessey - The Ultimate in ASIC Technology

Our broad range of ASIC products has grown to the point where we are now able to meet all the needs of ASIC users. We offer a full ASIC product range with a variety of options for digital, analog and mixed analog/digital applications, in gate arrays, standard cells, and full-custom. Advanced, state-of-the-art processes in fine geometry, high-density CMOS, bipolar and ECL technologies give you the highest levels of performance and system integration available today.

Plessey - Unparalleled CAD Support

The Plessey Design System (PDS) is a comprehensive suite of software em-

bracing the design, simulation and implementation of gate arrays, standard cell and compiled ASICs in CMOS and bipolar technologies.

Customers who want to use their own CAD workstations or simulators are accommodated by flexible design interfaces at various stages into PDS.

Plessey - Standard Products And Discrete Components

Plessey's standard product family offers the highest performance product range available in the world today. Capabilities range from CMOS DSP devices operating in excess of 20MHz to the world's most advanced 1.3GHz monolithic log amplifier.

High performance solutions are also offered in radio communications, digital

PLESSEY and the Plessey symbol are trademarks of the Plessey Company, PLC.

ce that gives you the edge.



PLESSE	Y KEY PR	OCES:	S TEC	CHNO	LOGY	
	BI	POLAR				
DESCRIPTION		Ft		TTER DTH	METAL LAYERS	
Industry standar	rd	400MHz	14	μm	1	
High voltage		200MHz	20	μm	1	
High speed lines	ar	4.5GHz	41	um	2	
High speed digit	tal	6GHz	3,	um	2	
Ultra-high speed	1	14GHz	0.6	6µm	3	
		MOS				
PROCESS FAMIL	LY	fCLOCK		MUM TURE	VSUPPLY	N.
KC Industry star	ndard CMOS	20MHz	4,	um	3-10V	
JG Double SiGat	e NMOS	10MHz	6,	um	9-18V	
VB High speed	CMOS	40MHz	2,	um	3-5V	
VJ Very fast CM	IOS	50MHz	1.5	ρμm	3-5V	
VQ Ultra fast CM	MOS	75MHz	1.	2μ	3-5V	
	BIPO	LAR (C	DI)			
PROCESS	EMITTER WIDTH/ FEATURE SIZE	GRID PITCH	MAX. SPEED	MAX. POWER	MIN. POWER	
ORIGINAL CDI	5µm					
CDI FAB I	3.75µm	11.5µm	10ns	2.4pJ	1.5pJ	
CDI FAB IIa	2.5µm	8µm	4ns	1.2pJ	0.8pJ	
Geometry chang	e (utilizing multi-	level differe	ntial logi	c-DML)		
CDI FAB IIb	2.5µm	8µm	800ps	0.8pJ	0.54pJ	
CDI FAB III	1.5µm	6µm	400ps	0.4pJ	0.27pJ	
CDI FAB IV	1.2µm	4.5µm	200ps	0.2pJ	0.14pJ	

frequency synthesis, data conversion, telecommunications, data communications and consumer products.

Complementing the standard IC family, Plessey manufactures a complete line of discrete components including FETs, transistors and diodes available in SOT-23 and TO-92 packages.

Plessey - Over Two Decades Of Quality Commitment

For more than 20 years, Plessey Semiconductors has been commited to supplying the latest technology, highest quality, and highest performance semiconductor products in the industry. With our unique combination of CAD support, major advances in process technology, and the most advanced research facility in the world, Plessey Semiconductors is, today, a totally commited leader in the industry.

To learn more on how Plessey can help you achieve the maximum performance that gives you the edge, send for our new comprehensive, full color, 72-page short form brochure, or call Plessey Semiconductors today.


In North America call 1-800-441-5665. Outside North America call 44-793-726666. For further information you can write to us at one of the following addresses:

Plessey Semiconductors 1500 Green Hills Road Scotts Valley, CA 95066 U.S.A.

Plessey Semiconductors Ltd. Cheney Manor, Swindon Wiltshire SN2 2QW United Kingdom







When it comes to page-printer electronics, only National puts it all together.

ALL TOGETHER FOR PRINTERS, SCANNERS, COPIERS, FAX MACHINES AND DESKTOP DISPLAYS

Introducing the NS32CG16 Printer/Display Processor.

The only fully programmable 32-bit, CMOS microprocessor tuned for graphics applications.

And the heart of the most cost-effective systems solution for a full range of imaging designs.

ALL TOGETHER: THE CHIP

The NS32CG16 combines the programmability of a high-performance 32-bit microprocessor with the power of a specialized graphics coprocessor. It includes 18 dedicated graphics instructions for:


- bit-aligned block transfers
 (BitBIT) with 16 logical operations for high-speed character moves and windowing
- line drawing (9 Mbits/sec)
- pattern drawing, replication, and filling (60 Mbits/sec)
- pattern magnification to support Epson and HP LaserJet™ emulations (1X, 2X, 3X, 4X)
- binary data compression/expansion for compact font storage under run-length-limited (RLL) encoding
- supports CCITT Group III and IV protocols for facsimile transmission
- on-chip clock generator

LaserJet and PCL are trademarks of Hewlett-Packard Corporation PostScript is a trademark of Adobe Systems, Inc.

AppleTalk is a registered trademark of Apple Computer Corporation IBM and PC/AT are registered trademarks of International Business Machines. Inc.

Ada is a registered trademark of the U. S. Government, Ada Joint Program Office

HPC AND ISE are trademarks of National Semiconductor Corporation ©1988 National Semiconductor Corporation



The NS32CG16 is the heart of a high-performance, cost-effective systems solution for applications like this page-printer controller.

- programmable power-down modes
- on-chip DMA support circuitry.

A true 2-address machine (for direct memory-to-memory graphics operations), the NS32CG16 has a 16-Mbyte linear address space to support large font storages, high-dpi (dots-per-inch) page buffers, and memory-intensive pagedescription languages (PDLs).

ALL TOGETHER: THE PERIPHERALS

The NS32CG16 is supported by a full range of peripheral devices, available now:

- hardware floating-point coprocessors for high-speed outlinefont calculations in PDLs like PostScript™ and PCL™
- DRAM controllers
- single-chip I/O support for RS232 Serial, Centronics Parallel, and AppleTalk* interfaces
- LAN support, including Ethernet, Thin Ethernet, StarLAN, and IBM* 3270/5250 protocols
- interrupt controllers with timers and parallel I/O ports.

ALL TOGETHER: THE TOOLS

The NS32CG16 is also supported by a full range of development

tools, available now:

- add-in cards to turn your PC/AT* or compatible into a powerful, multiuser development host
- a full set of language tools, including
 - assemblers, linkers, debuggers
 - optimizing compilers for C, Pascal, FORTRAN 77, and Ada*
- MicroCASE (formerly Northwest Instrument

Systems) Software Analysis Workstation for performance-tuning vour code

- National's In-System Emulator (ISE™) for complete hardware/ software integration
- the NS32CG16 Evaluation/Development Board to reduce development time and costs, and bring your design to market faster (in development).

ALL TOGETHER: THE PROOF

The NS32CG16 has already been designed-in by a number of major office peripherals manufacturers, such as Canon and Olivetti, and is now being evaluated by over 100 companies around the world.

But find out for yourself what the NS32CG16 can do in *your* design.

For more information immediately, call us toll-free at (800) 252-4488, ext. 731.

We think you'll be pleasantly surprised.

Altogether.



Not only can virtual instruments simulate many conventional instruments, they can function as unique, specialized instruments as well. Once uniform, easy-to-use software interfaces are introduced, virtual instruments will allow design engineers to export their instrumentation expertise to others.



Realizing the concept of virtual instrumentation promises to unleash a whirlwind of products. (Photo courtesy Colorado Data Systems)

SPECIAL REPORT

Virtual instruments

Charles H Small, Associate Editor

inally, computer-controlled instruments on a card that connect to industry-standard backplanes are emerging. Combining these instruments on a card with powerful, low-cost personal computers or single-board computers, design engineers will now be able to create virtual instrumentation. Although the capability for producing virtual instruments has existed for many years, previous attempts generally failed to gain widespread acceptance because of the high cost of the hardware and the lack of easy-to-use software. Realizing the concept of virtual instrumentation promises to not only automate the design engineer's measurement tasks, but also to allow him to export his instrumentation expertise far beyond the narrow confines of his lab. Unfortunately, though the hardware is now affordable, the available software still leaves something to be desired.

The promise of virtual instrumentation

Virtual instrumentation borrows its name from the computer engineer's lexicon. In computerese, virtual contrasts with physical, real, or logical (which is not to say that "virtual" equates with "spiritual," "unreal," or "illogical"). All engineers are familiar with real instruments: They come in cases and have front-panel controls that can be manipulated directly.

Engineers use virtual instruments, on the other hand, much like a programmer uses virtual memory. The computer's hardware allows the programmer to read and write to virtual memory at will, using a single set of commands, regardless of where the computer actually stores the data. The programmer doesn't care if his data resides in CPU registers, cache memory, main memory, or off-line storage.

Similarly, an engineer using virtual instrumentation works with a uniform software interface—perhaps a simulated front panel displayed on a CRT—to set up the instrument, capture and analyze data, and display or record readings. If you have multiple instruments in one system, the software can also oversee cross-triggering and stimulus-response coordination.


The physical instruments that the software drives *could*, strictly speaking, take many forms. They could be general-purpose, high-speed digitizers backed by appropriate analysis software; they could be standalone IEEE-488 instruments; or they could be instruments on a card plugged into the computer's backplane or a special instrumentation chassis.

The high-speed digitizer will serve to illustrate the concept of virtual instrumentation quite clearly. The analysis software can mimic several classical real instruments by reducing the same set of captured data in different ways. For example, by simply scaling and displaying the data points, the virtual instrument can function as an oscilloscope, or, by performing an FFT on the data, it can duplicate the working of a spectrum analyzer.

ATE spawns virtual instrumentation

Although virtual instruments will undoubtedly have a great effect on design engineers, the impetus behind virtual instrumentation is coming from the ATE comVirtual instruments have as yet failed to gain widespread acceptance because of the high cost of hardware and the lack of easy-to-use software.





The control software for Virtual Instrument's \$2995 virtual CAT multifunction instrument, which plugs into an IBM PC/AT, provides virtual front panels for an oscilloscope, function generator, frequency counter, and DMM.

munity. Two broad trends in electronics underlie the new virtual instruments based on instruments on a card, and ATE users are embracing both of these: powerful μP -based personal and single-board computers and advances in electronics miniaturization.

The ATE community has always tried to incorporate each emerging class of computer—mainframe, mini, scientific desktop, board-level, and personal—into its ATE systems. Lately, the ATE industry has been taking advantage of newer, more powerful personal computers and board-level computers as instrument controllers to replace the more-expensive scientific desktop computers and minicomputers. Also, advances in ASIC and surface-mount technology are allowing instrument makers in many cases to put an entire instrument on a single card. These two trends have made it possible for ATE makers to assemble low-cost, compact, and powerful test systems as substitutes for the more expensive and cumbersome "rack-and-stack" systems.

Designers have different goals


Without question, design engineers will begin to emulate their ATE colleagues and employ virtual-instrument systems based on instruments on a card for automated testing in the design lab. Nevertheless, restricting these devices solely to laboratory ATE is taking too narrow a view of their possible applications. Rather than merely following the ATE community's practice of putting computers into instrument systems, design engineers can now also think of putting virtual

instruments into the computerized systems that they have to design. Moreover, with these instruments on a card and appropriate software, design engineers can capture and then export their instrumentation expertise. The eventual destination of their computerized expertise can conceivably span all phases of electronics, from incoming inspection and prototype testing to manufacturing, field service, and customer use.

After all, to a design engineer, these new instruments on a card that plug into standard backplanes are another type of computer peripheral. The ATE community has done design engineers quite a favor. Perhaps Thomas Carlyle was right. As you may recall, it was the Victorian-era historian who said, "Technologists are little men in black coats who do something important while trying to do something else."

Digital designers appear receptive

Instrument makers report that digital designers—particularly those who perform computer simulations—are already clamoring for virtual instrumentation. Digital engineers want to use virtual instruments to perform reality checks on their computer simulations. They want to be able to feed data derived from component characterization and prototype testing back into their circuit-design simulations. This data allows the engineers to adjust the fudge factors in their simulations so that the simulator will produce more accurate results in the future. Similarly, design engineers want to import the results of environmental testing, quality control, and field-service repairs to refine their thermal



Writing test programs with Wavetek's Wavetest test-program generator is a 2-step process. First, you embed an instrument setup in an "icon" using a virtual front panel. Then, you embed the icons in a flow chart. You need not write any lines of conventional program-language code.

and environmental simulations.

Analog engineers, on the other hand, seem likely to remain satisfied with their existing real instruments. Indeed, certain instruments do not lend themselves to the instrument-on-a-card approach. Instruments based on scan-converter tubes and microwave instruments that use wave-guides, for example, are simply too bulky to fit on a card in a backplane. Such instruments will probably always be packaged in their own enclosures.

Whatever their discipline, all engineers, both analog and digital, could use virtual instruments exactly as they presently use real instruments while developing products in the lab. If virtual and real instruments were merely equivalent, though, design engineers would have no particular reason to switch to virtual



Virtual instruments such as these from Heath Zenith plug into a chassis that is an extension of the IBM PC/AT bus. The chassis also accommodates the instruments' signal connectors.

instruments for lab use. Virtual instruments do have significant advantages over real instruments, however.

First of all, a virtual-instrument system can learn and remember instrument setups and test procedures. Saving instrument setups benefits not only individual design engineers, but also allows several engineers to share an instrument system more easily because the system can be switched quickly from one engineer's job to another's. Further, an engineer can automate routine or repetitive tests. In some cases, these automated routines can later prove useful to manufacturing, quality-control, and field-service personnel.

And, depending on how well the control software performs its job, virtual instruments can include uniform, easy-to-learn controls so that engineers can use a variety of instruments without having to undergo a tedious learning or relearning period for each device. Lastly, virtual instruments are tightly coupled to a computer, which eases the task of analyzing and reducing data (see **Ref 1** for a roundup of analysis software). Many conventional real instruments, despite having names such as "spectrum analyzer" or "logic analyzer," do not, in fact, analyze anything—they merely capture and display data.

At present three classes of instruments on a card exist. These plug into, respectively, proprietary buses, personal-computer buses, and industry-standard instrumentation buses. Proprietary instrument-on-acard buses have been around the longest. Examples are the products that Summation and Colorado Data Systems

To a design engineer, instruments on a card are just another type of computer peripheral.

tems (CDS) offer. Rapid Systems, Heath Zenith, and Virtual Instruments Corp make instruments on a card that plug into the IBM PC/AT backplane, but no standardization efforts are underway for PC-based buses.

Avalanche of VXI Bus products impending

Right now, only CDS and National Instruments have instruments on a card for the new industry-standard VXI instrumentation bus (see **box**, "VXI Bus standardizes instruments on a card"). Many other instrument makers, however, intend to announce their line of VXI instruments at Autotestcon in Minneapolis, MN, October 4 to 6.

Regrettably, having new instruments on a card as the hardware base for virtual instruments is not enough to ensure that such instruments will be widely accepted. The real key to the acceptance of virtual instrumentation is software.

The history of software for IEEE-488 bus instruments offers some parallels for VXI Bus virtual-instrumentation software and may indeed portend the future. The original version of the IEEE-488 standard did a fairly thorough job of defining its hardware interface. After some initial confusion, which resulted in refinement of the standard, instrument manufacturers were able to develop instruments that complied with the standard's electrical requirements for handshaking, timeouts, interrupts, and response to polls.

Software, on the other hand, was left almost completely unspecified. Engineers found the task of programming IEEE-488 instruments annoying, frustrat-

VXI Bus standardizes instruments on a card

Both the US Air Force, through its MATE (modular automatic test equipment) program's IAC (instrument on a card) Subcommittee, and engineers, via the IEEE P1155 Committee, are determined to shrink test instruments down until they fit on a single card. Their goal is to make possible smaller, faster, and less-expensive test systems.

Last year, five test-equipment manufacturers, Colorado Data System, Hewlett-Packard, Racal Dana Instruments, Tektronix, and Wavetek, set up the VXI consortium and proposed the VXI Bus as the standard for instruments on a card. The VXI Bus is, literally, an extension of the VME Bus (IEEE 1014). Standard VME Bus cards can plug into a VXI Bus backplane because the VXI Bus is a superset of the VME Bus. Like VME Bus pc boards, VXI Bus pc boards can be Eurocard A or B size and have the P1 and P2, 96-pin connectors. VXI Bus pc

boards are also available in the larger C- and D-size boards, which measure approximately 13×9 in. and 13×14 in., respectively.

The D size is a triple-height Eurocard that sports an additional P3 connector. The P3 connector carries high-speed instrumentation signals. These signals include a 100-MHz clock and sync signal, additional power-supply feeds, additional ECL trigger lines, and 24 additional daisy-chained, local-bus lines.

Wide open spaces

The VXI Bus opens up the VME Bus's card spacing from 0.8 in. to 1.3 in. to allow the VXI Bus pc boards to be individually shielded. You can accommodate 20 VXI Bus boards in a standard 19-in. rack. Unlike the VME Bus spec, the VXI Bus specification dictates allowable levels of noise, EMI, and power dissipation because sensitive instruments need an electri-

cally clean and thermally stable environment.

A VXI Bus system can have as many as 256 devices. A single pc board can contain several devices or a single device can be spread over several pc boards. A system comprises a central-timing pc board (called the slot 0 board) and a maximum of 12 additional pc boards. The slot 0 board usually also has a controlling computer along with the system-timing circuitry.

The VXI Bus device protocols define how the various VXI Bus devices in a system divide up the system's address space. Each device gets a minimum of 64k bytes of address space for control and communication. Simple devices can get by with register commands; more-complicated devices use character strings similar to the existing IEEE-488 instruments' character strings for passing commands and data.


ing, and time consuming. Each instrument had its own pecularities—many of which could be found only by painful trial and error. No uniformity existed for common commands among all instruments or among command sets for a given class of instruments.

For example, many types of instruments have a trigger function that initiates a measurement. The IEEE-488 standard specifies a GET (group execute trigger) command that supposedly simultaneously triggers all instruments linked by an IEEE-488 bus. But some manufacturers programmed their instruments to respond to GET commands by stepping through a sequence of front-panel settings.

System DMMs are another example of a source of confusion. All system DMMs are very much alike, and a knowledgeable instrument user can generally operate an unfamiliar DMM almost immediately merely by inspecting the DMM's front panel. Such is not the case when operating these instruments over the IEEE-488 bus. Each manufacturer's system DMM has its own syntax for command strings.

Test generators ease pain

Finally instrument makers such as Wavetek, National Instruments, Hewlett-Packard, and Tektronix developed a class of general-purpose IEEE-488 software-development aids that run on common personal computers and, in some cases, on mainframes. (Ref 2 provides a roundup of existing IEEE-488 software tools. Note that Hewlett-Packard in Loveland, CO, has introduced similar software since the roundup appeared; for information on this product, see the Product




Unlike most VXI Bus instrument makers, National Instruments is not waiting until Autotestcon in October to introduce its first VXI Bus card. The \$3000 GPIB-VXI is a slot 0 VXI Bus controller that communicates with the outside world via the IEEE-488 bus.

Update on pg 105.) The makers of these software tools, all of whom belong to the VXI consortium (see box, "VXI Bus standardizes instruments on a card"), can easily adapt them to other virtual instruments besides IEEE-488 systems—particularly VXI Bus systems which, by design, can use the same command-string techniques as IEEE-488 instruments.

The IEEE-488 bus software tools work on the player-piano principle. To make a piano roll, a master pianist plays a special recording piano whose keyboard mechanism cuts the master roll, or program, as the pianist plays. From then on, untrained musicians can use copies of the master piano roll to play the piano without spending years mastering the intricacies of piano technique. Similarly, the IEEE-488 tools allow an expert to set up programming aids that follow a uniform, easy-to-use format so that less-sophisticated users can operate and program the instrument system painlessly.

Typically the tools offer two general types of programming aids. One, they present the end user with a software simulation of an instrument's front panel, and two, they provide a high-level, pictorial method of structuring programs. To operate the IEEE-488 tools, you first summon a virtual front panel for each instrument you plan to use. With a mouse, or some other graphic-entry tool, you manipulate (sometimes called "mouseing" or "mousageing" in virtual instrumentation jargon) various CRT simulations of knobs, sliders, dials, and pushbuttons to set up the instruments. Then you export these setups to the program-development



This two-board set for the IBM PC, available from Virtual Instruments Corp, replaces four conventional benchtop instruments.

Virtual-instrument software can mimic different real instruments by reducing the same set of captured data in different ways.

tool and structure the sequence in which your test program will use these setups. Some tools can analyze the instrument's captured data; others merely put the data into formats that common data-analysis programs can accept (**Ref 1**).

Panel conceals detail

Hidden beneath this high-level, graphically oriented software layer is a rat's nest of nitty-gritty detail. The virtual-front-panel software, for example, has to parse your manipulations of the virtual-front-panel controls and translate them into corresponding command strings for a particular instrument. If you were to program such an instrument with a conventional language, you would have to manually compile each command string yourself and insert them into function

Manufacturers of virtual instruments and software

For more information on virtual instruments and software such as those described in this article, contact the following manufacturers directly, circle the appropriate numbers on the Information Retrieval Service card, or use EDN's Express Request service.

Colorado Data Systems 3301 W Hampden Ave, Unit C Englewood, CO 80110 (303) 762-1640 Circle No 650

Heath Zenith Heath Co Benton Harbor, MI 49022 (616) 982-3200 Circle No 651

Hewlett-Packard Measurement Systems Operation Box 301 Loveland, CO 80539 (303) 667-5000 Circle No 652

Hewlett-Packard New Jersey Div 150 Green Pond Rd Rockaway, NJ 07866 (201) 627-6400 Circle No 653

National Instruments 12109 Technology Blvd Austin, TX 78727 (512) 250-9119 FAX (512) 250-0382 TLX 756737 Circle No 654 Rapid Systems 433 N 34th St Seattle, WA 98103 (206) 547-8311 FAX (206) 548-0322 TLX 265017 Circle No 655

Summation Inc 11335 NE 122nd Way Kirkland, WA 98034 (206) 823-8688 FAX (206) 823-7994 TLX 152219 Circle No 656

Tektronix Inc Box 1700 Beaverton, OR 97075 (800) 835-9433 TLX 151754 Circle No 657

Virtual Instrument Corp 32 Portland Ave Georgetown, CT 06896 (303) 544-9801 Circle No 658

Wavetek San Diego Inc Box 85265 San Diego, CA 92138 (619) 279-2200 Circle No 659 calls. Thus, the virtual front panel is, in effect, a subroutine-call generator.


The tools also provide the experienced user with an elaborate set of routines for constructing the virtual-front-panel graphics and linking the graphics to the proper command string. In addition, they provide equally elaborate utilities for formatting the data obtained from the instruments.

Tools suit ATE users, not designers

As useful and powerful as these IEEE-488 program generators are, they are targeted for ATE users, not design engineers. The tools' goal is to make it easy for a test engineer to concoct a program that an untrained line worker can use repetitively for production testing or incoming inspection.

Design engineers' needs are not exactly congruent with those of ATE engineers. For example, because test engineers doggedly remain faithful to Basic (which many others consider obsolete), most of the IEEE-488 tools use an "enhanced" Basic as a programming language. These test-Basic languages have been extensively enhanced to meet the real-world needs of test engineers. As long as an engineer's purpose is to generate no more than a canned test program, using these tools means no more inconvenience than learning the pecularities of an enhanced Basic.

If, however, you plan to integrate virtual instrumentation with other software-driven peripherals in your computer system or run the machine under some other operating system than DOS, then you will be more



Test generators such as HP's Interactive Test Generator can mix readings from several instruments at once on a single screen.



we never stop asking

HP's perfect balance between price and performance in logic analysis.

The balance is called value! And nobody can put more value on your bench than HP. With the HP 1650A and HP 1651A, you get powerful capabilities at prices that keep the bottom line where you like it—low.

HP Logic Analyzers: the extra measure.

The exceptional value stems from HP's proprietary "logic-analyzer-on-a-chip" technology which integrates state analysis, timing analysis and acquisition memory on a single IC. You get features like 25MHz state/100MHz transitional timing on all channels and two independent analyzers in a single instrument.

If your application is digital hardware, or if you're working with popular 8-bit μ Ps, choose our 32-channel HP 1651A at only \$3,900.

For your 8-, 16-, or 32-bit μP development applications, choose the 80-channel HP 1650A analyzer at only \$7,800. It offers full support for most popular μPs including the Motorola 68020 and the Intel 80386.

EDN September 1, 1988

Both analyzers are capable of crossdomain triggering which lets you simultaneously capture and display state and timing information with time correlation for powerful cause/

effect problem solving.
Each has a built-in disc
drive for storage
of setups and
measurements.
And additional
software tools
to make your
measurement
tasks easier.



Call HP for your free video! 1-800-752-0900, Ext. 215V

Get a hands-on feel for our HP 1650A and HP 1651A logic analyzers with our demo video and literature. They're free!



You'll see how we balanced price and performance-perfectly.

"No downtime."

When you need test equipment, you don't need downtime. Leasametric guarantees our equipment will work. Or we'll replace or repair it, usually within 24 hours.


Get the best names in the business. From the best name in the business. Leasametric. 1-800-553-2255



Instrument Rental Division 1164 Triton Drive Foster City, California 94404

Count on us.

CIRCLE NO 25



likely to program the peripherals in C or Pascal. In this case, the program-generation tools would be of limited utility. You could use them to generate the command strings and subsequently save the strings in a file. Then you could boot your regular program-development software, read the command strings, and insert them in the appropriate subroutine calls.

These tools reveal their ATE orientation in the way they interface with programming languages other than the enhanced Basic versions. They also perhaps indicate what could be a deficiency as far as virtual-instrumentation software for the VXI Bus is concerned. Most of the IEEE-488 software aids can call a library subroutine that you had previously compiled using a different language. But that path cannot easily be reversed that is, you cannot call a test program generated by the IEEE-488 program-generation tools from a program written in another language. Therefore, unless instrumentation-software vendors integrate their products with common languages and operating systems, such as C and Unix, design engineers will probably devise their own programming schemes for virtual instruments when incorporating these instruments in their designs.

EDN

References

1. Leibson, Steven H, "Laboratory-automation software," **EDN**, June 9, 1988, pg 114.

2. Harold, Peter H, "Program-generation tools for PCs ease IEEE-488 system integration," EDN, April 14, 1988, pg 71.

Article Interest Quotient (Circle One) High 497 Medium 498 Low 499

When it comes to ASICs, you need more than technology that works.

You need a partne



rship that works.

In today's highly competitive marketplace, it takes more than technology and tools to meet your ASIC needs. It takes a long-term partner you can count on. One who's ready to help you turn your hot idea into an even hotter new product.

At Fujitsu Microelectronics, we believe that the only way we can achieve our goals is to help you achieve yours. So we've committed our technical, financial and human resources to providing you with the ASIC technology, tools and trust you need to meet your objectives. From design support through volume production of your advanced VLSI ICs. The heart of your new products.

When you shake hands with Fujitsu, you get more than just a business deal. You get the industry's most experienced volume producer

of ASIC devices as a working partner.

We become an extension of your ASIC design team, providing you with a nationwide network of field application and technical resource engineers, ready to offer local technical support on both products and tools.

You also get ASIC sales and marketing support to help you smooth out all the administrative wrinkles.

Plus coast-to-coast technical resource centers, fully equipped with easy-to-use design tools. And local training and twenty-four hour design facilities, so you can work whenever inspiration strikes.

All supporting the most advanced process and manufacturing technologies in the industry, including CMOS, ECL, BiCMOS and LSTTL.

All of which is structured for the fast design input-to-prototype turnaround, design security and timely delivery of volume production you need to get to market faster.

It all adds up to a partnership that works. Which, after all, is everything an ASIC partner should be.



FUJITSU MICROELECTRONICS, INC


Everything an ASIC partner should be.

3545 North First Street, San Jose, CA 95134-1804 (408) 922-9000

EDN September 1, 1988 CIRCLE NO 67

Simplify your life with single source supply.

THE MOST POWERFUL16-BIT SINGLE-CHIP MICROCOMPUTER.




ffering higher integration, higher speed and enhanced functionality, the V25 meets more of your design needs. Which is why so many innovative designers are choosing the V25 for their 16-bit micro-based systems.

- ☐ High integration: programmable interrupt controller; 2-channel serial I/O port; three 16-bit timers; time-base counter and more.
- ☐ High speed: 16/32-bit temporary register/shifter; 16-bit loop counter and prefetch pointer.
- □ Enhanced interrupt handling: 8 programmable priority levels, hardware context switching for 8 register banks; 8-channel macro service controller.
- ☐ Two stand-by modes: halt and stop.

THE FIRST 2M-BIT CMOS EPROM.

EC has just launched UV EPROMs into the 2M-bit era. The new μ PD27C2001D gives you 2M-bit capacity in a 256K x 8 organization. High integration is complemented by high speed. With access times as fast as 150ns, our 2M-bit devices eliminate wait states for your CPU. Programming is also fast at 100μ s per byte. The 4-byte page write mode multiplies programming speed.

- ☐ Organization: 256K x 8.
- □ Access time: 150/170/200ns.
- □ Power consumption: 30mA max/ 6.7MHz operation; 100μ A max/ standby.
- \square Programming: 100μ s/byte with 0.1ms pulse at 12.5V; 4-byte/page write mode.
- □ Package: 32-pin 600 mil CerDIP with JEDEC standard pinout.



For fast answers, call us at:

USA Tel:1-800-632-3531. TWX:910-379-6985. W. Germany Tel:0211-650302. Telex:8589960. The Netherlands Tel:040-445-845. Telex:51923. Sweden Tel:08-753-6020. Telex:13839. France Tel:1-3946-9617. Telex:699499. Italy Tel:02-6709108. Telex:315355.

I hen you're buying semiconductors, multiple vendors can cause major mixups. To simplify everything, build a committed single-source relationship with one supplier: NEC.

We're the world's largest semiconductor manufacturer. We offer the industry's broadest lineup. The technology and quality of our components have made us an international leader in computers, communications and home electronics.

How do you get volume, variety, on-time delivery and applications support across the full spectrum of your semiconductor needs? It's simple. Build a single source relationship with NEC.

THE FASTEST4K-BIT ECL RAM.

ead and write speeds are the critical parameters for ECL RAM performance. NEC has cut access time to 5ns and write cycle time to 7ns with our new ultra-fast 4K-bit ECL RAMs. How did we boost performance that high?



By using super-shallow junction transistors, trench isolation technology and Schottky diode clamp-type memory cells. Both ECL 10K $(\mu PB10474A)$ and 100K $(\mu PB100474A)$ interface devices are available.

- ☐ Organization: 1K x 4. ☐ Access time: 5/7ns.
- □ Power consumption: 1.2W.
- □ Package: 10K 24-pin ceramic DIP; 100K
 - 24-pin ceramic DIP/QFP.
- ☐ Broad line of other ECL RAMs available: from 1K to 16K-bits; supplied in a diversity of organizations and speeds.

FAST AS A FLASH: 1M-BIT DUAL-PORT GRAPHICS BUFFER.

EC's new megabit dual-port buffer chip is designed for super fast graphics processing. A unique "Flash Write" function clears the screen in a flash. The 256K x 4 RAM port allows bit write and fast page mode for high-speed bit operations. The 512 x 4 serial port operates at clock speeds up to 33MHz to handle high resolution graphics. To add value to your image processing system, design-in our μ PD42274.

- ☐ Speed: RAS access 100/120ns; CAS access 25/30ns; serial read cycle -30/40ns.
- ☐ Power consumption: stand-by—3mA; random read/write (serial port active) -100/90mA.
- ☐ Package: 28-pin 400 mil ZIP and SOJ.*

*Under development.



Hitachi's Hi-BiCMOS[™] Process Makes High-speed, Energy-efficient Performance a Reality

Hummingbirds are light, agile, and incredibly fast. They consume energy efficiently as they dart from flower to flower, beating their wings faster than the human eye can follow. This kind of high-speed, power-efficient performance has not been available in a semiconductor—until now. Finally, no compromises.

Hitachi brings you second generation Bi-CMOS—Hi-BiCMOS—the advanced process technology that delivers ECL-like speed with power consumption comparable to CMOS. Hi-BiCMOS transcends generic Bi-CMOS by intermixing bipolar and CMOS structures at the basic cell level, for power-efficient, high-speed performance.

Hitachi has more than three years' experience fabricating Hi-BiCMOS parts. We've refined

Hi-BiCMOS into a reliable, high-yield process. You're assured of a dependable supply of devices, in production quantities—all with Hitachi's legendary quality.

A broad variety of mainstream devices, with leading edge performance, is now available as a result of Hitachi's Hi-BiCMOS process. Hitachi's newest 1M DRAMs use Hi-BiCMOS to achieve a fantastic 35ns access time. These fast memories feature high-performance with non-multiplexed addressing. They come in cool-running plastic packaging, and perform at half the access time of standard high-speed DRAMs.

Hitachi's Hi-BiCMOS SRAMs deliver 256K densities, with TTL I/O and 20ns access speeds.



That's enough density to build large cache memory arrays with unusually high hit rates. Plus, you have the product to support super system performance. And, we have 256K, 15ns ECL I/O devices now, with 10ns available in the near future.

Hitachi's Hi-BiCMOS gate arrays use advanced 1.3-micron structures with 1.0-micron effective lengths. On a system level, Hi-BiCMOS densities reduce chip count delays for performance comparable to ECL, but without ECL's power and heat penalties. The HG29M100 gives you: fast 400 ps gate delays with CMOS power consumption levels, advanced capabilities with 10,000 gates, 4.6K bits of on-board RAM and up to 220 I/Os. The HG21T30 offers you 3,000 gates and 90 I/Os with both ECL and TTL interfaces.


Hitachi's Hi-BiCMOS technology helps you eliminate frustrating design compromises. You can count on Hitachi's Hi-BiCMOS process to deliver the speed, density, and low-power performance in reliable, quality parts. For more information, call your local Hitachi Sales Representative or Distributor Sales Office today.

Hitachi America, Ltd. Semiconductor and IC Division 2210 O'Toole Avenue, San Jose, CA 95131 Telephone 1-408/435-8300



We make things possible





If you need a large voltage swing in a small package, try our new OPA445. Its compact size and voltage-handling ability make it an excellent device for ATE pin drivers, programmable power supplies, and controllers.

Key OPA445 Features

- ±10V to ±45V supply range
- ±15mA min output
- 10V/μs slew rate
- Monolithic economy and reliability
- 50pA max bias current
- 80dB min CMR
- 8-pin plastic DIP or TO-99
- -25/+85°C or -55/+125°C models
- \$3.80* each (OPA445AP) CIRCLE NO 70

For complete details on the new OPA445, call your Burr-Brown sales engineer or Applications Engineering, 602/746-1111. Burr-Brown Corp., P.O. Box 11400, Tucson, AZ 85734.

BURR-BROWN®

Video op amps find use in RF and active filters

Video op amps designed for radio frequencies offer relatively high output current and low power consumption in comparison with conventional op amps. They can work well in various high-frequency analog-signal-processing applications, including driving flash converters and active antialiasing filters.

Ken Schaefer and John Shier, VTC Inc

You can use some operational amplifiers designed specifically for RF purposes in several typical high-frequency analog-signal-processing applications. Conventional operational amplifiers are fabricated with slow high-voltage processes differing little from those in use in the late 1960s (Ref 1). These conventional amplifiers offer excellent accuracy, large signal swings, moderate output drive capability, and limited frequency response. By comparison, the op amps discussed here are made using a fast process and offer high current outputs. Designed to supply 50 mA of output current, their complementary class AB push-pull output stage uses fast PNP transistors (Fig 1). The scaled bipolar linear-IC process provides NPN transistors with $f_{\rm t}$ of 6 GHz and vertical PNP transistors with $f_{\rm t}$ of 1.5 GHz.




Fig 1—A simplified schematic for the VA705 video op amp shows the complementary class AB push-pull output stage.

Although the push-pull output is typical for op amps, it has not previously been available in an RF version because the output transistors in conventional RF amplifiers are not fast enough to track a high-frequency signal throughout its full excursion, as is required for AB operation. In complementary class AB operation, the base bias on the output transistors allows them to operate in their nonlinear region part of the time. The result is lower signal fidelity but also less power con-

Complementary class AB operation results in lower signal fidelity but also less power consumption.

sumption. At any given instant one of the output driver transistors Q_{14} and Q_{15} puts out only the actual current needed by the load, without the excess bias current needed in class A amplifiers. Your power requirement can thus decrease dramatically in comparison with the power needed by conventional class A amplifiers built with discrete components.

These video op amps achieve their high frequency by sacrificing the high breakdown voltages that conventional analog ICs offer; the video op amps operate with nominal supply voltages of $\pm 5 \mathrm{V}$, with typical signal swings to $\pm 2.5 \mathrm{V}$. These supply voltages and swings are usually not a serious limitation for RF applications, in which load impedances tend to be low (eg, 50 and 75Ω transmission lines), since the amplifiers are designed to supply ± 50 mA output currents.

The basic amplifier is available in seven versions, including a unity-gain compensated version (VA705) and two decompensated versions (VA708; VA707, A_V). Also available are dual and quad versions with identical properties. DIP, SOIC, and PLCC packages are offered. For applications requiring more precision, you can use the VA701. Two unity-gain video buffers (VA033, VA003) provide ± 100 mA of output current and a 300-MHz bandwidth. The amplifiers' basic parameters are summarized in **Table 1**.




Fig 2—This video op amp is configured to drive a flash A/D converter. The small element values are characteristic of video circuits, and the VA707 has ample drive capability for these low impedances.

Three prototype models of these amplifiers illustrate how well they work for RF signals in the 5- to 80-MHz region. Two of these come from the increasingly popular area of video-frequency sampled-data systems; the third example shows how to use them in high-speed instrumentation applications.

Op amps drive flash converters

CMOS flash A/D converters have become popular building blocks for digitizing video signals. The proper input-signal conditioning for these flash converters requires an input amplifier with enough speed not only to minimize settling time to a given accuracy but also to

OP AMP MODEL	OPEN-LOOP GAIN (dB)	CLOSED- LOOP GAIN (TYP V/V)	SLEW RATE (V/µSEC)	GAIN BAND- WIDTH (MHz)	OFFSET VOLTAGE (mV)	INPUT BIAS	POWEF (mW)
VA705	80	UNITY-GAIN STABLE	35	25	3	650 nA	75
VA708	80	DECOMPEN- SATED A _V >3	85	100	3	650 nA	75
VA707	80	DECOMPEN- SATED A _V >12	100	300	3	650 nA	75
VA701	120	PRECISION UNITY-GAIN STABLE	8	30	0.05	25 nA	80
VA711	120	DECOMPEN- SATED A _V >5	30	100	0.05	25 nA	80
VA033	Ô	VIDEO BUFFER A _V =1	2000	300	8	15 μΑ	280
VA003	0	VIDEO BUFFER A _V =1	700	300	8	15 μΑ	350




Fig 3—The Fig 2 circuit was measured without any series damping $(R_s=0)$ and with a load capacitance of $C_L=50$ pf; **a** shows the frequency-domain measurement, and **b** shows the time-domain response.

minimize harmonic, intermodulation, and phase distortions of the input signal. In general the amplifier should have a bandwidth three to six times that of the video input signal. For video signals, the bandwidth should be within 15 to 30 MHz. The amplifier must also be capable of driving capacitive loads up to 60 pF with no instability problems. Also, some voltage gain is often desirable.

Users of flash converters often find that the input amplifier is the most challenging part of the design. Instead of resorting to an expensive hybrid or discrete design to solve the problem, however, you could use a video op amp (Fig 2).

When designing an input amplifier for a flash converter, you usually want to be able to set not only the gain but also the bandwidth to a value that is optimum

for performance specifications such as signal fidelity and antialiasing. For a simple bandwidth adjustment, you could use a plain capacitor with a value of 40 to 60 pF because the input resistance is generally greater than 100 k Ω . For example, you might want to design an amplifier with a gain (A_V) equal to 8 (V/V), according to the formula:

$$A_{V}\approx 1+\frac{R_{3}}{R_{1}\!\!\parallel\!\!\left(R_{2}+\frac{R_{P}}{2}\right)}. \label{eq:AV}$$

The summing resistor R_2 serves to level-shift the output level to the commonly used flash converter's full-scale input level of 0 to 1V or 2V. Although the VA707 amplifier is specified for gains of 12 V/V or greater, you can use it at lower gain levels by keeping impedance levels small (500 Ω) and by using a phase-recovery capacitor (C_t) across the feedback resistor.

Step response reflects large bandwidth

The measured frequency response of the prototype circuit is shown in Fig 3a. Here the frequency response shows a 3-dB bandwidth point at 70 MHz with a peak in the 90- to 100-MHz range. The corresponding 1V step response in Fig 3b reflects this large bandwidth with a fall time of 4 nsec, while the 90- to 100-MHz peak is seen as ringing in the step response at this same frequency. The rising edge is somewhat slower than the falling edge and also exhibits a larger overshoot because the amplifier is at the edge of the slew-rate limit of about $100~\rm V/\mu sec.$

Assume that a 3-dB bandwidth of 30 MHz has been chosen as suitable for the 5-MHz video signal bandwidth. Because the basic amplifier bandwidth goes far beyond the 30-MHz requirement, you can add a series damping resistor (R_S) to the output to set the desired bandwidth. Thus if f-3 dB is equal to 30 MHz, then Rs equals $1/(2\pi f_{-3})_{dB}C_L$, or 106Ω . The response of the prototype circuit is shown in Fig 4 with R_s equal to 100Ω . The bandwidth is a flat 30 MHz, and, as expected, the high-frequency ringing has been eliminated. The accumulated phase error in the 5-MHz signal band is less than 25°. Again there is positive overshoot caused by the amplifier being at the edge of its slew-rate limit at 100 V/µsec. For smaller step amplitudes, the positive and negative overshoots are identical and less than 2% (Fig 5c). The amplifier's settling time is under 60 nsec.

Antialiasing filters are necessary to maintain base-

Users of flash converters often find that the input amplifier is the most challenging part of the design.




Fig 4—The Fig 2 circuit was also measured with series damping $(R_S=100\Omega)$ to reduce the bandwidth and a load capacitance of 50 pF. The frequency-domain measurement is in **a**. The 1V step response is in **b**; the 0.5V step response is in **c**.




Fig 5—You can configure the op amp in this basic 2-pole Sallen-Key amplifier at a fixed noninverting gain, generally from 1 to 3. The equations define the circuit's voltage transfer function.

band signal integrity in any sampled-data system. For video signals, because the critical specification is phase linearity, the filter of choice is generally the Bessel type, which in its ideal form produces a delayed replica of the input signal. However, because a Bessel filter doesn't have the sharp rolloff characteristics of a Chebyshev filter or the passband flatness of a Butterworth type, you may need a filter with more than six poles to meet the passband and/or stopband requirements. A single high-speed quad op amp provides a cost-effective solution to this problem. You can cascade filters with 1, 2, or 3 poles per stage in any combination to produce filters as high as the twelfth order.

Active RC filters are not new; what is new is the possibility of realizing such filters economically at video frequencies. In this example, the prototype implements the Sallen-Key type circuit (or $V_{\rm CVS}$), a popular method for active filters (Ref 2). In this type of circuit, you configure the op amp at a fixed noninverting gain, generally from 1 to 3 V/V. Fig 5 illustrates the basic 2-pole section. The equation defining this circuit is:

$$\frac{V_{\text{OUT}}}{V_{\text{IN}}} = \frac{\frac{K}{R_1 R_2 C_1 C_2}}{s^2 + \left(\frac{1}{R_1 C_1} + \frac{1}{R_2 C_1} + \frac{1}{R_2 C_2} - \frac{K}{R_2 C^2}\right) s + \frac{1}{R_1 C_1 R_2 C_2}}, (1)$$

where K is the voltage gain of each gain block, given by

$$K = V_{OUT}/V + = 1 + (R_4/R_3)$$
.

The noninverting stage should have gain flatness (less than 1 dB) and minimal phase-error accumulation (less than 45°) to well beyond the passband. The degree to which the VA4708 meets these requirements when K

TABLE 2—NORMALIZED RESISTOR VALUES FOR THE FILTER SECTIONS OF AN 8-POLE BESSEL FILTER

1		2	2		3	4	
R ₁	R ₂						
0.0892	0.350	0.176	0.117	0.114	0.241	0.0962	0.306
R ₁	R ₂	R ₃	R ₄	R ₅	R ₆	R ₇	R ₈

equals 2 V/V is shown in **Fig 6**. In the passband, the gain flatness is less than 0.15 dB, and phase-error accumulation is less than 10°. Stopband attenuation starts to soften at 28 MHz, however, because the phase passes through 45° here, and the approximation of K at 2 at 0° is no longer valid (**Fig 6**). The 6-dB peak at 120 MHz is far enough beyond the frequencies of interest to be of only secondary importance.

For this active-filter design, you can simplify $\mathbf{Eq}\ 1$ by making K equal to 2 and C_1 and C_2 both equal to C. Therefore, you have only the resistor values to manipulate to make the circuit act like a Bessel filter.

$$\frac{V_{OUT}}{V_{IN}} = \frac{\left(\frac{2}{R_1 R_2 C^2}\right)}{s^2 + s \left(\frac{1}{R_1 C}\right) + \frac{1}{R_1 R_2 C^2}}.$$

Now you must find resistor values for each stage such that the denominators correspond to the Bessel polynomial, which for an 8-pole filter is:

$$\begin{split} B_n &= (s^2 + 11.2s + 32) \times (s^2 + 5.68s + 48.4) \\ &\times (s^2 + 8.74s + 36.2) \times (s^2 + 10.4s + 34). \end{split}$$

(Ref 3). Thus for each stage:

$$s^2 + bs + c = s^2 + \frac{s}{R_1C} + \frac{1}{R_1R_2C^2}$$

where

$$b = \frac{1}{R_1C}$$

$$c = \frac{1}{R_1R_2C^2}.$$

To solve the equations for R_1 and R_2 , normalize to C=1. Then




Fig 6—The frequency response of the VA4708 when the voltage gain is 2 (a). The figure in b defines the circuit measured.

$$R_1 = 1/b R_2 = b/c$$
.

Table 2 lists the resultant normalized resistance values for each filter section.

To find the actual component values for the design, multiply the normalized R values (R_n) by $1/\omega_0 C$, where ω_0 is the desired bandpass frequency, and C is a value large enough (generally 50 pF) to swamp out package and board parasitics and consistent with keeping resistor values in the range from 50Ω to $1~k\Omega$ (see **Ref** 3 for the definition of ω_0). Note that whereas ω_0 for a Butterworth filter defines the -3-dB point independent of degree n, the Bessel filter attentuation at ω_0 decreases from -3 dB at n=1 to fractions of a dB as n gets larger.

For example, with an $F_{-3\ dB}$ bandwidth of 5.5 MHz, calculate R values for the first Bessel section of an eighth-order filter. First, choose a capacitance value of 100 pF ($\pm 2\%$). From the Bessel curves, $f_0=2$ MHz (**Ref** 3). Then:

$$R_1 = \frac{R_n}{2\pi f_0 C}$$

$$= \frac{0.0892}{(6.28)(2 \times 10^6)(10^{-10})}$$

$$= 70.7\Omega.$$

For video signals, because the critical specification is phase linearity, the filter of choice is generally the Bessel type.

In this case, choose a 71.5Ω resistor (±1%). By the same method,

$$R_2 = \frac{R_n}{2\pi f_0 C}$$
$$= 277\Omega.$$

In this instance, choose a 281Ω resistor ($\pm 1\%$).

The prototype filter has a $f_{-3 \text{ dB}}$ point at 6.5 MHz (**Fig 9a**), which is reasonably close given the sources of error. For example, one source of error is the lack of the flatness assumed for gain K=2; K has a peak of 0.2 dB at 6 MHz.

Calculate input impedance carefully

The filter input impedance is of considerable importance and is based on the circuit in Fig 8 and the following equations:

$$\begin{split} Z_{i} &= \frac{V_{IN}}{i_{i}} \\ &= R_{1} \bigg(\frac{V_{IN}}{V_{IN} - V_{1}} \bigg) \\ V_{2} &= \frac{V_{1}}{sCR_{2} + 1} \\ V_{1} &= \frac{(sCR_{2} + 1)V_{OUT}}{K}. \end{split}$$

Substituting **Eq 1** for V_{OUT} and letting $\omega_0 = 1/(R_1R_2C_2)$ and $s=j\omega$, you obtain, by algebraic manipulation, an




Fig 8—This circuit of the Sallen-Key filter section relates the basic values used to determine input impedance.

equation for input impedance:

$$Z_i = (\omega_0/\omega)^2 R_1 \bigg[-(\omega/\omega_0)^2 + j(\omega/\omega_0) \frac{\sqrt{R_1 R_2}}{R_1} + 1 \bigg].$$

You can approximate this equation for various frequency limits (**Table 3**).

Fig 7 is an example of an 8-pole video Bessel filter using the VA4708 quad op amp. The amplifier contains four cascaded Sallen-Key type 2-pole sections that result in an overall low-frequency gain of 8 V/V (2 V/V per section). The RC products of each section satisfy the coefficients of the Bessel polynomial. The prototype filter has a passband of 6.5 MHz (-3 dB), a group delay of 97 nsec, phase linearity of less than 2.5%, and a stopband rejection of more than 40 dB from 22 to 80 MHz.




Fig 7—If you use a video op amp that has cascaded Sallen-Key circuits, you can obtain this 6-MHz, 8-pole low-pass Bessel filter.

Fig 9 shows the measured response of the prototype for the Fig 7 circuit. Based on an equivalent input spot noise of 35 nV/ $\sqrt{\rm Hz}$ for each amplifier and a bandwidth of 6 MHz, the dynamic range of the input signal extends from 125 μV rms to 147 mV rms at 6.5 MHz (1.18V rms at the output) based upon a slew rate of 85 V/ μ sec.

You can model the filter's input impedance as a frequency-dependent RC series. Because of the controlled positive feedback of the Sallen-Key amplifier, the R value is actually negative at the passband frequencies. The Smith chart and adjoining table in Fig 10 show the filter's input impedance with a 75Ω input-termination resistor. Note that in the passband, although the termination resistor determines the input impedance for the most part, the effective R value goes

TABLE 3—APPROXIMATING IMPEDANCES FOR VARIOUS FREQUENCIES

FREQUENCY RANGE	z _i	RESPONSE
IN GENERAL:	1790/01/2	
LOW FREQUENCIES: $(\omega/\omega_0)^2 \le 0.1$	$\approx -(\omega_0/\omega)^2 R_1$	NEGATIVE RESISTANCE
RESONANCE: $\omega = \omega_0$	$=-j\sqrt{R_1R_2}$	CAPACITIVE
HIGH FREQUENCIES: $(\omega/\omega_0) \ge 10$	≈R ₂	POSITIVE RESISTANCE
WHEN USING FIG 8		
$(f/f_0)^2 = 0.01$ f=0.32f ₀ =36 MHz	$\approx -(f_0/f)^2 R_1$ $\approx -715\Omega$	
f=f ₀ =11.2 MH _Z	$=-j\sqrt{R_1R_2}$ $=-j142\Omega^*$	u caracteristic
$(f/f_0)^2 = 10$ f=3.2f ₀ =35 MHz	≈ R ₁ ≈ 71.5Ω	

NOTE

 $^*C_{eff} = \frac{1}{2}\pi f_0 X_0$ =100 pF

High-frequency caveats

One feature of high-frequency circuits not always appreciated by designers of conventional analog ICs is the high level of output current required. To produce useful signal swings, a typical 50 or 75Ω load draws 20 to 50 mA. The typical load capacitance (measured in tens of picofarads) then draws additional large signal currents. Driving a 50-pF capacitor at 4V p-p, for instance, would require another ±32 mA at least.

Circuit packaging and construction techniques are equally important because parasitic elements can have a decisive effect on RF-circuit behavior. Conventional DIPs, for instance, can behave like lowpass filters and thereby compromise circuit performance for frequencies as low as 50 MHz. Miniature SOIC and LCC packages, however, have reduced parasitics that lead to better RF performance. As an added bonus, the surface-mount boards used with these packages usually permit reduced lead

TABLE A—TYPICAL PARASITIC ELEMENTS FOR IC PACKAGES*

INPUT CAPACITANCE (TO ADJACENT PINS AND TO GROUND)	3 TO 10 pF (DIP) ~1 pF (28-PIN LCC)
PIN SELF-INDUCTANCE	8 TO 25 nH (DIP) ~4 nH (28-PIN LCC)
CHIP BONDING-PAD CAPACITANCE	0.3 TO 0.5 pF
CHIP WIRE-BOND INDUCTANCE	1 TO 2 nH

*THE VALUES VARY WIDELY FOR A DIP, DEPENDING ON THE PIN POSITION. THE CORNER PINS HAVE SEVERALFOLD MORE CAPACITANCE AND INDUCTANCE—ESPECIALLY FOR BIG DIPS LIKE 40-PIN TYPES.

lengths and smaller foil capacitances.

Table A lists the typical parasitic inductance and capacitance found in a DIP and an LCC, plus the bonding-pad capacitance and bond-wire inductance common to both packages. Bear in mind that pin parasitics vary widely with pin position. The corner pins have several times as much capacitance and inductance as the others—particularly for a large 40-pin DIP.

The **Table A** data shows that LC parasitics for the pins of a

large DIP can cause resonance at a few hundred megahertz, whereas surface-mount packages offer typical LC resonances at 1 GHz and above. Well below these resonances, however, are the package parasitics that can alter impedance levels, create phase shifts, and cause undesirable peaks in gain. Because even the SOIC and LCC packages can limit signal bandwidth below that inherent in the video-amplifier chip, you must consider hybrid construction for the very highest circuit performance.

Active RC filters are not new; what is new is the possibility of realizing such filters economically at video frequencies.

to values larger than 75Ω , which indicates a negative input resistance for the filter itself.

The filter passband extends to video frequencies, and if you are going to keep the capacitor values large enough to minimize parasitic effects, you need resistors that are one to two orders of magnitude smaller than

are customary in active filters. This smaller size causes no power-dissipation problems, however, because the signal levels are generally less than 4V (p-p), and the amplifiers can deliver output currents of only ± 50 mA.

You can also use video op amps as quad op amps in standard instrumentation amplifier (IA) configura-




Fig 9—The prototype filter in Fig 7 was measured for the frequency-domain response, which shows a 3-dB bandwidth of 6.5 MHz and a 40-dB stopband from 22 to 80 MHz a; group delay b; and time-domain response c.




Fig 10—This Smith chart and the adjoining table illustrate Fig 7 filter's input impedance with an input termination resistor of 75 Ω .

Display data which are externally divided into data for each row (660 dots) will be sequentially transferred in the form of 4-bit parallel data through shift registers by Clock Signal CP2 from the left top of the display face. When data of one row (640 dots) have been inputted, then latched in the form of parallel data for 640 lines of column electrodes by Latch Signal CP1. Then the corresponding drive signal will be transmitted to the 640 lines of column electrodes of the LCD panel by the LCD drive circuit. At this time, scan start up signal S has been transferred from the scan signal driver to the 1st row of scan electrodes, and the contents of the data signals are displayed on the 1st rows of upper and lower half of the display face according to the combinations of voltages applied to the scan and signal electrodes of the LCD. While the 1st rows of data are being displayed, the 2nd rows of data are entered. When 649 dots of data have been transferred then latched Unit Driving Method *** The LCD driver is 80 bits LSI, consisting of shift registers, latch circuits and LCD driver circuits,

THE REASONS YOU SHOULD BUY SHARP FLAT PANEL DISPLAYS **ARE ALL THERE** IN BLACK AND WHITE.

Sharp, the world leader in LCD and EL displays, introduces three new easy-to-read LCDs. With three times more contrast than conventional Super Twist High Contrast LCDs. So they give sharp clear pictures. Even at an angle.

All thanks to Sharp's new Double Super Twist technology.

These new units come in three sizes: $640 \text{ (W)} \times 400 \text{ (H)} \text{ dots}, 640 \text{ (W)} \times 480 \text{ (H)} \text{ dots}$ and $720 \, (W) \times 400 \, (H) \, dots$. Each with CCFT backlighting standard.

And, best of all, the display is black and white, just like a printed page. Which reduces headaches from eye strain and fatigue.

Getting your Sharp LCDs won't give you a headache either, if you call Marshall Industries. Because Marshall has a clear understanding of your needs. Like on-time delivery, complete inventories and production quantities.

Marshall is also the only national distributor to carry both Sharp LCDs and Yamaha controllers. These PC based controllers support all flat panel LCDs and EL displays.

For the sharpest flat panel displays around, call Marshall today.

After all, not all your decisions are going to be this black and white.













- (*Authorized Locations) Huntsville (205) 881-9235* AZ Phoenix (602) 496-0290* Tucson (602) 790-5687
- Irvine (714) 859-5050* Los Ángeles (818) 407-4100* Sacramento (916) 635-9700 San Diego (619) 578-9600°
- San Francisco (408) 942-4600* CO Denver (303) 451-8383* CT Connecticut (203) 265-3822*
- FL Ft. Lauderdale (305) 977-4880* Orlando (407) 767-8585* Tampa (813) 576-1399* GA Atlanta (404) 923-5750
- - MN Minneapolis (612) 559-22111
 - MO St. Louis (314) 291-4650° NC Raleigh (919) 878-9882° NJ N. New Jersey (201) 882-0320° Philadelphia (609) 234-9100°
 - NY Binghamton (607) 798-1611* Long Island (516) 273-2424*
- Rochester (716) 235-7620* OH Cleveland (216) 248-1788* Dayton (513) 898-4480* Westerville (614) 891-7580* OR Portland (503) 644-5050
- PA Pittsburgh (412) 963-0441*
 TX Austin (512) 837-1991*

Brownsville (512) 542-4589* Dallas (214) 233-5200* El Paso (915) 593-0706* Houston (713) 895-9200* San Antonio (512) 734-5100* UT Salt Lake City (801) 485-1551* WA Seattle (206) 747-9100*

WI Wisconsin (414) 797-8400

IL Chicago (312) 490-0155*
IN Indianapolis (317) 297-0483*
KS Kansas City (913) 492-3121*

Wichita (316) 264-6333*

MA Boston (508) 658-0810

MD Maryland (301) 840-9450*
MI Michigan (313) 525-5850*

An amplifier that contains four cascaded Sallen-Key type 2-pole sections results in an overall low-frequency gain of 8.




Fig 11—You can use a quad op amp to build an instrumentation amplifier. The amplifier shown is ac-coupled.




Fig 12—The ac-coupled instrumentation amplifier in Fig 11 shows this measured frequency response. The small-signal bandwidth is 20 MHz with less than 3 dB of peaking.

tions. Conventional op amps perform this function quite well to the 1-MHz level, at which point operation becomes difficult. Video op amps can extend IA operation to the 10- to 40-MHz range, depending upon the overall gain requirement.

The IA shown in Fig 11 is designed to yield an overall gain of 100. The small-signal bandwidth (Fig 12) is 20 MHz with less than 3 dB of peaking. The power bandwidth with a 3V p-p output signal is 10 MHz. Because of the cascaded nature of the IA, the gain-bandwidth product of 2 GHz extends well beyond that of an individual op amp, which is about 300 MHz.

The circuit in **Fig 11**, uses the C₁, C'₁, R₂, R'₂ network to insure input amplifier stability while the lead network C₃, C'₃, R₇, R'₇ maximizes the overall




Fig 13—In the instrumentation amplier in Fig 11, an input signal of 20 mV (p-p) at 10 MHz is contaminated by 2V (p-p) at commonmode signal at 1 MHz.




Fig 14—Using a quad video op amp, a dc-coupled instrumentation amplifier can achieve a gain of 3.

bandwidth. Capacitive coupling C_2 , ${C'}_2$ minimizes the output offset voltage to insure the maximum ac dynamic range. The lowest frequency that must be processed determines the C_2 value. For example, when $C_2=1~\mu F$, then $f_L=\frac{1}{2}\pi R_5 C_2=540~Hz$.

An IA can extract signals embedded in large amounts of common-mode noise. In Fig 13, an input signal ($V_{\rm IN+}$ and $V_{\rm IN-}$) of 20 mV (p-p) at 10 MHz is contaminated by 2V (p-p) of common-mode signal at 1 MHz. Since the IA's common-mode rejection is in excess of 60 dB at 1 MHz, the dominant output-signal component is the amplified version of the 10-MHz differential input signal.

The overall gain of the dc-coupled IA in Fig 14 is 3

Who offers you the broadest line of power semiconductors... Darlington, FETMOD, MOSBIP SCR/diode modules, rectifiers and thyristors?

Only POWEREX.

Powerex gives you what no one else does. Our one-source convenience and compatibility eliminate multi-source doubt. Our off-the-shelf availability means just-in-time delivery, instead of back-order delays <u>or</u> high inventory costs. We'll provide engineer-to-engineer phone conversations for an unbiased view of application needs and alternative component solutions. Best of all, POWEREX gives you leading-edge technology, rather than last-generation obsolescence. Take a look.



Only POWEREX offers you such a broad line of advanced power semconductor modules, including next generation FETMOD and cascade or cascode MOSBIP, rated at 8-300 A, 50-1,000 V for applications up to 100 kHz.



Only POWEREX offers you a complete line of low-power triacs and SCRs as part of the broadest line of power semiconductors available.



Only POWEREX offers you more advanced Darlington modules, including Application Specific (ASM™) modules: Single device, Phase-Leg, H-Bridge, Three Phase, Chopper and Common Emitter, 5-600 A, with V_{CEV (SUS)} from 200 to 1400 V.



Only POWEREX can provide a modular solution for all the key power components from logic interface devices, input rectifiers and DC regulating components to the output power stage. POWEREX now offers the world's widest array of input power stage thyristor and diode modules. Ratings of 20-800 A, with V_{DRM}/V_{RRM} from 400 to 3000 V. Circuit configurations include Single device, Phase-Leg, Three Phase Bridge and Center Tap in common cathode or common anode configuration.

Recent additions to the product line are a family of Center Tap fast recovery diodes rated at 20-100 A up to 1200 V, a new compact 150 A/1600 V Dual thyristor module, and a new 1200 V/300 A GTO thyristor module.

Only POWEREX offers you all this. For product literature, call POWEREX at 1-800-451-1415, Ext. 300. (In New York, 315-457-9334.) For application assistance, call 412-925-7272, or write POWEREX, Inc., Hillis Street, Youngwood, PA 15697.



Joint Venture Corporation of Westinghouse, GE and Mitsubishi.

Video op amps can extend IA operation to the 10- to 40-MHz range, depending upon the overall gain requirement.




Fig 15—The response of the circuit in Fig 13 extends from dc to a -3-dB point at 45 MHz.

TABLE 4-MEASURED PROPERTIES OF THE DC-COUPLED INSTRUMENTATION AMPLIFIER VALUE PARAMETER GAIN @ 50 kHz 2.99 3.00 GAIN @ 1 MHz GAIN @ 10 MHz GAIN TEMPERATURE -0.56% (T_A =+125°C) STABILITY AT 1 MHz -0.33% (T_A = -55°C) (REFERRED TO TA =25°C) BANDWIDTH 45 MHz GAIN FLATNESS < 0.3 dB (0 to 24 MHz) INPUT IMPEDANCE 4 MΩ II 4 pF 60 dB @ 1 MHz CMRR COMMON-MODE RANGE ± 3V WITH ± 5V SUPPLY ± 3V INTO 2 kΩ **OUTPUT VOLTAGE SWING** 2V INTO 50Ω

V/V; it uses the VA4708 as its basic building block. (The frequency response is shown in **Fig 15.**) The amplifier was tested over the full military temperature range (**Table 4**). Note that the gain flatness is less than $0.3~\mathrm{dB}$ with a $-3~\mathrm{dB}$ bandwidth of 45 MHz. Gain variations at 1 MHz are less than 0.6% over the military temperature range.

You can see from these examples how you can extend most of the standard op-amp techniques to the video region by using video op amps. Often the biggest problem is the less-than-ideal characteristics associated with the discrete components, the package parasitics, and the stray ground capacitance rather than the active elements. If you use these amplifiers with chip-andwire hybrid construction, you can obtain even better performance.

References

- 1. Schaefer, Ken and John Shier, "New ±5V standard unshackles analog-IC designers," *EDN*, June 9, 1988, pg 229.
- 2. Van Valkenburg, M.E., *Analog Filter Design*, Holt, Rinehart and Winston, New York, 1982, pg 171.
- 3. Al-Nasser, F. "Tables Speed Design of Active Filters," *EDN*, March 15, 1971, pg 23-32.

Authors' biographies

Ken Schaefer is a linear applications engineer for VTC. He received a BSEE from Marquette University in 1963. Prior to joining VTC in 1985, Ken worked in analog-circuit design for Ball Electronics, CDC, Raytheon, and General Motors. Ken's design experience includes CRT displays, switching regulators, and servomechanisms. In his leisure time, he races bicycles.




John Shier is the strategic marketing manager for VTC, and was heavily involved in planning VTC's analog products. He received a BS in physics from the California Institute of Technology in 1960, and an MS and PhD in physics from the University of Illinois in 1962 and 1966. He was a postdoctoral fellow at the Los Alamos Scientific Laboratory and a solid-state researcher for NASA before taking up IC work in 1970. John has held IC processing and design positions at Signetics, AMD, Intersil, Sperry Univac, and CDC before joining VTC. He is a senior member of the IEEE, and is currently the general chairman of the IEEE Bipolar Circuits and Technology Meeting. John is the author of 18 technical papers and holds 3 patents. In his spare time, he enjoys reading, sailing, and gardening.




Article Interest Quotient (Circle One) High 494 Medium 495 Low 496

Can you solve this problem with a one-clock telecom tester?



This ISDN transceiver requires synchronized transmit/receive data at 15.36 MHz *and* a bus interface pattern at 20 MHz. Given the tester's single master clock, what frequency do you program? What integer ratios do the dividers need?



If you settle for anything less than Synchromaster, the new


than Synchromaster, the new resource-per-pin mixed-signal test system from LTX, you're going to wind up one clock short. In order to produce test frequencies of 15.36 MHz and 20 MHz with a single-clock test system, you would have to choose integer ratios of 125 and 96 and set the pattern generator at 1.92 GHz — well beyond the typical 100-200 MHz range.

Only Synchromaster can produce the exact combination of frequencies this IC requires.

Its Dual Synchronous timing system uses *two* high-resolution generators, so patterns and waveforms aren't constrained to just ratios of a single frequency, as they are in single-generator testers.

We've been through exercises like this many times, for many years. In fact, no one else comes close to LTX in mixed-signal testing experience. That's why the Dual Synchronous timing system is a design fundamental. And that's why Synchromaster

Need more time? Get the tester with two clocks.



gives you the first total mixedsignal resource-per-pin design: 96 pins with complete analog, digital and DSP. System-wide coherence, eight timing markers per pin, on-the-fly time set switching, and pattern rates up to 80 MHz. And techniques for solving the problems of jitter, pulse mask testing and other telecom measurements ... without compromise.

Send for our White Paper: "Telecom Testing Without Hangups," for the details on Synchromaster's Dual Synchronous timing system. Better yet, use the telephone. Call Carol Everett at (617) 461 1000. Synchromaster. The new mixedsignal tester from LTX.

It's why time has run out on one-clock testers.



CIRCLE NO 74

Siliconia

The switch is on.

We offer a very broad capability in analog switch solutions, technologies and MIL parts. No wonder people are turned on.

When you need high-quality/high-performance analog switches and multiplexers, why not come to the people who have more than 600 device types and a wide variety of MIL-STD 883B, Rev C, DESC Standard Military Drawings and JAN38510 types.

A small	sample	of what	we can	offer:
/ t Ollian	Juilbio	or sellar	TTO Out	01101.

Switch	Description
DG200/DG201	CMOS Dual/Quad
DG211/DG212	CMOS Low-cost Quad
DG300A/303A	CMOS TTL Compatible
DG308A/309	CMOS Quad
IH5040-IH5047	High-level CMOS
IH5140-IH5145	Improved High-level CMOS
IH5148-IH5149	High-Level CMOS
IH 5341/5352	CMOS Dual/Quad/Video/RF
IH6108/6208	CMOS 8-/4-Channel Differential Mux
IH6116/6216	CMOS 16-/8-Channel Differential Mux
IH5108/IH5208	CMOS 8-/4-Channel Diff. Fault Protected Mux
IH5116/5216	CMOS 16-/8-Channel Diff. Fault Protected Mux
Coming soon:	
DG508A/509A	8-/4-Channel Differential Mux
DG528/529	8-/4-Channel Differential Mux with Latches
IH9108	8-Channel High-Voltage Mux with Latches
DG201A/202	CMOS 44V Quad

Choose your technology.

With a selection like ours, you can choose from nearly every major technology, including metal gate CMOS, JFET, DI CMOS and DMOS.

And you can choose the cost/performance that's best for your application. From our DG211 CMOS family at 35 cents per channel, to our standard-setting IH5341/5352 video switch family.

A multitude of multiplexers.

If it's multiplexers you're looking for, we won't

disappoint you. We offer a full family of CMOS monolithic multiplexers, including our new IH9108 8-channel High-Voltage Mux with Latches. It's designed for especially low drain-on, drain-off and source off-leakage.

Tops in military.

Look at this roll call: more than 150 switches and multiplexers that meet MIL-STD-883B Rev. C. And over 90 devices that are on DESC Standard Military Drawings and QPL.

That's more than anyone else in the business. We can deliver these parts in volume from our four certified Fab flows that are DESC-certified for JAN 38510 CMOS and bipolar production.

Switch to solutions.

Perhaps most important, when you switch to Intersil, you switch to solutions. We offer extensive applications engineering support. And we're developing solutions to the problems you face every day.

So, to get the widest variety of switches and multiplexers, in the widest variety of packages and technologies, there's just one thing you have to do:

Switch to Intersil.

For information on getting the right switch or mux for your military, computer, disk drive, instrumentation or communications equipment, contact your local GE Solid State sales office or distributor. Or call toll-free, 800-443-7364, extension 27.

In Europe, call: Brussels, (02)246-21-11; Paris, (1) 39-46-57-99; London, (276) 68-59-11; Milano, (2) 82-291; Munich, (089) 63813-0; Stockholm (08) 793-9500.

General Electric Company, U.S.A.



GE Solid State

EDN September 1, 1988

A Great Solu


We Put the STD Bus on a Card.

Octagon's 9500 System Card is a great solution to today's industrial needs, because everything you need is on one board. The 9500, an IBM PC™ and our PC SmartLINK™ are all you need to program and get your application running. It's convenient, it's easy.

• Even the software is built in—you can read and write MS–DOS™ files without the cost or complexity of using an industrial PC.

• The 9500 can replace 3 to 7 cards in a typical application. That means no mixing and matching hardware.

And all for only \$695. Make things easy on yourself—call for a data sheet today.



STD BASIC III and PC SmartLINK are trademarks

MD-DOS is a trademark of Microsoft Corporation.

CIRCLE NO 75

of Octagon Systems Corporation.


IBM PC is a trademark of IBM.

Westminster, CO 80030

FAX: 303-426-8126

303-426-8540

NEW 500 MEGASAMPLES/SEC 300 MHz DIGITAL PORTABLE





TEK PUSHES THE LIMIT...


AT THE PUSH OF A BUTTON.


AUTO SETUP

AUTO PASS/FAIL









AUTO MEASURE

AUTO SEQUENCE

ONLY FROM TEK.

The new Tek 2440 Digital Oscilloscope is the only portable offering a 500 MS/s sampling rate—on two channels simultaneously.

Capture signals competitors can't.

You can digitize, store and process single-shot phenomena to 200 MHz and repetitive signals to 300 MHz. At the touch of a button.

This is a scope built for solving tough problems fast.

Complete confidence in results.

Exclusive Tek digital features let you capture glitches as short as 2 ns with continuous sampling; automatically catch intermittent failures in babysitting applications; and see waveform changes virtually as they occur thanks to the high update rate.

With the 2440's 500 MS/s sample rate, 8-bit vertical resolution, and 0.0015% crystal-controlled timebase accuracy, you'll have complete confidence in the accuracy of your waveform data. You'll know what you're seeing is what's actually happening in your circuit.

The 300 MHz 2440 and 2432, along with the 150 MHz 2430A, drive like the scopes you're used to. They feature a familiar front panel and simple, one-level menus.

Built-in automation simplifies operation even more. The scopes set up at the touch of a button. And you can characterize waveforms instantly: press another button and read out your choices from 21 different measurements.

Powerful system components.

Powerful system components.

A digital

family you

already know

how to use.

On the design bench, the 2400 DS0s are effective standalone test systems. Full GPIB programmability, pass/fail testing and time-saving measurement sequencer make them equally powerful system components. With off-the-shelf software you can fully automate measurements and extend waveform analysis.

Don't settle for less. Get the total performance package only Tek delivers, feature for feature, spec for spec.



WHEN THE MEASUREMENT COUNTS, COUNT ON TEK.

No matter what you measure, Tek measures best.

The standard of excellence in portable scopes.

Analog or digital, standalone or automated, no other portables match Tek 2400 Series Oscilloscopes for sheer breadth of line, range of performance and wide choice of options.

Their proven reliability and built-in versatility are a result of Tek's dedication to superior waveform acquisition tailored to individual needs.

Answers at the touch of a button.

Six four-channel analog oscilloscopes combine pushbutton simplicity and leading-edge performance. They bring unprecedented efficiency to your design lab, production line or field service site. The top-of-the-line 2467 with Tek's patented microchannel plate CRT even makes single-shot pulses to 350 MHz visible—at the touch of a button.

A complete range of options further extend each scope's capabilities.

Scope for scope, feature for feature, Tek has the best solution for your measurement needs.

Ask your Tek representative for a demonstration. With the 2440 joining the family, there's an even better selection—in sample rate, performance and price. For more information, please return the reply card or call Tek direct:

1-800-426-2200.

Call Tek for details.





Use a single-chip μ C as the heart of your position controller

A single chip can be the basis of a computer-based position controller. This article provides enough detail about hardware and microcode to allow you to design your own position controller—even if you have little experience with motion control.

William C Warner, Consultant

You can design a position-loop controller by using a single-chip microcomputer (μ C). You must choose a μ C that possesses the following characteristics:

- a minimum of 2k bytes of internal ROM,
- a minimum of 128 bytes of internal RAM,
- an internal timer that can request interrupts,
- an external interrupt-request pin,
- serial transmit and receive pins,
- 11 digital output pins, and
- four digital input pins.

The Motorola 68701 or the Intel 8751 is suitable.

A position-loop controller has a lot to do

Fig 1 depicts a general dc servomechanism. The position-loop controller (hereafter known as the controller), on the left side of the figure, receives commands to move a table from one position to another at some speed. In response, the controller indicates the required motor speed and direction to a dc motor drive.

The drive employs a reading of actual motor velocity, provided by a tachometer, in an effort to make the motor run at the speed commanded by the controller. The motor turns a leadscrew clockwise or counterclockwise, causing the table to move right or left. As the leadscrew turns—and the table moves—an encoder emits pulses and the controller notes them. In this way the controller tracks table movement and knows when the table is in position.

The controller is aware of all pulses from the encoder, even those that occur when the leadscrew is supposed to be at rest but for some reason turns anyway. When the controller sees this uncommanded motion, it directs the motor drive to run the motor and put the table back into position. The controller must always automatically oppose unexpected motion; you can think of this opposition as a "reflex" of the controller.

The controller must respond to requests to suspend motion ("feedhold"), to resume motion, and to make emergency stops. Finally, the controller must accelerate and decelerate the motor and table in a way that does not overstress the mechanisms, waste time or cause the table to overshoot its destination.

The feedback unit—the system's resolution

An encoder rotates with the leadscrew; the encoder reports the motion of the leadscrew by sending signals on two channels. When the leadscrew turns with constant speed, the signals are square waves that are 90° out of phase. The controller detects the direction of the motion by noting which of the signals is leading; it determines the extent of the motion by counting the cycles.

EDN September 1, 1988

The controller must always automatically oppose unexpected motion; you can think of this opposition as a "reflex" of the controller.




Fig 1—This block diagram of a generalized servomechanism shows an overall position-feedback loop with feedback supplied by an encoder, and an inner velocity-feedback loop, in which a tachometer supplies the feedback.

Resolution, or positioning accuracy, is equal to the distance the table travels in one encoder cycle. Suppose that in 1 in. of table travel the encoder generates 100 cycles. The resolution of the position loop—the positioning accuracy—is, then, 0.01 in. (10 mils). This distance is called a "feedback unit;" it's the smallest distance over which the controller can move the table. The controller measures all larger departures in feedback units.

"Go" commands initiate motion

A "Go" command is an output from the controller intended to cause a move of one feedback unit. Suppose that the table in Fig 1 is at rest and you tell the controller to move it 5 in. to the right or the left. Under the assumptions of the previous paragraph, a 5-in. move is 500 feedback units. Therefore, the controller must issue 500 Go commands. A Go command simply acts to increment or decrement an "error count;" it increments the count when it commands clockwise leadscrew rotation and decrements the count when it commands counterclockwise rotation. RAM in the μC records the error count. The magnitude and sign of the error count determine the speed and direction of table motion.

The required table velocity determines the frequency of the Go commands. Suppose that the 5-in. move must occur at 10 in./sec. The controller must issue 500 Go commands in 0.5 seconds, or one Go command every 0.001 sec. The table's speed is called "feed rate." Ordinarily, you'd specify feed rate in inches per second or centimeters per second, but the controller converts the rate to feedback units per second, thus calculating the required frequency of Go commands. (Feedback units per second equals Go commands per second.) To achieve the desired feed rate, the μC 's internal timer generates periodic interrupts at the calculated frequency. These interrupts invoke a routine that increments the error count (for clockwise motion) or decrements it (for counterclockwise motion) once for each interrupt.

Multiple mechanisms keep the controller informed

The leadscrew turns the encoder, and the encoder provides position feedback to the controller. The feedback consists of signals on two channels, A and B. These signals indicate the direction of rotation of the leadscrew (and hence the direction of table movement), and they also indicate whether the leadscrew has turned far enough to move the table one feedback unit.

Fig 2a shows the signals on channels A and B. At constant velocity they are square waves; during acceleration they contract and during deceleration they stretch out. One complete cycle on channel A is called




Fig 2—When the motor velocity is constant, the encoder produces square waves. The controller can tell the direction of motion by determining which of the encoder's two output signals leads the other.

an encoder cycle. In the figure, one cycle exists between the markers X and Y. The encoder rotates through one complete cycle while the table moves one feedback unit.

If you term the controller output that causes movement a "Go command," you can call an encoder cycle (the encoder's response to movement) a "Gone cycle." The μC senses Gone cycles and adjusts its knowledge of where the table is and decrements or increments the error count accordingly. Usually, Gone cycles work against Go commands; Go commands build the error count, positive or negative, and Gone cycles, resulting from leadscrew rotation, drive the error count back toward zero. (However, Gone cycles don't always occur in response to commanded motion, nor do they always act to count the error back to zero, as demonstrated below.)

The μ C knows that one complete encoder cycle corresponds to one feedback unit of table movement, but it must take further action to determine the table's direction of motion. Notice that the two waveforms in Fig 2a are shifted one quarter cycle (90°) relative to each other. If you follow the signals from left to right, they progress as they would during clockwise motion. Note that signal A rises, then B rises, then A falls, then B falls, and so on. Signal B does what signal A does, except it does so one quarter cycle later; signal A is said to lead signal B. Channel A leads channel B during clockwise rotation. If you scan the signals from right to

left in Fig 2a—or from left to right in Fig 2b—they progress as they would in counterclockwise rotation: Channel B leads channel A.

Fig 3 shows channel A connected to a functional block labeled "Encoder-signal edge detection." This block represents circuitry that interrupts the μC every time the state of channel A changes. In response to the interrupt, the μC reads the states of the two encoder channels. If channel A is low, a falling edge on channel A must have caused the interrupt. If channel B is high at that time, the μC knows that a partial clockwise cycle has occurred. If channel B is low, the μC concludes that a partial counterclockwise cycle has occurred.

From time to time, an encoder will stop turning very near a point where the state of channel A changes. When it does, small vibrations in the mechanism can cause the signal to jitter (to rapidly alternate states). Were the µC to regard every transition of the signal as marking the boundary of a feedback unit, it would rapidly change its signal to the motor drive—an undesirable effect. The µC notes every transition in signal A, but it does not consider that the table has crossed a feedback-unit boundary until a complete cycle has taken place. The µC recognizes the occurrence of a complete cycle when it senses two transitions on channel A without a reversal in leadscrew direction. This requirement introduces hysteresis that keeps the µC from rapidly changing its signal to the motor drive while the encoder jitters around an edge in signal A. A consequence of the way the controller handles the jitter is that the boundary of a feedback unit shifts one quarter cycle after a reversal. After noting a complete encoder cycle, the µC updates both the error count and its understanding of the table position.

Error, following error, and velocity reference

RAM in the μC holds the error count. Go commands and Gone cycles increment and decrement that count. The error-count value is called "following error" or simply "error." It has magnitude and sign. The magnitude of the error is the number of feedback-unit moves that have been commanded but not taken, or the number of moves that have been taken but not commanded. The sign of the error indicates the direction in which the table is out of position.

The number 128 represents zero error. One count of error in the clockwise direction is 129. The maximum clockwise error is 255, which corresponds to 127 feedback units out of position in the clockwise direction.

The controller must accelerate and decelerate the motor and table in a way that doesn't overstress the mechanisms, waste time, or make the table overshoot.




Fig 3—The main position-loop-controller element is a single-chip microcomputer. Any of several types will do—the main requirements are that the chip incorporate a programmable timer and adequate ROM and RAM.

One count of counterclockwise error is 127. Maximum counterclockwise error is zero, which represents 128 feedback units out of position in the counterclockwise direction.

An error greater than 128 means one of two things. Either Gone cycles are lagging behind Go commands in a clockwise move, or the leadscrew has moved counterclockwise without a command to do so, as when the table overshoots its destination or drifts out of position. When the error is 127 or less, Gone cycles are lagging behind Go commands in a counterclockwise move, or the leadscrew has moved clockwise without a command.

Any time the error count changes, the μC writes the new value to a D/A converter (DAC) (Fig 3). The amplified output of the DAC is the Velocity Reference signal to the motor drive. This signal normally has a range of approximately -10 to +10V. When the error is zero (the error count is 128), Velocity Reference is 0V. Maximum clockwise error, written to the DAC, produces a +10V Velocity Reference signal; maximum counterclockwise error results in a -10V signal. A

positive signal indicates that the motor should turn clockwise; a negative signal indicates that it should turn counterclockwise.

The magnitude of Velocity Reference is proportional to the required motor speed. A large value means "run fast," a small value means "run slowly." Because there are 256 steps in the error count from 0 to 255—full-speed clockwise to full-speed counterclockwise—the velocity reference signal can take on 256 values from -10 to +10V.

An amplifier with adjustable gain amplifies the output of the DAC to produce the Velocity Reference signal. The amplifier's gain serves as the gain for the position loop. At any particular gain setting, the velocity reference signal and, hence, the speed of the motor, are proportional to the error's magnitude. The amplifier's gain is the constant of proportionality:

Velocity=gain×error.

The position-loop gain amplifies the effect of a given




Fig 4—Adjusting the gain that multiplies the velocity-feedback signal affects the servo's damping. You normally won't want overshoot, and you must limit the response speed to avoid overstressing the mechanical components. You'll usually want exponential response, like that shown here.

amount of error. When you set the gain very high, even a small error produces a large velocity. When you set the gain low, the error must be larger to produce the same velocity. In effect, the position-loop gain determines how seriously the motor drive treats an error. The higher the gain, the faster the motor will accelerate as the error grows, and the faster it will decelerate as the error falls. You must be able to adjust the gain to prevent damage to the system's mechanical components—different servomechanisms tolerate differing degrees of acceleration and deceleration.

Exponential acceleration and deceleration

Imagine the motor at rest with zero error. A 5-in. move begins. Go commands begin to increase the error (positively if the motor is going clockwise, negatively if it's going counterclockwise). The error grows because the motor and masses do not start to move immediately. As the error grows, the Velocity Reference signal grows. Eventually the leadscrew begins to turn and the encoder produces Gone cycles. The motor is just beginning to move, so the Gone cycles do not occur as fast as the Go commands do. The error continues to mount, but

not as fast as at first. As the error climbs, Velocity Reference climbs. Motor speed increases, increasing Gone-cycle frequency. The error grows more slowly still. Finally, the motor is up to speed, and every Go command is answered by a Gone cycle. Error remains constant and, consequently, so does motor speed. The table rides along at the programmed feed rate, and its position is a fixed number of feedback units behind the commanded position. This kind of acceleration, increasing speed at a decreasing rate, is exponential (**Fig 4a**).

Deceleration at the end of the move is also exponential. It happens like this: Once all of the Go commands have been issued, nothing further augments the error. But because there is still following error, the controller continues to drive the motor and the resulting Gone cycles begin to diminish the error. As the error count falls, Velocity Reference, motor speed, and Gone-cycle frequency all fall, so that although the error count is diminishing, it's doing so at a decreasing rate. The error continues to decline until, finally, the table is in position and error count and Velocity Reference are zero. At this point, as many Gone cycles have occurred as Go commands, so the table is at its final destination (Fig 4b). The motion of the motor after Go commands have stopped is called "taking up the error."

Overshoot, drift, and other unexpected motion

The encoder produces Gone cycles whenever the leadscrew rotates—even when the controller produced no Go commands. A nonzero error count, therefore, is not always the result of unanswered Go commands; sometimes it stems from uncommanded Gone cycles. No matter . . . error is error. Any nonzero error count creates a nonzero velocity-reference signal, which works to eliminate the error. If the table overshoots its destination, drifts, or is forced out of position, the resulting Gone cycles produce a nonzero error count and a velocity-reference signal that opposes the uncommanded movement. The motor fights to bring the table back into position and, as it succeeds, Gone cycles count the error down to zero.

When you have to stop the table, use feedhold

Note the Feedhold signal to the μC in Fig 3. Ordinarily this signal comes from a pushbutton. An operator presses the button to stop the table. When the μC senses a request to feedhold, its response is simple; it stops issuing Go commands. The motor will take up the error in exponential deceleration and stop. When the operator presses the button again, cancelling the re-

The resolution of the position loop is called a "feedback unit." It is the smallest distance that the controller can move the table.

COMMAND CHARACTERS ¹	DESCRIPTION		
F	FEEDHOLD. SUSPEND TABLE MOTION.		
С	CONTINUE. RESUME A SUSPENDED MOVE.		
Hdnnnn	GO HOME. THE SECOND CHARACTER—d—IS "C" IF THE TABLE WILL ENCOUNTER THE HOME SENSOR BY GOING CLOCKWISE; IT IS "W" IF THE LEADSCREW MUST ROTATE COUNTERCLOCKWISE TO DRIVE THE TABLE HOME. THE "nnnn" ARE FOUR ASCII-CODED HEX DIGITS REPRESENTING THE MAXIMUM NUMBER OF FEEDBACK UNITS TO MOVE IN A SEARCH OF HOME. THE CONTROLLER ADOPTS THIS VALUE AS THE MAXIMUM TRAVEL ALLOWED TO THE TABLE.		
Inn	SET FEED RATE. THE "nn" ARE TWO ASCII-CODED HEX DIGITS REPRESENTING THE HIGH AND LOW NIBBLES OF A BYTE THAT IN DICATES THE FEED RATE VALUE. FEED RATE IS SPECIFIED IN FEEDBACK UNITS PER 50 MSEC. MINIMUM FEED RATE IS ONE (20 FEEDBACK UNITS/SEC) AND MAXIMUM IS 50 (1000 FEEDBACK UNITS/SEC). THE NEW FEED RATE REMAINS IN EFFECT UNTIL A SUBSEQUENT SET-FEED RATE COMMAND CHANGES IT OR UNTIL YOU CHANGE IT IN THE MIDDLE OF A MOVE.		
R	RE-ENABLE CONTROLLER. YOU USE THIS COMMAND TO RE-ENABLE THE CONTROLLER AFTER SHUTTING IT DOWN OR TO ENABLE IT INITIALLY WHEN YOU APPLY POWER.		
Mnnnn	MOVE. THE "nnnn" ARE FOUR ASCII-CODED HEX DIGITS THAT REPRESENT THE ABSOLUTE POSITION (NUMBER OF FEEDBACK UNITS FROM HOME) TO WHICH THE CONTROLLER MUST MOVE THE TABLE. THE POSITION MUST BE LESS THAN OR EQUAL TO THE MAXIMUM TRAVEL SPECIFIED IN A PRECEDING HOME COMMAND. IF, DURING FEEDHOLD, YOU ABORT THE SUSPENDED MOVE, THE CONTROLLER ACCEPTS THE NEW MOVE BUT DOES NOT START IT UNTIL IT RECEIVES A CONTINUE COMMAND.		
Sbb	SEND BYTE. THE "bb" ARE TWO ASCII- CODED HEX DIGITS THAT REPRESENT THE ADDRESS OF A BYTE IN THE CONTROLLER". RAM. THE μC RESPONDS BY SENDING THE SPECIFIED BYTE AS TWO ASCII-CODED HEX DIGITS. THE FIRST NINE BYTES OF THE RAM (bb=00 TO bb=08) HOLD THE CONTROLLER". STATUS TABLE (SEE TABLE 3).		

NOTE:	
1. THE CONTROLLER RECOGNIZES THESE COMMANDS. (COM-
MANDS ARE STRINGS OF ASCII CHARACTERS SENT TO T	HE
CONTROLLER THROUGH THE SERIAL PORT	

TABLE 2—CONTROLLER'S RESPONSES TO COMMANDS

RESPONSE1	MEANING
С	COMMAND REJECTED BECAUSE OF A COM- MUNICATION ERROR. A CHARACTER IN THE COMMAND STRING SUFFERED A PARITY, OVER- RUN, OR FRAMING ERROR.
S	COMMAND REJECTED BECAUSE IT WAS OUT OF SEQUENCE. THE COMMAND IS NOT ALLOWED UNDER THE CURRENT CONDITIONS.
Y	COMMAND REJECTED BECAUSE IT WAS NOT WELL FORMED OR PARAMETERS WERE OUT OF RANGE (SYNTAX ERROR).
D	COMMAND HAS BEEN CARRIED OUT OR INITIATED.
Bnn	RESPONSE TO THE SEND-BYTE COMMAND; "nn" ARE TWO ASCII-CODED HEX DIGITS THAT REPRESENT THE VALUE OF A BYTE IN THE μ C'S RAM.

NOTE:

1. THE CONTROLLER GIVES THESE RESPONSEES TO COM-MANDS. THE RESPONSES ARE STRINGS OF ASCII CHARACTERS THAT ARE SENT THROUGH THE SERIAL PORT BY THE CON-TROLLER.

quest for feedhold, the μC resumes issuing Go commands, the error builds, and the motor accelerates. The controller remembers how many Go commands were left to go at the time of the feedhold request, and issues only that many more.

Error limits avert disaster

You must impose a limit on the clockwise and counterclockwise error. If the error count reaches a limit, the μC stops issuing Go commands and waits for the table to catch up. As the table does catch up, error falls below the limit and the controller resumes issuing Go commands.

By respecting an error limit, the controller can detect when the motor is out of control and running away. If the error count continues to grow beyond the error limit, even after Go commands have ceased, the motor is out of control and the controller must shut it down.

The motor will also run away if you connect it—or the encoder—backward. If you connect the motor backward, when you tell it to turn clockwise, it will turn counterclockwise. When you connect either the motor or the encoder backwards, Gone cycles will not diminish the error; in fact they will augment the error, adding to the Go commands. With nothing to diminish it, the error will grow without bound. Unless the controller shuts the motor down when the error count reaches a

value that's a few counts greater than the limit, the motor will run away.

To ensure agreement among all the components in the system, and to lessen the chance of connecting something backward, you can adopt the following conventions or their equivalent:

- View the motor from the shaft end when deciding which way is clockwise and which way is counterclockwise;
- Connect the motor to the drive so that a positive velocity-reference signal will cause the motor to turn clockwise;
- Connect the encoder to the controller so that the controller will see channel A leading channel B during clockwise rotation.

You can go home; sometimes you have to

The controller handles commands to move the table from position to position. But it does not always know the absolute position of the table. It only knows how many feedback units the table has moved from some starting point. In order to translate that information into knowledge of absolute position, the table must have a "home" location near one end of its travel. A sensor, tied to the μC , indicates the presence of the table at home. Whenever the controller is in doubt about absolute position (such as on power-up), it must refuse all commands to move the table until after it has received and executed a command to move the table to home.

The command to go home must include parameters that tell the controller which way to move and how many feedback units to go in search of home. The controller moves the table toward home at some slow speed. When the signal from the home sensor indicates that the table has arrived at home, the controller stops issuing Go commands. The motor takes up the error and the table comes to rest. The controller then sets its internal representation of table position to zero.

If, during the move toward home, the table hits the home sensor before accelerating fully, or if the table is activating the home sensor when the controller receives the "go home" command, the controller must move the table, at some low speed, far enough away from home to ensure that, during its move toward home and before it hits the home sensor, the table reaches its "homing speed." A table that is accelerating when it arrives at the home sensor will not come to rest at the place it would have if it had reached homing speed. When the table actuates the home sensor before reaching maxi-

TABLE 3—BYTES	THAT	DESCRIBE
KEYSYSTEM	PARAM	METERS

RAM ADDRESS	CONTENTS		
00	STATUS BYTE 0		
01	STATUS BYTE 1		
02	CURRENT FOLLOWING ERROR		
03	MOST SIGNIFICANT BYTE OF GREATEST ERROR THAT OCCURRED IN LAST MOVE		
04	LEAST SIGNIFICANT BYTE OF GREATEST ERROR THAT OCCURRED IN LAST MOVE		
05	MOST SIGNIFICANT BYTE OF TABLE POSITION		
06	LEAST SIGNIFICANT BYTE OF TABLE POSITION		
07	MOST SIGNIFICANT BYTE OF FEEDBACK UNITS LEFT IN A MOVE THAT IS UNDER- WAY OR HAS BEEN SUSPENDED		
08	LEAST SIGNIFICANT BYTE OF FEEDBACK UNITS LEFT IN A MOVE THAT IS UNDER- WAY OR HAS BEEN SUSPENDED		

mum speed, the controller can't position the table at home correctly.

If the controller were to fail while controlling the position of the table, it might not respond to encoder signals. Whatever error was presented to the D/A converter at the time that the controller failed would remain there. The table would ride along at the speed corresponding to that error to the end of its travel.

The watchdog circuitry pictured in Fig 3 stops the motor when the controller fails. This circuitry times out if the controller does not retrigger it often enough. The controller ought to be able to retrigger every 10 msec. If it doesn't, the controller has probably failed. (Maybe a software bug has caused it to lock up.) So the watchdog circuitry times out and stops the motor.

A position-loop controller can very easily signal when the table is at rest. Whenever the error is zero, the table is stopped and the microcomputer drives the Stopped output true (Fig 3).

Converse with the controller in its native tongue

The controller receives commands through a serial port as ASCII characters. Because the controller must spend most of its time responding to timer and encoder interrupts, the commands must be short and simple; they must be transmitted relatively slowly (1200 bps max). Commands begin with a single command character that identifies the command. They end with a single end-of-command character, such as a carriage return.

If the μ C regarded every signal transition as marking the boundary of a feedback unit, it would rapidly change its signal to the motor drive—an undesirable effect.

TABLE 4—INFORMATION CONTAINED IN THE SYSTEM STATUS BYTES

	CONDITIONS THAT SET BITS				
BITS	STATUS BYTE 0	STATUS BYTE 1			
0	ALL GO COMMANDS HAVE BEEN ISSUED	EMERGENCY-STOP COMMAND RECEIVED			
1	TABLE IS STOPPED	ERROR WENT ABOVE ERROR LIMIT			
2	TABLE IS "LOST" (MUST HOME)	ENCODER PULSES OUT OF SEQUENCY			
3	IN FEEDHOLD	ENCODER INTERRUPTS COMING TOO FAST			
4	SHUT DOWN; MUST RE- ENABLE (SEE BYTE 1)	COULDN'T FIND HOME			
5	TABLE IS AT HOME	COULDN'T LOSE "AT HOME" SIGNAL			
6	NO FEED RATE ESTABLISHED	(NOT USED)			
7	(NOT USED)	(NOT USED)			

Some commands include parameters, represented by ASCII characters between the command and end-of-command characters. **Table 1** details the commands.

The controller carries out a command and sends a response that tells the outcome. A response is one or three ASCII characters transmitted through the serial port. The response may indicate that the command has been carried out or initiated; it may indicate that the command was improperly formatted or illegal at the time it was received, or it may say that command characters have suffered transmission errors. Table 2 explains the controller's responses. A "success" response to a command that causes motion (move or go home) means only that the move has begun. You must poll the controller with send-byte commands until its status indicates that a move has been completed.

Table position and maximum error

The controller keeps track of the table's absolute position (feedback units from home). When it is at home, the table is in position zero. One feedback unit away from home is position one, and maximum travel away from home takes the table to position FFFF $_{\rm HEX}$. By definition, there is only one permissible direction away from home. The home command establishes whether the direction toward home is clockwise or counterclockwise.

The controller also saves the largest error that occurs during a move. This information is useful in setting the gain of the position loop. A large error means that the table did not accelerate quickly. When the maximum error equals the error limit, the table did not even reach programmed feed rate during the last move.

The controller keeps these values in its status table (**Tables 3** and 4); send-byte commands can read them out.

Emergency stop and re-enable commands

The controller must be able to tell the motor drive to stop the motor immediately when some dangerous situation exists. It uses the signal Emerg Stop (Fig 3) for this purpose. The controller asserts Emerg Stop when any of the following is true:

- the controller has detected encoder signals out of sequence,
- encoder interrupts have occurred faster than the controller can service them,
- the error has grown past the error limit,
- the controller has received the emergency-stop command,
- or the controller has just been turned on.

While asserting Emerg Stop, the controller makes no attempt to control or track the position of the table. It sets error and position to zero. It rejects all commands to move the table until it receives the re-enable command. When the controller receives that command, it stops asserting Emerg Stop and sets an internal "table-must-be-homed" flag. It begins to monitor the encoder signals and to update the error count. Listings 1 through 8 contain pseudocode that represents the major routines embedded in the position controller's μ C firmware.

Author's biography

Will Warner runs his own consulting business in Ann Arbor, MI. He specializes in the application of microcomputers to instrumentation and automation. He holds a BS in mathematics from Michigan State University. Before becoming a consultant, he worked for General Electric Co and Machine Vision International. Will's favorite spare-time activity is reading.



Article Interest Quotient (Circle One) High 488 Medium 489 Low 490

```
LISTING 1
** Power-up initialization and main control logic.
** After performing power-up initializations, the program enters
** an endless loop from which it controls the operation of the
** motor controller.
initialize parallel I/O
shut down motor due to power-up
clear status table
initialize variables
initialize serial I/O
clear serial-receive queue
clear serial-transmit queue
indicate "lost"
indicate "disabled"
table position = 0
indicate not in feedhold
indicate not homing
allow serial-receive interrupt
DO FOREVER
   retrigger watchdog one-shot
   update status table
   IF (emergency-stop input true) THEN
      shut down motor due to emergency-stop input
   IF (feedhold input true) AND (not disabled) THEN
      indicate in feedhold
   IF (a complete command has been received) THEN
      process the command
   IF (error = 0) THEN
      make table-stopped output true
   ELSE
      make table-stopped output false
   IF (serial transmit is ready to transmit again) THEN
      IF (a character is in the transmit queue) THEN
         dequeue a character and transmit it
   IF (homing in progress) THEN
      continue homing process
END
```

LISTING 2

```
/*

*** Service serial-receive interrupt.

**

*** Queue command characters to be analyzed by background code.

** Flag communication errors and end of command.

*/

disable serial-receive and Go-command interrupts
allow encoder interrupt if it is not disabled

read character from serial-receive register

IF not (unprocessed complete command in serial recv queue) THEN
    If (character suffered parity or framing error) THEN
        remember communication error occurred

ELSE
    queue character in serial-receive queue
    If (character is end-of-command character) THEN
```

LISTING 2 (Continued)

indicate complete command ready to be processed

allow all interrupts that were enabled on entry return from interrupt

LISTING 3

```
** Process a command received through the serial port.
** Queue a response to the command. If the command is
** acceptable, carry it out or set it in motion.
IF (a communication error occurred) THEN
  queue "C" to send (report communication error)
IF (no communication error) AND (command character is invalid) THEN
  queue "Y" to send (report syntax error)
IF (no communication error) AND (command character valid) THEN
   IF (command is send-byte command) THEN
      format specified byte into two ASCII-coded hex characters
      queue "B" and the two characters to send
IF (no communication error) AND (command character valid) THEN
   IF (not disabled) THEN
      DO CASE (command character)
         re-enable command:
            queue "S" to send (report command out of sequence)
         feedhold command:
            indicate in feedhold
            queue "D" to send (report success)
         continue command:
            IF (feedhold input false) THEN
               indicate not in feedhold
            queue "D" to send (report success)
         emergency-stop command:
            shut down motor due to emergency-stop command
            queue "D" to send (report success)
         set-feed-rate command:
            calculate new feed rate from cmd parameter characters
            IF (new feed rate within range) THEN
               adopt new feed rate
               queue "D" to send (report success)
            ELSE
               queue "Y" to send (report syntax error)
        move command:
            IF lost THEN
               queue "S" to send (report command out of sequence)
            ELSE IF (end point of move is out of range) THEN
               queue "Y" to send (report syntax error)
            ELSE IF (a move underway) AND (not stopped in feedhold) THEN
               queue "S" to send (report command out of sequence)
            ELSE
               start move to end point specified in the command
               queue "D" to send (report move begun)
        home command:
             IF (a move underway) THEN
                queue "S" to send (report command out of sequence)
                initiate homing process: home stage = 1
                indicate "lost"
                queue "D" to send (report homing begun)
      END
```

HP's family of motion-control products gives you everything you need for complete control.

Choose from a broad line of digital potentiometers, general-purpose motion-control ICs, snaptogether encoders, 2- and 3-channel encoders, and quadrature decoder counters.

This wide range of adaptable sensors and controls eliminates the need to design your own. And it provides you with HP's advanced digital optoelectronic technology in every product.


Best of all, they're backed by Hewlett-Packard. Which means you can always count on convenient worldwide field service and application

support.

If you'd like to take control, contact your authorized Hewlett-Packard distributor today. In the U.S.: Almac Electronics, Hall-Mark, Hamilton/Avnet, or Schweber In Canada: Hamilton/Avnet or Zentronics, Ltd.

Control yourself.

PACKARD



CIRCLE NO 76

```
LISTING 3 (Continued)
IF (no communication error) AND (command character valid) THEN
   IF disabled THEN
      DO CASE (command character)
         feedhold command:
         continue command:
         emergency-stop command:
         home command:
         move command:
         set-feed rate command:
            queue "S" to send (report command out of sequence)
         re-enable command:
            read and save initial states of encoder signals
            allow encoder interrupt
            make emergency-stop output false
            queue "D" to send (report success)
      END
clear "communication error" indication
clear "command awaiting processing" indication
```


LISTING 4

172

```
** Start a move
**
** Pass this routine the end point (in feedback units from home)
** of a move to be made. It calculates and saves the number of
** Go commands that must be issued to get to the end point from
** the present position. This routine calculates the frequency at
** which the Go commands must be issued in order to achieve the
** desired feed rate.
*/
IF (end point of move not equal present position) THEN
  IF (end point of move further from home than present position) THEN
      Go commands to issue = end point of move - present position
      IF (home is found moving CW) THEN
         indicate direction of move is CCW
      ELSE
         indicate direction of move is CW
  ELSE
      Go commands to issue = present position - end point of move
      IF (home is found moving CW) THEN
         indicate direction of move is CW
      ELSE
         indicate direction of move is CCW
   greatest error this move = 0
   calculate timer interrupt period needed to produce desired feed rate
  set up timer to interrupt after calculated time
   allow timer interrupt
```

Note: In the above, "present position" is where the table is with zero error; that is, where Go commands have moved it.





LINEAR PRODUCTS DATABOOK

OPERATIONAL AMPLIFIERS
COMPARATORS
INSTRUMENTATION AMPLIFIERS
ISOLATION AMPLIFIERS
ANALOG MULTIPLIERS/DIVIDERS
LOG/ANTILOG AMPLIFIERS
RMS-TO-DC CONVERTERS
SPECIAL FUNCTION COMPONENTS
TEMPERATURE TRANSDUCERS
SIGNAL CONDITIONING COMPONENTS & SUBSYSTEMS
DIGITAL PANEL INSTRUMENTS
APPLICATION SPECIFIC ICS
POWER SUPPLIES
COMPONENT TEST SYSTEMS

IF YOU'RE SEARCHING FOR A HIGH-PERFORMANCE OP AMP, YOU'RE LOOKING AT THE RIGHT BOOK.

```
LISTING 5
** Service timer (Go-command) interrupt.
** This routine runs in response to timer interrupts. It issues
** Go commands by augmenting the error count. This routine is
** invoked at a frequency which was calculated to produce the
** desired feed rate.
disable Go-command interrupt
start timer counting ticks to next interrupt
allow serial-receive interrupt
allow encoder interrupt if it is not disabled
IF (not in feedhold) THEN
   IF (direction is CW) AND (error < CW error limit) THEN
      increment error
  ELSE IF (direction is CCW) AND (error < CCW error limit) THEN
     decrement error
  write new error out to D/A
  decrement count of Go commands left to issue
   (in "toward home" stage of homing process) THEN
   IF (at-home input true) THEN
     Go commands to go = 0
IF (Go commands to go > 0) THEN
   enable Go-command interrupt
allow all interrupts not disabled
return from interrupt
```

LISTING 6

```
** Service external (encoder) interrupt.
** This routine runs in response to edges in one signal from an
** encoder. It diminishes the position-loop error if motion is
** commanded; it augments the error if motion is uncommanded.
IF (being re-entered) THEN
  shut down for encoder interrupts coming too fast
   indicate executing encoder interrupt handler (to catch re-entry)
   disable serial-receive and Go-command interrupts
   allow encoder interrupt
  read encoder signals channel A and channel B
   IF (channel A is low) AND (channel B is high) THEN
      IF previous states of channels were high/low THEN
         a CW encoder cycle has occurred: decrement error
         IF (home is CW) THEN
            decrement table position
         ELSE
            increment table position
   ELSE IF (channel A is low) AND (channel B is low) THEN
      IF previous states of channels were high/high THEN
```


Listing continued on pg 176



15µV max Offset Voltage **Ultralow Drift Op Amp**

AD707

Very High dc Precision 15μV max Offset Voltage 0.1μV/°C max Offset Voltage Drift 0.35μV p-p max Voltage Noise (0.1Hz to 10Hz) 8V/µV min Open-Loop Gain 0.32µV/V max CMRR 1μV/V max PSRR 1nA max Input Bias Current 1nA max Input Offset Current Dual Version Available: AD708



PRODUCT DESCRIPTION


The AD707 is a low cost, high precision op amp with state-of-theart performance that makes it ideal for a wide range of precision applications. The offset voltage spec of less than $15\mu V$ is outstanding for a bipolar op amp, as is the 1.0nA maximum input offset current. The top grade is the first bipolar monolithic op amp to offer a maximum offset voltage drift of 0.1µV/°C, and offset current drift and input bias current drift are both specified at 25pA/°C maximum.

The AD707's open-loop gain is $8V/\mu V$ minimum over the full \pm 10V output range when driving a $1k\Omega$ load. Maximum input voltage noise is 350nV p-p (0.1Hz to 10Hz). CMRR and PSRR are 130dB and 120dB minimum respectively

The AD707 is available in versions specified over commercial, industrial and military temperature ranges. It is offered in 8-pin plastic mini-DIP, small outline, hermetic cerdip and hermetic TO-99 metal can packages. Chips and Mil Standard/883 parts are also available

APPLICATION HIGHLIGHTS

- 1. The AD707's 13V/μV typical open-loop gain and 0.1μV/V typical common-mode rejection ratio make it ideal for precision instrumentation applications.
- 2. The precision of the AD707 makes tighter error budgets possible at a lower cost.
- 3. The low offset voltage drift and low noise of the AD707 allow the designer to amplify very small signals without sacrificing overall system performance.
- 4. The AD707 can be used where chopper amplifiers are required, but without the inherent noise and application problems.
- 5. The AD707 is an improved pin-for-pin replacement for the OP-07, OP-77 and the LT1001.



BIPOLAR OP AMP



If your analog applications demand precision performance, then you should demand our new AD707 – the world's best dc precision op amp.

The AD707 is the first bipolar monolithic to offer a maximum offset voltage drift of only

0.1μV/°C, and 15μV maximum offset voltage. These features, combined with its ultralow $0.35\mu V$ p-p voltage noise, allow the AD707 to amplify extremely small signals without sacrificing system performance.

The AD707 also provides an open-loop gain of $13V/\mu V$, which is the highest of any precision op amp, and unsurpassed 140dB CMRR and PSRR. So it's ideal for a wide range

of precision applications, including instrumentation and automatic test equipment.

All this precision makes it easy for you to work within tight error budgets. And because the AD707 is available at a low cost, you can easily work within your design budget, too. Versions start at only \$1.25 (in 100s).

For an even more accurate description of what the AD707 can do for you, call Applications Engineering at (617) 935-5565, Ext. 2628 or 2629.

Or write to Analog Devices, P.O. Box 9106, Norwood, MA 02062-9106.



Analog Devices, Inc., One Technology Way, P.O. Box 9106, Norwood, MA 02062-9106; Headquarters: (617) 329-4700; California: (714) 641-9391, (619) 268-4621, (408) 559-2037; Colorado: (719) 590-9952; Maryland: (301) 992-1994; Ohio: (614) 764-8795; Pennsylvania: (215) 643-7790; Texas: (214) 231-5094; Washington: (206) 251-9550; Austria: (222) 885504; Belgium: (3) 2371672; Denmark: (2) 845800; France: (1) 4687-34-11; Holland: (1620) 81500; Israel: (052) 911415; Italy: (2) 6883831, (2) 6883832, (2) 6883833; Japan: (3) 263-6826; Sweden: (8) 282740; Switzerland: (22) 31 57 60; United Kingdom: (932) 232222; West Germany: (89) 570050

```
LISTING 6 (Continued)
         a CCW encoder cycle has occurred: increment error
         IF (home is CCW) THEN
            decrement table position
         ELSE
            increment table position
   IF (error > error limit + 2) THEN
      shut down motor because motor out of control
   ELSE
      write error out to D/A
      save encoder signal states for next time
      IF (error > greatest error this move) THEN
         save error as greatest
indicate not executing encoder interrupt
allow interrupts that were enabled on entry and not disabled by shut down
return from interrupt
```

```
LISTING 7
** Control homing process
** While attempting to "home" the table, the main program loop
** calls this routine over and over (once per loop) until
** this routine indicates that the homing process is complete.
** This routine advances the homing process through several
** stages.
DO CASE (homing stage)
   stage 1:
      IF (table is already on home switch) THEN
         start a small, slow move away from home
         home stage = 2
         start a slow move toward home
         home stage = 3
      return
   stage 2:
      IF (move away from home is done) THEN
         start a slow move toward home
         home stage = 3
      return
   stage 3:
      IF (move toward home is done and zero error) THEN
         IF (table not activating home switch) THEN
            shut down motor due to failure to find home switch
         ELSE
            table position = 0
            IF (move toward home didn't reach homing speed) THEN
               home stage = 1
            ELSE
               homing done: home stage = 0
               indicate not "lost"
      return
END
```



Wide Bandwidth, Fast Settling Operational Amplifier

AD9611

FEATURES
Unity Gain Stable
Small Signal Bandwidth 280MHz
Full Power Bandwidth 220MHz
Settling – 13ns to 0.1%
Offset Voltage ± 0.5mV
Bias Current ± 1µA
Power Dissipation Independent of Load

APPLICATIONS
Driving Flash Converters
High Speed DAC I-to-V Conversion
Radar, IF Processors
Baseband and Video Communications
ATE/Pulse Generators
Imaging/Display Applications


PRODUCT DESCRIPTION

The AD9611 is a fast settling, wide bandwidth, low distortion, de coupled operational amplifier that combines exceptional ac and de specifications to establish a new standard of excellence. The combination provides designers with a unique solution when system speed and signal fidelity are critical.

Rise and fall times are 1.3ns. The -3dB bandwidth is 280MHz. $(G=\pm5)$; full power bandwidth is 220MHz. The AD9611 settles to 0.1% in 13ns and has flat frequency response over the rated bandwidth. The design is optimized to provide low distortion over the full bandwidth, which means "clean" amplification for driving high speed flash A/D converters.

Input offset voltage is $\pm 0.5 mV$ with $5\mu V/^{\circ}C$ drift; bias currents are typically $\pm 1\mu A$, and drift $75nA/^{\circ}C$. In most current-feedback amplifiers, bias current drifts are random. In the AD9611, inverting and noninverting bias currents drift in the same direction over temperature; this allows traditional resistor nulling for reducing effective output voltage drift.

The AD9611BH is rated for case temperatures from -25°C to +85°C; the AD9611TH is guaranteed from -55°C to +125°C. Contact the factory for information about 883 grade parts. All units are built and tested in a MIL-STD-1772 certified facility.



AD9611 Functional Block Diagram

PRODUCT HIGHLIGHTS

- The current-feedback architecture which is used instead of voltage feedback makes bandwidth relatively independent of gain. With G=0, -3dB bandwidth is 310MHz; at G=±5, bandwidth is 280MHz; at G=±20, bandwidth is 210MHz.
- 2. Extremely low distortion and noise are hallmarks of AD9611 performance. A 60MHz input tone is used for 100% testing of 2nd and 3rd harmonics; they measure 54dBc and 58dBc, respectively. With a 20MHz input, they measure 67dBc and 69dBc. Exceptionally low 3rd order two-tone intermodulation distortion (IMD) makes the AD9611 an ideal choice for communications/IF applications.
- 3. The AD9611 requires ± 5V power supplies and has an innovative current-steering output stage that keeps total circuit power dissipation essentially constant regardless of output drive (for loads ≤ 100Ω). Circuit power dissipation does not increase as the load is increased; the unit can be operated up to +110°C in still air without heat sinking.





am

dec

OPEN TO THIS PAGE FOR THE BEST PERFORMING HIGH-SPEED OP AMP.



If your present high-speed operational amplifiers are creating performance problems in your systems, you should consider the newest standard in high-speed op amps, our AD9611.

With a -3dB bandwidth of 280MHz typical (250MHz guaranteed), the AD9611 has the widest bandwidth of any dc-coupled op amp available. And with a 60MHz input tone, the second harmonic is -54dBc, so the fidelity and distortion performance are also unmatched.

When it comes to time domain and settling time performance, the AD9611 dominates there, too. Rise

and fall times are 1.3 and 1.5ns, respectively, and settling to 0.1% is just 13ns.

In addition, the AD9611 can deliver its fully rated load even in ambient temperatures of up to 110°C – unlike other high-speed op amps, which require heat sinking starting at 40°C . The AD9611 doesn't sacrifice dc performance either, since offset voltage is only 0.5mV and bias currents are $1\mu\text{A}$.

For more information on how the AD9611 provides optimum high-speed performance in dc-coupled op amps, call your nearest Analog Devices sales office, or our applications engineers at (919) 668-9511.

Analog Devices, Inc., One Technology Way, P.O. Box 9106, Norwood, MA 02062-9106; Headquarters: (617) 329-4700; California: (714) 641-9391, (619) 268-4621, (408) 559-2037; Colorado: (719) 590-9952; Maryland: (301) 992-1994; Ohio: (614) 764-8795; Pennsylvania: (215) 643-7790; Texas: (214) 231-5094; Washington: (206) 251-9550; Austria: (222) 885504; Belgium: (3) 237 1672; Denmark: (2) 845800; France: (1) 4687-34-11; Holland: (1620) 81500; Israel: (052) 911415; Italy: (2) 6883831, (2) 6883832, (2) 6883833; Japan: (3) 263-6826; Sweden: (8) 282740; Switzerland: (22) 3157 60; United Kingdom: (932) 232222; West Germany: (89) 570050

LISTING 8

```
** Shut down the motor for some reason

*/

disallow all interrupts
make emergency-stop output true
disable Go-command (timer) interrupt
disable encoder (external) interrupt
set error equal to zero and write it out to D/A
indicate "lost"
indicate "disabled"
indicate not in feedhold
Go commands left to go = 0
table position = 0
indicate not "homing"
indicate reason for shutdown
allow serial-receive interrupt if it was enabled on entry
```

WIDEST SELECTION, FASTEST DELIVERY, LOWEST PRICE When it comes to connecting discrete wires to electronic circuitry for 20 amp power or milliamp signal applications, who else but BUCHANAN could offer such a complete family of connectors to choose from? ... with the widest range of center-to-center spacing available — starting with the new subminiature 3.5mm

TRY A FREE SAMPLE IN YOUR APPLICATION

We'll be glad to put a sample BUCHANAN electronic connector in your hands. Just drop us a note on your letterhead describing your application. Or, call us at 1-800-221-0698, Ext. 415



INDUSTRIAL ELECTRICAL PRODUCTS

AMERACE CORPORATION INDUSTRIAL ELECTRICAL PRODUCTS 530 W. MT. PLEASANT AVENUE LIVINGSTON, NJ 07039 (201) 992-8400 TELEX: 13-8403 FAX: 201-992-9416

BUCHANAN

and service time. Send for the industry's most comprehensive catalogs.

connector. The most powerful name in the industry also gives you a wide variety of one-piece and plug-in configurations, the fastest delivery, and the lowest

BUCHANAN electronic connectors free you from special tools and soldering

irons. All you need for fast connections is a screwdriver, saving you installation

Available in edgecard, barrier strip, miniature, and custom configurations,

CIRCLE NO 27

applied cost.



500ns Settling BiFET Op Amp

AD744


FEATURES Fast Settling

500ns to 0.01% for 10V Step 1.5µs to 0.0025% for 10V Step

Slew Rate: 75V/µs

Total Harmonic Distortion (THD): 0.0003% >1000pF Capacitive Load Drive Capability with 10V/μs Slew Rate

Input Offset Voltage: 0.25mV max Input Offset Drift: 3µV/°C max Open Loop Gain: 250V/mV min Noise: 4µV p-p max, 0.1Hz to 10Hz



AD744 Settling Characteristics 0 to + 10V Step

PRODUCT DESCRIPTION

The AD744 makes a breakthrough in the high speed BiFET market by offering guaranteed maximum settling to 0.01% in 750ns. It also offers the excellent dc characteristics of the AD711 BiFET family with enhanced slew rate, bandwidth and load driving capability

The single-pole response of the AD744 provides fast settling: 500ns to 0.01% typically, and 750ns maximum. This feature, combined with high dc precision, makes the AD744 suitable for use as a buffer amplifier for 12-, 14- and 16-bit DACs and ADCs Furthermore, the AD744's low total harmonic distortion (THD) level of 0.0003%, low noise and gain bandwidth product of 13MHz make it an ideal amplifier for demanding audio applica tions. It is also an excellent choice for high speed instrumentation amplifiers and for use in active filters.


The AD744 offers optional custom compensation for additional design flexibility. This external compensation allows the AD744 to drive capacitive loads up to 2000pF and greater with full stability, making the AD744 outstanding for use as a coaxial cable driver. Alternatively, external decompensation may be used to increase the gain bandwidth of the AD744 to over 200MHz at high gains. This makes the AD744 ideal for use as an ac preamp in digital signal processing (DSP) front ends.

PRODUCT HIGHLIGHTS

THIS PAGE SE

HE OUESTION OF WH

- 1. The AD744 offers exceptional dynamic response. It settles to 0.01% in 500ns and has a 100% tested minimum slew rate of
- 2. The combination of Analog Devices' advanced processing technology, laser wafer drift trimming and well-matched ionimplanted JFETs provide outstanding dc precision. Input offset voltage, input bias current and input offset current are specified in the warmed-up condition and are 100% tested.
- 3. The AD744 has a guaranteed and tested maximum voltage noise of 4µV p-p, 0.1 to 10Hz.
- 4. The AD744 is a high speed BiFET op amp that offers excellent performance at competitive prices







A lot of companies say they have fastsettling, high-performance BiFET amps. But our AD744 settles to 0.01% in 500ns and to 0.0025% in 1.5µs-making it the world's fastest-settling, highest-performance BiFET. This superior settling, combined with excellent dc

performance, makes the AD744 unbeatable for active filters, and for buffering DACs and ADCs up to 16 bits.

The AD744, with a total harmonic distortion of just 0.0003%. low noise, a clean pulse response, and a gain bandwidth product of up to 200MHz, is also ideal for digital signal processing and audio applications.

If you work in communications, you'll appreciate the AD744's ability to drive loads greater than 2000pF with full stability. And you'll also appreciate the fact that the AD744 can drive a 1000pF

cap load while maintaining a slew rate of 10V/µs.

The AD744 isn't our only outstanding BiFET, either. The AD711 single, AD712 dual, and soon the AD713 quad, settle in 1 µs with the same high resolution as the AD744. If low power with precision is critical, try our AD548 single or AD648 dual.

Whichever BiFET your application requires, you'll find our products deliver excellent performance at an excellent price. For example, the AD744 starts at only \$2.25; the AD711 at \$.80; and the AD548 at \$.75 (100s).

If you'd like to see more proof on why we can say we make the best BiFETs, call Applications Engineering at (617) 935-5565, ext.

2628 or 2629. Or write to Analog Devices, P.O. Box 9106, Norwood, MA 02062-9106.



Analog Devices, Inc., One Technology Way, P.O. Box 9106, Norwood, MA 02062-9106; Headquarters: (617) 329-4700; California: (714) 641-9391, (619) 268-4621, (408) 559-2037; Colorado: (719) 590-9952; Maryland: (301) 992-1994; Ohio: (614) 764-8795; Pennsylvania: (215) 643-7790; Texas: (214) 231-5094; Washington: (206) 251-9550; Austria: (222) 885504; Belgium: (3) 237 1672; Denmark: (2) 845800; France: (1) 4687-34-11; Holland: (1620) 81500; Israel: (052) 911415; Italy: (2) 6883831, (2) 6883832, (2) 6883833; Japan: (3) 263-6826; Sweden: (8) 282740; Switzerland: (22) 31 57 60; United Kingdom: (932) 232222; West Germany: (89) 570050



AD840 Series

	AD840	AD841	AD842	AD843	AD844
Gain Bandwidth	400MHz	40MHz	80MHz	35MHz	60 to 430MHz
Min Stable Gain	10	Unity	2	Unity	Unity
Settling Time	100ns	110ns	100ns	110ns	100ns
(10V Step)	to 0.01%	to 0.01%	to 0.01%	to 0.01%	to 0.05%
Slew Rate	400V/μs	300V/µs	375V/μs	300V/μs	to 2,000V/μs
Quiescent Current (max)	12mA	12mA	14mA	12mA	6.5mA
Comments	HA2540	50mA min	100mA min	FET-Input,	Current Feedback,
	Improved	Output	Output	Replaces FET-	2nV/√Hz Noise
	Replacement	Current	Current	Input Hybrids	at 1kHz

THE REVOLUTION IN STARTS RI

Introducing our AD840 Series with ten new op amps—and the start of a revolution. Because now you can go to just one vendor and get more high speed op amps with higher precision and lower power than from anywhere else.

The AD840 Series, which includes high accuracy, low noise, low cost, FET-input and current-feedback amps, is the result of a major breakthrough we've made in analog process technology. A breakthrough that has not only led

to such diversity, but has also made each op amp a performance leader.

For example, several of the products in the AD840 Series offer gain-bandwidths greater than 400MHz, while others offer slew rates up to 2,000V/ μ s. And all AD840 products offer precision at high speeds, with unprecedented settling time performance as fast as 100ns to 0.01% (10V step) and offset voltage down to 75 μ V maximum.























High Speed Op Amp Selection Guide

AD840 Series

AD846	AD847	AD848	AD849	
46 to 600MHz Unity	50MHz Unity	175MHz 5	750MHz 25	Gain Bandwidth Min Stable Gair
100ns to 0.01%	120ns to 0.1%	100ns to 0.1%	80ns to 0.1%	Settling Time (10V Step)
450V/µs	300V/μs	300V/μs	300V/μs	Slew Rate
6mA	5.7mA	5.7mA	5.7mA	Quiescent Current (max)
Current Feedback, 75µV max Offset Voltage	Excellent Flash ADC Buffer	Stable into any Cap Load	Low Noise Pre-Amp	Comments
	46 to 600MHz Unity 100ns to 0.01% 450V/μs 6mA Current Feedback, 75μV max Offset	46 to 600MHz Unity 100ns to 0.01% 120ns to 0.1% 450V/μs 300V/μs 6mA 5.7mA Current Feedback, 75μV max Offset Flash ADC	46 to 600MHz Unity 50MHz Unity 5 100ns to 0.01% 120ns to 0.1% 100ns to 0.1% 100ns to 0.1% 500N/μs 300V/μs 300V/μs 5.7mA 5.7mA Current Feedback, 75μV max Offset Flash ADC Cap Load	46 to 600MHz Unity Unity 50MHz Unity 50MHz 175MHz 750MHz 25 100ns to 0.01% 120ns to 0.1% 100ns to 0.1% 100ns to 0.1% 100ns to 0.1% 100ns to 0.1% 500N/μs 300V/μs 300V/μs 300V/μs 5.7mA 5.7mA Current Feedback, 75μV max Offset Flash ADC ADG

HIGH SPEED OP AMPS GHT HERE.

This high performance isn't at the expense of power. In fact, each AD840 product consumes 25-50% less power than comparable amps, without sacrificing load drive current. Plus all parts operate with \pm 15V or \pm 5V supplies.

The high performance doesn't come at a high cost, either. You'll find that whether you use the AD840 Series op amps to bring a new standard of performance to your designs, or as replacements for industry standards, they're

all competitively priced.

If you'd like more information on why the AD840 Series makes us the new revolutionary leader in high speed op amps, call Applications Engineering at (617) 935-5565, ext. 2628 or 2629. Or write


to Analog Devices, P.O. Box 9106, Norwood, MA 02062-9106.



Analog Devices, Inc., One Technology Way, P.O. Box 9106, Norwood, MA 02062-9106; Headquarters: (617) 329-4700; California: (714) 641-9391, (619) 268-4621, (408) 559-2037; Colorado: (719) 590-9952; Maryland: (301) 992-1994; Ohio: (614) 764-8795; Pennsylvania: (215) 643-7790; Texas: (214) 231-5094; Washington: (206) 251-9550; Austria: (222) 885504; Belgium: (3) 237 1672; Denmark: (2) 845800; France: (1) 4687-34-11; Holland: (1620) 81500; Israel: (052) 911415; Italy: (2) 6883831, (2) 6883832, (2) 6883833; Japan: (3) 263-6826; Sweden: (8) 282740; Switzerland: (22) 3157 60; United Kingdom: (932) 232222; West Germany: (89) 570050

Dational Design

CAN THIS BE DONE?



A COMMUNICATION

DEVICE FOR THE

SPEECH - DEAF

REHABILITATION
SOCIETY....

the EARS design competition

FIRST PRIZE - \$100,000 PLUS A % OF ROYALTY

SECOND PRIZE - \$50,000 PLUS A % OF ROYALTY

THIRD PRIZE - \$25,000 PLUS A % OF ROYALTY

EXECUTIVE AUDIAL REHABILITATION SOCIETY

500 AMERICAN BANK TOWER P. O. Box 2703 CORPUS CHRISTI, TEXAS 78475 (512) 882-6557

JUDGES COMMITTEE

JACK S. KILBY, Dallas, Texas, Electronics Engineer
HOWARD H. ARNOLD, Lewisville, North Carolina, Electronics Engineer
JAMES S. NEWCOMB, St. Paul, Minnesota, Electronics Engineer
HUBERT W. UPTON, Arlington, Texas, Electronics Engineer — Alternate
PROFESSOR HUGH TOMLINSON, Corpus Christi, Texas — Coordinator

WINNERS 1986 SUGGESTION CONTEST

MILDRED CRUICKSHANK, Telephone connection ED POTTHARST, Multichannel memory

Competition

WE THINK YOU CAN!

HERE ARE 17,000,000 speech-deaf persons, i.e. do not understand speech, in the U.S. The objective is to provide a communication device that will allow one-on-one communication. The final EARS design, incorporating all possible operational advantages and economies of production, may be the composite of the prize winners' designs and may also incorporate features of the designs submitted by non-prize winners. Winners will be accorded cash and royalties. All royalties negotiated by EARS will be passed through to the contestants. The royalties will be apportioned by the Judges on the basis of their evaluation of the importance of each element submitted by any contestant which is included in the Final Production Design.

Those desiring to participate should apply (by mail or phone) for a registered entry blank to the Executive Audial Rehabilitation Society shown. Each entry shall include design, programming instruction and an operating "bread board" model which need not conform to the size goals. EARS will compensate those contestants (whose entries are adjudged to be operationally feasible) for the current cost of the components used to build the bread board operational model. The entries will be evaluated by the Judges on the basis of merit, i.e. operationally effective that can be produced at a reasonable cost.

Detailed conditions of the competition will be set out on the entry form. DEADLINES: Entry forms must be procured and returned to EARS not later than October 31, 1988. Designs and bread board models must be received by 5 P.M. on May 1, 1989.


All designs submitted and accepted by the Judges shall be the property of EARS. No essential conceptual element of a design shall constitute a conflict with an existing patent. Conceptual protection of the device has been established as of date of origin. Formal application for patents on pertinent features will be applied for by EARS. A firm of patent attorneys specializing in electronics is retained. All decisions by the Judges as to the award or non-award of prizes or royalty shall be final and shall not be subject to change, review or amendment by EARS., its Officers, Executive Committee or the design contestants.

DESIGN GOALS

- The goal is a design for a hand-held, lightweight real time communication device capable of being produced at economical cost. The design should allow a speaking person to communicate on a one-on-one real time basis with the hearing-impaired person in any situation where normal conversation occurs and will provide for filtration of extraneous noise. The goal is a device contained in approximately 6" x 8" x 1½". A 5" x 7" screen will be on one side. The speech-deaf person can place it on a desk or hold it in hand. The speaker will first read a text identifying his phonetic alphabet in the memory. A multi-position switch would allow storage of the phonetic alphabets of different persons. For telephone calls, the speech of a person (whose phonetic alphabet is in one of the memory channels or who reads the text into a new channel) will enter the communication device through a standard telephone plug. The device will be battery-powered with rechargeable batteries but provide for alternative operation with a voltage converter. Intensive electronic speech analysis combined with the personal phonetic alphabet of the speaker will result in the "real-time" production of the spoken words on the screen. The speech of the hearing-impaired person not fitting the phonetic alphabet of the memory should be filtered out automatically if possible, otherwise manually.
- 2 Equally important is a design for this device that can be manufactured economically so that the cost is within the means of this group of people, many of whom may be economically disadvantaged.


Introducing OmniLab 9240. Totally Integrated Scope-Analyzer-Stimulus.

- Combine a 100 MHz digital oscilloscope with a time-aligned, 200 MS/s 48-channel logic analyzer. Next add synchronized analog and digital stimulus generators. Then a remarkable new triggering system. What you have is the 9240 a whole new class of instrumentation. Expressly designed to speed challenging analog and digital analysis. And get you from concept to product faster.
- The 9240 is based on an innovative new instrument architecture that merges high-speed universal hardware and seamlessly-integrated software to create high-performance capabilities not available in separate instruments. Analog and digital traces are always time-correlated in a unique, single screen display. SELECT™ triggering bridges scope and analyzer techniques. And OmniLab's stimulus generators can playback captured or edited signals.
- Triggering, the most straightforward and complete solution **ever** to triggering dilemmas. It's one system, operating with synchronized analog and digital views of your data. By combining conventional oscilloscope and analyzer triggering with powerful RAM truth tables plus min/max time qualification as needed SELECT triggering helps you analyze hardware, debug software, and integrate systems more easily.
- OmniLab™ is a generation ahead of conventional digital scopes that often hide rarely occurring faults because they only show you a few cycles out of millions. With its continuous monitoring, you can use SELECT triggering to quickly catch every occurrence



of rare events like metastable states, bus contentions, missing pulses, and buried noise glitches.

- The 9240 is like having a complete benchtop of instruments integrated with your PC/AT or compatible. Which you can easily customize for digital development, analog development, or a combination of both.
- With OmniLab, your productivity will soar. Because you achieve results with fewer instruments. And in fewer steps than ever before. By no means least, the 9240 delivers the best price/performance you'll find anywhere, costing just \$8900 fully outfitted. And most importantly, without compromising a single high-performance spec. Not a one.
- For more information, call **toll free 800/245-8500.** In CA: 415/361-8883. Or write for complete literature.



ORION

702 Marshall Street, Redwood City, CA 94063 TELEX: 530942 FAX: 415/361-8970

Computer Integrated Instrumentation

*OmniLab, and SELECT are trademarks of Orion Instruments, Inc.

Digital synthesizer aids testing of complex analog, digital circuits

A digitally based signal synthesizer (DSS) provides the test engineer with a high degree of flexibility in the generation of test signals. When used with a digitizing scope, the DSS greatly simplifies the testing of complex analog and digital circuits such as those found on pc boards for hard-disk-drive applications.

Al Kovalick, Hewlett-Packard Co

Tester versatility is particularly important for the test engineer dealing with boards containing both analog and digital circuits. In the production environment, a test engineer normally has the choice of four primary approaches to board testing:

- In-circuit testing. Technicians in the actual target environment test and debug the boards. No actual tester is involved. In-circuit testing is low cost.
- Universal board testing. Universal board testing means a complete, integrated system for complex, general applications. Primarily used for device testing, these types of testers can also handle some functional tests. A universal board tester is expensive.
- Custom, one-of-a-kind, functional testing. Usually dedicated, one-of-a-kind testers don't see much use. They are moderately priced.

 Semicustom functional testing. Semicustom types of testers can usually handle several board types, see medium use, and feature programmable signal stimulus. The cost is moderate.

The choice of a tester depends on several factors. Among these are board complexity, board type (analog, digital, or mixed), frequency range (low, RF, or microwave), production volume, margin-testing requirements, and device or function-level testing requirements. Furthermore, if board adjustments are necessary, a functional test environment is usually required. Testing the boards over a range of input parameters—rather than simply at typical values—adds the assurance of product robustness. For these cases, a functional tester with wide control over input parameters is useful.

Testing mixed analog and digital circuitry

The semicustom functional tester is especially useful in situations where both analog and digital circuitry need to be tested—in disk-drive systems, for example. It provides a nondedicated, functional test system adaptable to board changes or to entirely new boards with the same board test system. You won't find a hard and fast definition for the semicustom tester, but it usually includes a digital multimeter (DMM), an analog signal source, a digitizing scope, and a digital word source and analyzer.

Most test engineers are keenly aware of the measurement flexibility that digitizing scopes offer. The more recently introduced DSS presents a flexible means of generating programmable analog signals. The combina-

As a complement to the digitizing scope, the digital signal synthesizer offers test engineers a flexible means of generating complex analog and digital signals.

tion of a digitally based source and analyzer provides a still higher order of flexibility.

The inclusion of a digital synthesizer in a semicustom tester lets you generate a wide range of signals. You can tailor these signals with a selectable level of added noise, jitter, offset, and other characteristics. And, with carefully controlled anomalies superimposed upon the ideal signal, you can test the board's performance with a superior degree of integrity. As an aid to board adjustment and calibration, digital synthesizers offer calibration-quality signals. For example, synthesizers can easily generate precision reference signals with AM, PM, FM, phase shift, and noise. The quality of the reference signal depends only on the spectral purity of the synthesizer's output.

To better understand the digital signal synthesizer,

consider its similarity to the compact disk (CD) player:

- The CD player has a rotating disk, which contains information that the laser reads. The information —in this case, music—is imprinted on the disk in the form of digital data. In a digital synthesizer, very fast memory replaces the rotating disk. The memory contains digital words that are played back in a sampled system.
- In a CD player, the sample data rate is 44.1 kHz, which corresponds to a sample every 22.6 μsec. In the DSS, the sample rate is 125 MHz, or a new sample every 8 nsec.
- CD players feature two 16-bit DACs, one for each stereo channel. The DSS employs one 12-bit DAC, largely because 16 bits is neither required at these extremely high rates nor possible given the

Testing disk-media certifiers

Both manufacturers of disk media and drive manufacturers who buy disk media need a way to test the quality of the drives' magnetic surfaces. There are established industry specifications for testing the media, and several manufacturers supply media certifiers.

Many tests are performed before a disk surface passes a quality check. Two tests that are usually needed to qualify a surface are the missing- and extrabit tests. Fig A shows a portion of a 16.66-msec code-bit sequence with two transitions reduced by 50%. The sequence is at a transition rate of 20 MTPS (million transitions per second). This signal has about 333,000 transitions per disk rotation.

You can input the missing-bit signal to the certifier hardware to verify its integrity over a range of reduction levels and a range of missing bits per revolution. Certifiers can be programmed to detect missing bits at a user-defined level. A good test of the certifier's ability to detect such missing bits is to send it a succession of signals, each with bit-reduction levels near the desired setting. In practice, the certifier will mark some bits as missing and some as not missing.

For example, assume that the certifier's missing-bit threshold is set to 50%. Now, send it several signals, each having a dif-

ferent, but known, bit reduction between 45 and 55%. You can determine the certifier's accuracy by noting its response to each signal.

Also of interest are the extrabit test, positive- and negativemodulation tests, the peak-shift test, and the AGC test. A welldesigned digital signal synthesizer can produce signals for all of these tests.




Fig A—This waveform shows two missing bits at 50% reduction. This type of signal is suitable for calibrating disk certifiers.

present state of the art.

- Most CD players have a sequencer that lets you play back the tracks in any order. The DSS has a sequencer that permits the playback of waveforms in any order.
- Both the CD player and the DSS use lowpass filters to reject all the sampling energy, and both have output amplifiers.

Testing disk-drive boards

As mentioned, DSSs are ideal for applications such as rigid-disk-drive testing. Disk-drive circuits require analog signals that are impossible to produce using conventional signal synthesizers or function generators. The addition of a DSS to a test system lets you create these signals and also provides more versatility than is otherwise possible.

Traditional Winchester-type drives have two types of read channels—data and servo. A companion read-data or read-servo board processes each channel. The servo system positions the read head exactly over the desired track. The read-data channel includes a mix of analog and digital circuitry (Fig 1). Because the read-data signals are not trivial in nature, a digital synthesizer is a perfect candidate as a source of such signals. The servo-channel signals are also quite complex. Typically, the test engineer has to develop signals with varying

data patterns, dropouts, jitter, and bit shift. You can use these signals for board-calibration adjustment as well.

The basic read-head signal results from changing media flux. If the signal is derived from a conventional ferrite head, the voltage-vs-time response to a flux change is a Lorentzian or modified Lorentzian pulse, which is best approximated by the sin³ waveform of Fig 2. (A DSS generated all the waveforms of Fig 2 through Fig 7.) The sin³ waveform needs a third harmonic for sufficient fidelity. For thin-film heads, the sin³ may be an insufficient approximation and other pulse models may be needed. Alternatively, a digital synthesizer




Fig 2—In this waveform of two isolated read-head transitions, the signal is modeled with a sin³ pulse doublet.




Fig 1—This typical read channel of a Winchester disk drive shows the functional blocks required for processing the complex signals from the read head.

EDN September 1, 1988

The DSS can easily generate precision reference signals with added AM, PM, FM, and phase-shift characteristics.




Fig 3—This filter-test waveform plots 50 tones of equal amplitude spanning dc to 50 MHz. To generate a composite signal with a small-amplitude peaking factor, each tone is phase compensated.

with 512k points of waveform memory can generate a 4-msec-long waveform that is completely user defined (the sampling-clock rate is 125 MHz). Using the memory-sequencer function within the digital synthesizer, you can generate a 16.66-msec signal that typically corresponds to one revolution of the rotating media. Also, with a 50-MHz output bandwidth, the digital synthesizer can generate a 2f signal (the highest data rate) of approximately 16 MHz. The third harmonic for a sin³ signal would be 48 MHz, very near the band edge of 50 MHz.

Testing the read channel filter

Next, consider a few examples of read-channel waveforms. (All the following read-channel waveforms were generated with the HP Waveform Generation Language (WGL).) For long waveforms, the duration of which exceeds 4 msec, the memory sequencer was used. Under these circumstances, generating waveforms that last hundreds of milliseconds is relatively easy.

Referring back to Fig 1, the channel filter usually consists of a lowpass filter with a phase equalizer. You can test the filter characteristics using a synthesizer, a digitizing scope, and a software-driven Fourier transform algorithm. In this case, the synthesizer generates a special signal that passes through the filter. The generated signal has about 50 equal-amplitude tones, which are uniformly spaced across the desired measurement bandwidth. This signal has special merit because of its unique phase characteristics. It is a broadband signal with the phase of each frequency component selected so as to minimize the peak-to-peak range of the composite signal (see Fig 3). The DSS is the ideal instrument to generate such a signal.




Fig 4—Following the rules for RLL (2,7) coding, this waveform shows the typical coded data from the read head. Each transition is treated as a logic 1; no transition is treated as a 0. After any transition, at least two logic 0s follow—to a maximum of seven.

Next, the scope captures the filter output and converts the result into a frequency-domain representation using a Fourier transform (that is, time-to-frequency) software algorithm. The frequency-domain information contains the filter amplitude and phase characteristics. The input to the filter under test is a signal with known-amplitude and -phase characteristics vs frequency. Any deviation from this signal at the filter output defines the transfer function. This method achieves the same result as a network analyzer would produce.

Data patterns vary

Although a discussion of coding is beyond the scope of this article, it is important to note that run length limited (RLL) codes are the rule in today's disk drives. The use of RLL codes has enabled disk-drive designers to pack data very efficiently onto the platter surface. As an example, Fig 4 shows an RLL (2,7) code sequence. Here, the spacing between magnetic transitions is a minimum of 2 and a maximum of 7 code-cell positions—hence the RLL 2,7 identifier. All transitions occur within a code cell, but not all code cells contain transitions. Code cells mark the locations where transitions may occur, but not necessarily where they do occur. Part of the beauty of RLL coding is that transitions cannot be too close or too far apart. Transition density is intelligently traded for transition-position information.

The DSS easily defined and generated the data stream of Fig 4. You can modify data patterns at will for testing the RLL decoder and for worst-case testing of frequency tolerance levels of the phase-locked loop. The loop oscillator output is the recovered clock source. The




Fig 5—This AGC-test waveform has a 5:1 amplitude reduction and a 2.5:1 frequency reduction. The amplitude step serves to test the AGC attack time.

loop must stay locked to the desired frequency without drift, even though the input data pattern varies wildly. Initially the loop is locked to a sync sequence. A thorough test of the channel filter and the phase-locked loop would require a sync frame, which consists of a series of pulses onto which the loop locks. It is usually located in the preamble to the data block. For margin testing, you can design the sync frame with aberrations on the individual pulses.

Besides testing filter characteristics, you also need to test **Fig 1**'s AGC block. Using the code sequence of **Fig 5**, you can test three important AGC parameters: amplitude dynamic range, attack time, and amenity to frequency deviations. As shown, the amplitude changes by a factor of 5:1 during an abrupt step. You can use one of the DSS markers to indicate the amplitude change and to trigger a scope to measure the AGC response.

Checking bit-shift susceptibility

Another area of interest is the window margin, or phase margin. The window in question is the width of the code-cell detection window in which a head transition is detectable with a high degree of certainty. Ideally, the transition will occur in the center of the window. The phase-locked-loop clock is used to identify the center of the detection span. All physical systems, however, have bit shift. This shift locates the detected bit off the ideal center. If too much shift occurs, the system will generate a read error.

Although a complete window-margin test needs the head disk assembly, a DSS can assist in testing the read channel for bit-shift susceptibility. Fig 6a shows 10 transitions isolated from a long bit stream that the DSS generated. Pulses A and B are shifted by 3.5 nsec compared to the other peaks. This small shift is difficult




Fig 6—The pulse stream shown in a has pulses A and B shifted in time by 3.5 nsec compared to all other pulses. The small shift is difficult to see. The signal in \mathbf{b} results from the shifted-minusunshifted operation. The result, E(t), has a peak amplitude of 128 mV, as predicted for a 3.5-nsec shift. Also, for all pulses other than A and B, E(t) is zero. E(t) provides proof that pulses A and B are indeed shifted.

to detect visually. Even smaller bit shifts make the shifted bit stream that much more difficult to observe.

One method for proving that the selected pulse or pulses have been shifted by the desired amount compares an unshifted sequence with a shifted one. The comparison takes the form of a subtraction: E(t)=unshifted sequence—shifted sequence. The difference error signal, E(t), is a direct function of the shifted sequence.

If you model the transition pulse stream as a \sin^3 shape and the shift is accomplished by phase shifting only the desired pulse by an amount α , then

$$E(t) = (\sin\Omega t)^3 - (\sin\Omega t + \alpha)^3. \tag{1}$$

where ω =pulse rate in rads/sec, α = α_0 phase shift in rads during the shifted pulse, and α =0 during the unshifted portions.

You can expand E(t) by using trigonometric identi-

Although a complete window-margin test needs the drive's head-disk assembly, a DSS can assist in testing the read channel for bit-shift susceptibility.

ties. Assuming that α is $\leq 18^{\circ}$, which is 10% of a pulse width, E(t) reduces to

$$E(t) = 4/3\alpha \left(-\cos\Omega t + \cos3\Omega t\right). \tag{2}$$

For larger pulse time shifts, you can calculate E(t) directly from $Eq\ 1$. It is obvious from $Eq\ 2$, however, that E(t) is a direct function of α . The maximum amplitude of E(t) is a direct measurement of the time shift between the unshifted and shifted pulses in the sequence. By differentiating $Eq\ 2$ and solving for its peak amplitude, you get a value that can be conveniently measured on a scope. Solving for the positive peak voltage yields $E(t)_{max}=1.16\alpha$.

To measure E(t) in a real system, though, you must first generate the unshifted sequence, and then capture it on a digitizing scope. The waveform is stored in waveform memory 1. Next, the shifted version is generated and stored in waveform memory 2. If the scope has sufficient vertical resolution, say eight bits, and you use digital averaging, then E(t)=waveform memory 1-waveform memory 2, as viewed on the scope.

Fig 6b displays E(t) as computed by the above method, with a 3.5-nsec time shift on pulses A and B (see Fig 6a). The α (time shift) for that pulse equals 0.11 rads, and $E(t)_{max}=127$ mV. Measuring E(t) in Fig 6b yields 128 mV. So indeed, pulses A and B have shifted by the desired amount. Note that E(t) equals 0 for all other pulses; indicating no time shift other than where it is required.

Using this method, you can successfully measure differential time shifts down to 100 psec. Also, by choosing a proper alpha (α), it's possible to generate pulse time shifts with 10 psec of resolution, despite the fact that DSS systems have discrete sampling rates. For example, although the HP 8770A has a sampling clock of 8 nsec, you can achieve very small time shifts (less than the sample clock) using this method. To achieve this extremely fine time-shift resolution, a DSS with a spectrally clean passband (low spurious content) and good amplitude resolution (12 bits) is required. Moreover, nonlinear phase response in the DSS may severely distort sin³ pulses. In fact, the sin³ pulse sequence is an excellent waveform for observing the effects of passband phase nonlinearity. Any nonsymmetry around a pulse peak is a result of phase nonlinearity. Besides testing the read data board for bit-shift susceptibility, you can use time-shifted sequences to test the phase-locked loop's transient response to either an impulse or a step in phase shift.




Fig 7—This servo pattern shows two sync pulses followed by four additional pulses. Pulses A, B, C, and D serve to achieve head-track alignment.

As mentioned earlier, the disk-drive servo system's function is to achieve good track-head alignment. Servo signals in Winchester disk drives are quite complex. The waveform of Fig 7 shows a portion of a servo read signal. The two left-most pulses are sync pulses. The heights of the other four pulses—labeled A, B, C, and D—are a function of the track-head alignment.

One particularly useful signal is the servo-head output during a track-seek operation. The head moves perpendicular to all tracks as it travels toward a final destination track. As the servo head seeks, the A, B, C, and D pulses move up and down in amplitude, somewhat like the pistons in a 4-cylinder car. In fact, the A, B, C, D pulse-set repeats its 4-banger motion after every four tracks.

By selecting a DSS that has a full-feature memory sequencer, you can generate a servo signal that exhibits complex crossing characteristics, such as the long-duration (25 msec) signals necessary for track-to-track seek operations. This type of signal is useful in testing the servo system's ability to find the desired destination track. At no time is the head disk assembly needed. Signal characteristics may include acceleration, deceleration, constant velocity, and A-B-C-D pulse profiles. In addition, you can determine open servo-loop transfer-function characteristics using a DSS as a complex signal source.

Part of the beauty of a DSS-based test system comes from its inherent repeatability. Over time and from tester to tester, system specifications change minimally. The tester-to-tester specification match is very good. Test engineers who must specify systems that are built offshore find this feature indispensable. Of course, to guarantee the tester's integrity, you must choose a DSS with a completely specified output passband—that



Everyone's talking about it now, but we've been shipping it since 1982. And we've continued to set the real-time standard every year since. RTUTM, our real-time enhanced UNIX

operating system, provides guaranteed response *plus* the flexibility and compatibility of AT&T System V and 4.2 BSD.

Scientists, engineers, systems integrators, and OEMs can choose from a family of MC68030/020-based multiprocessor computers, from 3 to 25 MIPS, with VMEbusTM and Multibus.TM They're designed for high-performance applications in data acquisition, digital signal processing, imaging, C³I, and real-time simulation.

What's behind the trend to real-time UNIX? Want to learn how your real-time application can benefit from UNIX power and compatibility?



UNIX is a trademark of AT&T Bell Labs. MASSCOMP and RTU are trademarks of Massacbusetts Computer Corporation. VMEBus is a trademark of Motorola Corporation. Multibus is a trademark of Intel Corporation.

CIRCLE NO 82

Send in the coupon below for your free copy of *Understanding Real-Time UNIX*, by Prof. John Henize.

Get *in tune* with the best real-time systems available.

1-800-451-1824 (MA 508-692-6200)



Send this coupon to MASSCOMP, Dept. I-DNOS, One Technology Way, Westford, MA 01886

- ☐ YES, please send a complimentary copy of Understanding Real-Time UNIX.
- ☐ Send me information on MASSCOMP real-time computer systems.

TITLE		
COMPANY		
ADDRESS		
CITY	STATE	ZIP
PHONE		

DESKTOP GATE ARRAY DESIGN

Like desktop publishing is revolutionizing publishing, we are revolutionizing gate array design. Our GATEAID PLUS/PC gate array design software:

- o runs on your PC/XT/AT/386
- matches the power of workstation tools, and
- costs \$945.

And unlike the logic supertankers of other suppliers, our gate arrays are efficient building blocks tailored for various functions such as:

- PLD replacement
- RAM and logic integration
- Bus logic integration, etc.

To order GATEAID PLUS/PC, or for more information on it or on our building block gate arrays, mail coupon below. Or call 1-800-338-GATE.

Mail to: Matra Design Semiconductor 2895 Northwestern Pkwy. Santa Clara, CA 95051

- ☐ I'd like to order a copy of GATEAID PLUS/PC on a 30-day trial basis. Bill me. (Include business card or letterhead).
- Send me information.

Name

Signature (Required)

Phone

Company

Address

EDN090188



MATKA
DESIGN SEMICONDUCTOR

1-800-338-GATE

is, both the amplitude and phase vs frequency should be specified, as well as any harmonics and spurious signals.

Semicustom tests, such as those described here, will likely find wider acceptance as engineers become familiar with the advantages of digital signal synthesizers. In addition to disk-drive-board testing, for example, a test system using digital signal synthesis lends itself to many other applications, including streaming-tape drives, video processors, adaptive filters, radar processors, and high-speed modems.

Author's biography

Al Kovalick is a research and development engineer with the Stanford Park Div of Hewlett Packard. He has been with HP for the past 14 years and currently works as a systems architect and hardware designer. Al has a BSEE from California State University at San Jose and an MSEE from the University of California at Berkeley. He studies and teaches bible topics, and he enjoys sailing in San Francisco Bay.



Article Interest Quotient (Circle One) High 491 Medium 492 Low 493

Graphic proof of high-tech leadership.



The Casio fx-7000G \$89.95. It's the world's first programmable scientific calculator with a graphic display. It can give form to your figures, instantly drawing graphs that depict your formulas and calculations.

With a screen measuring 16 characters by 8 lines, the fx-7000G can display enough information for some of your biggest ideas. And you can store graphs and formulas, then bring them back for an instant replay.

SHARP

With its 422 step memory and 193 functions—including linear regression, standard deviation and computer math—the fx-7000G lets you perform computer functions, without acquiring computer knowledge or incurring computer costs.

For additional capabilities, there's the fx-7500G (\$109.95). It has a larger memory capacity, with 195 functions, 4,006 memory steps, instant graph enlargement or reduction feature, plus a convenient horizontal folding format.


If you need even more power, our fx-8000G (\$119.95) techs you even higher, with 1,446 memory steps and 225 functions. And when hooked up with our optional FA-80 interface, it works with most parallel dot matrix printers or plotters including Casio's own models.

If you have any doubts as to who's the leader in high-tech calculators, just pick up an fx-7000G, fx-7500G or fx-8000G and draw your own conclusions.

CASIO Where miracles never cease

Casio, Inc. Consumer Products Division: 570 Mt. Pleasant Avenue, Dover, NJ 07801 Casio Canada Ltd., 2100 Ellesmere Road, Suite 240, Scarborough, Ontario M1H3B7

CIRCLE NO 102



HARTING/Austria, Vienna, Tel. 0222-68 68 18-0 · HARTING/Belgium, Relegem, Tel. 02-465.42.40 · HARTING/France, Fontenay-sous-Bois Cedex, Tel. (1) 487 706 26 HARTING/Great Britain, Biggin Hill, Tel. (09 59) 71411 · HARTING/Italy, Pioltello (Milan), Tel. 02-92100 847 · HARTING/Japan, Yokohama, Tel. 045-931.5718

NATURE MAY MAKE MISTAKES. BUT NOT US.

Every day, millions of connectors leave our unique, state-of-the-art production facilities. And each one complies with the very highest international standards and norms found in industry. Not only that, our reject rate is virtually nil despite the fact - or rather because of the fact - that production is completely automated. After all, people make mistakes, but electronic technology doesn't. Electronic controls and monitoring equipment don't miss a thing. The result is virtual perfection.

We at HARTING have invested decades of in-depth research and hands-on development to achieve this degree of perfection. That's why we produce each individual component of the final product ourselves and use only the best materials available. And that's why we carry out every single processing operation our-

selves. We make sure that each little detail is just right - because our costumers need to make sure

> With HARTING connector systems, you know perfection is designed in. After all, there's no telling what kind of havoc a single black sheep might

as soon as you start developing your next product.

They're just a phone call away.

World headquarters: HARTING ELEKTRONIK GmbH P. O. Box 1140 · D-4992 Espelkamp West Germany

☎ (05772) 47-1 · Tx 972310-11 he d

CONNECT UP WITH QUALITY -WITH HARTING.





HARTING/Netherlands, AM Etten-Leur, Tel. 01-608-35400 · HARTING/Norway, Oslo, Tel. 02-647590 · HARTING/Sweden, Spanga, Tel. (08) 7617980 HARTING/Switzerland, Schwerzenbach, Tel. 01-8255151 HARTING/USA, Chicago, Tel. (312) 519-7700

CIRCLE NO 83

Launch your design with the FIFOs that came in first.

You can't think FIFOs without thinking of the Winning Team first—SGS-THOMSON Microelectronics. We launched the standards our competitors continue to follow.

	MK4505	MK45264/5	MK4503	MK4501	
Organization	1K x 5	64 x 5 x 2	2K x 9	512 x 9	
Cycle Time	40 MHz	13.3 MHz	12.5 MHz	12.5 MHz	
Access Time Range	15-25ns	55-70ns	65-200ns	65-200ns	
Depth Expandable	X	-	x	x	
Width Expandable	X	x	х	x	
Packaging	300 mil 24/20 Pin DIP	300 mil 24 Pin DIP	600 mil 28 Pin DIP	600 mil 28 Pin DIP 32 PLCC	
Status Flag	E, F	E, F	E	Е	
E, Empty. F, Full. HF Half Full. AF, Almost Full.	HF, AF	AF	F	F	
AE, Almost Empty.	AE	AE	HF		
Availability	***		***	**	

Sampling now
 Off the shelf—4 wks. depending on package and speed
 Off the shelf—8 wks. depending on package and speed

The industry standard 512 x 9 MK4501 and 2K x 9 MK4503 use a CMOS RAM-based BiPORT[™] architecture: two ports operate at fully independent data rates and provide simultaneous read/write capability.

With blazing 15ns access speed and 40MHz serial I/O rates, the 1K x 5 MK4505 puts FIFOs on the fast track. The MK4505 is also the first FIFO to support two independent, asynchronous free-running clock inputs with a full complement of status flags, eliminating the need for extra registers and buffers. Plus, you can get all that speed and performance in an ultrathin space-saving 300 mil DIP. The SGS-THOMSON Master and Slave concept—another first—allows simpler, more economical width and depth expansion.

Want bidirectional FIFO performance? Try the MK45264/5, a unique combination of two FIFOs on a single chip, for fully asynchronous operation...again an SGS-THOMSON

With surface mount packaging, commercial and military grade devices, it's easy to see why SGS-THOMSON is the industry leader in FIFOs.

We have the production capability and the advanced technology to meet your delivery, pricing, performance and quality demands. And SGS-THOMSON will continue its leadership with FIFOs of higher density, faster speed and innovative architectures.



Join the Winning Team.

FREE MEMORY DATA BOOK

If second best isn't good enough for you, send for the facts that prove we're the FIFO leader. You'll find them in our free Memory data book. For your copy call 602/867-6259 or write SGS-THOMSON Microelectronics, 1000 E. Bell Road, Phoenix, AZ 85022.



CIRCLE NO 84





DN3000 with 15" 1024 x 800 monochrome display



\$5990

DN3000 with 19" 1280 x 1024 monochrome display



\$8900

DN3000 with 15" 1024 x 800 color display

If you think we don't have UNIX workstation for und



\$7990

DN3500 MC68030-based 4-MIPS workstation with 15" 1024 x 800 monochrome display



\$8990

DN3500 MC68030-based 4-MIPS workstation with 19" 1280 x 1024 monochrome display



\$9990

DN3500 MC68030-based 4-MIPS workstation with 15" 1024 x 800 color display

At Apollo, we believe that the real test of a computer company is not only how often it introduces new technology, but also how quickly it makes that technology available at a truly affordable price.

As testimony to this, we offer not simply one workstation under \$10,000, but two entire families of workstations, one of which starts at under \$5,000.

Consider the Series 3000.™ A Personal Workstation™ powered like a Porsche® but priced like a PC. \$4,990, to be exact. And the new Series 3500.™ An MC68030 machine that brings high performance to a new low. Making it possible for the first time to obtain a

a single high-performance er \$10,000, you're right.

4-MIPS monochrome system for less than \$8,000, and a 4-MIPS color system for less than \$10,000.

Prices that even include 4MB of memory, a floating-point coprocessor, an IBM PC AT* compatible bus, and a choice of Ethernet* or Apollo Token Ring networks.

In addition, like all Apollo workstations, these provide support for industry standards such as UNIX® (System V.3 and Berkeley 4.3), PHIGS, X Window System™ and a host of others, as well as network computing and PC compatibility.

The Apollo Series 3000 and Series 3500. Technology as high as the price is low.

apollo

For more information, call 1-800-323-1846, and in Massachusetts (1-800-847-1011) or write Apollo, 330 Billerica Road, Chelmsford, MA 01824.

Apollo is a registered trademark and Series 3000, Series 3500, and Personal Workstation are trademarks of Apollo Computer Inc. UNIX is a registered trademark of AT&T. Ethernet is a registered trademark of Xerox Corporation. X Window System is a trademark of MT. AT is a registered trademark of International Business Machines Corporation. Porsche is a registered trademark of Porsche North America, Inc.

EDN September 1, 1988 CIRCLE NO 86



DESIGN IDEAS

EDITED BY CHARLES H SMALL

Dual potentiometer controls up/down counter

Kenneth W Robbins
ANRO Engineering Inc, Lexington, MA

The circuit in **Fig 1** uses what would normally be a miswired potentiometer to control both the counting rate and direction of a counter. Note the wiring scheme of the section of the dual linear-taper potentiometer connected to the 7555 timer. This section controls the 7555's pulse rate. The values shown in **Fig 1** ensure that the timer will not output pulses when the potentiometer is at its midpoint; turning the potentiometer in either direction from its midpoint raises the voltage at the 7555's pin 7 and allows the IC to operate. Thus the potentiometer functions as an analog fine-tuning control for circuits that need a digital input.

At the potentiometer's midpoint, its other section does not upset the biasing of the inverter IC $_{2C}$, which is in its linear region. As long as this inverter is in its linear region, it, along with IC $_{2D}$ and the 1.0- μ F capacitor, forms a low-repetition-rate oscillator. While this

portion of the circuit oscillates, it alternately blinks the up and down LEDs (which indicate to the operator that the counter is not counting).

Turning the potentiometer in either direction from its midpoint changes the biasing on the inverter, taking it out of its linear region. Depending on the direction of turning, either the up or down LED will light. Further rotation causes the timer to begin emitting pulses, which flash the clock-pulse LED. The RC values shown and the dead band between lighting the up or down LEDs and lighting the clock LED allow an operator to produce just a single up or down count.

Because of potentiometer tolerances, you may need to connect a high-value resistor between the inverter potentiometer's wiper and ground or 5V, as appropriate, to achieve symmetrical control action; this unit required the $470~\mathrm{k}\Omega$ shown.

To Vote For This Design, Circle No 750




Fig 1—The dual-section potentiameter controls both the direction and count rate of the 4029 counter. When the potentiameter is at its midpoint, the 7555 timer is biased off, and the inverters driving the up and down LEDs function as a low-repetetion-rate oscillator to alternately blink the LEDs, which signals that the counter is not counting.

EDN September 1, 1988

Because you're thinking fast...

you need responsive suppliers as well as fast parts Comlinear is tuned in. With high quality, high-speed products. Assistance from R&D-level applications engineers to help develop your ideas quicker. Sales and distribution that get you what you need fast. Quality

What could you do with a 12ns settling op amp that has

instantaneous output clamping and Ins overload recovery?

With clamping performance like this-plus an 80MHz bandwidth and 12ns settling time to 0.05%the new CLC501 Clamping Op Amp is the residue amplifier you've been searching for in subranging A/D applications.

Its Ins overload recovery makes it the op amp you've wanted for resolving small signals ordinarily lost following large, saturating signals in radar, optical communications, and line testing

User-settable output clamping means it's the only high-speed op applications. amp that gives you a simple yet flexible solution for protecting


And its 50MHz clamping input downstream circuits. bandwidth opens up new design possibilities. Such as modulating a square wave to produce pulse amplitude modulation. When there's a new concept in op amps, there's no telling where the applications end.

Call today for details on the op amp designed to tickle your imagination.

CIRCLE NO 87



Fort Collins, Colorado 80525 4800 Wheaton Drive (303) 226-0500



Circuit lowers photodiode-amplifier noise

Rod Burt and R Mark Stitt Burr Brown, Tucson, AZ

Adding two passive components to a standard photodiode amplifier reduces noise (**Fig 1a** and **b**). Without the modification, the shunt capacitance of the photodiode reacting with the relatively large feedback resistor of the transimpedance (current-to-voltage) amplifier creates excessive noise gain.

The improved circuit (**Fig 1b**) adds a second pole, formed by R₃ and C₂. The modifications reduce noise by a factor of 3. Because the pole is within the feedback loop, the amplifier maintains its low output impedance.




Fig 1—The standard photodiode transimpedance amplifier circuit in a exhibits excessive noise because of the shunt capacitance of the photodiode. The improved circuit in b adds a second pole in the feedback loop to roll off the circuit's noise gain above its signal band limit

If you place the pole outside the feedback loop, you have to add an additional buffer, which would increase noise and dc error.

The signal bandwidth of both circuits is 16 kHz. In the standard circuit (**Fig 1a**), the 1-pF stray capacitance in the feedback loop forms a single 16-kHz pole. The improved circuit (**Fig 1b**) has the same bandwidth as the first circuit, but exhibits a 2-pole response.

If you set $C_1R_2=2C_2R_3$, the transimpedance transfer function is a 2-pole Butterworth (maximally flat in passband) type. At dc, both circuits' gain is 140 dB or $10V/\mu A$. The frequency response of both circuits is 3 dB down at 16 kHz. The conventional circuit rolls off at 20 dB/decade; the improved circuit rolls off at 40 dB/decade.

Fig 2 shows the noise gain of both circuits. The noise zero occurs at

$$f_Z = \frac{(R_1 + R_2)}{2\pi R_1 R_2 (C_0 + C_1)}$$

about 673 Hz for this example. Both curves do, indeed, show peaking at about 673 Hz because of the zero formed by the photodiode shunt capacitance. The added pole of the improved photodiode amplifier rolls off the




Fig 2—The improved circuit in 1b has one-third as much noise as the circuit in Fig 1a.

DESIGN IDEAS

noise above 20 kHz—well above the circuit's signal bandwidth of 16 kHz.

Another advantage of the improved circuit is its ability to drive a capacitive load. Because the output of the circuit connects to a large-value capacitor, driving a little extra capacitance presents no stability problems. Although the output has low dc impedance, the load

affects the ac transfer function. But with reasonable loads, the effect is minimal. With the values shown in Fig 1, a load of $10 \text{ k}\Omega$ in parallel with 100 pF has little effect on the circuit's response.

To Vote For This Design, Circle No 749

XOR gates add up/down function

Dil Sukh Jain

National Remote Sensing Agency, Hyderabad, India

You can transform an ordinary binary counter, such as a 7493, into an up/down counter with mode control by adding XOR gates (7486) to the counter's outputs (Fig 1). The circuit in Fig 1 counts up when the DN/UP line is low and down when the DN/UP line is high.

To use the 7493 counter to count out its maximum count length (0-15), connect the Q_A output to the $B_{\rm IN}$ input and apply clock pulses to the $A_{\rm IN}$ input. The RESET input, when high, inhibits the count inputs and simultaneously returns the ouputs A_0 through D_0 to low in the up-count mode or 15 in the down-count mode. For normal counting, the RESET input must be low.

You can easily cascade this counter by feeding the Q_D line to the clock input of a succeeding counter.

To Vote For This Design, Circle No 748




Fig 1—Adding XOR gates to a counter's outputs transforms an ordinary binary counter into an up/down counter with mode control. This circuit counts up when the DN/UP line is low and down when the DN/UP line is high.

Watchdog timer catches I/O-chip crashes

Barry Kaufman Multipath Inc, Pine Brook, NJ

Common watchdog-timer circuits will restart a μP if its software crashes, but the timers will not detect a problem with a programmable chip. I/O lines can inadvertantly serve as antennas to outside disturbances such as power surges, lightning hits, or even cosmic

rays. These disturbances can disrupt the control registers of programmable I/O ICs such as UARTS, disk controllers, and RS-232C or RS-488 interfaces without crashing the main program.

You can use two methods to extend your watchdog timer's coverage to include programmable ICs. You could strobe the watchdog timer via an unused I/O line rather than directly from the μP . That way, if the I/O





dc to 2000 MHz amplifier series

SPECIFICATIONS


MODEL	FREQ.	G	AIN. d	В		• MAX.	NF	PRICE	\$
	MHz	100 MHz	1000 MHz	2000 MHz	Min. (note)	PWR. dBm	dB	Ea.	Qty.
MAR-1	DC-1000	18.5	15.5	_	13.0	0	5.0	0.99	(100)
MAR-2	DC-2000	13	12.5	11	8.5	+3	6.5	1.50	(25)
MAR-3	DC-2000	13	12.5	10.5	8.0	+8 🗆	6.0	1.70	(25)
MAR-4	DC-1000	8.2	8.0	_	7.0	+11	7.0	1.90	(25)
MAR-6	DC-2000	20	16	11	9	0	2.8	1.29	(25)
MAR-7	DC-2000	13.5	12.5	10.5	8.5	+3	5.0	1.90	(25)
MAR-8	DC-1000	33	23	_	19	+10	3.5	2.20	(25)

NOTE: Minimum gain at highest frequency point and over full temperature range.

1dB Gain Compression
 +4dBm1 to 2 GHz

designers amplifier kit, DAK-2

5 of each model, total 35 amplifiers



only \$59.95

Unbelievable, until now...tiny monolithic wideband amplifiers for as low as 99 cents. These rugged 0.085 in.diam.,plastic-packaged units are 50ohm* input/output impedance, unconditionally stable regardless of load*, and easily cascadable. Models in the MAR-series offer up to 33 dB gain, 0 to +11dBm output, noise figure as low as 2.8dB, and up to DC-2000MHz bandwidth.

*MAR-8, Input/Output Impedance is not 50ohms, see data sheet. Stable for source/load impedance VSWR less than 3:1

Also, for your design convenience, Mini-Circuits offers chip coupling capacitors at 12 cents each.†

Size (mils)	Tolerance	Temperature Characteristic	Value
80 × 50 80 × 50 120 × 60	5% 10% 10%	NPO X7R X7R	10, 22, 47, 68, 100, 470, 680, 100 pf 2200, 4700, 6800, 10,000 pf .022, .047, .068, .1 <i>u</i> f
1	Order 50 per Va		.022, .047000, .1µ1

finding new ways ... setting higher standards



P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 Domestic and International Telexes: 6852844 or 620156

C113-Rev. D

DESIGN IDEAS

chip malfunctions, the watchdog timer will time out and restart the μP . Naturally, you must include a subroutine to reinitialize the I/O chip in the watchdog-timer routine.

Or you can take advantage of most I/O ICs' controlregister readback function. The Z80 routine in **Listing** 1 periodically reads the control registers, compares their present contents to their initial contents, and branches to the initialization code if there is a difference. A conventient location for this type of routine is right after the code that generates the watchdog timer's strobe.

To Vote For This Design, Circle No 746

LISTING 1 — Z80 ROUTINE

EXAMPLE OF RE-INITIALIZING I/O IC CONTROL REGISTERS IF AN UNKNOWN CHANGE IS DETECTED. FOR THIS EXAMPLE, ONE INTEL 82C55 IS PROGRAMMED SO ALL 24 I/O LINES ARE INPUTS AND A SECOND 82C55 IS PROGRAMMED SO ALL I/O LINES ARE OUTPUTS.

```
; PART OF INITIALIZATION ROUTINE THAT IS RUN ONCE WHEN
  THE PROGRAM IS STARTED, AFTER A HARDWARE RESET.
INIT:
                          ; Start of initialization code.
ALLIN:
          EQU
               9BH
                          ; Mode 0, all pins are input.
ALLOT:
          EQU
               80H
                           Mode 0, all pins are output.
INPOR:
                          ; Port address for input I/O
          EQU
               03H
                          ; IC control register.
OTPOR:
          EQU
               OBH
                          ; Port address for output I/O
                          ; IC control register.
WDPOR:
          EQU
              10H
                         ; Port address to strobe
                          ; watchdog timer IC.
          LD A, ALLIN
                         ; Load accum. with control byte.
          OUT (INPOR), A ; Send it to input IC.
          LD A, ALLOT
                         ; Load accum. with control byte.
          OUT (OTPOR), A ; Send it to output IC.
 PART OF THE MAIN PROGRAM LOOP.
                                  THIS CODE MUST BE
; RUN OFTEN ENOUGH TO KEEP THE WATCHDOG TIMER FROM
  RESETTING THE CPU.
        OUT (WDPOR), A
                        ; Strobe the watchdog timer.
        IN A, (INPOR)
                         ; Read input IC ctrl. register.
        CP ALLIN
                         ; Compare with what it should be.
        JP NZ, INIT
                         ; NZ = not same so reinitialize.
        IN A, (OTPOR)
                         ; Read output IC ctrl. register.
        CP ALLOT
                         ; Compare with what it should be.
        JP NZ, INIT
                         ; NZ = not same so reinitialize.
                          ; Continue with main program loop.
```

SUPER SEASING

Available Now 256K 25ns/64K 15ns

Micron just broke the SRAM speed barrier with our family of leading edge, super high speed CMOS SRAMs.

We've applied the same state-ofthe-art design and process technology used for our high quality DRAMs in development of our fast static RAMs — with some amazing results. At an incredible 25ns for 256K and 15ns for 64K,

At an incredible 25ns for 256K and 15ns for 64K, our SRAMs are breaking speed records. And we're not just sampling product, we're shipping production volumes.

Choose from a wide variety of components in DIP, SOJ and LCC packages, with densities from 16K to 256K and organizations of x1, x4 and x8.

And like all Micron memory products, our SRAMs are backed by the type of customer service and technical support that keeps you on

support that keeps you on the leading edge.

For additional information on how you can break the SRAM speed barrier, call 208-386-3900.

Micron, it's a name worth remembering.

Part #	Organization	Speed*	Packages
MT5C2561	256K X 1	25ns	PDIP, CDIP, SOJ, LCC
MT5C2564	64K X 4	25ns	PDIP, CDIP, SOJ, LCC
MT5C2565	64K X 4 $\overline{\text{OE}}$	25ns	PDIP, CDIP, SOJ, LCC
MT5C2568	32K X 8	25ns	PDIP, CDIP, SOJ, LCC
MT5C6401	64K X 1	15ns	PDIP, CDIP, SOJ
MT5C6404	16K X 4	15ns	PDIP, CDIP, SOJ
MT5C6405	16K X 4 OE	15ns	PDIP, CDIP, SOJ
MT5C6406/7	16K X 4 S. I/O	15ns	PDIP, CDIP, SOJ
MT5C6408	8K X 8	15ns	PDIP, CDIP, SOJ, LCC
MT5C1601	16K X 1	15ns	PDIP, CDIP, SOJ
MT5C1604	4K X 4	15ns	PDIP, CDIP, SOJ
MT5C1605	4K X 4 $\overline{\text{OE}}$	15ns	PDIP, CDIP, SOJ
MT5C1606/7	4K X 4 S. I/O	15ns	PDIP, CDIP, SOJ
MT5C1608	2K X 8	15ns	PDIP, CDIP, SOJ

*Slower speeds also available.

MICRON

TECHNOLOGY, INC.

MICRON TECHNOLOGY, INC., 2805 E. COLUMBIA ROAD, BOISE, IDAHO 83706 208-386-3900

Design Entry Blank

\$100 Cash Award for all entries selected by editors. An additional \$100 Cash Award for the winning design of each issue, determined by vote of readers. Additional \$1500 Cash Award for annual Grand Prize Design, selected among biweekly winners by vote of editors.

To: Design Ideas Editor, EDN Magazine Cahners Publishing Co 275 Washington St, Newton, MA 02158

I hereby submit my Design Ideas entry.

Name _____

Title _____ Phone ____

Company _____

Division (if any)

Street

City _____

_____ State ____ Zip ____

Design Title _____

Home Address

Social Security Number __

(Must accompany all Design Ideas submitted by US authors)

Entry blank must accompany all entries. Design entered must be submitted exclusively to EDN, must not be patented, and must have no patent pending. Design must be original with author(s), must not have been previously published (limited-distribution house organs excepted), and must have been constructed and tested.

Exclusive publishing rights remain with Cahners Publishing Co unless entry is returned to author or editor gives written permission for publication elsewhere.

In submitting my entry, I agree to abide by the rules of the Design Ideas Program.

Signed _

Date _

ISSUE WINNER

The winning Design Idea for the June 9, 1988, issue is entitled "Simple calculator acts as low-speed counter," submitted by J N Lygouras of the University of Thrace (Xanthi, Greece).

Your vote determines this issue's winner. All designs published win \$100 cash. All issue winners receive an additional \$100 and become eligible for the annual \$1500 Grand Prize. Vote now, by circling the appropriate number on the reader inquiry card.

Spare flip-flop forms inverter

Gary San Giacomo Electro-Biology Inc, Parsippany, NJ

The circuit in Fig 1 uses one-half of a dual D flip-flop as an inverter. When the input goes low, the flip-flop resets, and its \overline{Q} output goes high. When the input goes high, the reset line is released and \overline{Q} gets clocked low.




Fig 1—Adding a simple RC delay line to a spare flip-flop transforms it into an inverter with a maximum frequency of 10 MHz.

The RC delay between applying the input signal to the flip-flop's reset input and its clock input enables clocking the flip-flop on the input's positive edge. A 74HC74 dual D flip-flop, for example, requires a minimum recovery time of 5 nsec after releasing the reset input before strobing its clock input. Therefore, specing RC at ≥7.5 nsec provides adequate margin. The slight slowing of the clock edge presents no problem, because the clock input's maximum allowable rise time is a much longer 500 nsec. To prevent skewing of the output's symmetry, you should limit the maximum input frequency to less than 10 MHz.

To Vote For This Design, Circle No 747



DESIGN NOTES

Number 14 in a series from Linear Technology Corporation

September, 1988

Extending the Applications of 5V Powered RS232 Transceivers

High Speed Operation

Although the EIA RS232 specification is for a relatively slow communications protocol, many applications require RS232 transceivers to operate at higher frequencies. Devices such as the LT1080, LT1081, and the LT1130 series share a common design for the drivers and receivers and are capable of operating over 100 kilobaud.

Although the slew rate is controlled for all of the Linear Technology series of RS232 communications devices, for output levels limited to $\pm 6V$ the transition time is fast enough to allow high baud rates. With a slew rate of approximately 10V per microsecond, it only takes 1.2 microseconds for a 12V excursion. The two photos (Figure 1 and Figure 2) show the output waveform and delay associated with a 75kHz square wave input and a 100kHz square wave. Delay times are in the order of 0.5 microseconds and the total slew

time is approximately 1.2 microseconds. Output load is 3k. Receivers are much faster and can handle these baud rates with no problem. For higher communication rates, a differential signal is recommended.

Power Supply Tricks

The power supply generator on 5V powered devices is a charge pump circuit which generates approximately $\pm\,9V$ from a single 5V supply. Parallel operation of the supply charge pumps for 5V powered transceivers is easily achieved to minimize component count. The positive and negative supply have approximately $1\mu F$ of holding capacitance for energy storage. If several devices with charge pumps are used in the same system, the output supplies may be paralleled into a single pair of common energy storage capacitors.




Figure 1. Operation at 75kHz




Figure 2. Operation at 100kHz

Figure 3 shows two LT1080's with common power supply capacitors for energy storage. Twice the output current is available for external use. This eliminates two capacitors from the system. Individual charge pump capacitors are still needed on each of the devices.

Operation with +5V and +12V Supplies

The charge pump circuitry takes the input 5V and doubles it. The doubled voltage is then inverted to obtain a negative output. The only reason for doubling the input is to ensure adequate positive and negative output voltage to meet RS232 specifications. In PC systems, where +12V is available, the internal voltage doubler does not need to be used. The device may be connected directly to a +5V and a +12V supply. The +12V is then inverted to obtain approximately -11V. This eliminates one charge pump capacitor and one holding capacitor for the 12V output. Figure 4 shows an LT1080 connected to a 12V and 5V power supply. The +12V is connected into one of the charge pump capacitor pins rather than the 12V output pin. Supply current also decreases to about 9mA.




Figure 4. Operation with + 12V and + 5V Supplies




Figure 3. Paralleling Power Outputs

For literature about our complete line of RS232 products, call **800-637-5545**. For help with an application, call (408) 432-1900, Ext. 456.



The Sine of a Good Generator **Purity • Precision • Speed** heterodyne synthesis gives "instantaneous" settling • typically 0,0006% (-105 dB) distortion in the audio range (<0,1 ms) of frequency and amplitude ±0,1192mHz frequency accuracy throughout the 0,2Hz to 200 kHz range memory sweep feature with pre-defined amplitude weighting precision attenuator with ±0,026 dB (±0,3%) accuracy two models: Sine Generator Type 1051 and Sine/Noise across the entire 100 µV to 5V range Generator Type 1049 • very fast response time for all functions via IEEE-488 interface Brüel & Kjær Brüel & Kjaer Instruments, Inc. 185 Forest Street · Marlborough, MA 01752 USA · Telephone 617/481-7000 WORLD HEADQUARTERS: DK-2850 Nærum · Denmark · Telephone: +45 280 05 00 · Telex: 37316 bruka dk Australia (02) 450-2066 · Austria 02235/7550*0 · Belgium 02 · 242-97 45 · Brazil 246 8149 · Canada (514) 695-8225 · Finland (90) 80 17 044 · France (1) 64 57 20 10 Federal Republic of Germany (04106) 4055 · Great Britain (01) 954-2366 · Holland 03 402-39 994 · Hong Kong 5-487486 · Italy (02) 52 44 141 Japan 03-356-1711 · Republic of Korea 02-793-6886 · Norway 02-78 70 96 · Singapore 225 8533 · Spain (91) 268 10 00 · Sweden (08) 711 27 30 · Switzerland (042) 65 11 61 Taiwan (02) 713 9303 · USA (617) 481-7000 · Local representatives and service organisations world-wide

68030 - VME The Real *Single* Board Computer

The TP32V from Tadpole


• The Philosophy •

Designed for optimum system performance from a single full IEE 1014 VME board, the TP32V needs no other cards, piggybacks or mezzanines to deliver the full potential of the 16-33 MHz MC68030. To maximise overall throughput, all the onboard I/O facilities were designed to take advantage of hardware transfer buffers, DMA facilities and advanced DRAM arbitration techniques between competing resources.


The Specification

- MC68030 16-33MHz
- MC68450 4-channel DMA controller
- 4Mb multi-ported nibble-mode DRAM
- AMD Lance IEEE 802.3 Ethernet with DMA
- Z8530 SCC giving two DMA-driven RS232 sync/ asynchronous ports and two further RS232 asynchrous ports
- NCR 53C90 DMA-driven synchronous or asynchronous SCSI interface Floppy disk controller
- Full VME Rev C.1 IEEE 1014 interface
- 64-512Kb EPROM Battery-backed RTC/SRAM
- Full debug monitor Optional MC68881/2 FPU
- TP-IX/68K version of UNIX V.3.1* NFS, RFS, TCP/IP

The Design



The Evidence



Tadpole Technology

the driving force in 32-bit design

Tadpole Technology plc

Titan House, Castle Park, Cambridge, CB3 OAY, UK. Tel: 0223 461000 Fax: 0223 460727

Tadpole Technology Inc

Reservoir Place, 1601 Trapelo Road, Waltham, Massachusetts 02154, U.S.A. Tel: 0101-617-890-8898 Fax: 0101-617-890-7573

2157 O'Toole Avenue, Suite F, San Jose, California 95131, U.S.A. Tel: 0101-408-435-8223 Fax: 0101-408-435-8432

UNIX is a trademark of AT&T Ethernet is a trademark of the Xerox Corporation

*TP-IX V.3.1 is derived from UNIX V.3.1 VRTX is a trademark of Ready Systems


NEW PRODUCTS

COMPUTERS & PERIPHERALS

I/O BOARDS

- Offer data-transfer rates to 750 kHz
- Provide 512k-byte onboard memory


The DT1492 Series consists of nine analog and digital I/O boards for Sun workstations and other VME Bus computers. The boards feature a 512k-byte onboard memory and data-transfer rates to 750 kHz. An enhanced data-arbitration scheme allows you to perform simultaneous A/D, D/A, and digital I/O operations. The boards employ two onboard pacer clocks. You can configure the clocks to accept an external oscillator. Additional features include 12- or 16-bit input resolution;



software-selectable gains of 1, 2, 4, and 8 or 1, 10, 100, and 500 on most models; and two DACs. \$2195 to \$3695.

Data Translation Inc, 100 Locke Dr, Marlboro, MA 01752. Phone (508) 481-3700. TLX 951646.

Circle No 351



MOTION CONTROLLER

- Works as a stand-alone or with host computer
- Features 16 digital and 4 analog I/O lines with LEDs

The CN0170 provides programmable motion control for step-motor systems. This 2-axis controller operates as a stand-alone or with a host. It provides 16 digital and 4 analog I/O lines with LEDs. When connecting the controller to the host, you can use one of the two complete serial ports that are brought out to RS-232A plug connectors. The digital inputs and outputs are TTL compatible. The controller's analog input voltage ranges from 0 to 5V dc or 2 to 3V dc. In addition, the controller features an 8-bit ADC resolution. The controller's velocity ranges to 16,383.75 steps/sec with an accuracy of $\pm 0.01\%$. The CN170 requires a 8 to 12V dc supply with 500-mA max current. \$700.


Centent Co, 3879 S Main St, Santa Ana, CA 92707. Phone (714) 979-6491.

Circle No 352

A/D CONVERTER

- Features 10-bit resolution and a 150-MHz input bandwidth
- Samples at rates to 30 MHz max from dc

This A/D converter, the 4194 Model, provides a 10-bit resolution with sampling rates of 30 MHz max. It has a standard input voltage range of $2V_{PP}$ into 100Ω . The voltage ranges and impedance levels are user definable. The converter features an input bandwidth of 150 MHz and a slew rate of $400V/\mu sec$. The encode-command input and the digital and data-ready outputs are ECL compatible. The converter comes with internal track and hold, an encoder, timing circuitry, references, and latched output. It con-



sumes 14W. The converter's accuracy is $\pm 0.05\%$ FS. The pc board that holds the converter measures $35in^2$, \$2534 (25).

Teledyne Philbrick, 40 Allied Dr, Dedham, MA 02026. Phone (617) 329-1600. TLX 212711.

Circle No 353


ACQUISITION BOARD

- Uses the TLC32040 chip for data acquisition on IBM PCs
- Provides a 14-bit ADC and DAC

The DSP/AIB board provides data acquisition for an IBM PC, PC/XT, or PC/AT that uses TI's TLC32040 (or TLC32044) analog I/O chip. It features an ADC and a DAC, each

COMPUTERS & PERIPHERALS

with a 14-bit dynamic range. The board directly replaces a codec chip or interface. It can sample up to 20 kHz synchronously and asynchronously. The board interfaces with most DSP boards through a serial interface. Acquisition can occur at 20 kHz in single-channel mode and at 10 kHz in dual-channel mode. In addition, the board provides a 50-pin parallel interface for I/O. You can connect up to five boards to the parallel bus for a 10-channel max sampling at 10 kHz or 5-channel max sampling at 20 kHz. The analog input has an antialiasing filter with a programmable high-frequency



cut-off from 3.6 to 10 kHz. The analog output has a SinX/X filter with a 10-kHz cutoff. \$495.


Sonitech International Inc, 83 Fullerbrook Rd, Wellesley, MA 02181. Phone (617) 235-6824. TWX 650-328-1622.

Circle No 354

SBX MODULE

- Decodes outputs from an incremental quadrature encoder
- Provides a 4-stage digital filter

The Model 4324 SBX bus expansion module for interfacing an incremental quadrature encoder accepts either TTL or CMOS inputs. It has a presettable 24-bit synchronous up/down counter for pulse counting or for quadrature pulse decoding. The maximum input rate is 333 kHz in the quadrature decode mode and 2 MHz in the count mode. The module can generate interrupts for an index



pulse, an overflow or an underflow condition, or when the count value matches a presettable value. In addition, the board has a 4-stage digital filter for noise reduction in an industrial environment. The module mounts directly on the company's model 4312 quadrature input card for the STD Bus. \$220.

Technology 80 Inc, 658 Mendelssohn Ave N, Minneapolis, MN 55427. Phone (800) 328-4827, ext 1680; in MN, (612) 542-9545.

Circle No 355



When you're looking for input on raster plotters, take a look at some major CalComp output. Twenty-four different versions from the fastest growing raster family in the world. (With more family members arriving soon.)


Every raster plotter incorporates more industry firsts, more choices. From simple, colorful business graphics to the complexity of super-dense integrated circuit design, mapping, etc.

The 5800 and 5700, our color and black-and-white electrostatic plotters, deliver speed, superior resolution, multiple configurations and A to E size plots.

For CAD graphics, PlotMaster™ produces quick-check "A" size presentation-quality color. Or plug ColorMaster® into your PC and through **CalComp**atibility, you can run the most popular business presentation graphics software.

 $\textbf{ColorMaster} \text{ is a registered trademark of CalComp.} \ \textcircled{c} \ 1987 \ \textbf{CALCOMP}$

COMPUTERS & PERIPHERALS



DAUGHTER BOARD

- Provides a TMS320C17 development system
- Features 256k words of on-chip memory

The 320/PC-17 daughter board, when used with the vendor's algorithm development package (ADP), lets you develop software and hardware with the Texas Instruments' TMS320C17 DSP microcomputer. The board features a 256k-word, on-chip RAM; a 4k-word ROM; and an 8k-byte program RAM. The board's DSP features a serial port

with a timer and a coprocessor interface and lets you access off-chip RAM. The board's utility software includes a debugger, a line-by-line assembler, a signal editor, and other utility tools. \$895.


Atlanta Signal Processors Inc, 770 Spring St, Atlanta, GA 30308. Phone (404) 892-7265.

Circle No 356

DSP BOARD

- Employs both scalar and vector processors
- Computes a 1024-point FFT in 1.070 msec

By employing a hybrid architecture containing a 12.5-MHz ADSP2100 scalar processor and two 25-MHz ZR34161 vector processors, the DBSVSP-1 digital-signal-processing board can compute a 1024-point FFT spectral analysis (including windowing and magnitude calculations) in 1.070 msec. As a result.



you can use the board to analyze analog signals with bandwidths of approximately 0.5 MHz in real-time applications. To increase throughput, you can operate multiple boards in serial or parallel. The board has an onboard FIFO buffer and dual-port RAM, and it offers direct interfaces for 12-bit ECL- or 16-bit TTL-level data. Interfaces to either the VME Bus or the AT bus







The first family? You bet. First in high-resolution 400 DPI color. First in pin-point accuracy with electronic registration. First in embedded controllers to save space. First with convenient ROM pack firmware. First with flexibility of over 2,000 line and area fill colors. And too many more firsts to talk about here.

There's also a national 800 helpline, 425 trained service persons, 46 service centers nationwide, 32 international field offices, and on-site service. And a single supply source.

Don't be the last to learn about the first family. Call 1-800-CALCOMP or write CALCOMP, P.O. Box 3250, Anaheim, CA 92803. In Canada, call (416) 635-9010.

We draw on your imagination.™



We Draw On Your Imagination and PlotMaster are trademarks of CalComp.

CIRCLE NO 29

are available on a separate card that can control as many as four of the DSP boards. From £3500.

Data Beta, Unit 7, Chiltern Enterprise Centre, Theale, Berkshire RG7 4AA, UK. Phone (0734) 303631. TLX 849021.

Circle No 357

I/O BOARDS

- Provide industrial I/O for Multibus II systems
- Incorporate 2500V isolation from the Multibus II system

The FAB410 and FAB420 are respectively an optically isolated digital input board and a relay isolated output board for Multibus II systems. The FAB410 provides you with two groups of 16 digital inputs. The first four inputs of each group can generate system interrupts on either their rising or falling edges. The inputs accept 24V inputs, but

can be optionally reconfigured to operate with 12 or 48V inputs. Optocouplers on the inputs provide 2500V isolation between the inputs and the Multibus II system, and a programmable digital filter with a time constant of between 10 µsec and 300 msec is provided after the optical isolation. Built-in self-test facilities allow you to apply standard voltages to the inputs and disconnect the input ground line. The FAB420 output board provides four groups of eight outputs. Each output comprises a 120V/1A relay, which provides 2500V isolation from the Multibus II system. Both boards incorporate displays that allow you to monitor the states of their inputs or outputs. FAB410, Fr 6800; FAB420, Fr 8500.

Centralp Automatismes, 16 rue Gabriel Péri, 92120 Montrouge, France. Phone (1) 42533617. TLX 632380.

Circle No 358

DISK DRIVES

- Have capacities of 374M, 689M, and 840M bytes
- Furnish data-transfer rates to 2.4M bytes/sec

The R8600 Series disk drives are compatible with IBM RT/PC computers. They contain disk controllers and have SMD interfaces. You can configure the controllers to control any combination of four drives. You can transfer data to the drives at a 2.4M-byte/sec max rate. They have a 15-msec average access time and come in three disk capacities: 374M, 689M, and 840M bytes. They are compatible with IBM PC/AT-Bus computers. In addition, the drives provide compatibility with DOS, SCO Xenix, and Novell 2.1 operating systems. \$5900 to \$9900 (OEM).

CFN Industries, 30-A Lindbergh Ave, Livermore, CA 94550. Phone (415) 443-1672. TLX 821892.

Circle No 359

FREE

When is it practical to develop a custom hybrid? What about my specific circuit requirements? What are the costs, and how long does it take?

HYBRID ANSWERS

Get fast answers to these important hybrid questions with HEI's Express Quote Service. Call, write or FAX today for your HEI Express Quote Kit, and we'll respond promptly with clear answers and without obligation.

HEI has 20 years of experience in custom hybrid circuit development. The company offers innovative hybrid design and manufacturing capabilities, fast service, and consistent production quality.

HEI inc.

Box 5000, 1495 Steiger Lake Lane, Victoria, MN 55386 Phone: 612-443-2500 FAX: 612-443-2668

COMPUTERS & PERIPHERALS



MEASURING UNIT

- Uses ultrasound to locate objects 30 ft away
- Communicates with a computer via an RS-232C link

The UDM-RMU (remote measurement unit) distance-measuring device communicates with a controller over an RS-232C link. It uses two Polaroid ultrasonic transducers to locate objects from 0.5 to 30 ft away with an accuracy of ±1% and a resolution of .05 in. The unit calculates the distance to an object and sends the data via a 60-ft RS-232C cable as two ACII numbers delimited by a space character (20H) and terminated with a carriage return (0DH). Communications take place at 9600 baud with no parity and 1 stop bit. A wall-mount power supply powers the unit. The unit weighs 1.8 lbs and four mounting screw holes let you attach the remote unit to a flat surface. It operates from 0 to 70°C with a humidity of 5 to 95%. \$495.

Contaq Technologies Corp, 15 Main St, Bristol, VT 05443. Phone (802) 453-3332.

Circle No 360

COMPUTER BOARD

- Has an 80C196 µP with two timer/counters
- Provides an 8-channel, 10-bit ADC

The CP-196 CMOS single-board computer offers a 16-bit 80C196 μP . It features two parallel ports; a serial port; and an 8-channel, 10-bit A/D converter. In addition, the


processor provides eight high-speed I/O lines and two 16-bit timer/counters. The board provides up to five 8-bit parallel ports. It has buffered RS-232C and RS-422 ports, and a third serial port operates as both an RS-232C and an RS-422 port. All three ports are brought out to 2×20 header connectors. The board's memory features a 60k-byte

EPROM and RAM on four JEDEC 28-pin ICs. The board measures 5.375×8 in. and requires a 5V supply. Bare board, \$100; assembled with 32k-byte EPROM and 28k-byte RAM, \$500.

Allen Systems, 2151 Fairfax Rd, Columbus, OH 43221. Phone (614) 488-7122.

Circle No 361

PULL A LIGHT SWITCH.



FROM THIS... TO THIS.

EL is light years ahead: No catastrophic failure. No filament to break. Immune to shock and vibration.

Uniform surface brightness and color: A single Durel lamp can replace a group of individual incandescent bulbs and costly light pipes.

Low power consumption: Typically less than 2mA per sq. in. at 115V, 400Hz. Ideal for battery power and low-current drain applications.

Thin: Nominal thickness of 0.024" (0.6mm) for space-efficiency.


Pliable: Flexibility permits bending to fit unique shapes.

High visibility in smoke/fog: Ideal for emergency lighting. Call or write for information.



NEW PRODUCTS

INTEGRATED CIRCUITS



VIDEO SHIFT REGISTER

- Features 40-bit, 250 MHz capability
- Provides integration for systems running at over 125 MHz

Adapting to a variety of frame buffers and RAM-DAC structures, the Bt424 video shift register reduces component count in high-resolution graphics systems. Because it employs both TTL and ECL circuitry, the register provides a low-to-high speed interface that simplifies system timing. With a 40-bit multitap

architecture, the register works with systems running at rates of 125 MHz or faster. You can use the device with other high-speed bipolar products in the vendor's line. The chip operates from a single 5V supply or 5V and -5.2V supplies. It consumes 1.25W and comes in a 68-pin PGA package. \$62(100).

Brooktree Corp, 9950 Barnes Canyon Rd, San Diego, CA 92121. Phone (619) 452-7580. TLX 383596.

Circle No 365

DIP and SO packages; the 78P234 in 20-pin DIP and SO packages. \$10.68 (100).

Silicon Systems, 14351 Myford Rd, Tustin, CA 92680. Phone (714) 731-7110.

Circle No 366

CMOS MAC CHIP

- 25-MHz multiply-accumulate rate
- TTL-compatible inputs and outputs


Featuring an 8×8-bit parallel architecture, the TMC2208 has a 40-nsec cycle time (25-MHz multiply-accumulate rate). You can specify the input data as two's complement or unsigned magnitude, yielding a fullprecision 16-bit product. You can accumulate products to a 19-bit result. The chip features selectable accumulation, subtraction, rounding, and accumulator preload. The inputs and outputs are registered and TTL compatible. The device operates from a single 5V supply and comes in a 48-pin ceramic DIP or plastic package. Ceramic DIP, \$21; plastic package, \$15 (1000).

TRW LSI Products Inc, Box 2472, La Jolla, CA 92038. Phone (619) 457-1000.

Circle No 367

INTERFACE CHIPS

- Provide transmit and receive functions for T1 or CEPT lines
- Convert signals to TTL level
 Providing the interface for T1 and
 CEPT digital lines, two single-chip
 bipolar ICs perform receive, transmit, and loop-back functions. The
 SSI-78P233 transceiver conforms to
 North American T1 standards; the
 SSI-78P234 to worldwide CEPT
 standards. The receiver extracts
 data from the incoming bit stream
 and converts it to TTL-level signals. The ICs employ a trimmed,
 analog, phased-locked loop and a
 precision external resistor. No
 other tunable or precision compo-




nents are required. The transmitter accepts TTL data and clock signals, converts them to an alternate-mark-inversion bit stream, and lets you equalize and shape outgoing pulses according to the line length. The ICs require only a single 5V supply. The 78P233 comes in 24-pin

PULSE DETECTOR

- Features embedded servo circuit
- Wide-bandwidth amplifier eliminates gain adjustment

The DP8468B disk-pulse detector meets the requirements of 3.5- and 5.25-in. hard-disk drives. The chip, which has a maximum storage capacity of 200M bytes, works with standard drives or with drives that employ RLL codes. The device features an on-chip embedded servo circuit that allows it to position the disk head at the true center of a track. The chip's wide-bandwidth differential amplifier provides auto-



Now, with Mitsubishi's transportable memory cards, you can have the flexibility of carrying 32K Bytes to 2M Bytes of SRAM, OTPROM or masked ROM in your pocket. That means read/ write capability (without a disk drive), remote from central data storage, plus the flexibility to interchange memory types



(SRAM, OTPROM, masked ROM), upgrade and downgrade memory density, and change data width (8 bits, 16 bits). All with an extremely rugged device that's the size of a credit card (86mm x 54mm x 3.4mm).

The Applications Are Virtually Endless.

From personal computers to printers, portable equipment to telecommunications, the applications are as creative and endless as the imagination. Anywhere transportable memory and massive data storage are required, Mitsubishi's transportable cards offer the highest memory densities available on a device this small.

Save On Systems Design Costs.

Mitsubishi's transportable memory cards offer standardized card connectors and pin assignments for easy memory interchange and density upgrade, without designing multiple host system models. Plus, future system redesign is simplified or eliminated.

Extremely High Density Memory.

The key to Mitsubishi's extremely high density memory cards is the VSOP (very-small-outlinepackage). Pioneered by Mitsubishi, the VSOP is over four times smaller (in overall volume) than its equivalent pin

count, standard surface mount package. In fact, the VSOP is smaller than the footprint of the equivalent chip-on-board technology making it possible to pack up to 16 memory ICs,

 $13.8 \text{ mm } \times 8.0 \text{ mm } \times 1.0 \text{ mm} = 110.4 \text{ mm}^3$

 $15.4 \text{ mm} \times 9.8 \text{ mm} \times 1.0 \text{ mm} = 150.9 \text{ mm}^3$

SOP

 $17.5 \text{ mm} \times 12.2 \text{ mm} \times 2.2 \text{ mm} = 469.7 \text{ mm}^3$

Chip-On-Board

Mitsubishi designed its memory cards specifically for transportable applications. And, that means cards that are rugged and reliable. Even if a card is dropped, loss of valuable data is virtually eliminated, due to Mitsubishi's flexible, four-layer PCB and enhanced soldering techniques.

If you want to design-in massive, transportable data storage with the flexibility to interchange memory types and densities, Mitsubishi memory cards give you the maximum memory mileage. For more information call or write today: Mitsubishi Electronics America, Inc., Semiconductor Division, 1050 East Argues Avenue, Sunnyvale, CA 94086. (408) 730-5900.

plus standard interface circuitry on one card. "Transportable" Means "Rugged."

Additionally, the cards are ESD protected to 25K volts, with connectors guaranteed for 10,000 insertions.

Quality Through Commitment.



 Regional Offices:
 SOUTH CENTRAL, Carrollton, TX (214) 484-1919
 NEW ENGLAND, Woburn, MA (617) 938-1220

 NORTHWEST, Sunnyvale, CA (408) 730-5900
 NORTHERN, Minnetonka, MN (612) 938-7779
 MID-ATLANTIC, Piscattaway, NJ (201) 981-1001

 SOUTH WEST, Torrance, CA (213) 515-3993
 NORTH CENTRAL, Mt. Prospect, IL (312) 298-9223
 SOUTH ATLANTIC, Norcross, GA (404) 662-0813

SOUTHEAST, Boca Raton, FL (305) 487-774 CANADA, St. Laurent, Quebec, (514) 337-6046 Because you're thinking fast... count on us for the speed you need.

Now, 19ns settling op amps that survive saturations and shorts...

Comlinear's two new high-speed op amps bring you built-in protection against saturation. Plus simple shortcircuit protection. That means easy solutions for fast input and output amplifiers in systems where signal level or load can't be controlled.

use as little as 57mW...

Our new 170MHz CLC205 offers fast dynamic performance and power consumption down to 57mW (with ±5V supplies). A settling time of 24ns to 0.05% is complemented by the drive performance of a ±12V output swing and ±50mA output current.

or drive up to ±100mA.

For higher drive, call for our 180MHz CLC206 which will drive up to ±100mA and settle in just 19ns (to 0.1%). It is coupled with a high slew rate of 3400V/µs and delivers a large-signal bandwidth of 70MHz at 20Vpp.

Both of these new op amps give you saturation and short-circuit protection plus tested and guaranteed performance at half the price of other high-speed amps. Now you can be safe at high speed.








INTEGRATED CIRCUITS

matic gain control, which eliminates the need for factory gain adjustments. The gating channel uses a differential comparator with hysterisis to avoid problems caused by false signals. The DP8468B functions with data rates to 15M bps. Available in a 28-pin plastic leaded chip carrier, the device costs \$10 (1000).

National Semiconductor Corp, Box 58090, Santa Clara, CA 95052. Phone (408) 721-6725. TLX 346353.

Circle No 368



A/D CONVERTERS

- 15- and 25-usec conversion
- 150-mW (max) power consumption

The SP674A and HS574A are 12-bit monolithic A/D converters that are pin-compatible with Harris's twochip HI674A and Analog Devices' AD574A. The SP674A and HS574A contain an internal 10V reference, a clock, and 3-state output buffers for direct interfacing to 8-, 12-, or 16-bit μP buses. The SP674A has a typical conversion time of 12 µsec (15 µsec max); the HS574A's typical conversion time is 15 µsec (25 µsec max). Both converters offer standard bipolar and unipolar input ranges of $\pm 5V$, $\pm 10V$, 0 to 10V, and 0 to 20V. Maximum linearity error is ± 0.5 LSB. The company guarantees no missing code to 12 bits over the specified temperature range. Both ADCs operate from 5V and 12 to 15V supplies and feature a maximum power consumption of 150 mW. Packaging options include a ceramic 28-pin DIP and a ceramic 28-pin LCC. The converters are available in the commercial, industrial, and military temperature ranges. Depending on grade and screening, \$25 to \$160.

Sipex Corp, Hybrid Systems Div, 22 Linnell Circle, Billerica, MA 01821. Phone (617) 667-8700. FAX 617-667-8310.

Circle No 369

WATCHDOG IC

- Provides sequenced reset signals
- Has a programmable time-out period


Incorporating voltage comparators, a programmable timer, and reset sequencing logic, the H6060 can act as a power supply monitor or as a reset generator for µP systems. It generates reset outputs of both polarities. You can program the length of the recovery interval from 3 msec to 3 minutes. The IC generates a low-voltage alarm output prior to the reset. The device can function with a minimum of 3.5V; its output signals remain in a defined state even when the device's supply voltage falls to zero. The IC monitors 5 or 3.5 to 5.5V supplies. The vendor can program the device's voltage thresholds for other applications. Around \$2.50.

EM Microelectronic-Marin SA, H-2074 Marin, Switzerland. Phone (038) 352141. TLX 952790.

Circle No 370

CMOS PLDs

- Feature 12-nsec propagation delay
- Maximum current is 115 mA
 The GAL16V8A-12 and GAL20V8A-12 are 20- and 24- pin PLDs,
 respectively. They employ electrically erasable CMOS technology to
 provide a 12-nsec propagation delay. The E²CMOS technology allows complete ac, dc, and functional
 testing during manufacture. The
 PLDs feature a data-retention life
 of more than 20 years, according
 to the vendor. The PLDs let you
 replace any common 20- or 24-pin



without the workout.

If you spend time working with IC or Discrete semiconductors, you should get to know our DIGESTs. Because they can make your work go a whole lot easier.

Quickly compare electrical specs, packages, pinouts; find alternate sources or replacement information; or go directly from generic or part numbers to technical and manufacturer data. All at your fingertips...your own personal library at your desk.

Involved with MIL SPEC or Hi-Rel components? Our Hi-Rel/ Military Digest can lighten your load. Simplified cross-referencing and a user-friendly format eliminate time-wasting searches through QPL's, MIL-STD 1562, DESC drawings and manufacturer catalogs. Searches that previously took hours can be done in minutes.

And to keep up with the latest technology, the DIGESTs feature optional Updates, automatically sent to you either quarterly or semiannually.

We offer the DIGESTs separately, discount them in quantity, and, of course, all DIGESTs carry our 30-day moneyback guarantee. We also lease our database on magnetic tape.

To find out more about how the DIGESTs can simplify your workload, call our toll-free numbers.

The D.A.T.A. DIGESTs: getting out the work doesn't have to be a workout anymore.

the DIGESTs™

where semiconductor selection begins

Call toll-free 1-800-854-7030, Ext. 570. In CA 1-800-421-0159, Ext. 570 • 9889 Willow Creek Road • P.O. Box 26875 • San Diego, CA 92126



programmable logic device. Both models operate at a current of 115 mA max. The vendor offers develoment tools, such as programming and software packages. GAL16V8A-12, \$8.32; GAL20V8A-12, \$9.51 (100).

Lattice Semiconductor Corp, 5555 NE Moore Ct, Hillsboro, OR 97124. Phone (503) 681-0118. TLX 277338.

Circle No 371

12-BIT HYBRID ADC

- 1-usec conversion time
- Pin-programmable inputs

The ADC-511 12-bit A/D converter features a maximum conversion time of 1 usec and a typical power dissipation of 925 mW. It is packaged in a 24-pin DIP. The ADC-511 contains an internal clock and an internal reference that supplies 10V at 1.5 mA externally. Based on a digitally-corrected subranging architecture, the hybrid's digital inputs and 3-state outputs are CMOS and TTL compatible. You can select straight/offset-binary or complementary-binary/-offset output coding. A pin-programmable feature lets you select either unipolar analog inputs from 0 to 10V or bipolar analog inputs from -5 to +5V. The ADC-511 operates from ± 15 and +5V dc power supplies over the 0 to 70°C temperature range. \$99 (1000).


Datel Inc, 11 Cabot Blvd, Mansfield, MA 02048. Phone (617) 339-3000. TLX 951340.

Circle No 372

VIDEO SWITCH

- Low standby power
- 8-MHz bandwidth

Designed for broadcast-quality switching matrices, the GX414 video crosspoint switch has frequency response that is flat within ± 0.075 dB from dc to 8 MHz. The chip has a standby power consumption of only 5.7 mW when disabled.



The GX414 is configured as a 4×1 switch containing 4 analog video switches and a 2-to-4 decoder. An enable input lets you parallel GX414s and operate them in a switching matrix with multiple inputs and a common output. When enabled, the switch makes a fully buffered unilateral transmisssion path with a typical off-isolation of 100 dB at 10 MHz. Available in DIP and SOIC packages, the GX414 costs \$5.73 and \$6.21, respectively (1000).

Gennum Corp, Box 489, Station A, Burlington, Ontario, Canada L7R 3Y3. Phone (416) 632-2996. TLX 0618525.

Circle No 373

MICRO-CHANNEL CHIP

- Provides decoding and logic functions
- Has DMA arbitration

The 88C01 chip provides a microchannel interface. It reads configuration information when the power is turned on. The chip provides programmable decoding for extended memory, expanded memory, I/O ports, and ROM. It lets you define registers and address memory lines. The chip provides DMA and burst-mode DMA. The pinouts are optimized for micro-channel board layout. The device meets the microchannel drive requirements without buffering, and has multiplexed memory address lines for direct connection to 1M-bit DRAMs. \$27.50 (100).

Capital Equipment Corp, 99 S Bedford St, Burlington, MA 01803. Phone (617) 273-1818.

Circle No 374



(216) 439-4091 Telex 6502820864 Fax (216) 439-4093

25971 Cannon Road • Cleveland, Ohio 44146 London (0734) 86-12-87 • Paris (1) 34810178 • Zurich (01) 821 9444

BEE-Z

Our Personal488™ IEEE (GPIB)

• DOS device driver loads at power-on

BASIC ON SRQ GOSUB capability

• Hewlett-Packard style commands

• DMA transfers over 300K bytes/s

• Up to four IEEE boards/computer

• DMA and interrupt channel sharing

· Compatible with popular languages (no extras to buy), including BASICA,

GWBASIC, Quick BASIC, Compiled

BASIC, Turbo BASIC, True BASIC,

Pascal, Turbo C, Microsoft C, Aztec C,

TBASIC, Turbo Pascal, Microsoft

Lattice C, Microsoft Fortran,

AutoCAD, and many more.

. Call or send for your

FREE Technical Guide

· 2 year warranty

Lotus 1-2-3/Symphony/Measure,

ASYST, DADISP, Test Windows,

· 30 day money-back guarantee

• NEC-7210 compatible software • Serial/Parallel/IEEE port redirection

interfaces for PC/AT/386 &

easy-to-use features:

PS/2s are packed with these

Milan 02-4120360 • Linkoping 013 11 01 40 • Amsterdam 01830-35333 Vienna (0222)253626 • Munich ,and other European, North African, and Middle East countries not listed (089) 710020.



ANY WAY YOU CONFIGURE IT, PHILIPS ISOTOP PACKS MORE POWER.

Choose ISOTOP—the universal package for power semiconductors.

Now, no matter which power circuit you use, ISOTOP packs everything you need to handle up to 1,200V and 120 amps into a single component less than 6 cm3 in size.

ISOTOP packages provide a compact, universal format with standard configurations for all of the basic power functions. Internal construction includes a heat-spreading mount as well as ceramic insulation ensuring low thermal resistance and 2,500V rms isolation. ISOTOP features:

- · the most power in the smallest space— 1,200V and 120 amps in 6 cm3
- low inductance
- · ultra high power and density with low profile
- · high frequency operation with low RFI
- low capacitance
- fully isolated package with 2,500V rms

Pleases	send me more information on
how IS	OTOP power semiconductor
	es save space and cut design
	nd coete

NAME

COMPANY

ADDRESS

CITY/STATE/ZIP.

TELEPHONE/ext.

YOUR APPLICATION.

TYPE OF CIRCUIT(S).

Amperex Electronic Company, Providence Pike, Slatersville, RI

Attention: Marketing Communications

- up to 50 kW operation in AC/DC motor drives, welding equipment, converters, switches
- easy mounting on PCBs with solder on, screw-on or fast-on direct connectors

ISOTOP comes in a fast-growing family of semiconductor technologies. High-power epitaxial and Schottkybarrier rectifiers, thyristors, GTOs, darlingtons and switching transistors are all available for quick delivery right now. PowerMOS. triac and other versions will be available soon. Any way you configure it, there's more power to you with ISOTOP.

Send for details.








Fast-on

DISCRETE SEMICONDUCTOR PRODUCTS GROUP

PHILIPS



SLIC ICs.



Choose RIFA for the world's leading family of Subscriber Line Interface Circuits. First in the field with monolithic SLIC production, we now offer the widest selection, to suit every application. Many of our industry-standard devices are now second-sourced; our leadership in bipolar production techniques guarantees space-age reliability.

PBL 3736.

Originally designed for Central Office use, also recommended for high-quality PABX applications. Full-line interfacing in compact CERDIP package. On-board voltage switching regulator cuts power dissipation and the need for special heat sinking. Features include polarity reversal and a digital interface for efficient operating parameter control.

PBL 3762.

High-performance, resistive-feed SLIC designed for PABX. Excellent longitudinal-to-metallic balance, 63dB min, 70dB typical, meets FCC requirements easily. Special -40° C version for outdoor use, eg in Subscriber Loop Carrier Systems.

PBL 3739.

Special version of PBL 3736 designed for very high density PABX line cards. Built-in switching voltage regulation, very low heat dissipation, in 44-pin J-lead Quad CERPAC for surface mounting.

Call up RIFA and discover the fullest set of data, longest experience and genuine design partnership.

We're in the lead



403 International Pkwy Richardson, TX 75085-3904 Telephone (214) 480-8300 Telefax (214) 680-1059

ERICSSON

RIFA is a member of the Ericsson Group


NEW PRODUCTS

COMPONENTS & POWER SUPPLIES

POWER SUPPLIES

- Available with power outputs of 100W
- Switching frequency ranges from 80 to 200 kHz

MW Series switching power supplies are available in 15, 30, 50, and 100W versions. Standard outputs are 5, 12, 15, and 24V. The 15, 30, and 50W models are available with triple outputs, and the 100W version provides four outputs. Input voltage specs at 85 to 264V dc. Power density ranges from 1.52 to 2.21W/in.³, and efficiency is as high as 65%. Switching frequencies span an 80- to 200-kHz range. All versions offer overcurrent and overvoltage protection. The supplies meet FCC Class B noise standards



as well as UL478 and CSA requirements. The operating range is 0 to 60°C. Custom variations, such as output voltage and current, are available at no charge. \$85 to \$235.

Toko America Inc, 1250 Feehanville Dr, Mount Prospect, IL 60056. Phone (312) 297-0070. FAX 312-699-7864.

Circle No 380



PROXIMITY SENSOR

- Features a dual-range capability
- Provides a wide sensing beam

The Model 9501A proximity sensor is designed to help the automated guided vehicles (AVGs) used in industrial settings to avoid collisions. Unlike other sensor designs, the 9501A creates a wide fan-shaped sensing region that has two sepa-

rate detection ranges. This dual-range capability allows the AGV to have a slow-down zone as far as 10 feet ahead and a stop zone as close as 4 feet ahead. The unit's sensing technology provides high gains in the sensing region and a sharp cut-off beyond the maximum range. As a result, the sensor will detect both light and dark objects while it ignores backgrounds. The 9501A features built-in test capability (self-diagnostics) and is unaffected by other sensors operating nearby. \$325.

Opcon Inc, 720 80th St NW, Everett, WA 98203. Phone (206) 353-0900.

Circle No 381

DPMs

- Feature ±0.1% accuracy
- Handle ±20V dc inputs

DP-1350 Series 31/2-digit DPMs employ a dual-slope integrating A/D converter and full-differential inputs. The -1350 and -1354 models



have ± 2 - and ± 20 V dc full-scale input ranges, respectively. Both models feature LED displays with 14.3-mm-high characters, a hold function, an 86-dB CMRR, and ±0.1% accuracy. They draw only 1W (5V at 200 mA). The internal reference can be replaced by an external reference to accommodate ratiometric measurements. The meters feature user-selectable decimal-point placement, automatic polarity changeover, full autozeroing, and overrange indication. The operating range is 0 to 50°C, and the temperature coefficient is ± 100 ppm/°C. \$79.

Acculex, 440 Myles Standish Blvd, Taunton, MA 02780. Phone (508) 880-3660. TLX 503989.


Circle No 382

COMPONENTS & POWER SUPPLIES

CHOKES

- Windings balanced within 1%
- Meet UL and CSA regirements


RL1361-1 and RL1361-2 commonmode chokes are designed with outof-phase windings that are balanced within 1%. When used at power-line inputs, they can cancel or suppress EMI transients sufficiently to meet industry specifications. Standard units meet UL and CSA requirements. Units can also be manufactured to VDE specifications. Operating temperature is -55 to $+130^{\circ}\mathrm{C}$. All units will withstand a 2500V ac hipot test for winding-to-winding and winding-to-core. More than 80 standard models, designed for pc-board mounting, are avail-



able. Current ratings range from 100 mA to 5.5A. MIL-spec and encapsulated models are also available. From \$0.95 (10,000). Delivery, stock to eight weeks ARO.

Renco Electronics Inc, 60 Jefryn Blvd E, Deer Park, NY 11729. Phone (516) 586-5566. FAX 516-586-5562.

Circle No 383



ENCODERS


- Noncontacting direct rotary-todigital converters
- Operate from one 5V supply

Softpot Models SPM-50 and SPM-100 optical shaft encoders convert shaft angle, speed, and direction into real-time digital information. A torque-loaded shaft provides the feel of a limitless potentiometer for front-panel man-to-machine interface applications. The -50 and -100 encoders respectively provide 50 and 100 cycles to generate 200 and 400 quadrature codes per revolution. The internal electronics, which draw only 50 mA from a 5V supply, include two solid-state light sources. The miniature encoders are housed in a package that measures only 0.8 in. in diameter. \$22 (100).

U S Digital Corp, 12371 Kensington Rd, Los Alamitos, CA 90720. Phone (213) 594-0094. FAX 213-594-6091.

Circle No 384

KEEPING IT SIMPLE




Intel development tools and support services keep your path to success clearly marked and free from obstacles. They help you reduce unnecessary steps. Avoid wrong turns. And eliminate dead ends altogether.

Intel tools keep the complex process of developing with today's microprocessors and microcontrollers simple.

Intel Development Tools. The Short, Sure Path to Success.

For more information and a catalog of Intel development tools, call toll free:

ARROW ELECTRONICS. I-800-77ARROW.



VOICE MODULE

- Provides solid-state answerphone facilities
- Interfaces to mobile or cellular radio equipment

Employed in the audio stages of mobile or cellular radio systems, the CXM1380 voice store-and-retrieval module provides facilities similar to those of a conventional answering machine. However, instead of using audio tape, the module uses a deltamodulation codec and static RAM to provide a totally electronic system. You can record the answer message using the existing mobile radio or cellular phone handset, and a message-skip facility allows you to rapidly review recorded messages. The module, which is housed on a 3.8 × 1.97-in. pc board, requires only one 5V supply and logic-level, call-progress control signals from the phone set. £153 (100).

Consumer Microcircuits Ltd, 1 Wheaton Rd, Witham, Essex CM8 3TD, UK. Phone (0376) 513833. TLX 99382.

Circle No 385

Mx-Com Inc, 4800 Bethania Station Rd, Winston-Salem, NC 27105. Phone (919) 744-5050.

Circle No 386

TRANSFORMERS

- Connect modem terminals to the telephone lines
- Meet international standards for creepage and clearance

TH Series coupling transformers are designed to meet European/International standards, such as VDE,


BSI, and Australian Telecom, as well as FCC Part 68 requirements. Despite their $0.81 \times 0.66 \times 0.75$ -in. size, the pc-board-mountable units meet the creepage and clearance requirements of international standards. Designed to interconnect voice/data modem terminals to the telephone lines, the TH2104 and TH2106 transformers are rated at

 $600:600\Omega$ at 0 mA dc. Both windings of the 2106 are center-tapped. Typical insertion loss is 1.0 dB, and minimum return loss at 300 Hz measures 22 dB. \$5.75 (500) for the TH2104.

Microtran Co, Box 236, Valley Stream, NY 11582. Phone (516) 561-6050. TWX 510-225-8412.

Circle No 387





Only one company offers and backs all the development tools you'll ever need. For every microprocessor and microcontroller you'll ever need.

Languages, debuggers, emulators and utilities. For all Intel architectures including the 8051, 8096/196, 8086/186/286, 80386, and the all new 32-bit 80960 family.

All the right tools. Only from Intel.

Intel Development Tools. The Short, Sure Path to Success.

For more information and a catalog of Intel development tools, call toll free:

ARROW ELECTRONICS. I-800-77ARROW.

NEW PRODUCTS

CAE & SOFTWARE DEVELOPMENT TOOLS

C LIBRARY FOR OS/2

- Lets you port your programs from MS-DOS to OS/2 and back
- Manages the entire user interface C-Worthy Interface Library is a system of pretested functions for creating and managing the user interface of your application programs. The user interface can resemble that of the OS/2 Presentation Manager or of Lotus 1-2-3, or it can be uniquely adapted to meet the needs of your application. The library contains more than 350 functions for on-line help, error handling, screen displays, and data input. The documentation includes examples of how to use the functions, a detailed description of each function, and indexes. A Forms Interface package for designing reports is also available. The libraries are compatible with version 5.1 of the Microsoft C compiler, and you can order the libraries for either MS-DOS or OS/2 (prices are the same for both). C-Worthy library,


\$195; with Forms Interface Library, \$295; with source code for both libraries, \$495.

Solution Systems, 541 Main St, Suite 410, S Weymouth, MA 02190. Phone (800) 821-2492; in MA, (617) 337-6963.

Circle No 390

SIMULATOR

- Library includes models of many DSP and digital functions
- Runs on Macintosh computers
 Extend is a modular, behavioralsimulation program that runs on
 Apple's Mac II, Mac SE, and Mac
 Plus computers. It lets you build
 block diagrams, insert the function
 of each block in the form of a script,
 and then connect the blocks together to form a system model.
 When you run a simulation, the results are both plotted as waveforms
 and presented as tabular data. The
 scripting language (ModL) provides
 more than 60 functions for plotting,



math, queuing, statistics, and diagnostics. The simulator works with the vendor's advanced electronics engineering libraries, which provide icons and scripts for a wide variety of both analog and digital functions, including A/D and D/A converters, amplifiers, filters, VCOs, and phase-locked loops. Extend, \$495; libraries, free with Extend until 1 September, 1988, and \$95 thereafter.

Imagine That! 7109 Via Carmela, San Jose, CA 95139. Phone (408) 365-0305.

Circle No 391

EPLD DESIGN TOOLS

- Allows you to design EPLDs on an IBM PS/2
- Makes full use of the VGA graphics features

A-PLUS lets you enter an EPLD (erasable programmable logic device) design as a schematic, in statemachine language, or in Boolean or netlist formats. You can create macrofunctions or use TTL functions from the vendor's macrofunction library. The program performs logic minimization and automatically fits the logic into the smallest EPLD that will hold the design. You can use the program with the vendor's series of EPLDs. SAM+PLUS package performs a similar series of functions with the EPS family of function-specific EPLDs. These EPLDs use a microsequencer architecture to create


complex state machines and highperformance controllers. They are available from the vendor and from WaferScale Integration Inc. A-PLUS software, \$1750. The vendor also supplies a complete hardware/ software development system that includes A-PLUS, related CAE software options, and programming hardware for \$5995.

Altera Corp, 3525 Monroe St, Santa Clara, CA 95051. Phone (408) 984-2800.

Circle No 392



MICRO-LOGIC II. The CAE tool with a 10,000-gate digital simulator for your PC.



Spectrum Software's MICRO-LOGIC II® puts you on top of the most complex logic design problems. With a powerful total capacity of 10,000 gates, MICRO-LOGIC II helps engineers tackle tough design and simulation problems right at their PCs.

MICRO-LOGIC II, which is based on our original MICRO-LOGIC software, is a field-proven, second-generation program. It has a high-speed event-driven simulator which is significantly faster than the earlier version.



Timing Simulator

The program provides you with a top-notch interactive drawing and analysis environment. You can create logic diagrams of up to 64 pages with ease. The software features a sophisticated schematic editor with pan and zoom capabilities.




Shape Editor

A 200-type library of standard parts is at your fingertips. And for a new high in flexibility, a built-in shape editor lets you create unique or custom shapes.

MICRO-LOGIC II is available for the IBM® PC. It is CGA, EGA, and Hercules® compatible and costs only \$895 complete. An evaluation version is available for \$100. Call or write today for our free brochure and demo disk. We'd like to put you in touch with a top digital solution.

- Total capacity of 10,000 gates
- Integrated schematic editor
- Fast assembly language routines
- Standard parts library of 200 types
- Event-driven timing simulator

- Built-in shape editor
- Multiple delay models
- Printer and plotter hard copy



Schematic Editor



1021 S. Wolfe Road, Dept. E Sunnyvale, CA 94087 (408) 738-4387

MICRO-LOGIC II is a registered trademark of Spectrum Software.

Hercules is a registered trademark of Hercules Computer Technology IBM is a registered trademark of International Business Machines, Inc.

ASIC ANALYSIS

- Allows ac and dc measurements of prototype ASICs
- Offers Shmoo-plotting of test results

The Characteristic and Timing Analysis (CTA) package allows you to automate any Logic Master measurement, collect and format the test results for analysis, and control the Logic Master from a spreadsheet program. CTA is compatible with any product contained in the vendor's Logic Master ASICverification family. The program provides menu-driven routines for making ac and dc measurements of prototype ASIC devices and for the Shmoo-plotting of the interaction of any two device variables. One of the menus lets you measure propagation delay, setup time, and hold time. You can also create your own analysis routines using any of the 30 preprogrammed CTA functions. Prices start at \$3000 for the Logic

Master ST workstation.

Integrated Measurement Systems, 9525 SW Gemini Dr, Beaverton, OR 97005. Phone (503) 626-7117.

Circle No 393



DATA LINK

- Transfers files between DEC and Datapoint computers
- Uses an ArcNet LAN

The Daft file-transfer package allows you to transfer data between

DEC VAX minicomputers and Datapoint Corp computers, using the Datapoint high-speed ArcNet network facility. The package provides transfer of text files between Datapoint machines running either Datapoint RMS or DOS, and VAX computers running VAX/VMS. The package comprises a file transfer server program for the Datapoint computer, a VAX/VMS driver to drive the ArcNet interface, user interface and transfer protocol programs for the VAX computer, and a Q Bus or Unibus ArcNet interface card. To speed data transfers, they are performed in binary mode wherever possible. Utilities are provided that allow you to perform off-line conversion between VMS and Datapoint formats. You can also automate data transfers and format conversions. On-line help facilities are included in the user interface. A Q Bus version for a MicroVAX sells for \$7800. The Unibus version costs ap-

the low profile answer to the high power question . . .

The next time you ask yourself how to get all that power into such a small space, think of Intronics.

Introducing our new 100 Watt triple output, low profile DC/DC converter.

The KZ 400 Series does the job of three single output converters in a much smaller area—saving you valuable board space. It costs significantly less than individual converters and saves time and money on installation and inspection.

Designed primarily for the telecommunications, computer and instrumentation markets, the KZ 400 is metal encased with six-sided shielding and comes with a number of standard features. With 20 standard single and triple output models to choose from, it boasts a wide input range of 20-60 VDC and 36-72 VDC.



The KZ 400 delivers an impressive 80% typical efficiency and has a fixed switching frequency of 200 KHz. Line/load regulation specifications are ±1% main channel and ±5% auxiliaries. The unit is available in PC board and side mount models.

Get all the power you need at a lower cost—while increasing valuable board space. And at Intronics, you also get dependable service and product support. Call Intronics today at (617) 964-4000 about the

new 100 Watt KZ 400 triple output DC/DC converter—the answer to your high power needs.



A Powerful Profile...

57 Chapel Street, Newton, MA 02158 617-964-4000 TWX 710-335-6835 TELEX 200095 INTL UR FAX 617-527-3310 proximately \$9200.

Comendec Ltd, Aston Science Park, Love Lane, Aston Triangle, Birmingham B7 4BJ, UK. Phone 021-359-0981. TLX 33435.

Circle No 394

LINKING SOFTWARE

- Speeds transfer rates with datacompression algorithm
- Allows 15 simultaneous communications exchanges

Relay Gold version 3.0 enables personal-computer communications and micro-to-mainframe linking. It employs a data-compression algorithm that speeds transfer rates. The software lets you communicate asynchronously and maintain 15 simultaneous sessions. It lets you download data without leaving the application. An IBM PS/2 Adapter/A support facility gives you access to IBM PS/2 computers. You can use the

software with 160k bytes in resident mode. It emulates the IBM 3101; VT220; VT240; 3278 Models 2, 3, 4, 5; and 3279 Models 2 and 3. The software can run at 38,400 bps max. \$295; upgrade from an earlier version, \$75.

Relay Communications Inc, 41 Kenosia Ave, Danbury, CT 06810. Phone (800) 847-3529; in CT, (203) 798-3800.

Circle No 395

OS-9 SHELL

- Provides a Unix-like shell for the OS-9/68k operating system
- Includes high-level language commands

The SH software package provides you with a programmable shell-command interpreter for the OS-9/68k operating sytem. Acting as a user interface to the operating system, the package provides a shell that is fully compatible with a stan-

dard Unix operating system shell. Its features include parameter passing, string substitution, and definition of variables. The control-flow primitives allow bidirectional communication between the operating system shell and invoked processes. You can use return codes or standard command outputs as arguments or inputs to the shell to determine control flow. You can also perform calculations and check files and shell variables for their type and state. In addition to AND and OR command groupings, the shell includes high-level commands such as if-then-else, do-while, and case statements. The SH package is supplied on an OS-9 diskette. \$650.

EKF Elektronik GmbH, Weidekampstrasse 1a, 4700 Hamm 1, West Germany. Phone (02381) 12630. TLX 828621. FAX 023-811-5067.

Circle No 396

Turn Good Ideas Into Good Articles

With EDN's FREE Writer's Guide!

Would you like to get paid for sharing your clever engineering ideas and methods with your professional colleagues? If so, then send for EDN's new FREE writer's guide and learn how.

You don't need the skills and experience of a professional writer. And you don't need to know publishing jargon. All you *do* need are a little perseverance, your engineering skills, and the ability to communicate your ideas clearly.

Our new writer's guide takes the mystery and intimidation out of writing for a publication. It shows you how to write for EDN using



skills you already have. Plus, it takes you stepby-step through the editorial procedures necessary to turn your ideas into polished, professional articles.

Get your FREE copy of EDN's writer's guide by circling number 800 on the Information Retrieval Service Card or by calling Sharon Gildea at (617) 964-3030.

EDN September 1, 1988 231


NEW PRODUCTS

TEST & MEASUREMENT INSTRUMENTS

HANDHELD DMM/SCOPE

- Features dual-channel operation
- Stores three waveforms/channel in battery-backed memory


The Model 200 portable 21/2-lb DMM/oscilloscope provides dual-channel operation. It samples at 3M samples/sec max and offers autoranging. The unit lets you store three waveforms/channel in a battery-backed memory. You can also use ac power to run the unit. The display lets you set sensitivity, time-base, trigger source and slope, and mode parameters. The unit features manual override and an overload indicator. A printer interface lets you evaluate data and document your work on hard copy.



\$1645.

Leader Instruments Corp, 380 Oser Ave, Hauppauge, NY 11788. Phone (800) 645-5104; in NY, (516) 231-6900.

Circle No 420



ADC EVALUATOR

- Tests 10-bit ADC working at 20M samples/sec
- Employs an 80386 μP and an 80387 coprocessor

The PTS101 A/D characterization system evaluates ADC performance. The system targets applications such as high-speed data acquisition and image processing. Employing an 80386 µP and 80387 coprocessor, this evaluator can test ADCs working at 20M samples/sec with a 10-bit resolution. If your ADC has tighter specs, the evaluator provides IEEE-488 ports that let you drive high-performance generators and acquisition units. Using two internal cards, the system controller generates arbitrary and

data-acquisition functions. Matching probes are also provided. The vendor's software package is menudriven and features a 5-color display. \$18,950.

Tektronix Inc, Measurement Systems Div, Jack Murdock Industrial Park, Box 3500, M/S C1-894, Vancouver, WA 98668. Phone (800) 835-9433, ext 170.

Circle No 421

DSP EMULATORS

- Support TMS32020 and TMS320C25 processors
- Allow real-time no-wait-state execution to 40 MHz

The HP 64786A performs emulation-bus analysis and in-circuit emulation of systems based on the TMS32020 DSP. The HP 64786AL adds state and timing analysis. All units perform real-time no-wait-state emulation. In some systems that use the TMS320C25, you can operate without wait states at clock rates to 40 MHz max. The emulators include 64k words of dual-ported memory that you can allocate in



1k-byte blocks. You can configure the memory as emulation or target RAM or ROM, or as guarded memory. The units provide 8-level sequencing, time tags, prestore, and hardware-implemented code-coverage analysis. For developing multiprocessor systems based on any of 40 8-, 16-, and 32-bit μPs, a coordinated-measurement bus links to the vendor's 64000-UX-intermodule bus. This connection allows the cross-triggering of as many as 32 HP 64700-series analyzers. \$13,300 to \$16,500.

Hewlett Packard Co, 19310 Pruneridge Ave, Cupertino, CA 95014. Phone local sales office.

Circle No 422



SIMPSON UNIVERSAL FREQUENCY COUNTERS.

COUNT ON US FOR ACCURACY.

Simpson's new high precision, eight digit frequency counters give you an eye into the world of critical clock signals, RF oscillators and data communications.

Readings of frequency (to 1.3 GHz), frequency ratio (A/B), period, time interval (A to B) and totalized count combined with multi-channel triggering let you find circuit problems that might otherwise go unnoticed.

Simpson's *Professional Series* frequency counters allow for accurate measurements to be

taken on complex and noisy wave-forms by using the variable trigger controls and built-in, low pass filter. One model even offers you selectable attenuation and



AC/DC coupling, allowing the inputs to accommodate a range of signal characteristics. For more complex measurement situations involving two interdependent frequencies, an external clock can be substituted for the internal oscillator. This feature enables you to investigate a wide spectrum of frequencies—from computer circuitry to satellite communications.

Try the new lineup of *Professional Series* frequency counters from Simpson. It all adds up to accuracy and reliability.

Simpson Professional Series products are made in USA.

simpson

CIRCLE NO 104

TEST & MEASUREMENT INSTRUMENTS

DATA LOGGERS

- Record 200 readings/sec on internal floppy disk
- Handle 600 channels, using slave scanners

Data loggers in the 3531 series can store 200 measurement results/sec on a floppy disk in an internal drive. The ASCII files created are compatible with MS-DOS and Hewlett-Packard LIF (Logical Interchange Format). Without an expansion chassis, and without additional signal conditioning, the loggers can support 200 inputs, which can be a mixture of voltages (including those derived from thermocouples), currents, resistances (including the output of resistance thermometers and strain gauges), and binary phenomena (including on/off events, frequencies, and time intervals). The units also provide analog and digital outputs for control of machinery and processes. With the addition of slave chassis, you can expand these loggers to 600 channels. An RS-232C port is standard equipment; RS-422 and IEEE-488 ports are optional. Unit with keyboard, display, thermal printer, disk drive, and optional ports, \$9950; unit without options or peripherals, \$5150. Delivery, eight weeks ARO.


Schlumberger Instruments, 20 North Ave, Burlington, MA 01803. Phone (617) 229-4825.

Circle No 423

PC-BASED SCOPE

- Stores 4k or 16k samples
- Has 10-step software-controlled attenuators

The SDS-5000 digital storage oscilloscope plugs into the IBM PC bus or the vendor's instrument chassis. It includes dual A/D converters with a maximum sampling rate of 20M samples/sec; it stores 4k sam-



ples or an optional 16k samples. The unit's 10-step software-controlled attenuators allow you to set full-scale input sensitivity from 4 to 40 mV. The software lets you pretrigger and post-trigger, zoom, delay sweeps, add, subtract, and average signals. In addition, it allows you to make cursor measurements and store or retrieve waveforms on disk. \$1995.

Heath/Zenith, Hilltop Rd, Saint Joseph, MI 49085. Phone (616) 982-3200.

Circle No 424



This is only a part of our line of joysticks, trackballs, mouse controls, control grips and interface circuits. There's just too much to fit into a single picture. So we can probably supply exactly what you need, off the shelf.

On the other hand, it's quite possible that the control you need doesn't exist. Yet. That's why many of our most successful controls are designed to meet "impossible" requirements no standard control could come close to satisfying.

If you need an existing control, or one to be designed, you can depend on our superior performance and exceptional reliability.

For a complete picture of what we can do for you, call or write.



Measurement Systems, Inc. 121 Water Street, Norwalk, CT 06854, U.S.A. (203) 838-5561

SMALL NEWS



PC-based 8051 emulation priced to fit any engineer's desk...MicroICE. From \$1495.*

Need full in-circuit emulation capability for your 8051-family applications? We've got small news for you:

MicroICE™ emulators from MetaLink.

MicroICE fits your budget—and fits on your desk. They're the world's smallest, full-featured 8051 ICE units.

Loaded with capability, a compact, easy-to-operate MicroICE unit takes up less of your already crowded workspace—about ½ the space of competitive units. And, priced from \$1495 to \$2495, our 8051-family emulators cost up to **two-thirds less**.

The MicroICE line offers you the same high performance (compared to

our existing MetaICE specialized emulators) with even more features for about half the cost. So, you stretch your budget and give your designers more full-time emulation access—critical when you have multiple projects.

Why MetaLink? We're the 8051 experts. We understand how to maximize your design time—and get you the best performance from your 8051 application—so you can control your development deadlines.

And, you'll like the way we do business: Immediate delivery from our distributors, and comprehensive on-line technical help as close as your phone—direct from MetaLink.

- Full symbolic debug
- High-level language support
- · Menu-driven interface
- Real time and transparent emulation up to 16 MHz
- Single line assembler and disassembler
- 2-Kbyte trace buffer
- 16 break trace triggers
- Hardware supporting over 128,000 break conditions
- 16 to 64 Kbyte of program memory
- 16 to 64 Kbyte of external data memory
- Support of NMOS and CMOS devices

Special offer:

Evaluate MicroICE with your PC. Call Meta-Link for your free demo diskette. Or, for qualified customers, we offer a free, 10-day trial. Phone 1-800-METAICE. (1-800-638-2423)




MetaLink Corporation P.O. Box 1329 Chandler, Arizona 85244-1329 (602) 926-0797 TELEX: 4998050 MTLNK FAX: (602) 926-1198

* Price is U.S. list.
PC is a trademark of International Business
Machines Corp.

Distributors:

Advanced Digital Group (213) 598-9645 S.C.A
Comtel Instruments (216) 442-8080 W.PA, W.V., OH, MI, KY
Comtel Midwest (312) 392-4040 WI, IL, IN, MO, IA, KS, NE
Monument Technical (215) 884-3737 E.PA, NJ, DL

Oasis Sales (602) 277-2714 AZ, NM
Pen-Tech (919) 852-6000 FL, GA, MS, AL, TN, NC, SC
Syntek (206) 488-0394 WA, OR
Technisell (603) 893-1333 NH, VT, MA, ME, CT, RI
T-Squared (315) 463-8592 NY (except NYC)



A Wide Lineup Builds Quality and Reliability

From small to medium sizes, from character to graphic displays, Toshiba has a wide lineup of LCDs with high quality and superior readability. The new technology (H-TN and W-ST) offers you easier reading. And built-in controllers enable easy operation. There's even a module that accepts an EL backlight. So when you look for an LCD — look for Toshiba.

Character Display Type with Built-in Controller

High character height and easy-to-read display. Easy-to-use design thanks to high contrast TN.

Model name	Number of characters	Outline dimensions (mm)		
TLC-671	16 × 1	80 × 36 × 12		
TLC-241	16×1	80 × 36 × 12		
TLC-491	16×2	80 × 36 × 12		
TLC-731	16×4	87 × 60 × 12		
TLC-501	20 × 2	116 × 37 × 12.5		
TLC-721	20×4	98 × 60 × 12		
TLC-691	24 × 1	126 × 36 × 12		
TLC-771	24×2	118 × 36 × 12		
TLC-601	40 × 1	182 × 33.5 × 13		
TLC-591	40×2	182 × 33.5 × 13		
TLC-1001	40 × 4	221 × 76 × 12.5		
*TLC-673-JO	16×1	80 × 36 × 14		
*TLC-493-JO	16×2	80 × 36 × 14		

*Built-in LED backlight

Graphic Display Type with Built-in Controller

Clear display thanks to high contrast TN. Easy-to-use C/G, RAM and ROM built-in types.

Model name	Number of dots	Outline dimensions (mm)	Controller	Built-in EL module
TLC-1021	120 × 64	85 × 70 × 20	T6963C	TLC-1021-EO
TLC-682	160 × 64	125 × 50 × 18	T6963C	
TLC-711A	240 × 64	180 × 65 × 12	T6963C	TLC-711A-EC
TLC-1013	160 × 128	129 × 104.5 × 14	T6963C	TLC-1013-EO
TLC-1091	240 × 128	241 × 125.3 × 12	T6963C	TLC-1091-EO
TLC-1101	160 × 32	140 × 40 × 12	T6963C	_

We provide many options.

We can meet the need for customized products.

ST LCD Module

Clear and easy-to-read display with white background (W-ST). High contrast and wide viewing angle.

Model name	Number of dots	Outline dimensions (mm)	Controller	Built-in EL module
TLX-1021	120 × 64	85 × 70 × 20	T6963C	TLX-1021-EO
TLX-711A	240 × 64	180 × 65 × 12	T6963C	TLX-711A-EO
TLX-1013	160 × 128	129 × 104.5 × 14	T6963C	TLX-1013-EO
TLX-1301V	240 × 128	241 × 125.3 × 12	T6963C	The same and
TLX-1391	128 × 128	85 × 100 × 14	T6963C	TLX-1391-EO
TLX-341AK	128 × 128	93.2 × 86.6 × 12	(T6963C)	1007 200
TLX-1241	480 × 128	277 × 86 × 14	(T7779)	-
TLX-761	640 × 64	320 × 47 × 14	(T6963C)	100-46

): Recommended controller ICs.

In Touch with Tomorrow

TOSHIBA

Toshiba America, Inc., Chicago Office: 1101A Lake Cook Rd., Deerfield, IL 60015 Tel: 312-945-1500 Western Area Office: 2021 The Alameda, Suite 220, San Jose, CA 95126 Tel: 408-244-4070 Eastern Area Office: 25 Mall Road, 5th Floor, Burlington, MA 01803 Tel: 617-272-4352

EDN PRODUCT MART

This advertising is for new and current products.

Please circle Reader Service number for additional information from manufacturers.



Schematic and PCB Software

Create and revise schematics and PCBs quickly and simply with **HiWIRE-Plus**® and your IBM PC. Use symbols from HiWIRE-Plus's extensive library, modify them, or create your own quickly and pain-lessly. Netlist, bill-of-materials, and design-checking utilities are included. HiWIRE-Plus is \$895 and comes with a thirty-day money-back guarantee.

Wintek Corp.

1801 South St., Lafayette, IN 47904 (800) 742-6809 or (317) 742-8428

CIRCLE NO 325



CIRCLE NO 326

CABINETS. ENCLOSURES & POWER SUPPLIES For any need, Top Quality On-Time, On-Budget

- Complete line of enclosures & power supplies for single & dual
- 31/2" & 51/4" floppy disk half & full height hard disk
- Complete line of power supplies to match your needs
- Reliability of an industry leader
- All production done in house

QUANTITY & DEALER DISCOUNTS AVAILABLE



Electronics

18543 Parthenia St Northridge, CA 91324

Call (800) 635-5555 In CA (818) 993-4801

CIRCLE NO 329

The Best Programming Site money can buy. (Isn't the most expensive.)

The 135 is a gang and set programmer with Universal device capabilities, making obsolescence obsolete. It supports more devices than any other production programmer (virtually all EPROMs up to 40 pin). It has options to program logic devices, 40 pin micros and bipolar PROMs. On board memory is expandable to 2 MB. The 135 comes with 12 months of FREE updates plus an 18 Month Warranty. And, 4 operating modes plus DATA I/O* protocol compatibility mean unmatched

BYTEK, the leader in low cost/high performance technology.

Fax: 1-407-994-3615 Telex: 499 8369 BYTEK *DATA I/O is a registered trademark of DATA I/O Corporation.

Model 135-U \$1,895.00

Model 135-E \$995.00 (U.S.)



BYTEK CORPORATION Instrument Systems Division,

CIRCLE NO 330

Where unique data recording/storage solutions are expected." **CIRCLE NO 328**

3105 Patrick Henry Drive, Santa Clara, CA 95054

To advertise in Product Mart, call Joanne Dorian, 212/463-6415

free copy contact:

Precision Echo, Inc.

WIDEBAND

CATALOG

INSTRUMENTATION

RECORDER/REPRODUCERS

Airborne, shipboard and laboratory magnetic tape and disc recording/storage/reproducing systems for military and industrial applications are described in a new comprehensive catalog. For a



Lead Year's main SPSs products are:

- PS/2 models - 386 tower models
- 286/386-type PC/AT models Mini Tiger' super compacts

- Cubic Baby AT models
 PC/XT models
 O - OEM are welcome

your electronics great!











SWEDEN Contact us today for more information on how Lead Year's Tiger Power make

Lead Year Enterprise Co., Ltd.

3F, No. 481, Chung Hsiao E., Rd., Sec. 6,
Taipei, Taiwan, R.O.C.
TIGER POWER P.O. BOX 53-352 Taipei Tel: 886-2-7857852
PCXT PCAT. Bully AT and PSR are Information Bulleman Grand Grander Comp.

CIRCLE NO 331

SYNCHRONOUS/ASYNCHRONOUS

RS-422, RS-485, RS-232, CURRENT LOOP

SYNCHRONOUS COMMUNICATION

DMA facility

Byte sync, SDLC, HDLC

RS-422, RS-485, RS-232

ASYNCHRONOUS COMMUNICATION

- Selectable interrupt
- Address selectable
- Current Loop, RS-422, RS-485, RS-232





Leaders in Communication Technology

TOLL FREE: 1-800-553-1170

478 E. Exchange St. Akron, Ohio 44304 (216)434-3154 TLX:5101012726 FAX:(216)434-1409

CIRCLE NO 333

SCHEMA II Schematic Capture



FREE Demo Disk: 1-800-553-9119

SCHEMA's success is the talk of the CAE industry and thousands of satisfied SCHEMA owners know why. Incredible speed, ease of use, and power have made SCHEMA a best-selling schematic capture program for engineering professionals the world over.

Now, SCHEMA II is available.

SCHEMA II sells for \$495 and sup ports most common IBM PC/XT/ AT configurations. Please call today for a free SCHEMA II demo disk

OMATION

CIRCLE NO 334



UNIVERSAL I/O

This board has nine 8 bit parallel I/O ports (8255's) and 16 analog inputs. Each analog input has a 0-5 volt range, 8 bit resolution 20 Meg. input impedance. Conversion time is 200 us per channel. This board also has interrupt-timer circuitry, prototyping area. A dip switch is used to select the I/O address (32 are used). The ports interface via 16 pin ribbon cables. This board uses a full size slot. Order Part number 83-064A at \$229.95 from

John Bell Engineering, Inc. 400 Oxford Way Belmont, CA. 94002 (415) 592-8411

CIRCLE NO 335




CIRCLE NO 336




CONVERT RGB INTO COLOR COMPOSITE VIDEO

Now you can convert RGB computer signals into NTSC composite video with the ENC series of RGB Encoders. Three different models are available for compatibility with most analog and TTL RGB computers having 15 kHz scan rates. Output of ENCs can drive VCRs, projection TVs, and monitors. Interface cables and application assistance available. Only \$395.00 each.



Tel: (516) 499-0907 FAX: (516) 499-0321


CIRCLE NO 337



SIMPLIFY BOARD LAYOUT

MICRO/Q ceramic decoupling capacitors share board mounting holes with IC pins to simplify board design. Now add more active devices with increased density in the same space, or design the same package on a smaller board. Rogers Corp., 2400 S. Roosevelt St., Tempe, AZ 85282. 602/967-0624.

CIRCLE NO 338



E(E)PROM PROGRAMMER \$495 (Kits from \$165)

- No personality modules; Menu driven device selection.
- Built-in Eraser/Timer option (\$50); Conductive foam pad.
- Direct technical support; Full 1 year warranty.
- Stand alone duplication & verify (27XX parts). • Quick pulse algorithm (27256 under 60 sec).
- 27xx to 1 Mbit; 25xx; 68xx; CMOS; EEPROMS.
- 8741,-2,-4,-8,-8H,-9,-9H,-51,-C51,-52,-55, 9761 & more.
- IBM-PC, Apple, CPM or Unix driver; Autobaud RS232.
- Offset/split Hex, Binary, Intel & Motorola 8,16,32 bit.
- Manual with complete schematics.


VISA MC AMEX Call today for datasheets !!

B&C MICROSYSTEMS

355 WEST OLIVE AVE. SUNNYVALE, CA 94086 PH: (408) 730-5511 FAX: (408) 730-5521 TELEX: 984185

CIRCLE NO 339

To advertise in Product Mart, call Joanne Dorian, 212/463-6415



IEEE-488, PARALLEL, and SERIAL PORTS PLUS 4M BYTES of MEMORY

- Control any instrument. RS232 or '488.
- 4Mbytes of extended/expanded memory.
- Software library and memory manager.
- High speed DMA. Risk free guarantee.



Capital Equipment Corp. 99 South Bedford St. Burlington, MA. 01803

FREE demo disk. Call (617) 273-1818

CIRCLE NO 340

MIL-STD-1772 Certified



High speed 12-bit A/D converter

Full military or comm'l operation. Series 5200 are successive approximation devices with 13 or $50\mu s$ conversion times. Available in four input ranges: $\pm 5V$, $\pm 10V$, 0 to $\pm 10V$ and - 10V to 0. All devices have ± 1/2LSB linearity guaranteed over full operating temp range. Serial or parallel data output and 470mW(typ) power consumption. Second source.

Advanced Analog

a division of Inted 2270 Martin Avenue

Santa Clara CA 95050 (408) 988-4930

CIRCLE NO 341



MOUSE-TRAK The Stationary Alternative For Precision and Comfort!

This new space saving input device emulates both Microsoft and Mouse Systems RS-232 mice. With MOUSE-TRAK you can watch your screen and not your mouse running off your deek

running off your desk.

With a single connection to your computer, no power supply or mouse pad is

necessary.

MOUSE-TRAKS ergonomic design with soft wrist pad puts complete control of cursor and input at your fingertips.

Special features include speed control, allowing the user to toggle the resolution with a 4:1 ratio. User definable input keys offers added versatility and comfort. Pricing - \$139.00 - \$179.00

For further information

ITAC SYSTEMS, INC.

3121 Benton Drive, Garland, Texas 75042 U.S.A. 1-800-533-4822 Fax 214-494-4159

CIRCLE NO 342

DEBUG

Microprocessor software on your PC

uP Simulators for: 68HC11, 65C02, 8051, Z80, 6301, 6801, 8048, 6805, 6809, 8085, 6800.

- · Eliminates need for hardware debugging tools.
- · No waiting for EPROMs to program.
- \$95 each. Immediate delivery.

Mecklenburg Engineering

P.O. Box 744, Chagrin Falls, OH 44022 (216) 338-1900

CIRCLE NO 343



5W to 80W DC/DC Converter

- Compact size, low ripple 8 I/O isolation, min. 500VDC
- Single/dual/triple/quad output
- High Eff. up to 85% Excellent output regulation
- Over current & short current protection

Portable Computer Power Supply

- Compact size
- Universal input from 90-260 VAC continue
- AC/DC, DC/DC, battery charge, all in one
- Application for LCD/Plasma/EL portable computer

CIRCLE NO 344

KENSMAR INTERNATIONAL ENTERPRISE CO., LTD. 7FI-1, No. 160, Sec. 5, Nan-King E. Rd., Taipei, Taiwan, ROC Tel: (02)7636651 (REP) P.O.Box 67-822 Tix: 29805 KENSMAR Fax: 886-2-7678763




Serial data analysis on your PC.

Source and monitor modes: datascope and breakout box; ASCII and EBCDIC; trigger processing, live data display, adjustable buffer size. Custom cabling included.

800 562-8378

Advanced Computer Consulting, Inc. 700 Harris Street, Suite 101 Charlottesville, Virginia 22901

CIRCLE NO 345



Flow Charting II+ The New Plus for Fast Flowcharting

FLOW CHARTING is new! It's now

Flow Charting II+, with more speed + more functions + more printing options;

· 10 text fonts; 26 shapes; · Line mode can stop at a shape; Backspace key can erase a line to its origin; Free text entry anywhere, or select auto-centering; Vertical or horizontal printing; one chart or multiple charts.

Used by Fairchild, Bechtel and more than 500 other major corporations. Edit quickly and accurately — even major edits — with Flow Charting II+, the Specialist. See your retail store or call:

PATTON & PATTON

1-800-525-0082, Outside California 408-629-5376, California/International

CIRCLE NO 346



6800-Family Development Software

Combine our software and your editor for a powerful development system. Our C-Compilers feature a complete implementation (excluding bit fields) of the language as described by Kernigan & Ritchie and yields 30-70% shorter code than other compilers. Our Motorola-compatible Assemblers feature macros and conditional assembly. Linker and Terminal Emulator are included. **Wintek Corporation**, 1801 South St., Lafayette, IN 47904. (800) 742-6809 or (317) 742-8428

CIRCLE NO 347

angle) Sets The Pace!

Tango's ease-of-use, rich functionality and crisp output have brought tens of thousands of boards to life, quickly and



Start-to-finish design tools include:

\$495 Tango-Schematic With Library Manager, \$495 Tango-PCB 1 mil Grid, 9 Layers, Gerber Output, \$495 Tango-Route Autoroutes 90+%, Fast!, Tango-Tools 8 Money-Saving Utilities \$295

Let's discuss your design needs Toll-Free, or order a full function Evaluation Pkg, just \$10. VISA/MC.

800 433-7801 619/695-2000 Satisfaction guaranteed. ACCEL Technologies, 7358 Trade St., San Diego, CA 92121

CIRCLE NO 348

To advertise in Product Mart, call Joanne Dorian, 212/463-6415

EDN September 1, 1988

EPROM PROGRAMMER \$349



THE EP-1's A GREAT VALUE & HERE'S WHY:

- HE EP'-1'S A GHEAT VALUE & HEHE S WHY:

 READS, PROGRAMS, COPIES OVER 306 PROMS AND EEPROMS
 FROM 29 MANUFACTURERS INCLUDING 2716-27513, 2804-28256, 27011

 READS & WRITES INTEL, MOTOROLA, STRAIGHT HEX AND BINARY
 OPTIONAL HEADS PROGRAMM INTEL 874X, 8751, 87051, 8755
 MENU-DRIVEN CHIP SELECTION BY MFG & PIN; NO MODULES
 FAST, SLOW, QUICK PULSE PROGRAMMING ALGORITHMS
 SPILITS FILES BY BASE ADDRESS AND ODD/EVEN (16822 BIT)
 ALL INTELLIGENCE IN UNIT; 280 MICROPROCESSOR BASED
 5, 12, 5, 21, 25 VOLT PROGRAMMING FOR CMOS AND -A SUFFIX PARTS
 FREE PC-DOS SOFTWARE

 #RS232 TO ANY COMPUTER
 GOLD TEXTOOL 2IF SOCKET

 SAME DAY SHIPMENT

 GRERPATES, CHECKS CHECKSUM

- GOLD TEXTOOL ZIF SOCKET SAME DAY SHIPMENT
- ONE YEAR WARRANTY
- GENERATES, CHECKS CHECKSUMS
 TWO FREE FIRMWARE UPDATES
- MONEY-BACK GUARANTEE • UV FRASERS FROM \$34.95 CALL TODAY FOR MORE INFORMATION

BPMICROSYSTEMS

800/225-2102 713/461-9430 TELEX 1561477 10681 HADDINGTON #190 HOUSTON, TX 77043

CIRCLE NO 349



Z80,000™ AT-BUS SBC (ATZ80K)

Zilog's new Z320TM 32-bit pipelined CPU/MMU/CACHE unit is the heart of this PC-/ATTM coprocessor, passive-back-plane master, or stand-alone SBC. Get 2 to 5 MIPS performance at 10 MHz with 1M or 4M 32-bit burst-mode nowait-state RAM, 432-pin EPROM/EEPROM sockets for up to 512K 32-bit burst-mode no-wait-sate non-volatile storage. 2 RS-232 ports, 24 I/O lines, 3 16-bit counter/timers, an 8-bit DIP switch, and an SBX connector. Debugger, assembler, and C available

Call or write for more information

Single Board Solutions, Inc. 20045 Stevens Creek Blvd., Cupertino, CA 95014 (408) 253-0250

Z80,000 & Z320 are trademarks of Zilog PC-AT is a trademark of IBM

CIRCLE NO 350

RS-232C INTERFACE AND MONITORING EQUIPMENT CATALOG FROM B&B ELECTRONICS

WRITE or CALL for YOUR FREE COMPREHENSIVE B & B ELECTRONICS CATALOG TODAY!



tive text for B&B's complete line of RS-232 converters, RS-422 converters, current loop converters, adapters, break-out boxes, data switches data solitters short haul moderns, surge protectors, and much, much more. Most products meet FCC Part15J.

TODAY Your RS-232 needs for quality, serand competitive prices will be more

than met by B&B ELECTRONICS

direct fron

Manufacturer to you, no middleman!
Money-back guarantee! Same-day shipment! One-year warranty on products! Technical support available.


Vrite For Your FREE Catalog Today!

B&**B** electronics

1518 J Boyce Memorial Drive, P.O. Box 1040 • Ottawa, IL 61350 **Phone:** 815-434-0846

CIRCLE NO 751

CHIP COILS DC-DC CONVERTERS PULSE TRANSFORMERS



Our Chip Coils is good for your miniaturization & surface mounting. DC-DC Converters, pulse transformers & band pass filters is now complete with excellent functions. We also supply choke coils, power chokes, linearity coils, toroidal coils, pulse transformers, coupling transformers, power transformers and others. Send for details today.



OEM and Agent Inquiries Invited

ABC TAIWAN ELECTRONICS CORP.

No. 422, Sec. 1, Yang Fu Rd., Yangmei 32627, Taoyuan, Taiwan, R.O.C.

Tel: (03) 4788088, Telex: 32379 ABCEC Fax: (03) 4755503

CIRCLE NO 752

Analog Circuit Simulation

NEW IS SPICE/386 \$386.00

Runs on 386 PC's in protected mode with DOS 3.1 & up. Uses 287, 387 or W1167 coprocessor

- IS_SPICE, \$95.00: Performs AC, DC and Transient analysis; runs on all 80?86 PC's in real mode.
- PRE SPICE, \$200.00: Adds Monte Carlo Analysis, Sweeps, Optimization, libraries and algebraic parameter evaluation
- Intu_Scope, \$250: A graphics post processor works like a digital oscilloscope. Easy to use with all the waveform operations you will ever need.
- SPICE_NET, \$295: Schematic entry for any SPICE simulator. Automatically makes a SPICE net list and places Intu_Scope waveforms on your schematic.
- 30Day Money Back Guarantee

intusoft

PO Box 6607 San Pedro, CA (213) 833-0710 90734-6607

CIRCLE NO 753

A Lot For A Little

Reach 137,000 specifiers of electronics components, equipment, and systems for only \$780.

EDN Product Mart

TTC OFFERS HIGH QUALITY **BUT LOW COST PRODUCTS**



Connector

JEDEC Type

PLCC

SIMM is a Trade Mark of Wang's Laborotories.

SIMM Socket


- SIMM Socket (Special disign) -Signle Row & Double Rows (Vertical & Angle) All can be stacked.
 PLCC Socket -28p. 32p. 44p. 52p. 68p. 84p
 Edge Card Connector; -6p. 36p. 50p. 60p. 62p.80p.
- Edge Card Confector; 49, 39, 39, 39, 60, 52, 50, 86, 98p, 100p, 104p.

 I.C Socket -8p, 14p, 16p, 18p, 20p, 24p, 28p, 40p, 34p (16p & 18p can be changeable)-4 Rows
 Shunts (Mini Jumpers) -Open entry, close entry, pin Headers: 2p-40p (Single Row or Double Rows
 Straight or right Angle)

TTC Shih Hsin Precision Corp. Address: No. 284 JUN SHINN STREET, SHU-LIN TOWN, TAIPEI, TAIWAN, R.O.C. TEL: 886-2-6894655, 6894656 TELEX: 33210 TTCCO FAX: 886-2-6894657

CIRCLE NO 756

CIRCLE NO 754



VME PARALLEL I/O

This low cost VME board has two 68230 parallel interface/timer chips that give it six 8 bit parallel I/O ports, 8 handshaking lines, two 24 bit timers and interrupt circuitry. This board is a double high Eurocard DTB slave A24 or A32, D16. This board has a multipurpose prototype area. You can build your circuit on the board or build a piggyback board that plugs onto the four 34 pin headers. Two of the headers connect to the two 68230's I/O ports and the other two headers connect to the P2 connector..

ORDER Part Number 88-168A \$399.95 John Bell Engineering, Inc. 400 Oxford Way, Belmont, CA 94002 (415) 592-8411 9am to 4pm

CIRCLE NO 757

CIRCLE NO 755

FREE DEMO DISK Filter designs, plots, and selects component values for active.

passive L-C, and digital filters up to order 30. Full support for Allpass, Elliptic, Bessel, Butterworth, Chebyshev, and Inverse Chebyshev filters. Can design lowpass, highpass, bandpass, and bandstop filters. Filter will transform any filter function into the Z-domain for digital IIR filters. Screen editor allows modification of the transfer function for custom filters. Filter

does Monte Carlo analysis, Bode and Transient Analysis plots.


California Scientific Software

160 E. Montecito #E, Sierra Madre, CA 91024

(818) 355-1094

Fully menu driven, Filter is \$900 for the IBM PC.

To advertise in Product Mart, call Joanne Dorian, 212/463-6415



TIMING DIAGRAM SOFTWARE

Design Aid:

Quickly draw and edit waveforms. **Documentation Tool:**

Easily label waveform drawings.

IBM PC with mouse required.

To order Timing Diagram, send check or money order for \$149 to:

CEDRUS

10980 S. W. 81st. Tigard, OR 97223

(503) 620-2510

CIRCLE NO 758

UNIPRO™ UNIVERSAL PROGRAMMER AND MEMORY/TTL IC TESTER FOR PC/XT/AT



E(E)PROM (16K-1MB) PAL (20 & 24 pins) BIPOLAR 8741/42/48/49/50 CPU 87(C)51/44 CPU **DYNAMIC/STATIC RAM &** TTL TESTER Option: 4 Socket Adaptor only \$585 complete

Other products available. Individual programmers for E(E) PROM (up to 1MB), PAL, BIPOLAR, 8748 series, 8751 series, Memory/TTL Tester, and gang programmers with 4, 8, and 16 sockets. Also industrial quality EPROM Eraser with timer and safety switch is available. (erases 30 of 28 pin eproms at a time) OEM & Distributor welcome. 10% educational discount

473 Sapena Ct. #24 Santa Clara, CA 95054 Tel) 408-727-6995 FAX) 408-727-6996 1-800-541-1975

C-51

XELTEK

In-Circuit Emulators

M/C **AMEX**

CIRCLE NO 761

8051/52 PL/M-51



- Source level debug for PL/M-51 and C-51 IBM-PC/XT/AT/386 windowing interface with EGA 43-line, color, and mouse support Complex Hardware real-time breakpoints
- Hardware Trace Buffer with filtering control
- Program performance analysis
- 8 level hardware sequencer, Pass Counters
- NO PC PLUG-IN Boards

SIGNUM SYSTEMS 1820 14th St., Santa Monica, CA. 90404

(213)450-6096 telex: 362439

CIRCLE NO 764



I line x 24 Character

Probably just what you need: Accepts parallel and serial (RS232, RS422, 20ma loop) ASCII inputs. Selectable baud rates (300-9600). NEMA 12 bezel. Model

List price only \$499.00 (Also available, NEMA 4X SS bezel at \$689.00)



CHERRY ELECTRICAL PRODUCTS

an, IL 60087 • 312-360-3500 • FAX: 312-360-3566

CIRCLE NO 759

No WAITING FOR COMPLETE, LOW PRICED, CHIP COMPONENT KITS

CC-1 Capacitor Kit contains 365 pieces, 5 ea. of every 10% value from 1pt to .33μt. CR-1 Resistor Kit contains 1540 pieces; 10 ea. of every 5% value from 10Ω to 10 megΩ. Sizes are 0805 and 1206. Each kit is ONLY \$49.95 and available for Immediate One Day Delivery!

Order by toll-free phone, FAX, or mail. We accept VISA, MC, AMEX, COD orders, or company PO's with approved credit. Call for free detailed brochure.



Entire U.S.A. 1-800-854-0547

CIRCLE NO 762

'D" SIZE PLOTTER




- · Repeatability .001" Speed at 7" Per Second
- · Vacuum Paper Hold Down
- High Resolution Circles: Suitable for **PCB** Artwork

(415) 490-8380 ZERICON

STEVENSON BUSINESS PARK BOX 1669 • FREMONT, CA 94538

CIRCLE NO 765



PC488B

IEEE-488 INTERFACE CARD WITH BUILT - IN BUS ANALYZER

- GPRASIC package complements IBM/Microsoft BASIC interpreter and compiler to create a programming environment similar to HP desktop computers.

 Additional libraries of over 20 high level 488 dedicated functions for C, Pascal or Fortran available (\$50).

 Powerful menu-driven bus analyzer, which can run in the foreground or in the background while 488 programs or commands are executed, features program stepping, break points and real time bus data capture (4k circular buffer) instant toggling between foreground and Analyzer screen.

 Complete Talker/Listener/Controller capability.

 Dipswitch selectable Base Address, IRQ, DMA


VISA MC AMEX Call today for datasheet!!

B&C MICROSYSTEMS

355 West Olive Ave, Sunnyvale, CA 94086 PH: (408)730-5511 FAX: (408)730-5521 TELEX: 984185

CIRCLE NO 760

WINPOINT A FULL RANGE OF CONNECTORS & SOCKET



IC SOCKETS-8, 14, 16, 18, 20, 22, 24, 28, 40, 42, 48 contact LCC SOCKET-68 contact PLCC SOCKET-28, 32, 44, 52, 68, 84 contact series

Winpoint Electronic Corp.

P.O.Box 89-80, Taipei, Taiwan, R.O.C. Office: No. 47, Chi-Wei St., San Chung City, Taipei, Taiwan, R.O.C. Tel: (02) 986-0208, 984-0209 Telex: 34227 WINPOINT Fax: 886-2-9838555

CIRCLE NO 763

Macintosh II, SE, Plus Universal Cross-Assembler \$299.00



Includes editor and universal cross-assembler instruction tables and example source programs for ALL of the following MPU's, MCU's, and DSP's:



Generates intel hex, Motorola-S records, and straight binary output compatible with most EPROM programmers and in-circuit emulators.

Available for MS-DOS systems and the ATARI ST series. Inquire about our MEMULATOR In-Circuit EPROM Emulators.

MEMOCOM DEVELOPMENT 0 0 L S

1301 Denton Drive Carrollton, Texas 75006 (214) 466-9906

CIRCLE NO 766




Books for calculator applications

The vendor is offering profession-specific solution books for the HP-27S and the HP-28S. The five books available for the HP-27S are titled Real-Estate, Banking, and Leasing; Business Finance and Accounting; Marketing and Sales; Personal Investment and Tax Planning; and Technical Applications. For the HP-28S calculator, the titles are Algebra and College Math; Calculus; Electrical Engineering; Probability and Statistics; Vectors and Matrices; and Mathematical Applications. \$9.95 each.

Hewlett-Packard, Corvallis Div, 1000 NE Circle Blvd, Corvallis, OR 97330.

INQUIRE DIRECT




Brochure covers µP development products

The 12-pg brochure, *Microprocessor Development Environments*, presents an overview of the vendor's in-circuit emulation products and software development tools. It

provides development-tool solutions for embedded μP designs, as well as product information. Photographs and charts complete the publication.

Applied Microsystems Corp, Box 97002, Redmond, WA 98073.

Circle No 400



App note explains switched-capacitor filters

AN3: Applications for Switched-Capacitor Building Blocks discusses part values for a variety of tested circuits using switched-capacitor building blocks. Among the circuits detailed are a ±5V precision instrumentation amplifier, a variable-gain amplifier, relative-humidity signal conditioners, an LVDT (linear variable differential transformer) signal conditioner, and A/D and V/F converters. It also provides complete schematics.

Linear Technology Corp, 1630 McCarthy Blvd, Milpitas, CA 95035.

Circle No 401

Summary and comparison of ADC performances

The 2-pg application note, AD7578 and AD7582 Performance with Reduced V_{DD} Supply (12V $\pm 10\%$), summarizes typical performance at 12V V_{DD} for 100- μ sec, 12-bit ADCs and compares it with the data-sheet



specifications for 15V operation. Among the topics included are accuracy, timing, power-supply current, and logic inputs and outputs. Also included are a table showing accuracy results and a diagram illustrating the interfacing of the ADCs to an IBM PC.

Analog Devices, Literature Center, 70 Shawmut Rd, Canton, MA 02021.

Circle No 402

Report helps you evaluate communications technologies

The 390-pg volume, The Impact of Evolving Communications Technologies, helps you assess the impact of major communications developments on public and private networks. The table of contents provides a single-source reference to subjects ranging from artificial intelligence to voice synthesis and recognition. The report presents applications, economic and technical considerations, and technical comparisons. Each section of the book details a technology, such as local area network/metropolitan area network (LAN/MAN) and wide-band services, fiber optics, ISDN, and virtual networks. Tables, diagrams, and flow charts illustrate the text.

Bellcore Licensing, 290 W Mt Pleasant Ave, Livingston, NJ 07039.

Circle No 403

A proprietary process and long analog tradition have made Micro Power Systems a leader in CMOS flash converters. Our rapid success has caused such growth that we have immediate career opportunities available for experienced individuals to join us in the design of ADC's, DAC's and ASIC circuits, as well as in the customer support arena.

ANALOG IC PROJECT MANAGER/LEADER

You should have 4+ years of IC design experience with a strong analog background. Hands-on management skills are required in order to perform all aspects of IC development from product definition through production release. Please respond to Dept. PM.

ANALOG IC DESIGNERS

To qualify, you must possess 1-3 years of IC design experience with the ability to spec, design and simulate analog functions and subcircuits. Knowledge of CMOS and bipolar processes would be a plus. Please respond to Dept. AD.

APPLICATIONS ENGINEER

Responsibilities will include technical support of customers, writing applications notes and conducting customer and sales training seminars. You will also support our marketing department in the definition and introduction of new products. We require excellent oral/written communication skills and 2+ years of relevant experience. Please respond to Dept. AE.

ALL POSITIONS REQUIRE A BS OR MS IN ELECTRICAL ENGINEERING OR EQUIVALENT.

We offer a small, dynamic company atmosphere with expanding opportunities, as well as a comprehensive compensation package. Please send your resume to Micro Power Systems, Professional Staffing, 3151 Jay Street, Santa Clara, CA 95054-0965. No phone calls, please. We are an equal opportunity employer.



MICRO POWER SYSTEMS

NATIONWIDE

2000 OPENINGS **ENGINEERS** MANAGEMENT

Salaries from 30K-100K exclusively employer fee paid These current openings need to be filled now Please send your resume today to:

Personnel Recruiting Placement Association 16 W. Pacific Ave., Suite 9 Henderson, NV 89015 OR 2020 Cheviot Hills Dr. Springfield, OH 45505

> OR 3824 Barrett Dr., Suite 205 (A) Raleigh, NC 27609 (702) 564-9007

PARALLEL **PROCESSING**


B.S. or M.S. in EE and up to 10 years experience in microcomputer applications. Desire a knowledge of digital hardware and some background in board level computers. The position involves primarily software development with proficiency in assembly language (preferably 68000) required. Also desire some experience with either Pascal or C and UNIX operating systems. Exposure to parallel processing a plus.

Sverdrup Technology, Inc. is a company engaged in providing skilled scientific, engineering and technical support for PROPULSION, ENERGY, and SPACE programs for NASA Lewis Research Center in Cleveland,

Located in Middleburg Hts., Ohio, a pleasant smalltown suburb of Cleveland, we offer a low cost of living and a high quality of life. We are minutes away from Lake Erie and water sports, and are surrounded by the famous Emerald Necklace Natural park system.

If you qualify and are interested in joining our team of professionals, please submit your resume to: Bruce Cantwell, Personnel Manager, SVERDRUP TECHNOLOGY, INC., P.O. Box 30650-Midpark Branch, Middleburg Hts., OH 44130. Principals Only. No Phone Calls, Please. An Equal Opportunity Employer M/F/H/V.

Sverdrup Sverdrup Technology, Inc.



It's easy for companies to see what's going on around them.

Market trends. New product developments. Competitive activities. What sets Motorola's Semiconductor Products Sector apart is focus on our internal force. The power of a strong partnership with our people. People who are the source of innovation.

It is this

unwavering belief in employee participation and recognition that is the foundation of our technical achievement. That invites our continued growth and success.

When you enter Motorola's Semiconductor Products Sector, you enter a storm of activity that excites the imagination of the designing and discriminating mind.

Specific needs for development and support of our 88000, 68000 and 56000 product lines has created a world of opportunities in Motorola's High-End Microprocessor design organization in Austin, Texas for:

MASK LAYOUT DESIGNER

Work with schematics, logic diagrams and engineering notes to plan and execute topological design of VLSI MPU circuits. Support revisions of existing design and direct design staff. Requires Associate Degree and 2-5 years related experience.

CIRCUIT DESIGN ENGINEERS

Perform design and analysis of high speed CMOS circuits related to microprocessors and peripherals, and assist test/product engineers. Requires BSEE and 2+ years experience with knowledge of microprocessor functionality and characteristics.

32-BIT PRODUCT MANAGER

Responsible for the success of the 32-bit Product Line. Duties include forecasts, price strategy, competitive analysis, cost analysis, new product introduction, first level technical contact with customers and intra company representation. Requires BSEE and 3+ years experience in computer systems; MBA helpful.

PRODUCT ENGINEERS

Responsible for yield/cost management and improvement, characterization of products to support design, manufacturing and quality improvements, and customer interface. Requires BSEE and 1-5 years experience with knowledge of microprocessor functions and characteristics.

SOFTWARE ENGINEERS

Design, implement and maintain operating systems, compilers, assemblers, simulators and run-time support packages for the M68000 and M88000 product families. Requires BSCS, BSEE or equivalent and programming experience in a UNIX C environment and/or Graphics.

CAD/CAE ENGINEERS

Design, develop and maintain the CAD/CAE tools for integration to design engineering system. Requires strong knowledge of related tools and standards.

SYSTEMS DESIGN ENGINEERS

Responsible for definition/development of 16/32 bit microprocessor and peripheral elements/various combinations and development of design methodology for ASIC based design. Requires BSEE/BSCS and 3-5 years experience or MSEE/MSCS and 1-3 years experience including strong background in computer architecture and High Level Language. Experience in ASIC software tool development is a plus.


In addition to the highly competitive salaries and benefits of Motorola, our desirable Austin location offers rolling hills, clear blue lakes, affordable housing and warm Texas hospitality. Explore one of these opportunities now. Send your resume to the attention of Brett Rodgers, Motorola Semiconductor Products Sector, Dept. HE988, 1112 W. Ben White Blvd., Suite 200, Austin, TX 78704.



MOTOROLA

Semiconductor Products Sector

An Equal Opportunity/Affirmative Action Employer



American history?

It doesn't have to be. The American semiconductor chip need not slip into the Smithsonian as merely a faded icon of bygone U.S. ingenuity and technical leadership.

History is what you make it.

And SEMATECH, a new developmental manufacturing collaboration between government and industry, plans to return the U.S. to a preeminent position in semiconductor manufacturing.

The biggest companies in the business are with us, such as IBM, Hewlett-Packard and AT&T.

Now we need you. SEMATECH is hiring the top minds in the industry to join our 5-year, billion-dollar-plus commitment. Here at our advanced laboratories in Austin, Texas, you'll join a skilled staff in the development of new manufacturing techniques.

With your help, we can put the American semiconductor back on the upswing. Before it goes down in history.

Assembly

Openings are available for Manufacturing and Ceramic Engineers.

Test

Several openings exist for Test Engineers to work with IBM and AT&T during technology transfers.

Total Quality Deployment

We're in need of a Vendor QA Manager, an Analytical Chemist, and Engineers/Technicians in the areas of: Failure Analysis - Electrical/Physical Failure Analysis - SEM/EDX - Electron/Ion Beam Analytical Instrumentation - Chemical Analysis & Instrumentation - Gas Analysis - Reliability Engineering & Stress.

Manufacturing Systems Development

Seek individuals qualified to work in the positions and areas of: Manager, System Transfer & Sustaining - Manager, Business Systems - Personnel Computer Support - Engineering Systems Statistician - Senior Analyst, Data Base and Data Architecture - Analyst, Specification & Control - Network Services Specialist - Manager, Automation & Robotics - Case and End-user Tools Specialist - Computer Operations Supervisor.

Strategic Planning Manager and Competitive Analysis Engineer

Requires extensive experience in semiconductor analysis, reverse engineering, planning and setting strategies. Advanced degrees required.

Program Managers

Planning, production control, budget, scheduling, and manufacturing and engineering coordination for program modules of all aspects of semiconductor manufacturing.

Technicians

Lithography Development Techs to assist engineers installing and qualifying photolithography equipment. Contamination Techs to help measure purity of process chemicals, gasses, and ultrapure water. Etch Techs to help install and start-up develomental/pilot line and supporting equipment.

Circuit Design Engineers

Will work on manufacturing demonstration vehicle which is primarily concerned with manufacturing interface design problems.

Development Specialists

Seek a variety of individuals with specialized experience in the areas of: Standards & Metrology - Optical/Electrical Properties Physical Properties - Auger Spectroscopy - X-Ray Photoelectron Spectroscopy - Secondary Ion Mass Spectrometry - Rutherford Backscattering - Scanning Electron Microscopy - Transmission Electron Microscopy.

Facilities

Openings available for: Fab Support Manager - Facilities Planning Manager - Manufacturing Engineer - Facilities Engineer - Contamination Control Engineer - Planning Engineer - Facilities Contamination Control Manager.


SEMATECH offers competitive salaries and an advanced manufacturing environment in the attractive, growing city of Austin. For immediate consideration, send resume to: SEMATECH, 2706 Montopolis Drive, Austin, TX 78741. Equal Opportunity Employer.



A World of High Technology

Beneath the Sea

At GE Electronic Systems Department, our engineers are continually being challenged with projects of national scope. Our technological leadership is evidenced in AEGIS, the US Navy's Surface Fleet's automated shipboard combat system, and with the development of AN/BSY-2, the fully integrated combat system for the SSN 21 SEAWOLF, the Navy's newest attack submarine. The challenge continues and we seek leaders to join our team of professionals...



- **SENIOR SYSTEMS ENGINEERS**
- **SENIOR SOFTWARE ENGINEERS**
- **SENIOR COMBAT CONTROL ENGINEERS**

- **SENIOR RADAR SYSTEMS ENGINEERS**
- **SYSTEMS ENGINEERS**

And Beyond...

- DIGITAL DESIGN ENGINEERS
- **SOFTWARE DESIGN ENGINEERS**
- ELECTRONIC PACKAGING DESIGN ENGINEERS

On the Surface with AEGIS



Join GE ESD and enter a world in which you'll receive the recognition for your achievements that you deserve, including a competitive salary and comprehensive benefits package including dental and tuition.


We are located in Moorestown, New Jersey, a pleasant suburban environment just 15 miles outside of Philadelphia with close proximity to leisure activities of the shore and mountains.

Forward your confidential resume to: H. Ford, GE-ESD, Bldg. 127-102, Moorestown, NJ 08057. Equal Opportunity Employer. U.S. Citizenship Required.



GE Aerospace

Electronics Systems Department





Join The American Team

At Micron, we're committed to making American-made memory products the standard of the industry, and as part of our team, you'll work on the leading edge of sub-micron, multi-megabit technology. Located in the beautiful foothills of Boise, Idaho, Micron offers a state-of-the-art environment — both on and off the job — and a quality of life, and diversity of recreational opportunities, that equals the quality of our products. Make a memorable career move and choose Micron — the team that makes great American memories.

Engineering Opportunities

- Device Physics
- Thin Films
- Implant
- · Analytical Chemist
- · E-Beam and Optical Lithography
- Field Applications
- Test
- Product
- · QA/FA
- Material Science
- Modeling/Simulation/Characterization
- · PVD
- · Dry Etch
- CVD

Research & Development Projects

- Planar Sub-Micron Contacts/Vias
- Sub-Micron CMOS Transistors
- · Reliable Metal Interconnect
- Source, Drain and Poly Self-Aligned Silicide
- Local Interconnection
- E-Beam Direct Exposure Systems
- Aggressive N + /P + Space
- · High Pressure Oxidation
- · Rapid Thermal Processing
- Multi-Level Metalization
- Ultra-Clean Technology
- Advanced Metrology
- Hi-Energy Implantation
- · Ultra-Thin Dielectric Technology
- 3D Technology
- · Zero SER Technology
- · Facility Automation

Production

- CMOS DRAMS (256K, 1M, 4M, 16M)
- Fast SRAMS (16K, 64K, 256K, 1M)
- High Density Video RAMS (256K, 1M)
- Customer Supplied High Density Logic for use in Rel Sensitive Applications
- ASM Memory


Reliability Qualification

- Advanced Smart Burn-In Capability
- 5 Million Device Hours Per Day/ Per Part/Per Process
- · Full Process/Product Qualification



MICRON TECHNOLOGY, INC., 2805 E. COLUMBIA ROAD BOISE, IDAHO 83706 (208) 383-4038

N EQUAL OPPORTUNITY/AFFIRMATIVE ACTION EMPLOYER



Toward Man's Full Life®

Medtronic Inc. is one of the world's leading producers of biomedical devices. We are currently seeking qualified professionals for the following positions:

SOFTWARE ENGINEERING MANAGER

Our Pacing Systems Group has an opportunity for an engineering professional to manage an Instrumentation Group. The position is responsible for the design and development of new instruments for the Pacing Business Unit. Product responsibility is from conception through manufacturing start experience and involves extensive interface with Marketing and Product Planning.

The key position requires a BSCS or BSEE, experience designing instruments with Embedded Real-Time Software and 3 years management experience of software based products. MSCS with BSEE undergraduate preferred.

SOFTWARE ENGINEERS

Our Pacing Systems Group has several excellent openings for software engineering professionals to work in our Instruments Development and Support Group. This group is seeking engineers at various experience levels to participate in the development of software for several of our instrument products. These professionals should possess:

- BS in Computer Science or Computer Engineering
- 3+ years experience in software development on instrumentation or small scale systems
- Software test experience
- Extensive experience with C or other high level languages

For our principal software engineering positions, we require 5+ years of experience with demonstrated leadership abilities.

PRINCIPAL ELECTRICAL DESIGN ENGINEER

Our Product Development organization within the Pacing Systems Group has immediate openings for electrical engineers to work with IC designers to develop state-of-the-art analog circuitry. These positions also provide system development, physiological testing, as well as provide technical work direction to a design and development team.

These key positions require a BSEE with 5 years design experience. Medical electronic experience and an MSEE are extreme positives.

SENIOR ELECTRICAL DESIGN ENGINEER

We currently have openings in our Product Development Group for Senior Electrical Design Engineers to work with IC designers to develop state-of-the-art digital circuitry. Responsibilities include systems development, simulation and timing analysis of digital CMOS integrated circuits.

Qualified candidates will have a BSEE with a minimum of 3 years design experience. Medical electronics experience and an MSEE are a plus.

Medtronic Inc. offers a highly competitive compensation and benefit package plus the opportunity for personal recognition in an environment where new ideas and initiative are encouraged. To be considered for any one of these positions, please send your resume in confidence to: Jan Kelly, MEDTRONIC INC., 7000 Central Avenue N.E., Minneapolis, MN 55432.



An Equal Opportunity Employer M/F

EDN's CHARTER

EDN is written for professionals in the electronics industry who design, or manage the design of, products ranging from circuits to systems.

EDN provides accurate, detailed, and useful information about new technologies, products, and design techniques.

EDN covers new and developing technologies to inform its readers of practical design matters that will be of concern to them at once or in the near future.

EDN covers new products

- that are immediately or imminently available for purchase
- that have technical data specified in enough detail to permit practical application
- for which accurate price information is available.

EDN provides specific "how to" design information that our readers can use immediately. From time to time, EDN's technical editors undertake special "hands-on" projects that demonstrate our commitment to readers' needs for useful information.

EDN is written by engineers for engineers.



275 Washington St Newton, MA 02158 (617) 964-3030

BUSINESS/CORPORATE STAFF

Peter D Coley VP/Publisher Newton, MA 02158 (617) 964-3030; Telex 940573 Ora Dunbar, Assistant/Sales Coordinator

Deborah Virtue Business Director Newton, MA 02158 (617) 964-3030

Mark J Holdreith Advertising Sales Director Newton, MA 02158 (617) 964-3030 Heather McElkenny, Assistant

NEW ENGLAND John Bartlett, Regional Manager Chris Platt, Regional Manager 199 Wells Ave Newton, MA 02159 (617) 964-3730

STAMFORD 06904 George Isbell, Regional Manager 8 Stamford Forum, Box 10277 (203) 328-2580

NEW YORK, NY 10011 Daniel J Rowland, Regional Manager 249 West 17th St New York, NY 10011 (212) 463-6419

PHILADELPHIA AREA Steve Farkas, Regional Manager 487 Devon Park Dr, Suite 206 Wayne, PA 19087 (215) 293-1212

CHICAGO AREA Clayton Ryder, Regional Manager Randolph D King, Regional Manager Cahners Plaza 1350 E Touhy Ave, Box 5080 Des Plaines, IL 60017 (312) 635-8800

DENVER 80206 John Huff, Regional Manager 44 Cook St (303) 388-4511

DALLAS 75243 Don Ward, Regional Manager 9330 LBJ Freeway, Suite 1060 (214) 644-3683

SAN JOSE 95128 Walt Patstone, Regional Manager Bill Klanke, Regional Manager Philip J Branon, Regional Manager James W Graham, Regional Manager 3031 Tisch Way, Suite 100 (408) 243-883

LOS ANGELES 90064 Charles J Stillman, Jr Regional Manager 12233 W Olympic Blvd (213) 826-5818

ORANGE COUNTY/SAN DIEGO 92715 Jim McErlean, Regional Manager 18818 Teller Ave, Suite 170 Irvine, CA (714) 851-9422

PORTLAND, OREGON 97221 Pat Dakin, Regional Manager Walt Patstone, Regional Manager 1750 SW Skyline Blvd, Box 6 (503) 297-3382

UNITED KINGDOM/BENELUX Jan Dawson, Regional Manager 27 Paul St London EC2A 4JU UK 44 01-628 7030 Telex: 914911; FAX: 01-628 5984

SCANDINAVIA Stuart Smith 27 Paul St London EC2A 4JU UK 01-628 7030 Telex: 914911; FAX: 01-628 5984

FRANCE/ITALY/SPAIN Alasdair Melville 27 Paul St London EC2A 4JU UK 01-628 7030 Telex: 914911; FAX: 01-628 5984

WEST GERMANY/SWITZERLAND/AUSTRIA Wolfgang Richter Sudring 53 7240 Horb/Neckar West Germany 49-7451-7828; Telex: 765450 EASTERN BLOC Uwe Kretzschmar 27 Paul St London EC2A 4JU UK 01-628 7030 Telex: 914911; FAX: 01-628 5984

FAR EAST Ed Schrader, General Manager 18818 Teller Ave, Suite 170 Irvine, CA 92715 (714) 851-9422; Telex: 183653

HONG KONG John Byrne & Associates Ltd. 1613 Hutchison House 10 HGarcourt Road Central Hong Kong Tel. 5-265474 Thx: 61708 WEDIN HX Fax: 5-8106781

JAPAN
Kaoru Hara
Dynaco International Inc
Suite 1003, Sun-Palace Shinjuku
8-12-1 Nishishinjuku, Shinjuku-ku
Tokyo 160, Japan
Tel: (03) 366-8301
Telex: J2322609 DYNACO

KOREA Kim Kyong-Hae, BK International Won Chang Bldg, 3rd Floor 26-3 Yoido-dong, Youngdungpo-ku Seoul 150, Korea Tel: 785-6665; FAX: 784-1915 Telex: K32487 BIZKOR

SINGAPORE/MALAYSIA/INDONESIA/THAILAND/ THE PHILIPPINES/AUSTRALIA/NEW ZEALAND Asia Pacific Media House PTE Ltd Peter Cheong 100 Beach Rd #24-03 Shaw Tower Singapore 0718 Tel: 2915354; Telex: RS 50026 MESPLY

TAIWAN
Acteam International Marketing Corp
6F, No 43, Lane 13
Kwang Fu South Rd
Mailing Box 18-91
Taipei, Taiwan ROC
760-6209 or 760-6210
Telex: 29809; FAX: (02) 7604784

PRODUCT MART Joanne Dorian, Manager 249 West 17th St New York, NY 10011 (212) 463-6415

CAREER OPPORTUNITIES/CAREER NEWS
Roberta Renard, National Sales Manager
(201) 228-8602
Janet O Penn, Eastern Sales Manager
(201) 228-8610
103 Eisenhower Parkway
Roseland, NJ 07068

Ellen Sherwood, Western Sales Manager 12233 West Olympic Blvd Los Angeles, CA 90064 (213) 826-5818

Maria Cubas, Production Assistant (201) 228-8608

Susan M Campanella, Advertising/Contracts Coordinator Nan Coulter, Advertising/Contracts Coordinator (617) 964-3030

William Platt, Sr, Vice President, Reed Publishing USA Cahners Magazine Division

Terry McDermott, President, Cahners Publishing Co Frank Sibley, Group Vice President, Electronics/Computers Tom Dellamaria, VP/Production & Manufacturing

Circulation Denver, CO: (303) 388-4511 Sherri Gronli, Group Manager Eric Schmierer, Manager

Reprints of EDN articles are available on a custom printing basis at reasonable prices in quantities of 500 or more. For an exact quote, contact Joanne R Westphal, Cahners Reprint Service, Cahners Plaza, 1350 E Touhy Ave, Box 5080, Des Plaines, IL 60018. Phone (312) 635-8800.

ADVERTISERS INDEX

ABC-Taiwan Electronics Corp 240	Itac Systems Inc
ACCEL Technologies Inc	ITT ElectroMechanical
Advanced Analog	Components Worldwide 4 ITT Pomona Electronics 46
Consulting Inc	JMR
Advanced Micro	John Bell Engineering 238, 240
Devices	John Fluke
Advantest America60	Manufacturing Co Inc*6
Amerace Corp	Kensmar
AMP48-49	Kepco Inc
Amperex Electronic Corp*223	KO Sheng**
Analog Devices Inc 173, 175, 177,	Leadyear Enterprise Co Ltd 238
179, 180-181 Ancot Corp	Leasametric Inc
Ancot Corp	Linear Technology Corp 209-210
Apex Microtechnology Corp 45 Apollo Computer 198-199	LTX Corp
Applied Microsystems Corp 14-15	Marshall
Astec	Matra Design Systems
Bayer AG**	Maxell
B&B Electronics Mfg Co 240	Measurement Systems Inc 234
B&C Microsystems 238, 241	Mecklenburg Engineering 239
BP Microsystems 240	Memocom
Bruel & Kjaer Instruments 211	Mentor Graphics Corp 10-11
Burr-Brown Corp	MetaLink Corp
Bytek Corp	Micro Dimensions Inc
CAD Software Inc	MicroCASE20
Caldock Electronics Inc 112, 113	Micron Technology Inc
Calcomp	Microtek Lab** 6 Mini-Circuits
Capital Equipment Corp 239	Laboratories 26, 27, 205, 254
Casio Inc	Mitsubishi Electronics America
Cedrus	Inc/Semiconductor Div
Cherry Electrical	National Instruments 50
Products Inc	National Semiconductor
Chips and Technologies	Corp
Comlinear Corp 202, 220	NEC Corp
Communication Specialists 241	Nicolet Test Instruments Div
Communications	Octagon Systems
Specialties Inc	Omation Inc
DATA Inc	Orion Instruments
Data I/O Corp	Otto Controls
Deltron Inc	
Elan Digital Systems 106	Patton & Patton
Electronic Solutions	Phillips Components
Ericsson Components	Inc**
E-T-A Circuit Breakers	Plessey Semiconductor 115-117
Society	Powerex Inc
Fujitsu	Precision Interconnect
Microelectronics Inc 129-131	Precision Monolithics Inc
GE Solid State 18-19, 40-41,	Qua Tech Inc
152-153	Quantum Corp
Golem Systems	Raytheon Semiconductor Div 76
Good Fold**	Ready Systems54-57
Harris/3M	Rogers Corp
Harting Electronics 194-195	SGS-Thomson
HEI Inc	Microelectronics
109, 127, 171	Siemens AG, Karlsruhe**
Hitachi America Ltd* 134-135	Siemens Components Inc*
Intel/Arrow Electronics 226, 227	Signum Systems
International Rectifier	Simpson Electric Co
Intronics	Single Board Systems 240
Intusoft	Sipex Corp-Hybrid Systems 78
I/O Tech Inc	Source Electronics Corp

Spectrum Software	
Sprague Electric Co 65	
Stanford Applied Engineering 111	1
Stanford Research	
Systems Inc	3
Tadpole Tech	
TEAC Corp**	+
Tektronix Inc 8, 155-158, 159-160)
Telebyte Technology Inc 100)
Teledyne Philbrick	١
Teradyne Inc	1
Thomas and Betts Corp39	
Topaz Semiconductor	
Toshiba America Inc28-29	
Toshiba Corp)
TRW/LSI Products Inc	3
VTC Inc	2
Wavetek	3
Winpoint Electronic Corp241	1
Wintek Corp 237, 239	4
Xeltek	
Xicor Inc69	
Zax Corp58	
Zericon	1
Ziatech Corp	1
Zilog Inc	7

Recruitment Advertising . . 243-248

GE-ESD Kevex Corp Micron Technology MicroPower Systems Motorola Sematech

*Advertiser in US edition
**Advertiser in International edition

This index is provided as an additional service. The publisher does not assume any liability for errors or omissions.

"EDN MAGAZINE'S PRODUCT MART SECTION IS HELPING US BECOME A LEADER IN OUR MARKETPLACE."

Raymond J. Schnorr Vice President of Marketing ACCEL Technologies

As Vice President of Marketing, Ray Schnorr

is responsible for marketing ACCEL Technologies' affordable, professional software that meets the design needs of electrical engineers. He operates on a fixed budget and demands results. "When it comes to buying media, I'm interested in two things: performance and price. With EDN's Product Mart section, I pull high-volume sales leads and meet my budget," says Schnorr.

In nineteen months, ACCEL has sold 5000 software packages to 3000 sites. "Our ½-page Product Mart ads in EDN magazine are allowing us to reach our target audience." And Schnorr sees more for EDN and ACCEL. "We have significant growth plans for ACCEL, and running bigger ads in EDN will be part of the strategy to get there.



EDN magazine works for ACCEL Technologies. It can work for you.

EDN

Where Advertising Works

Index is Now on Floppy Disk! Now you can utilize EDN magazine's Technical

Article Database Index right on your computer screen. When used with your IBM PC or compatible computer, this new floppy-based index gives you all the benefits of our printed index . . . and more:

• Fast computer searches and sorts

 AND and OR capabilities to precisely specify your search criteria

· Printout of search results


The index lists articles printed in EDN, EDN NEWS, Electronic Design, Electronics, Electronic Products, Computer Design, and ESD. Two installments are available—covering articles published from May to October, 1987, and from November 1987 to April 1988.

EDN'S index is compatible with most popular programs, including 1-2-3 from Lotus, MailMerge from MicroPro International, and dBASE from Ashton-Tate. It also works with Buttonware, Inc.'s PC-File+, a "shareware" database manager that you can order from us.*

Our Technical Article Database Index on your computer will mean added convenience for you. Order your copy today.

*EDN provides fully functional copies of PC-File+ for a nominal reproduction fee. Receipt of PC-File+ does not constitute ownership, which must be purchased from Buttonware for \$69.95 if you continue to use the program, but merely the right to evaluate the program's capabilities. EDN assumes no responsibility for the programs

PC-File+ runs on IBM PCs and compatible computers and requires 384k bytes of memory, two double-sided floppy disk drives or one double-sided floppy drive and a hard disk, an 80-column display, and MS-DOS or PC-DOS version 2.0 or later.



ORDER FORM

EDN's Technical Article Database Index on IBM PC DSDD floppy disc

copies at \$19.95 = Installment | (May 1987-October 1987) (\$21.95 for non-US) Installment 2 copies at \$19.95 = (November 1987-April 1988) (\$21.95 for non-US) copies at \$14.95 = PC-File + database software (3 disks) (Available only in US, Canada, and England) (\$16.95 for non-US)

Check or money order made out to EDN Reprints must accompany each check. No COD. Massachusetts residents add 5% sales tax. Foreign checks must be drawn on a US Bank, issued in US currency.

Send to:

Technical Article Database Index **EDN Magazine** Cahners Building 275 Washington Street Newton, MA 02158-1630

Please Print clearl This is your mailin	y. g label.		
NAME			
TITLE			
COMPANY			
ADDRESS			
CITY	STATE	ZIP	

LOOKING AHEAD

EDITED BY CYNTHIA B RETTIG

Hardware outpaces software in information technology

Consistent gains in the price/performance ratio for computerizedinformation hardware products allow workers at all levels to access more data at lower costs and explore more possibilities in shorter periods of time, thus speeding the decision-making process, according to The Diebold Group Inc (New York, NY). However, the consulting firm found that the development of new kinds of software, like expert systems or new generations of integrated applications, is increasingly expensive and slow to reach the market. Software products thus appear to retard qualitative changes.

During the last two years, Diebold points out, vital improvements or breakthroughs have changed products in nearly every major branch of hardware-based information technology. For most hardware components, manufacturers are using two or more feasible technologies in their products, and other promising technologies are in different stages of research or development. For digital circuitry, the firm points out, the number of basically distinct options has been

SOME EXPECTED ADVANCES IN INFORMATION TECHNOLOGY

YEAR	GENERIC TECHNOLOGY COMMERCIALIZED
2000	3-DIMENSIONAL SCENE SIMULATION WITH COMPUTER GRAPHICS
2000	AUTOMATED SIMULTANEOUS TRANSLATION OF MULTILINGUAL CONVERSATIONS
1995	16 M-BYTE DYNAMIC RAM SUPER CHIPS
1995	HEAD-MOUNTED STEREOSCOPIC DISPLAY
1992	"VISIBLE MEMORY" DISPLAY SCREEN: SURFACE IS DISPLAY MEMORY
1990	ALL-OPTICAL DIGITAL LOGIC CIRCUITS SUPERCONDUCTIVE CERAMIC LOGIC CIRCUITS
1989	VOICE-ACTIVATED WORD PROCESSOR, 20,000-WORD VOCABULARY

(SOURCE: THE DIEBOLD GROUP INC)

increasing at the rate of one or two per year. For system and application software, on the other hand, the rate of change is much slower and the number of viable alternatives far fewer.

One major result of the disparity in the technological-growth rates of hardware and software technology is the steady increase in the ratio of the cost-of-use to the cost-of-acquisition. Today a personal computer has a greater computational power and storage capacity than a mainframe of the mid-sixties or a minicomputer in the mid-seventies, but it costs about 1000 times less. Yet, except for word-processing

and spreadsheet programs, a personal computer demands almost as much time for program development as its more expensive ancestors.

Hardware products are also becoming more reliable and adaptable. For software, increasing functions and speed can mean a reduction in reliability and adaptability. Diebold does point out that software is showing improvements in some areas. Better user interfaces, for example, are reducing the cost of use, and a new generation of integrated tools are appearing for software development.

Growth in UPS market spawns new strategies

The strong demand for uninterruptible power supplies (UPSs) in the US has captured the attention of both domestic and foreign manufacturers, according to Venture Development Corp (Natick, MA). The 1988 UPS market in the US is estimated to be \$789.1 million; it's expected to grow rapidly and reach \$1.3 billion by 1991.

Foreign manufacturers have approached the US market both di-

rectly and indirectly. Some foreign companies have established their own marketing and service organizations. Others, such as Fuji Electric and Merlin-Gerin, have legal agreements with US companies that let the domestic companies manufacture and/or market products on behalf of the foreign concern. Only a few foreign UPS manufacturers have actually established themselves as important participants in the US market.

VDC found that, in order to com-

pete in the UPS market, a company has to establish a local presence. Generally, UPS manufacturers don't succeed very well in any distant markets against strong local competition. The market research company concludes that companies must know their markets well, do some research on foreign markets, and perhaps build local production facilities—as well as marketing and service organizations—if they want to offer competitive pricing.

tiny SPDT switches

absorptive ... reflective

dc to 4.6 GHz from \$3295

Tough enough to pass stringent MIL-STD-883 tests, useable from dc to 6GHz and smaller than most RF switches, Mini-Circuits' hermetically-sealed (reflective) KSW-2-46 and (absorptive) KSWA-2-46 offer a new, unexplored horizon of applications. Unlike pin diode switches that become ineffective below 1MHz, these GaAs switches can operate down to dc with control voltage as low as -5V, at a blinding 2ns switching speed.

Despite its extremely tiny size, only 0.185 by 0.185 by 0.06 in., these switches provide 50dB isolation (considerably higher than many larger units) and insertion loss of only 1dB. The absorptive model KSWA-2-46 exhibits a typical VSWR of 1.5 in its "OFF" state over the entire frequency range. These surface-mount units can be soldered to pc boards using conventional assembly techniques. The KSW-2-46, priced at only \$32.95, and the KSWA-2-46, at \$48.95, are the latest examples of components from Mini-Circuits with unbeatable price/performance.

Connector versions, packaged in a 1.25 x 1.25 x 0.75 in. metal case, contain five SMA connectors, including one at each control port to maintain 3ns switching speed.

Switch fast...to Mini-Circuits' GaAs switches.

SPECIFICATIONS

Pin Model Connector Version		KSW-2 ZFSW-	And the same of	KSWA-	
FREQ. RANGE	(dc-4.6	GHz	dc-4.6	GHz
INSERT. LOSS (dl dc-200MHz 200-1000MHz 1-4.6GHz		0.9	1.1 1.3	typ 0.8 0.9 1.5	
ISOLATION (dB) dc-200MHz 200-1000MHz 1-4.6GHz		typ 60 45 30	50 40	typ 60 50 30	50 40
() [)	ON OFF	1.3:1		1.3 1.4	
SW. SPEED (nsec rise or fall time		2(typ)	3(typ)	
MAX RF INPUT (bBm) up to 500MHz above 500MHz		+17		+17	
CONTROL VOLT. OPER/STOR TEN		-5V c		-5V o	n, OV off to +125°(

\$32.95

finding new ways ... setting higher standards



P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500
Fax (718) 332-4661 Domestic and International Telexes: 6852844 or 620156

C 117 REV. D

\$48.95 \$88.95

PRICE (1-24)

REVOLUTION REACHES THE BRIDGE.



Introducing the IR2110 high-voltage, bridge driver. The high side and

the low side. Volume Without the HIII down side. Lowin

It works

off-line, anywhere worldwide. Inputs are LSTTL
and CMOS compatible. With two
independently controlled outputs
to drive upper/lower HEXFET*
and IGBT power supply and motor
control circuits.

This is powerful stuff. Each output can drive up to 2A.

With its dv/dt
TOLOAD immunity
making it
almost inde-

All at frequencies well above 1MHz!

DRIVER

Of course you won't be needing transformers, optical isolation or 60% of your drive components. That's the beauty and simplicity of this 500V bridge driver. Just add a

CIRCLE NO 97

diode, a resistor, a capacitor and the design's complete.

The IR Revolution has reached the bridge. The bridge between control and power.

Cross over. Call us at (213) 607-8899 and ask about the

IR2110 Bridge Driver.

IR210

233 Kansas Street, El Segundo, CA 90245



DASH OPENS DOORS TO MORE VENDORS, SERVICES, AND SYSTEMS.

DASH™ Schematic Designer from FutureNet® gives you options no other schematic capture package can. With more than one hundred DASH-Partners providing a broad range of complementary products and services, DASH's industrystandard format is accepted virtually everywhere. So you won't end up with just a schematic. When you design with DASH, you'll have more choices in technologies, CAE systems, foundries, and service bureaus. DASH is a universal front end design tool that has already opened doors for thousands of users worldwide.

AN OPEN DOOR TO ASIC VENDORS.

DASH has won the support of dozens of ASIC vendors, including National Semiconductor, Mitsubishi, Motorola, LSI Logic, MMI, Hitachi, and Xilinx. They provide vendor-specific symbol libraries and/or accept DASH netlists for simulation so you can design



DASH runs on 80386 and 80286 machines, IBM® personal computers, and the Sun-3 Series.

ASICs in DASH. Whatever your choice of vendor or technology—PLDs, LCAs, gate arrays, or other semicustom devices—DASH is the schematic entry software of choice.

AN OPEN DOOR TO CAD SYSTEMS.

Translators to a wide variety of PCB and simulation systems are available from FutureNet and our DASH-Partners. DASH is the only design

entry tool that can be used throughout your company, in multiple CAD environments, regardless of the mix of vendors.

AN OPEN DOOR TO SERVICE BUREAUS.

When you don't want to do it all yourself, DASH gives you access to outside services. Service bureaus throughout the world accept the DASH netlist as standard input for their design, wire wrap, and PCB manufacturing services.

FREE DASH-PARTNERS DISKETTE. Take the first step. Call us today for your

free copy of the DASH-Partners diskette of vendors, services, and systems that support DASH. You're on the threshold of new design freedom.

1-800-247-5700 Ext. 264

Data I/O Corporation 10525 Willows Road N.E., P.O. Box 97046, Redmond, WA 98073-9746, U.S. A. (206) 867-6899/Telex 15-2167
Data I/O Canada 7255 Airport Road, Suire 302, Mississauga, Ontario L4V IV2 (416) 678-0761
Data I/O Europe World Trade Center, Strawnskylaan 533, 1077 XX Amsterdam, The Netherlands +31 (0) 20-6622866/Telex 16616 DATIO NL
Data I/O Japan Sumitomoseimei Higashishirbashi Bildg., 8F, 2-1-7, Higashi-Shinbashi, Minato-ku, Tokyo 105, Japan
(33) 432-6899/Telex 2525-288 DATAIO J

FutureNet